SIDE STAND ACCIDENT PREVENTOR

TEAM PROJECT REPORT

Submitted by

2023118014 YUVAN KUMAR
2023118017 ADVIK VEER

in partial fulfillment for the professional core course
ME 23404: Product Design and Development

DEPARTMENT OF MECHANICAL ENGINEERING
COLLEGE OF ENGINEERING GUINDY
ANNA UNIVERSITY, CHENNAI

ANNA UNIVERSITY, CHENNAI - 600 025

PROJECT SUMMARY

Title of the Project Work	**SIDE STAND ACCIDENT PREVENTOR**
Students' Reg. No. & Name	**2023118014 YUVAN KUMAR** **2023118017 ADVIK VEER**
Course Code & Title	**ME23404 Product Design & Development**
College	Dept. of Mechanical Engineering, College of Engineering Guindy Anna University, Chennai – 600 025

We may have witnessed motorcycle accidents because of the surface hindrance of retracted positioned side stand. One of the most common problems that are encountered in using the side stand is negligence or carelessness to kick back the side stand. The negligence may be due to absence of mind, urgency, divergence in concentration and few other reasons, which may prevent the rider to kick back the side stand to its original position (released position). Failure to kick back the side stand for any of the reasons stated above may hit the side stand to surface of road and there by affect the stability of the vehicle and lead to accident of the vehicle and riders involve in the accident, sometimes fatal. To ensure safety of the rider, during absence of mind, negligence, urgency or carelessness the side stand lock link helps in knowing the state of side stand prior to movement of vehicle

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	PROJECT SUMMARY	2
	TABLE OF CONTENTS	3
1.	**Introduction**	5
	1.1 General Introduction	5
	1.2 Objective of Project	
	1.3 Need for the Project	
	1.4 Scope of the project	
	1.5 Methodology	
2.	**Customer Need Analysis (CNA) & Specification Design**	
	2.1 Customer Need Analysis	
	2.1.1 Identification of Target Users	
	2.1.2 Understanding Rider Challenges	
	2.1.3 Problems with Existing Solutions	
	2.1.4 Importance of a Mechanical Solution	
	2.1.5 Expected Benefits for Customers	
3	**Concept Generation & Concept Selection**	
	3.1 Concept Generation	
	3.1.1 Problem Definition	

3.1.2 Brainstorming of Possible Solutions

3.1.3 Shortlisting Feasible Concepts

3.1.4 Innovative Ideas Considered

3.2 Concept Selection

3.2.1 Selection Criteria (Safety, Cost, Simplicity, Reliability, Ease of Installation)

3.2.2 Comparison of Concepts

3.2.3 Final Concept Selection

3.2.4 Justification for Selected Concept

4 Final Product Specifications & Prototyping

4.1 Final Design Overview

4.2 Materials Used

4.3 Fabrication Process

4.3.1 Design and Planning

4.3.2 Welding Process

4.3.3 Surface Finishing

4.3.4 Installation on Motorcycle

4.3.5 Final Inspection and Quality Check

4.4 Working Principle of prototype

4.5 Testing of Prototype

4.5.1 Static Testing

4.5.2 Dynamic Testing

Conclusion

References

CHAPTER - 1

INTRODUCTION

1.1 General Introduction

Motorcycle accidents are often caused by various mechanical and human errors, one of which is the surface hindrance created by a side stand left in the extended position. One of the most common problems encountered when using the side stand is the rider's negligence or carelessness in retracting it before moving the vehicle. This negligence may arise due to absent-mindedness, urgency, distraction, or other factors that can prevent the rider from remembering to kick back the side stand into its retracted, safe position.
When a rider forgets to retract the side stand, it may come into contact with the road surface during vehicle movement. This interaction can severely affect the stability of the motorcycle, causing a loss of balance and potentially leading to an accident. Such accidents not only endanger the life of the rider but also pose risks to other individuals on or near the road. In some cases, the consequences can be severe, even fatal.

Recognizing the risks associated with an unretracted side stand, it becomes essential to incorporate mechanisms that enhance rider safety. One

such solution is the side stand lock link. This device serves as a preventive measure by alerting the rider to the state of the side stand before the vehicle is set in motion. By providing a physical or electronic indication of whether the side stand is properly retracted, the side stand lock link helps to eliminate the risk posed by human error due to absent-mindedness, urgency, or carelessness. The integration of a side stand lock link is therefore a crucial safety innovation, aiming to reduce accidents, improve rider awareness, and promote responsible riding practices. It ensures that, regardless of the rider's mental state at the moment, a safeguard is in place to prevent the motorcycle from being operated unsafely due to an extended side stand.

1.2 Objective of the Project

The main objective of this project is to improve the safety of motorcycle operation by introducing a mechanical interlock between the side stand and the clutch mechanism. In many motorcycle accidents, failure to retract the side stand before moving the vehicle leads to serious instability issues, often resulting in accidents that can cause injury or even death. This problem usually occurs due to human errors such as absent-mindedness, urgency, distraction, or carelessness.

To address this critical safety concern, a rod was welded to connect the side stand to the clutch system. The purpose of this welded rod is to create a mechanical link such that the clutch operation is directly influenced by the position of the side stand. In this system, the clutch cannot be fully engaged unless the side stand is properly retracted. Consequently, if the side stand remains in the deployed (down) position, the rider is physically prevented from operating the motorcycle normally, thus reducing the likelihood of setting the vehicle into motion unsafely.

Through this mechanical connection, the project aims to:

- Prevent the motorcycle from moving when the side stand is down.
- Force the rider to retract the side stand before the vehicle can be operated.
- Reduce the dependency on the rider's memory or attentiveness, ensuring automatic safety action.
- Decrease the number of accidents caused by unretracted side stands.
- Offer a low-cost, robust, and maintenance-free safety solution compared to electronic systems.

By welding the rod as a direct mechanical link, the system remains simple and reliable without the complexity and potential failures associated with electrical sensors or switches. The project focuses on creating a practical, affordable solution that can be implemented in both new motorcycles and retrofitted into existing ones to enhance overall road safety.

Thus, this project is an effort toward minimizing human error and promoting safer riding habits through innovative but straightforward mechanical engineering.

1.3 Need for the Project

By introducing a mechanical linkage between the side stand and the clutch mechanism, the rider is naturally compelled to retract the side stand before the motorcycle can move. This approach simplifies the process by integrating it into the natural operation of the vehicle, removing the dependence on the rider's memory or additional electronic alerts. Since the motorcycle will not function normally unless the side stand is in the proper position, the risk of

starting the vehicle with the side stand down is effectively eliminated.

This project, therefore, addresses a critical gap in motorcycle safety especially for vehicles that are not equipped with modern electronic safety systems. It aims to provide a universally adaptable, durable, and maintenance-free solution that can be implemented with minimal cost and effort.

In summary, the need for this project stems from the urgency to:

- Prevent avoidable accidents caused by unretracted side stands.
- Improve the overall safety standards for motorcycles.
- Create a user-friendly, mechanical interlock system that can be easily installed and maintained.
- Offer a practical solution that aligns with the needs of diverse riders, from urban commuters to rural users.
- Encourage a culture of safer riding practices without adding complexity to the vehicle design.

Meeting these needs not only protects the rider and others on the road but also sets a foundation for broader improvements in two-wheeler safety technology.

1.4 Scope of the Project

The scope of this project is focused on designing, fabricating, and implementing a simple, reliable mechanical system that links the motorcycle's side stand to its clutch mechanism. The project aims to develop a solution that enhances rider safety by ensuring that the motorcycle cannot move unless the side stand is fully retracted.

This system is purely mechanical, involving the welding of a rod between the side stand and the clutch lever or mechanism. The main features and limitations that define the scope are as follows:

Design and Fabrication: Designing a mechanical linkage that effectively prevents clutch engagement when the side stand is down. Fabricating and installing the linkage using basic mechanical processes such as cutting, welding, and fitting.

Testing and Validation: Testing the functionality of the system to ensure that it reliably locks the clutch mechanism when the side stand is deployed and releases it once the side stand is retracted.

Mechanical Operation Only: The project focuses solely on mechanical solutions and does not involve electronic sensors, alarms, or digital systems.

Application Range: The system is designed primarily for motorcycles and scooters without existing side stand safety features. It can be adapted to a variety of models with minor adjustments.

Cost-Effectiveness: Emphasis is placed on using readily available materials and simple manufacturing techniques to keep the solution affordable and easy to maintain.

Limitations:

- The system may require model-specific adjustments based on different motorcycle designs.

- It does not replace existing electronic safety systems but serves as a mechanical alternative.

- Installation requires minor modifications to the motorcycle frame or clutch mechanism.

1.5 Methodology

The methodology followed in this project involves a systematic approach to designing, fabricating, and testing a mechanical linkage system between the motorcycle side stand and clutch mechanism to enhance rider safety. The steps are detailed below:

1. Problem Identification

The first step involved identifying the problem associated with riders forgetting to retract the side stand, leading to potential accidents. A mechanical solution was selected to avoid reliance on costly or failure-prone electronic systems.

2. Concept Development

A basic concept was developed where a mechanical rod would be welded between the side stand and clutch lever assembly. This linkage would block the normal clutch operation when the side stand is deployed, forcing the rider to retract the stand before riding.

3. Material Selection

Suitable materials were selected for the linkage rod. Factors such as strength, durability, resistance to wear, and ease of welding were considered. Mild steel was chosen due to its adequate mechanical properties and ease of fabrication.

4. Design and Measurement

Measurements were taken on the motorcycle to determine the optimal length, positioning, and alignment of the rod. Careful planning was done to ensure that the movement of the side stand directly influences the clutch without hindering normal operation once the stand is retracted.

5. Fabrication Process

- The rod was cut to the required length.
- The attachment points were cleaned and prepared for welding.
- The rod was welded securely between the side stand and a strategic point on the clutch mechanism.
- Additional support brackets or adjustments were made if necessary to ensure smooth operation.

6. Testing and Adjustments

- After fabrication, the system was thoroughly tested:
- The motorcycle was tested with the side stand in the deployed position to ensure the clutch could not engage properly.
- The system was checked after retracting the side stand to confirm that the clutch functioned normally.
- Necessary adjustments were made to the rod or welding points to optimize functionality and eliminate any stiffness or obstructions.

7. Safety and Reliability Verification

Several test runs were conducted under different conditions to verify the reliability of the linkage mechanism. The focus was on ensuring that the system did not interfere with regular riding operations and maintained long-term durability.

8. Documentation

The final step involved documenting the entire design, fabrication, and testing process for reporting purposes and to serve as a guide for future improvements or wider implementation.

CHAPTER - 2

CUSTOMER NEED ANALYSIS (CNA) & SPECIFICATION DESIGN

2.1 Customer Need Analysis

Motorcycles are a popular mode of transportation due to their affordability, fuel efficiency, and ease of navigation through traffic. However, two-wheelers also come with significant risks, particularly concerning rider stability and balance. One common but often overlooked cause of motorcycle accidents is the rider forgetting to retract the side stand before initiating movement. A deployed side stand can catch on uneven surfaces, bumps, or during leaning turns, destabilizing the vehicle and leading to dangerous crashes.The analysis of customer needs began by studying accident data, interacting with daily motorcycle users, and observing rider behaviors. It was found that forgetting to retract the side stand is more frequent than generally acknowledged, and that many riders, especially during quick starts or emergency departures, neglect this critical safety check. This small oversight can have catastrophic consequences.

Existing preventive measures, such as electronic side stand sensors, are mainly found in newer or premium motorcycles. These electronic systems are not available in many mid-range, economy, or older two-wheelers. Furthermore, users in rural or semi-urban regions often prefer mechanical, maintenance-free solutions over electronic alternatives, as the latter can be expensive to repair and less durable under tough road conditions.

Hence, there is a clear and urgent need for a low-cost, robust, mechanical solution that can ensure rider safety without relying on the rider's memory or on electronic components prone to failure. A system that mechanically enforces safe behavior would meet an important demand in the market, improve overall road safety, and significantly reduce accidents caused by the extended side stand issue.

This analysis clearly shows that a mechanical side stand-clutch interlock system would effectively meet the pressing safety needs of a wide range of motorcycle users.

2.1.1 Identification of Target Users

In order to effectively design a solution, it is important to clearly define and understand the group of customers who will most benefit from it. Based on the customer need analysis, the primary target users for the mechanical side stand lock system can be categorized as follows:

Daily Commuters:

Riders who use motorcycles for daily travel to work, school, or business often operate under tight schedules. In their rush, they may frequently forget to retract the side stand. These riders require a system that automatically

enforces safety without adding extra steps to their routine.

Rural and Semi-Urban Riders:

In many rural areas, motorcycles are the primary mode of transport. However, electronic sensor systems are rare because of cost, maintenance challenges, and lack of easy access to repair facilities. Riders here need a durable, mechanical solution that works reliably in rough conditions like dirt roads, water exposure, and high vibrations.

Older Motorcycle Owners:

Riders who use older motorcycle models that do not come equipped with built-in safety sensors would benefit significantly from a simple retrofittable mechanical linkage. It allows them to upgrade their vehicles without the cost and complexity of installing electronic systems.

Beginner or Inexperienced Riders:

New riders often make mistakes due to a lack of riding habits or training. A mechanical system that prevents the clutch from engaging if the stand is down provides an important safety backup, reducing the chance of accidents during the learning phase.

Fleet Operators and Delivery Services:

Businesses that operate motorcycle fleets, such as delivery services, could benefit from this system to ensure their riders consistently operate vehicles safely, reducing liability from accidents caused by unretracted side stands.

Each of these user groups shares a common need for affordable, reliable, low-maintenance, and easy-to-operate safety mechanisms. Thus, the

mechanical side stand-clutch interlock addresses the diverse safety concerns across a broad spectrum of motorcycle users.

2.1.2 Understanding Rider Challenges

Understanding the real-world challenges faced by motorcycle riders is critical in developing an effective safety system. Through observation, surveys, and study of accident data, several factors were identified that contribute to the problem of riders forgetting to retract the side stand before moving their vehicle:

Absence of Mind:

Riders often get distracted by their surroundings, mobile phones, conversations, or simply daydreaming. In such cases, basic safety checks like retracting the side stand are easily forgotten. Riders may even start riding without noticing the stand is still deployed.

Urgency and Rush:

In situations where riders are in a hurry — such as catching public transport connections, reaching work or appointments on time, or delivering goods within tight deadlines — important pre-ride checks are sometimes skipped. The focus shifts from safety to speed, increasing the risk of accidents caused by a deployed side stand.

Distraction by Surroundings:

Busy environments, such as crowded city streets or marketplaces, overload a rider's attention. In such cases, external distractions make it more likely that the rider misses steps in their routine, such as retracting the side stand.

Carelessness and Habitual Negligence:

Some riders, especially those with poor riding habits or less formal training, may develop a habit of not performing a thorough check before riding. Overconfidence or a casual attitude towards basic safety checks often leads to such negligence.

Fatigue and Stress:

Riders who are physically tired or mentally stressed due to personal or professional reasons have reduced focus and slower reactions. In these cases, even trained riders may unintentionally forget to retract the side stand.

Inexperience:

New riders or learners may not yet have developed strong riding habits. They may simply overlook retracting the side stand due to inexperience and lack of muscle memory.

These challenges highlight that depending solely on human attention is risky and unreliable, especially when safety is concerned. It becomes clear that an automated or forced mechanism is necessary to ensure that the side stand is retracted before a motorcycle can be operated safely.

2.1.3 Problems with Existing Solutions

Currently, some motorcycles are equipped with electronic side stand safety mechanisms, which typically include sensors connected to the ignition or clutch circuit. While these systems have been somewhat effective, they also present significant problems that limit their overall adoption and effectiveness:

High Initial Cost:

Electronic side stand interlock systems increase the manufacturing and purchase costs of motorcycles. These systems involve sensors, wiring, electronic control units, and software integration, making them expensive additions especially for budget motorcycles.

Complexity and Maintenance Issues:

Electronic systems are sensitive to environmental factors such as dust, moisture, vibrations, and heat, all of which are common in typical riding environments. Over time, sensors and wiring can fail or degrade, leading to costly repairs. In regions where service centers are not easily accessible, maintaining these systems becomes difficult and expensive.

Limited Retrofit Options:

Installing electronic side stand sensors on motorcycles that did not originally come with them is complicated. It requires skilled labor, precise electrical modifications, and sometimes even reprogramming of the engine control unit (ECU). As a result, it is practically unavailable for older motorcycles or for low-budget customers.

Dependence on Electronic Reliability:

Any malfunction in the sensor or wiring can either disable the safety feature entirely or, worse, cause false alarms or sudden engine shutdowns while riding. This dependency on electronics makes the system less reliable in harsh conditions.

Not User-Serviceable:

Riders cannot easily diagnose or fix issues related to electronic

systems on their own. Any malfunction typically requires a visit to a service center, adding time, inconvenience, and cost.

Because of these drawbacks, many riders either do not have access to such safety features or choose not to use them. In contrast, a purely mechanical solution — like the side stand and clutch rod linkage proposed in this project — offers a simpler, low-maintenance, and much more cost-effective alternative that can be easily fitted, used, and trusted for the life of the motorcycle.

2.1.4 Importance of a Mechanical Solution

After analyzing rider challenges and the shortcomings of existing electronic solutions, it becomes evident that a mechanical approach offers significant advantages in addressing the problem of unretracted side stands. The mechanical solution proposed — connecting the side stand to the clutch mechanism via a welded rod — addresses the issue directly, reliably, and affordably.

The importance of opting for a mechanical solution can be understood from several key perspectives:

Simplicity and Reliability:

Mechanical linkages are inherently simple, involving direct physical connections without the need for electronics, sensors, or control systems. This simplicity translates into higher reliability, as there are fewer components that can fail, especially under rough riding conditions, exposure to weather, or after long periods of use.

Low Cost:

A mechanical system is extremely cost-effective compared to electronic alternatives. Materials like steel rods are inexpensive and readily available, and the fabrication involves basic welding and fitting operations, which significantly lowers the overall cost for users.

Ease of Maintenance:

Unlike electronic systems, mechanical linkages can be easily inspected, maintained, and repaired without specialized tools or expertise. Riders or local mechanics can manage repairs, making it practical for use even in remote areas.

No Dependence on External Power:

Mechanical systems do not require electricity to function, eliminating the risks associated with power failure, wiring corrosion, or sensor malfunctions. The system operates independently of the motorcycle's battery or electrical circuits, ensuring consistent operation under all conditions.

Universal Applicability:

The mechanical solution can be adapted and fitted to a wide range of two-wheeler models — old or new — without requiring complex alterations. This makes it ideal for mass deployment among different types of motorcycles and scooters.

Increased Rider Safety and Discipline:

By physically preventing the clutch from engaging while the side stand is deployed, the mechanical linkage forces the rider to retract the side stand before starting the vehicle. This not only ensures safety but also gradually builds better riding habits and discipline among users.

Thus, a mechanical side stand locking system is not just a low-cost alternative; it is arguably a better, more robust, and practical solution for millions of motorcycle riders, especially in developing countries and rural areas where affordability and durability are crucial.

2.1.5 Expected Benefits for Customers

The introduction of a mechanical side stand-clutch interlock system brings with it a host of valuable benefits tailored specifically to customer needs:

Enhanced Rider Safety:

The most direct benefit is the significant reduction in accidents caused by the side stand being left down. By preventing clutch engagement unless the stand is retracted, it ensures that the motorcycle is stable and safe for riding.

Cost-Effective Safety Enhancement:

Since the system involves simple mechanical parts and minimal modification, it provides an affordable solution to a serious safety issue. This is particularly important for budget-conscious customers and for fleet operators looking to improve safety across many vehicles without incurring heavy costs.

Durability and Longevity:

Made from sturdy materials like mild steel, the mechanical linkage is capable of withstanding the harsh conditions motorcycles are subjected to — including rain, dust, vibrations, and rough terrains — without frequent need for

repairs or replacements.

Low Maintenance:

Mechanical systems require very little maintenance. Periodic checks for loosening or wear are sufficient. In the rare event of failure, repairs are simple, quick, and inexpensive, as they do not involve complex parts or diagnostics.

Adaptability:

This system can be retrofitted to a wide variety of motorcycle makes and models. It is not restricted to factory-built features, thus allowing owners of older motorcycles to enhance their vehicle's safety without needing to purchase a new bike.

Improved Riding Habits:

Over time, riders become conditioned to always check and retract the side stand, even on motorcycles that may not have such a system. This positive habit formation contributes to overall better riding discipline and reduces careless riding practices.

Peace of Mind:

Knowing that their motorcycle will not start moving improperly provides riders with greater confidence, reducing anxiety and allowing them to focus better on their riding and road conditions.

In conclusion, the mechanical side stand lock system not only solves an existing safety problem but does so in a way that is sustainable, scalable, and genuinely helpful to a wide range of motorcycle users.

CHAPTER - 3

CONCEPT GENERATION & CONCEPT SELECTION

3.1 Concept Generation

Concept generation is the first step towards solving the design problem systematically. In the context of this project — developing a side stand safety mechanism linked mechanically to the clutch system — concept generation involved identifying, exploring, and evaluating different mechanical methods to prevent motorcycle movement when the side stand is not properly retracted.

A creative and structured approach was applied during concept generation to ensure that all potential solutions were considered, ranging from traditional mechanical linkages to more innovative, hybrid ideas. Emphasis was placed on simplicity, feasibility, affordability, and robustness, because the ultimate goal is to create a system that can be easily implemented and widely adopted across different types of motorcycles.

To arrive at a suitable solution, a multi-stage concept generation

process was followed:

- Careful restatement and breakdown of the core problem.
- Brainstorming sessions involving multiple stakeholders, including riders and mechanics.
- Application of engineering judgment to filter impractical ideas.
- Selection of the most promising concepts for further evaluation.

This structured process ensured that the chosen solution was not merely based on intuition or guesswork but on thorough analysis, creative thinking, and practical understanding of real-world needs.

3.1.1 Problem Definition

A clear and comprehensive definition of the problem is critical to guiding the concept generation and eventual design. The problem, in simple terms, can be stated as:

"Develop a mechanical system that prevents a motorcycle from moving unless the side stand has been fully retracted."

However, when we break it down further, several detailed requirements and constraints emerge:

Key Problem Elements:

Safety Concern:

Riders often forget to retract the side stand, leading to sudden instability when turning or during movement, causing accidents.

Human Factors:

Forgetfulness, distraction, urgency, carelessness, and fatigue contribute heavily to the risk, and any solution must work independently of human attention.

Mechanical Integrity:

The system must physically ensure that critical operations like engaging the clutch (and therefore riding) cannot occur when the side stand is down.

Low Cost and Simplicity:

Since the majority of motorcycles, especially in developing regions, are cost-sensitive, the solution must be affordable and easy to install or retrofit.

Durability and Maintenance:

The system should withstand harsh outdoor conditions such as rain, dust, mud, and heat, with minimal maintenance requirements.

Non-Electronic Requirement:

To avoid complexity, failures, and dependency on electric circuits, a purely mechanical system was preferred.

Problem Constraints:

- No significant modification to the basic vehicle structure (to preserve warranty and minimize cost).
- Easy operability and no significant additional effort for the rider.
- Must not compromise the motorcycle's ability to park safely on an inclined or uneven surface.

Problem Opportunities:

- Improve rider habits by introducing a physical consequence for not retracting the stand.
- Enhance overall motorcycle safety without relying on electronics.
- Create a system adaptable to a wide variety of two-wheeler models.

By precisely defining the problem and understanding all surrounding factors, the team ensured that the concept generation phase would focus on practical, achievable, and high-impact solutions, ultimately leading to safer roads and better riding experiences.

3.1.2 Brainstorming of Possible Solutions

Brainstorming is a vital creative technique used to generate a wide range of ideas without immediately judging or rejecting them. For this project, brainstorming sessions were conducted with students, faculty members, motorcycle technicians, and daily motorcycle users to gather insights from different perspectives.

The following key ideas emerged during the brainstorming phase:

Mechanical Linkage to Clutch (Rod Mechanism):

Connect the side stand to the clutch lever through a mechanical rod. If the side stand is deployed, the clutch cannot be engaged, thus preventing the motorcycle from starting to move. This ensures physical prevention rather than just warnings.

Spring-Loaded Auto Retraction Stand:

Modify the stand with a strong spring mechanism, such that once the load is lifted off the side stand (i.e., when the bike becomes upright), the stand automatically retracts. However, risks like instability on parking surfaces were highlighted.

Side Stand Locking Lever:

Design a lever that must be manually reset after lifting the side stand; unless reset, the motorcycle's clutch or gear system remains mechanically locked.

Mechanical Blocking of Gear Lever:

A blocking mechanism that locks the gear shifter when the side stand is down. The gear cannot be shifted into first gear unless the stand is fully retracted.

Audible Mechanical Bell Alarm:

Attach a simple mechanical bell that rings due to vibration or wheel movement if the side stand is deployed. Though it serves as a warning, it relies heavily on rider response and does not physically prevent movement.

Wire Rope Linkage to Brake Pedal:

Connect a thin steel cable from the side stand to the rear brake pedal, disabling braking action unless the stand is retracted. However, this could dangerously compromise braking safety if the system fails.

Magnet-Based Retraction System:

Using magnets to pull the side stand back into the retracted position when the bike becomes upright. This idea was ultimately seen as expensive and

unreliable.

Important Factors Considered During Brainstorming:

- Mechanical simplicity and ease of understanding by riders.
- Safety enhancement without rider burden.
- Compatibility with various motorcycle models.
- Low production and installation cost.
- Ability to function under different weather and terrain conditions.

Through this brainstorming, many ideas were discussed. Some were combined or refined to create new hybrid ideas, while others were discarded for being impractical, costly, or unsafe.

3.1.3 Shortlisting Feasible Concepts

Once the brainstorming phase was complete, it became necessary to evaluate the practicality of each idea and narrow down the options to the most feasible concepts. The following criteria were used for shortlisting:

Effectiveness:

Does the idea completely prevent riding with the side stand down?

Feasibility:

Can the system be manufactured and installed easily without major vehicle modifications?

Affordability:

Is the system low-cost enough for mass adoption, especially in cost-sensitive markets?

Maintenance:

Is the system robust, requiring little to no maintenance over the lifetime of the motorcycle?

Universality:

Can the system be easily adapted for different models and makes of motorcycles?

After applying these criteria, the following concepts were shortlisted:

1. Clutch Interlock Rod Mechanism (Chosen Concept):

A simple metal rod connecting the side stand to the clutch lever assembly. If the side stand is not retracted, the clutch cannot be fully operated, thereby blocking movement.

2. Spring-Loaded Automatic Retraction Stand:

A side stand fitted with a strong return spring, automatically retracting when the bike becomes upright.

Reasons for Preferring the Rod Mechanism Over Spring Retraction:

- A spring might retract the stand while the motorcycle is parked, leading to falls and damage.
- Springs can lose tension over time, reducing reliability.
- A mechanical rod system directly blocks movement and remains reliable without depending on spring tension or rider intervention.

Thus, the clutch-side stand rod linkage emerged as the most reliable and safest option, perfectly matching the project's goals.

3.1.4 Innovative Ideas Considered

While the primary focus was on simple mechanical solutions, several innovative and creative ideas were also explored to ensure no possibilities were overlooked. Although these ideas were not ultimately selected, they showcased the breadth of thinking and helped solidify confidence in the final chosen design.

Hydraulic Actuated Lock:

A small hydraulic piston activated by the side stand position to lock the clutch lever. Although technically interesting, the cost, maintenance complexity, and potential for fluid leaks made it impractical.

Electronic Side Stand Sensor with Mechanical Override:

Combining a sensor that detects side stand position with a mechanical clutch interlock. This hybrid system would ensure double protection but at increased cost and complexity, contrary to the goal of simplicity.

Gear Position Sensor Linkage:

A mechanical or electrical device that prevents the engine from starting or shifting into first gear if the side stand is down. Though effective in modern motorcycles, it is complex for retrofitting older models.

Magnetic Latch Retraction System:

A large permanent magnet placed near the side stand to attract and

retract it when not loaded. Practical challenges like size, strength loss, and environmental interference made this idea unsuitable.

Chain-and-Sprocket Miniature Retraction:

Using a mini chain drive to retract the side stand automatically when the wheel starts moving. Again, complexity, cost, and maintenance ruled this idea out.

These innovative approaches were important for ensuring that all angles were covered, and that the final chosen solution was truly the best fit, balancing safety, simplicity, and affordability.

3.2 Concept Selection

After generating multiple concepts during the brainstorming phase, the next critical step was systematic evaluation and selection of the most suitable concept. Concept selection involves carefully comparing different alternatives against a set of defined criteria to identify the best solution for the given problem.

The primary goal during this stage was to select a concept that not only solves the core problem (preventing movement with a deployed side stand) but also aligns with practical realities such as manufacturing ease, installation simplicity, long-term reliability, and affordability for motorcycle users.

- A structured approach using engineering decision-making tools was employed:
- Setting clear selection criteria based on customer needs and project goals.
- Comparing different concepts using a decision matrix (Pugh matrix) to

objectively rate each solution.

Selecting the concept that scored the highest across critical parameters.

This thorough process ensured that the final concept choice was logical, data-driven, and defensible.

3.2.1 Selection Criteria

To fairly and comprehensively evaluate the various concepts generated during brainstorming, a set of selection criteria was established. Each criterion directly addresses important functional, economic, or practical aspects of the project:

1. Safety Effectiveness
   - The primary purpose of the project is to prevent accidents due to the side stand being deployed during vehicle motion.
   - The selected concept must guarantee physical prevention of vehicle movement unless the side stand is retracted.
   - Concepts relying on rider attention alone were rated lower for this criterion.

2. Simplicity
   - The simpler a mechanism is, the more reliable it tends to be.
   - Mechanical simplicity reduces chances of malfunction, simplifies manufacturing, and improves ease of maintenance.
   - A simple design also ensures that installation and usage require minimal learning or technical expertise.

3. Cost Efficiency

- The concept must be low-cost both in terms of manufacturing and implementation.
- It should be affordable enough for mass production and adoption, particularly in price-sensitive markets where motorcycles are common.
- High-cost solutions like electronic sensors or hydraulics were considered less favorable.

4. Ease of Installation and Retrofitting

- Many motorcycles already in use may not have built-in safety systems.
- The solution should be easy to install both in existing motorcycles (retrofitting) and during new vehicle manufacturing.
- It should not require significant modification to the motorcycle's original structure or design.

5. Reliability and Durability

- The concept must be capable of withstanding regular use, harsh outdoor conditions (rain, dust, mud, heat), and rough handling.
- It should require minimal maintenance once installed and maintain functionality over the vehicle's lifetime.

6. User Friendliness

- The system should work automatically or intuitively, without requiring additional conscious effort from the rider during normal use.
- Riders should not feel inconvenienced or frustrated while operating the

system.

7. Maintenance Requirements

- The chosen concept should not introduce complex maintenance schedules or require frequent servicing.
- Long-term reliability with little to no user attention is essential for real-world success.

Weightage of Criteria

In addition to listing the criteria, different weightages were assigned to reflect their importance in the project:

Criteria	Weight (%)
Safety Effectiveness	30%
Simplicity	20%
Cost Efficiency	15%
Ease of Installation	15%
Reliability and Durability	10%
User Friendliness	5%
Maintenance Requirements	5%

This weighting helped in prioritizing solutions that emphasized safety and simplicity the most, in alignment with the project's ultimate purpose.

3.2.2 Comparison of Concepts

Once the selection criteria were finalized, a systematic comparison of the shortlisted concepts was performed to determine the most suitable solution for the project.

The two main concepts considered were:
Concept 1: Clutch Interlock Rod Mechanism
Concept 2: Spring-Loaded Automatic Retraction Stand

Each concept was analyzed carefully against the predefined selection criteria such as safety effectiveness, simplicity, cost efficiency, ease of installation, reliability, user friendliness, and maintenance requirements.

Comparison Overview:

Safety Effectiveness:

The clutch interlock rod mechanism provides a physical barrier to vehicle movement unless the side stand is retracted. It prevents clutch operation when the side stand is down, ensuring the motorcycle cannot move unintentionally.

In contrast, the spring-loaded stand relies on passive retraction, which might sometimes fail due to spring fatigue or partial engagement, reducing its reliability in critical moments.

Simplicity:

The rod mechanism offers a very straightforward mechanical linkage between the side stand and the clutch lever. The movement is direct and easy to understand.

The spring mechanism, while simple in appearance, requires precise spring calibration and might involve additional adjustments over time to maintain effectiveness.

Cost Efficiency:

Both concepts are relatively low-cost. However, the rod linkage uses standard materials (metal rods, bolts, simple brackets) that are cheaper and more durable than specially tensioned springs, which may vary in cost depending on the strength and material quality.

Ease of Installation and Retrofitting:

Installing the clutch interlock rod mechanism is relatively easy and can be done with basic tools. It requires attaching the rod securely between the stand and the clutch linkage with minimal alteration to the motorcycle frame.

The spring-loaded stand may require modification of the side stand pivot area, correct spring mounting, and careful adjustment, making installation slightly more complicated.

Reliability and Durability:

The mechanical rod system is highly durable, as it involves only solid mechanical parts with minimal wear and tear.

On the other hand, springs are prone to fatigue, loss of tension, corrosion, and eventual failure under prolonged use, especially under harsh environmental conditions.

User Friendliness:

With the clutch interlock rod, the system is automatic — the rider naturally retracts the side stand when engaging the clutch.

The spring system automatically retracts the stand when upright but might confuse users if the stand does not deploy properly on uneven surfaces, thus affecting parking stability.

Maintenance Requirements:

The rod system requires little to no maintenance after installation.

Springs may need periodic inspection and replacement over time, increasing the burden on maintenance.

Summary of Comparison:

- Spring-Loaded Stand is simpler and easier to install but less reliable and less safe.
- Gear Lever Lock is safer but much more complex and costly.
- Mechanical Bell Alarm is simpler and cheaper but depends on rider attention, making it unsafe.
- Clutch Interlock Rod offers a balanced performance: good safety, simplicity, durability, and no reliance on electronic systems.

3.2.3 Final Concept Selection

Based on the above comparison and scoring, the Clutch Interlock Rod Mechanism was selected as the final concept for the project.

This concept involves a physical mechanical connection between the side stand and the clutch lever or clutch cable system. When the side stand is

deployed (i.e., down), the rod prevents the clutch from being fully engaged, making it impossible to ride the motorcycle unless the stand is retracted.

Thus, it effectively forces the rider to retract the side stand before starting to move, ensuring safety without requiring any active reminder or reliance on rider attentiveness.

Advantages of Chosen Concept:

- Highest safety assurance: physically prevents vehicle motion.
- Mechanical simplicity: easy to manufacture and maintain.
- Low cost: affordable even for low-end motorcycles.
- Ease of retrofitting: adaptable to various existing models.
- Durability: functions well under different weather and road conditions.

The final selection reflects a balanced, realistic, and highly practical solution to the identified problem.

3.2.4 Justification for SelectedConcept

The selection of the Clutch Interlock Rod Mechanism is justified based on multiple strong points:

1. Safety Priority

This concept directly blocks movement without requiring the rider to pay attention or remember to retract the side stand.

It removes the human error element entirely, which is the primary cause of side-stand-related accidents.

2. Simplicity and Reliability

Purely mechanical systems are inherently reliable because they don't suffer from electrical faults, battery drain, or sensor misreadings.

Fewer moving parts also mean less wear and tear and long service life.

3. Low Cost and Accessibility

Manufacturing and installation costs are minimal, allowing mass deployment even in rural or budget-sensitive areas.

Parts used (steel rod, brackets) are widely available and cheap.

4. Compatibility

The system can be easily adapted to different motorcycles with minor adjustments, allowing widespread use without major redesigns.

Suitable for both older and new generation motorcycles without altering the existing vehicle architecture.

5. Maintenance-Free Operation

Once installed, the rod linkage system requires almost no maintenance apart from occasional visual inspection.

No lubrication, calibration, or adjustments are needed under normal conditions.

6. Better Parking Safety

Compared to spring-based stands that might retract unintentionally, this system ensures that parking stability is never compromised, as the stand remains firmly deployed when needed.

Thus, based on thorough engineering reasoning, practical

experience, and the goal of maximum road safety enhancement, the Clutch Interlock Rod Mechanism was conclusively selected as the most appropriate solution for the project.

CHAPTER - 4

FINAL PRODUCT SPECIFICATIONS & PROTOTYPING

4.1 Final Design Overview

The final product developed in this project is a mechanical safety enhancement system designed to prevent motorcycles from moving forward while the side stand is still deployed. The mechanism is simple, durable, and specifically crafted for low-cost implementation without compromising on effectiveness.

The core concept involves welding a rigid metal rod that acts as a physical linkage between the side stand and the clutch lever mechanism. This rod effectively locks the clutch lever's full operation when the side stand is down. Only when the side stand is retracted into its proper, safe position does the clutch lever regain its complete functional movement, thus allowing the vehicle to be operated normally.

Key Features of the Final Design:

Purely Mechanical Operation: No reliance on electrical systems, sensors, or hydraulic components, which increases system reliability and reduces the risk of failure.

Passive Safety System: The rider does not need to actively remember to retract the stand; the mechanism ensures that riding is impossible unless the stand is up.

Robust Construction: Made with durable materials (e.g., mild steel rods) that can withstand repeated use, harsh environmental conditions, and vibrations typical of motorcycle operation.

Ease of Retrofitting: The system can be installed easily on a wide range of existing motorcycles with minimal modification, making it accessible to a large market.

Maintenance-Free: After installation, the system requires little to no ongoing maintenance, contributing to overall ease of ownership.

Detailed Working Principle:

1. Side Stand in Deployed Position:

When the side stand is deployed, the rod interferes with the clutch lever mechanism. As a result, the rider cannot completely engage the clutch to shift into gear and move forward. This effectively prevents the motorcycle from being ridden with the stand down.

2. Side Stand Retracted:

When the rider manually lifts and retracts the side stand into the correct position, the rod shifts to a position that frees the clutch lever mechanism. This allows the clutch to be pressed fully, enabling normal riding operation.

3. Automatic Functionality:

The mechanism operates without requiring any special action from the rider beyond the standard side stand retraction motion. It is fail-safe by design, meaning that the safety feature is always active whenever needed.

Why This Design Was Chosen:

- Through extensive analysis and comparison of different concepts, this welded rod linkage system was chosen because it:
- Directly addresses the core safety issue.
- Introduces minimal changes to the original vehicle architecture.
- Ensures reliability and longevity.
- Keeps the overall project cost very low, making it ideal for mass application.
- Does not significantly affect the normal aesthetics or handling of the motorcycle.

By implementing this solution, the final product greatly enhances rider safety, particularly in situations where distractions, urgency, or carelessness might otherwise lead to accidents involving a deployed side stand.

4.2 Materials Used

In the development of the final prototype, material selection played a crucial role in ensuring the strength, durability, and cost-effectiveness of the safety mechanism. After considering several options, Mild Steel was selected as the primary material for fabricating the rod and associated components.

Material: Mild Steel

Mild Steel, also known as low carbon steel, was chosen because of its favorable mechanical properties and wide availability. It offers an excellent balance between strength, machinability, weldability, and cost, making it the ideal choice for automotive safety applications where heavy-duty performance is essential.

Properties of Mild Steel:

- ✡ Tensile Strength: Approximately 400–550 MPa, providing sufficient resistance to mechanical stress.
- ✡ Hardness: Reasonably hard to resist deformation but not brittle, ensuring flexibility under varying loads.
- ✡ Weldability: Mild Steel is highly weldable, allowing for strong, reliable joints with minimal risk of cracking or material weakening.
- ✡ Ductility: Good ductility enables the rod to endure slight flexing without breaking, important for a component exposed to constant vibrations.
- ✡ Corrosion Resistance: While Mild Steel is not highly corrosion-resistant by itself, it can easily be coated or painted to improve longevity.
- ✡ Cost: Mild Steel is affordable and readily available, helping to keep the overall project cost low.

Components and Materials Used:

1. Connecting Rod:
   - ➢ Material: Mild Steel
   - ➢ Purpose: To physically link the clutch lever mechanism to the side stand. The rod must be strong enough to withstand rider clutch operation forces

without bending.

2. Brackets and Mounting Clamps:
   - Material: Mild Steel flat bars
   - Purpose: To securely fasten the rod at critical points along the motorcycle chassis, ensuring stable positioning.
3. Welding Electrodes:
   - Material: Mild Steel compatible electrodes (E6013 or similar)
   - Purpose: Used for arc welding to join the rod firmly with the side stand assembly and clutch mechanism without compromising strength.
4. Surface Coating (Optional but Recommended):
   - Material: Anti-rust primer and black enamel paint
   - Purpose: To protect the mild steel components from environmental exposure, moisture, and prevent corrosion, thereby enhancing service life.

Why Mild Steel is Ideal for this Application:

- It can be easily bent, cut, and welded according to design needs.
- It maintains mechanical strength even after welding.
- It is cost-effective, supporting the project's objective to create an affordable safety solution.
- Surface protection (painting or galvanizing) is simple and inexpensive, ensuring good durability in real-world use.

4.3 Fabrication Process

The fabrication process forms the backbone of translating the proposed design into a functional prototype for enhancing two-wheeler safety. In this project, the main objective of fabrication was to create a direct mechanical linkage between the side stand and the clutch lever mechanism through a fixed rod system.

Every stage of fabrication was planned and executed carefully to ensure operational effectiveness, reliability, and long-term durability of the mechanism, especially considering the rough conditions motorcycles typically face on roads.

The fabrication process broadly involved the following phases:

- ✓ Planning and Design Preparation
- ✓ Material Preparation
- ✓ Rod Alignment and Trial Fitting
- ✓ Welding and Assembly
- ✓ Surface Finishing
- ✓ Installation and Testing

A systematic, step-by-step approach was necessary to ensure that the final assembly worked seamlessly without interfering with other components of the motorcycle.

Attention to detail at each step was critical to maintaining the integrity of the prototype and to guarantee smooth functioning throughout its operational life.

4.3.1 Design and Planning

Before beginning the physical fabrication, a detailed planning phase was undertaken.

Proper design and planning were essential to avoid errors during welding and assembly, and to ensure the mechanism worked as intended without causing obstruction to the rider or the motorcycle's existing systems.

Key Activities During Design and Planning:

- Assessment of Motorcycle Layout:

The side stand assembly, clutch lever mechanism, and surrounding parts were closely examined to identify a feasible path for the rod linkage. It was important to ensure that the rod could be installed without interfering with other critical components such as gear shift levers, footrests, or wiring harnesses.

- Determining Connection Points:

Suitable attachment points on both the side stand and the clutch assembly were selected. These points were chosen based on their mechanical strength, accessibility, and their ability to transmit movement efficiently from the side stand to the clutch lever.

- Movement Analysis:

The natural movement of the side stand and clutch lever was studied. It was necessary to understand how these two parts move independently so that the rod linkage could be designed to interact with them without causing excess strain, jamming, or misalignment.

- Load Considerations:

Basic load considerations were taken into account, such as the forces applied by the rider when using the clutch and when moving the side stand. The design needed to ensure that the linkage would not fail under normal operational stresses.

- Trial Simulations:

Before cutting or welding anything, simple manual simulations were performed. By using temporary fixtures like clamps and wires, a mock-up of the rod movement was created to observe how the clutch and side stand would behave together when linked.

- Finalizing Fabrication Approach:

After satisfactory mock-up results, the exact procedure for material

preparation, welding, and final installation was outlined. The decision was made to create a strong welded linkage, ensuring a permanent and maintenance-free setup.

4.3.2 Welding Process

Welding formed one of the most important steps in the fabrication of the side stand–clutch interlock mechanism. The quality of welding directly determined the strength, durability, and operational reliability of the entire system.

Key Steps in Welding:

- Positioning and Tack Welding:

Initially, the Mild Steel rod was positioned between the side stand and clutch connection points using temporary clamps. A few light tack welds were applied to hold the rod in place while allowing adjustments if needed.

This step was essential to ensure that the final positioning aligned correctly with the motion of both the clutch lever and the side stand.

- Alignment Check:

After tack welding, the movement of the side stand and clutch lever was manually tested. It was verified that:

- When the side stand was down, the rod restricted full clutch movement.
- When the side stand was up, the clutch operated freely without obstruction. If any misalignment was observed, the tack welds were reheated, and the rod was repositioned for perfect functionality.
- Full Welding:

Once the correct positioning was confirmed, full welding was performed along all joints.

Continuous weld beads were created around each joint to ensure a strong mechanical bond between the rod and the side stand and between any brackets added to the frame.

- Control of Heat Input:

Proper technique was used to avoid overheating, which could have caused warping of thin metal sections near the side stand pivot or clutch lever mounts.

The welding was done in short passes, allowing cooling periods between passes.

- Inspection After Welding:

After the welding cooled, all joints were visually inspected for common defects such as cracks, undercuts, or incomplete fusion. Minor touch-ups were carried out where needed to guarantee a smooth, defect-free weld.

The goal of the welding process was to ensure that the linkage was rigid, vibration-resistant, and capable of withstanding repeated operational cycles without failure.

4.3.3 Surface Finishing

After completing the welding process, surface finishing was carried out to enhance the appearance of the fabricated assembly and to protect it from environmental damage such as rust and corrosion.

Key Steps in Surface Finishing:

- Cleaning Welded Joints:

All welded areas were cleaned thoroughly using a wire brush and hand tools to remove welding slag, splatter, and any surface impurities.

- Grinding and Smoothing:

Grinding tools were used carefully to smooth the welded areas and eliminate sharp edges or rough surfaces that could pose safety risks or cause mechanical interference.

The grinding also helped to give the final assembly a neat and professional appearance.

- Surface Preparation for Painting:

The entire linkage assembly, including the welded rod and any mounting brackets, was cleaned with a degreasing agent to remove oil, dust, or debris. This step ensured good adhesion of the paint.

- Rust Protection:

An anti-rust primer was applied to the cleaned metal surfaces. The primer served as a barrier against moisture and atmospheric oxygen, significantly reducing the risk of rust formation over time.

- Painting:

After the primer dried, a coat of durable enamel paint was applied to the assembly.

The paint used was weather-resistant to withstand exposure to rain, mud, and heat during regular motorcycle use.

- Final Touch-Ups:

After the paint dried, the assembly was inspected, and any uncoated areas were touched up manually to ensure full coverage and a uniform finish.

Surface finishing not only improved the aesthetics of the system but also ensured that the fabricated parts could survive long-term usage without degradation or performance loss.

4.3.4 Installation on Motorcycle

After fabrication and surface finishing, the next critical phase was the installation of the mechanism onto the motorcycle.

Proper installation was essential to ensure that the newly fabricated side stand–clutch interlock system performed its intended function effectively without hindering any of the motorcycle’s existing controls.

Key Steps in Installation:

Mounting the Fabricated Rod Assembly:

The rod assembly was carefully aligned between the side stand and the clutch lever mechanism.

Care was taken to fit it naturally into the motorcycle's frame layout without interfering with the rider’s legs, wiring, or other mechanical parts.

Secure Fastening:

Brackets or anchor points, if fabricated along with the rod, were securely fastened to the motorcycle chassis and clutch assembly.

Where necessary, bolts, nuts, and washers were used to add extra mechanical security along with welding joints.

Movement Testing:

Once installed, the movement of both the side stand and clutch lever was checked manually:

When the side stand was in the down position, the linkage prevented the clutch lever from being fully pressed, thus stopping the rider from engaging gears.

When the side stand was retracted to the up position, the clutch movement was fully free and smooth, allowing normal gear engagement.

Adjustment and Fine-Tuning:

Minor adjustments were made to ensure:

The rod tension was appropriate (neither too tight nor too loose).

The clutch lever felt natural in the hand without unexpected resistance when the stand was up.

No unnecessary friction or stress was generated on the clutch cable or side stand spring.

Clearance Checking:

Finally, it was confirmed that there was enough clearance between the rod and other moving parts such as the foot peg, brake pedal, and gear shifter.

The installation was done meticulously to ensure that the rider could operate the vehicle comfortably and that the safety system would not cause any accidental hindrance during riding.

4.3.5 Final Inspection and Quality Check

After installation, a comprehensive inspection and testing phase was conducted to verify the proper functioning and reliability of the entire system.

This phase was essential to ensure that the prototype would deliver consistent performance over time and under real-world riding conditions.

Key Activities During Final Inspection:

Operational Testing:

The motorcycle was tested in a stationary position first.

Multiple cycles of deploying and retracting the side stand were

performed while engaging and disengaging the clutch lever to ensure consistent functionality.

Road Testing:

Short rides were conducted to observe the performance during actual motorcycle movement.

The rider attempted to start the bike with the side stand down — the system successfully restricted clutch engagement, thereby preventing unintended motion.

Strength Testing:

Moderate force was applied manually on the rod to test the strength of welds and joints.

The rod remained firm without any sign of bending, cracking, or loosening.

Safety Evaluation:

- It was confirmed that the system did not pose any safety hazard.
- It did not interfere with the rider's natural posture or foot movements.
- It did not obstruct any regular maintenance tasks such as lubricating the chain or adjusting the gear shifter.

Visual Inspection:

- A detailed visual inspection was carried out to ensure:
- Proper paint coverage (no exposed bare metal prone to rust).
- Welds were intact and free from cracks or defects.

- No sharp edges or projections were present that could harm the rider or mechanic.

Documentation:

Observations, test results, and any minor issues encountered during installation and testing were recorded for future reference and further design improvements if needed.

4.4 Working Principle of Prototype

The working principle of the fabricated side stand–clutch safety mechanism is based on a mechanical interlock system that physically restricts the operation of the clutch when the side stand is deployed (down) and allows normal clutch operation when the side stand is retracted (up).

This ensures that the motorcycle cannot move forward under its own power unless the side stand has been properly disengaged, thereby greatly enhancing rider safety.

Core Idea:

- A rigid Mild Steel rod is permanently connected between the side stand and the clutch lever mechanism.
- The position of the side stand directly influences the clutch lever's freedom of movement.
- This mechanical connection ensures no reliance on electronics or sensors — making the system simple, durable, and low-maintenance.

Step-by-Step Working:

1. Side Stand Down (Deployed Position):
   - When the rider forgets to retract the side stand, the rod linkage restricts the clutch lever movement.
   - As a result, the rider is unable to fully engage the clutch, preventing the motorcycle from being shifted into gear or starting to move.
   - The resistance at the clutch lever immediately alerts the rider that an action (retracting the side stand) is required before proceeding.
   - This physical feedback acts as a safety reminder without the need for electronic alarms or indicators.
2. Side Stand Up (Retracted Position):
   - When the side stand is fully retracted, the rod linkage relieves the restriction on the clutch lever.
   - The clutch operates smoothly and normally, allowing the rider to engage gears and ride as usual.
   - No resistance is felt in the clutch lever, and the motorcycle can be started and operated safely.

4.5 Testing of Prototype

After the fabrication and installation of the side stand–clutch interlock mechanism, a structured testing process was carried out to validate its functionality, reliability, and real-world performance.The purpose of testing was to ensure that the system worked consistently under various conditions and fulfilled the objective of enhancing rider safety.

Testing was conducted in both static (stationary) and dynamic (riding) conditions to simulate real operational environments.

4.5.1 Static Testing

Static testing involved evaluating the mechanism's performance while the motorcycle was stationary.

Testing Procedures:

Side Stand Deployed:

- With the side stand in the down position, attempts were made to press the clutch lever and shift the gear.
- It was observed that the clutch lever movement was mechanically restricted, preventing full clutch engagement and thus preventing the bike from being moved forward.

Side Stand Retracted:

When the side stand was lifted into the retracted position, the clutch lever returned to normal free movement, and gear shifting was possible without any obstruction.

Repeated Cycle Test:

- The side stand was moved up and down repeatedly, and each time the linkage correctly restricted or freed the clutch lever as intended.
- No misalignment, loosening, or malfunctioning was observed after multiple cycles.

Mechanical Inspection:

Visual inspection was done to check for any signs of fatigue, bending, or wear in the rod and welded joints after repeated testing.

4.5.2 Dynamic Testing (Road Testing)

Dynamic testing involved testing the motorcycle in motion to observe the system's performance under real riding conditions.

Testing Procedures:

Attempting to Ride with Side Stand Down:

When the rider attempted to move the motorcycle with the side stand down, the clutch lever restriction prevented proper engagement of gears, thereby alerting the rider immediately.

Normal Riding with Side Stand Up:

- With the side stand retracted, the motorcycle operated normally without any issues.
- Gear shifting and clutch operation were smooth, with no unusual resistance or mechanical noise.

Vibration and Load Testing:

- The motorcycle was driven over uneven surfaces and speed breakers to check if vibrations affected the rod linkage.
- The system remained intact, and there was no loosening or malfunction due to road vibrations.

CONCLUSION

The primary objective of this project was to design and implement a simple, reliable, and effective mechanical system to prevent motorcycle accidents caused by unretracted side stands. Through the fabrication of a Mild Steel rod linkage connecting the side stand to the clutch lever, we successfully created a mechanical interlock mechanism that enhances rider safety without the need for complex electronics or sensors.

The working principle was based on physically restricting clutch movement when the side stand was deployed, thus preventing the rider from engaging gears and starting the motorcycle inadvertently. The mechanism was fabricated with careful material selection, precision welding, and proper surface finishing to ensure durability, strength, and long-term performance.

The prototype underwent rigorous static and dynamic testing. The results clearly demonstrated that the system effectively:

- Prevented vehicle movement with the side stand down.
- Allowed normal clutch operation when the side stand was retracted.
- Remained reliable under real-world riding conditions and vibrations.
- Required minimal maintenance due to its simple mechanical

design.

This project highlights how a low-cost, easy-to-implement safety solution can significantly reduce the risk of accidents caused by human negligence or distraction.

It also emphasizes the importance of design thinking focused on rider behavior and real-world usage.

In conclusion, the fabricated side stand–clutch lock mechanism achieved all its intended objectives. It provides a practical, robust, and user-friendly solution that can be further refined and adapted for a wide range of two-wheeled vehicles to promote safer riding practices.

REFERENCES

1. Practical implementation and fabrication experience gained during the development of the side stand–clutch lock mechanism.

2. Motorcycle maintenance manuals and service handbooks referred for understanding side stand mechanisms and clutch system layouts (e.g., Hero, Honda, Bajaj models).

3. Design of Machine Elements by V.B. Bhandari – for material selection (Mild Steel) and mechanical linkage design fundamentals.

4. A Textbook of Machine Design by R.S. Khurmi and J.K. Gupta – for welding practices, load considerations, and mechanical joint reliability.

5. Observations from real-world motorcycle accidents caused due to unretracted side stands, collected from local service centers and rider feedback.