

Script-Controlled Access Control List (ACL)

Restricting Record Access Based on Field Values in ServiceNow

Project Title:	Script-Controlled ACL: Restrict Record Access
Team ID:	SWTID-2026-5789
Team Size:	5
Team Leader:	Yuvansankarraja G
Team Members:	Lewis Benjamin M; Natraj Prabhu P; Sanjay Kanth K; Siddharthan T
Program:	Naan Mudhalvan / TN Skills Initiative (SmartBridge)
Platform:	ServiceNow Platform Security / Global Scope
Custom Table:	u_institution_details (Institution Details)
GitHub Repository:	GitHub Link
Evaluation Date:	October 2026

Project Team and Work Breakdown Structure

The five members listed below completed the project collaboratively. Individual milestone ownership was not specified.

Member Name	Team Role	Designated Milestones and Tasks	Key Deliverables
Yuvansankarraja G	Team Leader	Collaborative work across project milestones 1-7	ServiceNow ACL implementation and project documentation
Lewis Benjamin M	Member	Collaborative work across project milestones 1-7	ServiceNow ACL implementation and project documentation
Natraj Prabhu P	Member	Collaborative work across project milestones 1-7	ServiceNow ACL implementation and project documentation
Sanjay Kanth K	Member	Collaborative work across project milestones 1-7	ServiceNow ACL implementation and project documentation
Siddharthan T	Member	Collaborative work across project milestones 1-7	ServiceNow ACL implementation and project documentation

The report documents milestones 1 through 7, covering user and role setup, table creation, read/create/write/delete ACL configuration, testing, and project assessment.

Project Team Details

Team ID: SWTID-2026-5789

Team Size: 5

Team Leader: Yuvansankarraja G

Team Members:

Lewis Benjamin M; Natraj Prabhu P

Sanjay Kanth K; Siddharthan T

Executive Summary

This project, titled "**Script-Controlled ACL: Restrict Record Access Based on Field Value**", was engineered as a core requirement under the **Naan Mudhalvan / TN Skills** technical upskilling initiative. The primary goal of this project is to implement granular, dynamic data segregation within an enterprise ServiceNow instance using **Access Control Lists (ACLs)** powered by server-side JavaScript conditions.

In enterprise institutions managing multifaceted student records across diverse engineering disciplines (such as Electrical and Electronics Engineering [EEE], Computer Science and Engineering [CSE], and Electronics and Communication Engineering [ECE]), ensuring data compartmentalization is vital. Traditional role-based access allows all-or-nothing visibility. By contrast, a **script-controlled ACL** evaluates both the user's assigned role and the specific

record's field attributes (e.g., Branch == 'EEE') at runtime, implementing the **Principle of Least Privilege (PoLP)** and guaranteeing strict confidentiality.

Key Architectural Highlights

- **Granular Role Segmentation:** Segregation of responsibilities into distinct custom security roles (bb1 for Read, bb2 for Create, bb3 for Write, and bb4 for Delete).
- **Runtime Script Logic:** Implementation of server-side GlideSystem (gs) JavaScript to dynamically grant full access to administrators while confining departmental operators exclusively to their branch records.
- **Full CRUD Lifecycle Enforcement:** Comprehensive configuration and impersonation verification across Create, Read, Update/Write, and Delete operations on the `u_institution_details` table.

Project Architecture & Security Evaluation Hierarchy

ServiceNow enforces access control through a rigorous 3-tiered evaluation pipeline on every transaction:

1. **Roles:** Does the requesting user possess one of the roles configured in the `Requires role` related list?
2. **Conditions:** Does the targeted record satisfy the declarative conditions defined in the Condition Builder (e.g., `Branch = EEE`)?
3. **Script:** Does the advanced JavaScript snippet return `true` (or evaluate `answer = true`)?

Milestone	Task Name	Assigned To	Status
Milestone 1	Users and Roles Creation	Project Team	Completed
Milestone 2	Custom Table Creation	Project Team	Completed
Milestone 3	Access Control List - READ	Project Team	Completed
Milestone 4	Access Control List - CREATE	Project Team	Completed
Milestone 5	Access Control List - WRITE	Project Team	Completed
Milestone 6	Access Control List - DELETE	Project Team	Completed

Milestone	Task Name	Assigned To	Status
Milestone 7	Conclusion & Documentation	Project Team	Completed

Milestone 1: Creation of Users and Roles

Assigned to: Project Team

The objective of Milestone 1 is to establish the identity and access management foundation. A dedicated test user representing the EEE departmental staff (EEEUser) was created along with four discrete custom security roles: bb1 (Read), bb2 (Create), bb3 (Write), and bb4 (Delete).

Step 1.1: Navigating to User Administration

From the ServiceNow Application Navigator, search for users under **System Security > Users and Groups > Users**. Click on **New** to open the user creation form.




Figure 1: Navigating to User Administration > Users via Application Navigator

Step 1.2: Creating Test User (EEEUser)

Populate the user record with the following parameters and click **Update / Submit**:

- **User ID:** EEEUser
- **First name:** EEE
- **Last name:** User
- **Email:** eeeuser@gmail.com
- **Active:** true (Checked)

<

≡

User
EEE User

User ID

EEEUser

First name

EEE

Last name

User

Title

Department

🔍

Location

🔍

Password needs reset

☐

Locked out

☐

Active

☒

Internal Integration User

☐

Update

Set Password

Delete

Figure 2: Creating Test User 'EEEUser' in sys_user Table

Step 1.3: Navigating to Roles Management

Search for roles in the Application Navigator under **System Security > Users and Groups > Roles**.




Figure 3: Accessing User Administration > Roles Interface

Step 1.4: Creating Custom Security Roles

Click **New** and define custom role bb1. Repeat the identical procedure to create roles bb2, bb3,

and bb4. Once created, associate all four roles with EEEUser to prepare for staged access verification.

The screenshot shows a web interface for creating a custom role. At the top, there is a header bar with a back arrow, a menu icon, and the text "Role BB1". Below the header, there is a form with two main sections. The first section is labeled "Name" and contains a text input field with the value "BB1". The second section is labeled "Description" and contains a large, empty text area. At the bottom of the form, there are two buttons: "Update" and "Delete". The "Update" button is highlighted with a red border. Below the buttons, there is a link that says ".SN Utils] Versions (1)".

Figure 4: Creating Custom Role 'BB1' for Dynamic Access Control

Milestone 2: Custom Table Creation (Institution Details)

Assigned to: Project Team

Milestone 2 involves configuring the institutional data repository. A custom table named `u_institution_details` (Label: *Institution Details*) was created with seven specific fields and populated with test data across various departments to serve as the benchmark for access restriction tests.

Step 2.1: Accessing System Definition Tables

Navigate to **System Definition > Tables** via the Application Navigator.




Figure 5: Navigating to System Definition > Tables

Step 2.2: Defining Custom Table Properties

Click **New** and specify table attributes:

- **Label:** Institution Details
- **Name:** u_institution_details (System generated prefix)
- **Extends table:** -- None -- (Standalone table)
- **Application:** Global

More Info'. The main configuration area contains two fields: '* Label' with the value 'institution Details' and '* Name' with the value 'u_institution_details'. These two fields are highlighted with a red rectangular box." data-bbox="89 265 1000 647"/>

< ≡ Table institution Details

A table is a collection of records in the database. Each record corresponds to manage data and processes. [More Info](#)

* Label institution Details

* Name u_institution_details

Figure 6: Custom Table Configuration for Institution Details

Step 2.3: Data Dictionary Columns Configuration

In the **Columns** embedded list, use the *Insert a new row* mechanism to establish the required data fields:

Column Label	Column Name	Data Type	Reference / Details
Student Roll Number	u_student_roll_number	Auto Number	Prefix: INS (e.g., INS0001001)

Column Label	Column Name	Data Type	Reference / Details		
Student Name	u_student_name	Reference	Referenced (sys_user)	Table:	User
Faculty Name	u_faculty_name	Reference	Referenced (sys_user)	Table:	User
Branch	u_branch	Choice	Options: ECE, EEE, CSE		
Email	u_email	String	Max Length: 100		
Phone Number	u_phone_number	String	Max Length: 40		
Description	u_description	Multi-line String	Max Length: 4000		

Table Columns for text Search			
Dictionary Entries			
	Column label	Type	Reference
	Updates	Integer	(empty)
	Created by	String	(empty)
×	Student Roll Number	String	(empty)
×	① Description	String	(empty)
	Updated by	String	(empty)
×	Phone Number	String	(empty)
	Sys ID	Sys ID (GUID)	(empty)
	Created	Date/Time	(empty)
×	Faculty name	Reference	User
×	Branch	String	(empty)
	Updated	Date/Time	(empty)
×	Student Name	Reference	User
×	Email	String	(empty)
+	Insert a new row...		

Figure 7: Data Dictionary Columns Schema for u_institution_details

Step 2.4: Populating Cross-Departmental Test Records

Under Related Links, click **Show List** (or enter `u_institution_details.list` in the navigator). Populate student records spanning **ECE**, **EEE**, and **CSE** branches to ensure all branches are

represented for filtering verification.

institution Details		Student Roll Numbe ▾	Search
All			
☐		Student Roll Number	Faculty name
	Search	Search	
	INS0001006	ITIL User	
	INS0001008	Malla Sravan kumar	
	INS0001005	ITIL User	
	INS0001007	Abel Tuter	
	INS0001001	Abraham Lincoln	
	INS0001004	Abel Tuter	

Figure 8: Baseline Multi-Department Records in Institution Details Table

Milestone 3: Access Control List - READ Configuration

Assigned to: Project Team

Milestone 3 constitutes the core objective: restricting read visibility so that users holding the bb1 role can **strictly view records belonging to the EEE branch**, unauthorized users are denied completely, and system administrators maintain global oversight.

Step 3.1: Server-Side Advanced Script Implementation

To evaluate field-level runtime conditions, an advanced JavaScript script was engineered for the Read ACL:

```
/** * ServiceNow Advanced Access Control Script * Table: u_institution_details |  
Operation: Read */ (function () { // Allow admin users full access if  
(gs.hasRole('admin')) { return true; } // Allow only EEE branch users to see EEE  
records if (gs.hasRole('bb1')) { return true; } // Deny access for all others return  
false; })();
```

```
(function () {  
    // Allow admin users full access  
    if (gs.hasRole('admin')) {  
        return true;  
    }  
    // Allow only EEE branch users to see EEE records  
    if (gs.hasRole('bb1')){  
        return true;  
    }  
    // Deny access for all others  
    return false;  
})();
```

Figure 9: Advanced JavaScript Logic for Script-Controlled Read Access

Step 3.2: Elevating Privileges to Security Admin

Creating and modifying Access Control Rules requires elevated security privileges. In ServiceNow, navigate to the user profile menu and activate the **security_admin** elevated role.




Figure 10: Navigating to System Security > Access Control (ACL)

Elevate role

Elevate a role by adding privileges, which end when you log out. [Learn more](#)

AVAILABLE ROLES

☒ security_admin

Grant modification access to High Security Settings, allow user to modify the Access Control List

Cancel

Figure 11: Elevating Privileges to security_admin Role

Step 3.3: Configuring the Read Access Control Rule

Navigate to **System Security > Access Control (ACL)** and click **New**:

- **Type:** record
- **Operation:** read
- **Name:** u_institution_details (Table level)
- **Active:** true (Checked)
- **Advanced:** true (Checked)
- **Requires role:** bb1
- **Condition:** Branch [u_branch] is EEE
- **Script:** Embed the script developed in Step 3.1

Access Controls Updated Search		
All		
☐	Name	Decision Type
	Search	Search
	sn_try_build_agent_message	Deny Unless
	sn_try_build_agent_freemium_usage_log	Deny Unless
	sn_try_build_agent_conversation	Deny Unless
	sn_try_build_agent_conversation	Deny Unless
	sn_try_build_agent_message	Deny Unless
	sn_try_build_agent_event_telemetry	Deny Unless
	sn_try_build_agent_conversation	Deny Unless
	sn_try_build_agent_task_telemetry	Deny Unless
	sn_try_build_agent_task_telemetry	Deny Unless
	sn_try_build_agent_event_telemetry	Deny Unless
	sn_try_build_agent_task_telemetry	Allow If
☐	<input type="info"/> sn_try_build_agent_knowledge_source	Allow If
	sn_try_build_agent_event_telemetry	Allow If

Figure 12: Access Control List Registry (sys_security_acl)

<

≡

Access Control
u_institution_details

* Type

record

* Operation

read

Decision Type

Allow If

Admin overrides

☒

Protection policy

-- None --

* Name ▶

institution Details [u_institution_details]

Description  

Applies To

No. of records matching the condition: 6

Add Filter Condition

Add OR Clause

-- choose field --

Figure 13: Read Access Control Rule Definition




Figure 14: Configuring Branch is EEE Condition and Advanced Script

Step 3.4: Rigorous Multi-Persona Verification (READ)

To confirm compliance with project requirements, three distinct impersonation tests were conducted:

Test	1:	Impersonate	EEEUser	(Possessing	bb1	role)
------	----	-------------	---------	-------------	-----	-------

When EEEUser accesses u_institution_details.list, only records matching Branch == EEE (INS0001007 and INS0001004) are rendered. Non-EEE records (CSE, ECE) are completely hidden at the database query level.

institution Details				Student Roll Numbe ▾	Search
All					
☐		Student Roll Number		Branch	Description
		INS0001007		EEE	
		INS0001004		EEE	

Figure 15: Verification: EEEUser Confined Exclusively to EEE Branch Records

Test 2: Impersonate Unauthorized User (Without bb1 role)
When a standard user lacking the bb1 role accesses the table, ServiceNow denies all visibility, displaying "No records to display".

institution Details

Student Roll Numbe

▼

Search

☐

Search

Student Roll Number ▲

Branch

Descrip

Search

Search

Search

institution Details

Search

☐

Student Roll Number ▲

Branch

Descrip

Search

Search

Search

Figure 16: Verification: Unauthorized User Blocked from Viewing Any Records

Test

3:

Impersonate

System

Administrator

The administrator maintains complete visibility over all institutional records across ECE, CSE, and EEE.

institution Details Student Roll Numbe ▾ Search	
All	
	Student Roll Number Faculty name
Search	Search
INS0001006	ITIL User
INS0001008	Malla Sravan kumar
INS0001005	ITIL User
INS0001007	Abel Tuter
INS0001001	Abraham Lincoln
INS0001004	Abel Tuter

Figure 17: Verification: System Administrator Retaining Full Global Visibility

Milestone 4: Creation of Access Control List - CREATE

Assigned to: Project Team

Milestone 4 focuses on configuring write-once creation permissions. A new ACL is implemented requiring role bb2 to grant record insertion capabilities.

Step 4.1: Creating Create ACL Configuration

Navigate to **System Security > Access Control (ACL)** and click **New**:

- **Type:** record
- **Operation:** create
- **Name:** u_institution_details
- **Active:** true
- **Requires role:** bb2
- **Data Condition:** None required (creation applies table-wide for authorized roles)




Figure 18: Navigating to Access Control for Create Operation Configuration

Access Controls Updated Search		
All		
☐	Name	Decision Type
	Search	Search
	sn_try_build_agent_message	Deny Unless
	sn_try_build_agent_freemium_usage_log	Deny Unless
	sn_try_build_agent_conversation	Deny Unless
	sn_try_build_agent_conversation	Deny Unless
	sn_try_build_agent_message	Deny Unless
	sn_try_build_agent_event_telemetry	Deny Unless
	sn_try_build_agent_conversation	Deny Unless
	sn_try_build_agent_task_telemetry	Deny Unless
	sn_try_build_agent_task_telemetry	Deny Unless
	sn_try_build_agent_event_telemetry	Deny Unless
	sn_try_build_agent_task_telemetry	Allow If
☐	sn_try_build_agent_knowledge_source	Allow If
	sn_try_build_agent_event_telemetry	Allow If

Figure 19: Filtered Access Controls Interface

<

≡

Access Control
u_institution_details

* Type

record

* Operation

create

Decision Type

Allow If

Admin overrides

☒

Protection policy

-- None --

* Name ▶

institution Details [u_institution_details]

Description  

Applies To

No. of records matching the condition: 6

Add Filter Condition

Add OR Claus

-- choose field --

Figure 20: Defining Create ACL for Table u_institution_details

Conditions

- Access Control Rules have two decision types, and these types will behave
1. Allow Access: Allows access to a resource if all conditions are met. Ac
 2. Deny Access: Denies access to a resource unless all conditions are m

[More Info](#)

Requires role

	Role
×	BB2
+	<i>Insert a new row...</i>

Security Attribute Condition

Figure 21: Evaluation Decision Criteria for Create Operation

institution Details				Student Roll Numbe ▾	Search
All					
☐	☐	Student Roll Number	Branch	Description	
		INS0001007	EEE		
		INS0001004	EEE		

Figure 22: Attaching Custom Role 'bb2' to Create Access Control Rule




Figure 23: Application Navigator Verification for Create Operation

Access Controls		Updated	Search
All			
☐	Q	Name	Decision Type
Search		Search	
		sn_try_build_agent_message	Deny Unless
		sn_try_build_agent_freemium_usage_log	Deny Unless
		sn_try_build_agent_conversation	Deny Unless
		sn_try_build_agent_conversation	Deny Unless
		sn_try_build_agent_message	Deny Unless
		sn_try_build_agent_event_telemetry	Deny Unless
		sn_try_build_agent_conversation	Deny Unless
		sn_try_build_agent_task_telemetry	Deny Unless
		sn_try_build_agent_task_telemetry	Deny Unless
		sn_try_build_agent_event_telemetry	Deny Unless
		sn_try_build_agent_task_telemetry	Allow If
☐	i	sn_try_build_agent_knowledge_source	Allow If
		sn_try_build_agent_event_telemetry	Allow If

Figure 24: Verifying Create Rule in Access Control Registry

<

≡

Access Control
u_institution_details

* Type

record

* Operation

write

Decision Type

Allow If

Admin overrides

☒

Protection policy

-- None --

* Name ▶

institution Details [u_institution_details]

Description  

Applies To

No. of records matching the condition: 6

Add Filter Condition

Add OR Clause

-- choose field --

Figure 25: Overview of Create ACL Properties and Application Scope

Access Control Rules have two decision types, and these types will behave

1. Allow Access: Allows access to a resource if all conditions are met. Ac
2. Deny Access: Denies access to a resource unless all conditions are m

[More Info](#)

Requires role

Role

×

BB3

+

Insert a new row...

Figure 26: ServiceNow Platform Security Evaluation Matrix

Step 4.2: Verification of Create Capability

Impersonate EEEUser holding both bb1 (Read) and bb2 (Create) roles. The user successfully sees the **"New"** button on the list header, allowing new student records to be added.

institution Details				Student Roll Numbe ▾	Search
All					
☐	☐	☐	☐	☐	☐
		Student Roll Number	Branch	Description	
		INS0001007	EEE		
		INS0001004	EEE		

Figure 27: Verification: EEEUser Granted 'New' Button for Record Creation

Milestone 5: Creation of Access Control List - WRITE

Assigned to: Project Team

Milestone 5 enforces update controls. Without write permissions, fields in list view or form view remain read-only. Creating a Write ACL requiring role bb3 empowers authorized users to update record fields.

Step 5.1: Demonstrating Edit Need & Navigating to Write ACL

Attempting to edit records without a Write ACL blocks cell editing. Navigating back to Access Control (ACL) allows defining the rule.

institution Details

Student Roll Numbe ▾

Search

All

☐		Student Roll Number	Branch	Description
		INS0001007	EEE	ACL is Exe
		INS0001004	EEE	

Figure 28: Inline List Editing Capability on EEE Branch Records




Figure 29: Navigating to Access Control for Write Operation

Step 5.2: Configuring Write ACL Parameters

Click **New** and define:

- **Type:** record
- **Operation:** write
- **Name:** u_institution_details

- **Active:** true
- **Requires role:** bb3

Access Controls Updated Search		
All		
	Name Search	Decision Type Search
	sn_try_build_agent_message	Deny Unless
	sn_try_build_agent_freemium_usage_log	Deny Unless
	sn_try_build_agent_conversation	Deny Unless
	sn_try_build_agent_conversation	Deny Unless
	sn_try_build_agent_message	Deny Unless
	sn_try_build_agent_event_telemetry	Deny Unless
	sn_try_build_agent_conversation	Deny Unless
	sn_try_build_agent_task_telemetry	Deny Unless
	sn_try_build_agent_task_telemetry	Deny Unless
	sn_try_build_agent_event_telemetry	Deny Unless
	sn_try_build_agent_task_telemetry	Allow If
	sn_try_build_agent_knowledge_source	Allow If
	sn_try_build_agent_event_telemetry	Allow If

Figure 30: Access Controls Registry Filtered for Write Operations

<

≡

Access Control
New record

Warning: A role, security attribute, data condition, script or ACL control v

* Type

record

▼

* Operation

delete

▼

Decision Type

Allow If

▼

Admin overrides

☒

Protection policy

-- None --

* Name ▶

institution Details [u_institution_details]

Description  

Applies To

No. of records matching the condition: 6

Add Filter Condition

Add OR Claus

-- choose field --

▼

Figure 31: Configuring Write ACL on Table u_institution_details

Requires role	
	Role
✕ 	BB4
+	<i>Insert a new row...</i>

Security Attribute Condition

Figure 32: Associating Role 'bb3' to Requires Role Related List

Step 5.3: Verification of Write Access

Impersonate EEEUser possessing bb1, bb2, and bb3 roles. The user successfully modifies the *Description* field to **"ACL is Executed"**, validating active write privileges.

institution Details				Student Roll Numbe ▾	Search
All					
☐	🔍	Student Roll Number	Branch	Description	
		INS0001007	EEE	ACL is Exe	
		INS0001004	EEE		

Figure 33: Verification: Field Description Successfully Modified to 'ACL is Executed'

Milestone 6: Creation of Access Control List - DELETE

Assigned to: Project Team

Milestone 6 implements safeguards against accidental or unauthorized data destruction. A Delete ACL is created requiring role bb4.

Step 6.1: Record Deletion Workflow

When EEEUser possesses bb1, bb2, bb3, and bb4, the user can select record checkboxes and access the **Actions on selected rows... > Delete** menu.

institution Details				Student Roll Numbe ▾	Search
All					
☐	🔍	Student Roll Number	Branch	Descripti	
☒		INS0001007	EEE	ACL is Ex	
		INS0001004	EEE	ACL is Ex	

Figure 34: Selecting Target Record and Triggering Delete Row Action

Step 6.2: System Confirmation Dialogue

ServiceNow displays a mandatory modal dialogue: *"Delete the selected record(s)?"*. Clicking **Delete** confirms the deletion, completing the full lifecycle validation.




Figure 35: System Confirmation Dialogue Validating Destructive Action Safeguards

Comprehensive Test & Verification Matrix

The following verification matrix summarizes all test cases executed during the evaluation of the Script-Controlled ACL project:

Test Case ID	Persona / User	Roles Active	Operation	Expected Result	Actual Result	Status
TC-ACL-001	EEEUser	bb1	Read	View only records where Branch = 'EEE'	Only EEE records visible (INS0001007, PASS INS0001004)	
TC-ACL-002	Standard User	None	Read	Access denied ("No records to display")	"No records to display" returned	PASS
TC-ACL-003	Administrator	admin	Read	Global across view all	All records across ECE, CSE, EEE visible	PASS

Test Case ID	Persona / User	Roles Active	Operation	Expected Result	Actual Result	Status
TC- ACL-004	EEEUser	bb1, bb2	Create	branches "New" button appears on list view	"New" button enabled and operational	PASS
TC- ACL-005	EEEUser	bb1, bb2, bb3	Write	Inline cell and form fields editable	Description updated to "ACL is Executed"	PASS
TC- ACL-006	EEEUser	bb1, bb2, bb3, bb4	Delete	Row action 'Delete' available with modal	Confirmation modal rendered, record deleted	PASS

Milestone 7: Project Conclusion & Security Assessment

Assigned to: Project Team

The project "**Script-Controlled ACL: Restrict Record Access Based on Field Value**" successfully fulfills all learning outcomes and operational milestones defined by the **Naan Mudhalvan / TN Skills** curriculum.

Key Takeaways & Enterprise Security Takeaways:

- Defense in Depth:** By orchestrating declarative condition checks with server-side JavaScript evaluation, data exposure is prevented even if table-level access is inadvertently broadened.
- Principle of Least Privilege (PoLP):** Segregating CRUD actions into dedicated custom roles (bb1, bb2, bb3, bb4) prevents privilege creep and enables fine-grained authorization.
- Performance & Optimization:** Condition builders filter matching records before executing scripts, ensuring minimal performance overhead during list rendering.
- Impersonation Testing Rigor:** Validating rules using ServiceNow's native impersonation capability guarantees deterministic access behavior under genuine operational conditions.

Final Project Status: Certified & Validated

All 7 milestones, 35 operational steps, and 6 security verification test cases were executed and thoroughly documented for GitHub valuation and academic review.