

The first line of input contains an integer representing the number of pages in the reference string. \

The second line contains the page reference string as a sequence of integers.

The third line contains an integer representing the number of available frames.

Output Format

The output displays the total number of Page Faults and the total number of Page Hits after processing the entire reference string using the LRU page replacement algorithm.

Sample Input 1

5

1 2 3 4 5

5

Sample Output 1

Enter number of pages in reference string:

Enter the reference string:

Enter number of frames:

Total Page Faults: 5

Total Page Hits: 0

How it works

Step	Page	Frame State	Hit/Miss
1	1	1 - - - -	Fault
2	2	1 2 - - -	Fault
3	3	1 2 3 - -	Fault
4	4	1 2 3 4 -	Fault
5	5	1 2 3 4 5	Fault

Select Language : C (GCC 9.2.0)

```
1 #include <stdio.h>
2
3 int main() {
4     int n, frames;
5
6     printf("Enter number of pages in reference string: \n");
7     scanf("%d", &n);
8
9     int pages[n];
10    printf("Enter the reference string: \n");
11    for(int i = 0; i < n; i++) {
12        scanf("%d", &pages[i]);
13    }
14
15    printf("Enter number of frames: \n");
16    scanf("%d", &frames);
17
18    int frame[frames], lastUsed[frames];
19    int hits = 0, faults = 0;
```

Test Cases 2

Run Sample Cases

Run All Cases

Custom Test Case

> Custom Test

Sample Test Case

> Test Case - 1

> Test Case - 2