```
src_ip = socket.inet_ntoa(iph[8])
dest_ip = socket.inet_ntoa(iph[9])
print("Source IP:", src_ip)
print("Destination IP:", dest_ip)
print("Packet Length:", len(packet))
```

OUTPUT :

Packet Sniffer Started....
Source IP : 192.168.1.10
Destination IP : 192.168.1.1
Packet Length : 79

RESULT :

Thus, a RAW socket program was successfully implemented to capture & display network packets.

EXP.NO : 15
DATE :

AIM :

To anal
using th

ALGORITHM

1. Install
2. Select
3. Configu
4. Run wi
5. Open
6. Analyz
and HT

INPUT :

The wi

OUTPUT :

Webal
* Nu
* Nu
* Mo
* Da
* Bro
* HTT

RESULT :

The
and the

EXP. NO : 14 IMPLEMENTING PACKET SNIFFING USING RAW SOCKETS

DATE :

AIM :

To implement packet sniffing using RAW sockets in python.

ALGORITHM :

1. Create a RAW socket
2. Bind the socket to the network interface.
3. Receive packets continuously.
4. Read the packet header.
5. Display the source & destination IP addr.
6. Display the protocol used.
7. Continue until the user stops the program.

INPUT :

Network packets received through the network interface.

CODE :

```
import socket
s = socket.socket(socket.AF_INET, socket.SOCK_RAW,
                  socket.IPPROTO_IP)
s.bind(("0.0.0.0", 0))
s.setsockopt(socket.IPPROTO_IP, socket.IP_HDRINCL, 1)
print("Packet Sniffer Started...")
While TRUE:
    packet, addr = s.recvfrom(65565)
    ip_header = packet[0:20]
    iph = struct.unpack("!BBHHHBBH4s4s", ipheader)
```