Status	Finished
Started	Sunday, 11 October 2026, 7:07 PM
Completed	Sunday, 11 October 2026, 7:11 PM
Duration	3 mins 24 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the use of seek() method in files?

a. sets the file's current position within the file

b. sets the file's current position at the offset ✓

c. none of the mentioned

d. sets the file's previous position at the offset

The correct answer is:
sets the file's current position at the offset

Question **2**

Correct

Mark 1.00 out of 1.00

What does the encoding parameter in the open() function specify?

a. The buffer size

b. The encoding format of the file ✓

c. The size of the file

d. The mode of the file

The correct answer is: The encoding format of the file

Question **3**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

- a. writelines() ✓
- b. write()
- c. write_all()
- d. write_list()

The correct answer is: writelines()

Question **4**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

- a. write() ✓
- b. read()
- c. append()
- d. insert()

The correct answer is: write()

Question **5**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

- a. tell()
- b. seek() ✓
- c. fseek()
- d. ftell()

The correct answer is: seek()

Question **6**

Correct

Mark 1.00 out of 1.00

What is the default mode in which the open() function opens a file?

- a. Read ✓
- b. Append
- c. Write
- d. Binary

The correct answer is: Read

Question **7**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

- a. readchar()
- b. read(size) ✓
- c. readline()
- d. readlines()

The correct answer is: read(size)

Question **8**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

- a. readlines(1)
- b. read(1)
- c. line()
- d. readline() ✓

The correct answer is: readline()

Question **9**

Correct

Mark 1.00 out of 1.00

Default EOL character of text file in python is ,

- a. \n ✓
- b. space
- c. ,
- d. \t

The correct answer is:
\n

Question **10**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

- a. It does nothing
- b. It clears the old data and starts fresh ✓
- c. It raises an error
- d. It appends data to the file

The correct answer is: It clears the old data and starts fresh

Question **11**

Correct

Mark 1.00 out of 1.00

What is the result of the following code?

```
with open("example.txt", "r") as f:
    data = f.read()
print(data)
```

- a. Prints the entire content of the file ✓
- b. Prints an error message
- c. Prints the first 10 characters of the file
- d. Prints each line of the file

The correct answer is: Prints the entire content of the file

Question **12**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

a. a list of integers
b. str
c. a list of lines ✓
d. a list of single characters

The correct answer is:
a list of lines

Question **13**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

a. EOFError
b. None
c. 0
d. An empty string ✓

The correct answer is: An empty string

Question **14**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. readlines() ✓
b. readlist()
c. readline()
d. read()

The correct answer is: readlines()

Question **15**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for writing, we use _____

a. outfile = open("c:\scores.txt", "w")

b. outfile = open(file = "c:\\scores.txt", "w")

c. outfile = open("c:\\scores.txt", "w") ✓

d. outfile = open(file = "c:\scores.txt", "w")

The correct answer is:
outfile = open("c:\\scores.txt", "w")