

```
{
  "name": "Selenium to Playwright Converter",
  "nodes": [
    {
      "parameters": {
        "formTitle": "Selenium to Playwright Converter",
        "formDescription": "Paste your Selenium test code below and get the equivalent Playwright code.",
        "formFields": {
          "values": [
            {
              "fieldLabel": "Selenium Code",
              "fieldType": "textarea",
              "fieldName": "seleniumCode",
              "placeholder": "Paste your Selenium script here...",
              "requiredField": true
            },
            {
              "fieldLabel": "Target Language",
              "fieldType": "dropdown",
              "fieldName": "targetLanguage",
              "fieldOptions": {
                "values": [
                  {
                    "option": "TypeScript"
                  },
                  {
                    "option": "JavaScript"
                  }
                ]
              }
            }
          ]
        }
      }
    }
  ]
}
```

```
        "option": "Python"
    },
    {
        "option": "Java"
    },
    {
        "option": "C#"
    }
]
},
"requiredField": true
}
]
},
"options": {
    "buttonLabel": "Convert",
    "path": "selenium-to-playwright"
}
},
"id": "f83d17c4-20df-4cff-bef3-3138d9f8dc11",
"name": "Submit Selenium Code",
"type": "n8n-nodes-base.formTrigger",
"typeVersion": 2.6,
"position": [
    0,
    112
],
"webhookId": "3158b2c4-d20c-4471-9338-d7096973fcab"
},
```

```

{
  "parameters": {
    "promptType": "define",
    "text": "=Convert the following Selenium test code to equivalent Playwright code in {{
$json.targetLanguage }}.\n\nSelenium code:\n```\n{{ $json.seleniumCode }}\n```",
    "messages": {
      "messageValues": [
        {
          "message": "You are an expert test automation engineer specializing in migrating Selenium test
suites to Playwright. Produce idiomatic, working Playwright code that preserves the original test intent,
waits, assertions and locators. Prefer Playwright auto-waiting and web-first assertions over explicit
sleeps. Map Selenium locators to Playwright locators appropriately. Return ONLY the converted
Playwright code inside a single fenced code block, with a brief comment at the top noting any manual
follow-ups required. Do not add explanatory prose outside the code block."
        }
      ]
    },
    "batching": {}
  },
  "id": "44cd5cd7-fbf3-4262-8626-bf2b2d043bf3",
  "name": "Convert to Playwright",
  "type": "@n8n/n8n-nodes-langchain.chainLlm",
  "typeVersion": 1.9,
  "position": [
    224,
    112
  ]
},
{
  "parameters": {
    "model": "openai/gpt-oss-120b",

```

```
"options": {
  "maxTokensToSample": 4096,
  "temperature": 0.2
},
"id": "5715e12f-3473-4bbf-b3bd-49dfadb33f11",
"name": "Groq Model",
"type": "@n8n/n8n-nodes-langchain.lmChatGroq",
"typeVersion": 1,
"position": [
  304,
  336
],
"credentials": {
  "groqApi": {
    "id": "xuX3cS8iB2Shcjyu",
    "name": "Groq account"
  }
},
{
  "parameters": {
    "operation": "completion",
    "respondWith": "showText",
    "responseText": "<h2>Converted Playwright Code</h2><p>Target language: {{ $('Submit Selenium Code').item.json.targetLanguage }}</p><pre style='white-space:pre-wrap;background:#1e1e1e;color:#e6e6e6;padding:16px;border-radius:8px;overflow:auto;'>{{ $json.text }}</pre>"
  },
  "id": "e652ec7b-cf96-4d4a-bbcf-0e9bcd8567e8",
```

```
"name": "Show Playwright Code",
"type": "n8n-nodes-base.form",
"typeVersion": 2.5,
"position": [
  576,
  112
],
"webhookId": "0296fc72-2baa-483d-b56d-01dc44d00019"
}
],
"pinData": {},
"connections": {
  "Submit Selenium Code": {
    "main": [
      [
        {
          "node": "Convert to Playwright",
          "type": "main",
          "index": 0
        }
      ]
    ]
  },
  "Convert to Playwright": {
    "main": [
      [
        {
          "node": "Show Playwright Code",
          "type": "main",
```

```
      "index": 0
    }
  ]
]
},
"Groq Model": {
  "ai_languageModel": [
    [
      {
        "node": "Convert to Playwright",
        "type": "ai_languageModel",
        "index": 0
      }
    ]
  ]
},
"active": false,
"settings": {
  "executionOrder": "v1",
  "binaryMode": "separate"
},
"versionId": "a4c81438-fd1c-473c-813a-01eca0decc05",
"meta": {
  "instanceId": "1f983b7837a95aab2b411ea86def58ab94f02cda98f65ef335b252a6f49e938d"
},
"nodeGroups": [],
"id": "nZLom6Cq3Fh5gipb",
"tags": []
```

}

Input form :

The screenshot shows a web browser window with the address bar displaying "nishamohan09.app.n8n.cloud/form-test/selenium-to-playwright". Below the address bar, there is an orange notification box that says "This is a test version of your form". The main content area is a light blue box with the title "Selenium to Playwright Converter". Below the title, it says "Paste your Selenium test code below and get the equivalent Playwright code." There are two main input fields: "Selenium Code *" with a text area containing the placeholder "Paste your Selenium script here..." and "Target Language *" with a dropdown menu. The dropdown menu is open, showing options: "Select an option ...", "TypeScript", "JavaScript", "Python", "Java", and "C#". At the bottom of the form, it says "Form automated with n8n".

Selenium to Playwright Converter

Paste your Selenium test code below and get the equivalent Playwright code.

Selenium Code *

Paste your Selenium script here...

Target Language *

Select an option ...

Select an option ...

TypeScript

JavaScript

Python

Java

C#

Form automated with n8n

Output form:

Converted Playwright Code

Target language: TypeScript

```
``typescript
// Note: Replace "your_username" and "your_password" with real credentials or use environment
variables.

import { test, expect } from '@playwright/test';

test('Login test - verify dashboard appears after successful login', async ({ page }) => {
  // 1. Navigate to the login page
  await page.goto('https://example.com/login');

  // 2. Fill in login credentials
  await page.locator('#username').fill('your_username');
  await page.locator('#password').fill('your_password');

  // 3. Click the login button
  await page.locator('#loginButton').click();

  // 4. Verify that the dashboard welcome message becomes visible
  const dashboardMessage = page.locator('#dashboard-welcome-message');
  await expect(dashboardMessage).toBeVisible({ timeout: 10000 });

  // Optional: Log result to console (Playwright test runner already reports pass/fail)
  console.log('Test Passed: Login successful!');
});
``
```