



# **Learn Complete Python In Simple Way**



# **DICTIONARY DATA STRUCTURE STUDY MATERIAL**



- ☞ We can use List, Tuple and Set to represent a group of individual objects as a single entity.
- ☞ If we want to represent a group of objects as key-value pairs then we should go for Dictionary.

**Eg:**

- rollno ---- name
  - phone number -- address
  - ipaddress --- domain name
- 
- ☞ Duplicate keys are not allowed but values can be duplicated.
  - ☞ Hetrogeneous objects are allowed for both key and values.
  - ☞ Insertion order is not preserved
  - ☞ Dictionaries are mutable
  - ☞ Dictionaries are dynamic
  - ☞ indexing and slicing concepts are not applicable

**Note:** In C++ and Java Dictionaries are known as "Map" where as in Perl and Ruby it is known as "Hash"

## **How to Create Dictionary?**

- `d = {}` OR `d = dict()`
- We are creating empty dictionary. We can add entries as follows

```
1) d[100]="durga"
2) d[200]="ravi"
3) d[300]="shiva"
4) print(d) → {100: 'durga', 200: 'ravi', 300: 'shiva'}
```

- If we know data in advance then we can create dictionary as follows
- `d = {100:'durga', 200:'ravi', 300:'shiva'}`
- `d = {key:value, key:value}`

## **How to Access Data from the Dictionary?**

We can access data by using keys.

```
1) d = {100:'durga', 200:'ravi', 300:'shiva'}
2) print(d[100]) #durga
3) print(d[300]) #shiva
```

If the specified key is not available then we will get `KeyError`  
`print(d[400])` → `KeyError: 400`



We can prevent this by checking whether key is already available or not by using `has_key()` function or by using `in` operator.

`d.has_key(400)` → Returns 1 if key is available otherwise returns 0

But `has_key()` function is available only in Python 2 but not in Python 3. Hence compulsory we have to use `in` operator.

```
if 400 in d:  
    print(d[400])
```

### Q) Write a Program to Enter Name and Percentage Marks in a Dictionary and Display Information on the Screen

```
1) rec={}
2) n=int(input("Enter number of students: "))
3) i=1
4) while i <=n:
5)     name=input("Enter Student Name: ")
6)     marks=input("Enter % of Marks of Student: ")
7)     rec[name]=marks
8)     i=i+1
9) print("Name of Student", "\t", "% of marks")
10) for x in rec:
11)     print("\t", x, "\t\t", rec[x])
```

```
D:\Python_classes>py test.py
Enter number of students: 3
Enter Student Name: durga
Enter % of Marks of Student: 60%
Enter Student Name: ravi
Enter % of Marks of Student: 70%
Enter Student Name: shiva
Enter % of Marks of Student: 80%
```

Name of Student	% of marks
-----	-----
durga	60%
ravi	70 %
shiva	80%



## How to Update Dictionaries?

- ☞ `d[key] = value`
- ☞ If the key is not available then a new entry will be added to the dictionary with the specified key-value pair
- ☞ If the key is already available then old value will be replaced with new value.

```
1) d={100:"durga",200:"ravi",300:"shiva"}
2) print(d)
3) d[400]="pavan"
4) print(d)
5) d[100]="sunny"
6) print(d)
```

### Output

```
{100: 'durga', 200: 'ravi', 300: 'shiva'}
{100: 'durga', 200: 'ravi', 300: 'shiva', 400: 'pavan'}
{100: 'sunny', 200: 'ravi', 300: 'shiva', 400: 'pavan'}
```

## How to Delete Elements from Dictionary?

### 1) del d[key]

- It deletes entry associated with the specified key.
- If the key is not available then we will get `KeyError`.

```
1) d={100:"durga",200:"ravi",300:"shiva"}
2) print(d)
3) del d[100]
4) print(d)
5) del d[400]
```

### Output

```
{100: 'durga', 200: 'ravi', 300: 'shiva'}
{200: 'ravi', 300: 'shiva'}
KeyError: 400
```

### 2) d.clear()

To remove all entries from the dictionary.

```
1) d={100:"durga",200:"ravi",300:"shiva"}
2) print(d)
3) d.clear()
4) print(d)
```



### Output

```
{100: 'durga', 200: 'ravi', 300: 'shiva'}  
{}
```

### 3) del d

To delete total dictionary. Now we cannot access d.

```
1) d={100:"durga",200:"ravi",300:"shiva"}  
2) print(d)  
3) del d  
4) print(d)
```

### Output

```
{100: 'durga', 200: 'ravi', 300: 'shiva'}  
NameError: name 'd' is not defined
```

## Important Functions of Dictionary:

### 1) dict():

To create a dictionary

- d = dict() → It creates empty dictionary
- d = dict({100:"durga",200:"ravi"}) → It creates dictionary with specified elements
- d = dict([(100,"durga"),(200,"shiva"),(300,"ravi")])  
→ It creates dictionary with the given list of tuple elements

### 2) len()

Returns the number of items in the dictionary.

### 3) clear():

To remove all elements from the dictionary.

### 4) get():

To get the value associated with the key

**d.get(key)**

If the key is available then returns the corresponding value otherwise returns None. It won't raise any error.



### **d.get(key,defaultvalue)**

If the key is available then returns the corresponding value otherwise returns default value.

```
1) d={100:"durga",200:"ravi",300:"shiva"}
2) print(d[100]) → durga
3) print(d[400]) → KeyError:400
4) print(d.get(100)) → durga
5) print(d.get(400)) → None
6) print(d.get(100,"Guest")) → durga
7) print(d.get(400,"Guest")) → Guest
```

### **5) pop():**

**d.pop(key)**

- It removes the entry associated with the specified key and returns the corresponding value.
- If the specified key is not available then we will get KeyError.

```
1) d={100:"durga",200:"ravi",300:"shiva"}
2) print(d.pop(100))
3) print(d)
4) print(d.pop(400))
```

### **Output**

durga

{200: 'ravi', 300: 'shiva'}

KeyError: 400

### **6) popitem():**

It removes an arbitrary item(key-value) from the dictionary and returns it.

```
1) d={100:"durga",200:"ravi",300:"shiva"}
2) print(d)
3) print(d.popitem())
4) print(d)
```

### **Output**

{100: 'durga', 200: 'ravi', 300: 'shiva'}

(300, 'shiva')

{100: 'durga', 200: 'ravi'}

If the dictionary is empty then we will get KeyError

d={}

print(d.popitem()) ==>KeyError: 'popitem(): dictionary is empty'



## 7) keys():

It returns all keys associated with dictionary.

```
1) d={100:"durga",200:"ravi",300:"shiva"}
2) print(d.keys())
3) for k in d.keys():
4)     print(k)
```

### Output

```
dict_keys([100, 200, 300])
100
200
300
```

## 8) values():

It returns all values associated with the dictionary.

```
1) d={100:"durga",200:"ravi",300:"shiva"}
2) print(d.values())
3) for v in d.values():
4)     print(v)
```

### Output

```
dict_values(['durga', 'ravi', 'shiva'])
durga
ravi
shiva
```

## 9) items():

It returns list of tuples representing key-value pairs.

[(k,v),(k,v),(k,v)]

```
1) d={100:"durga",200:"ravi",300:"shiva"}
2) for k,v in d.items():
3)     print(k,"--",v)
```

### Output

```
100 -- durga
200 -- ravi
300 -- shiva
```





## 10) copy():

To create exactly duplicate dictionary (cloned copy)

```
d1 = d.copy();
```

## 11) setdefault():

```
d.setdefault(k,v)
```

- If the key is already available then this function returns the corresponding value.
- If the key is not available then the specified key-value will be added as new item to the dictionary.

```
1) d={100:"durga",200:"ravi",300:"shiva"}
2) print(d.setdefault(400,"pavan"))
3) print(d)
4) print(d.setdefault(100,"sachin"))
5) print(d)
```

### Output

pavan

```
{100: 'durga', 200: 'ravi', 300: 'shiva', 400: 'pavan'}
```

durga

```
{100: 'durga', 200: 'ravi', 300: 'shiva', 400: 'pavan'}
```

## 12) update():

```
d.update(x)
```

All items present in the dictionary x will be added to dictionary d

## Q) Write a Program to take Dictionary from the Keyboard and print the Sum of Values?

```
1) d=eval(input("Enter dictionary:"))
2) s=sum(d.values())
3) print("Sum= ",s)
```

### Output

```
D:\Python_classes>py test.py
```

```
Enter dictionary: {'A':100,'B':200,'C':300}
```

```
Sum= 600
```



**Q) Write a Program to find Number of Occurrences of each Letter present in the given String?**

```
1) word=input("Enter any word: ")
2) d={}
3) for x in word:
4)     d[x]=d.get(x,0)+1
5) for k,v in d.items():
6)     print(k,"occurred ",v," times")
```

**Output**

```
D:\Python_classes>py test.py
Enter any word: mississippi
m occurred 1 times
i occurred 4 times
s occurred 4 times
p occurred 2 times
```

**Q) Write a Program to find Number of Occurrences of each Vowel present in the given String?**

```
1) word=input("Enter any word: ")
2) vowels={'a','e','i','o','u'}
3) d={}
4) for x in word:
5)     if x in vowels:
6)         d[x]=d.get(x,0)+1
7) for k,v in sorted(d.items()):
8)     print(k,"occurred ",v," times")
```

**Output**

```
D:\Python_classes>py test.py
Enter any word: doganimaldoganimal
a occurred 4 times
i occurred 2 times
o occurred 2 times
```



**Q) Write a Program to accept Student Name and Marks from the Keyboard and creates a Dictionary. Also display Student Marks by taking Student Name as Input?**

```
1) n=int(input("Enter the number of students: "))
2) d={}
3) for i in range(n):
4)     name=input("Enter Student Name: ")
5)     marks=input("Enter Student Marks: ")
6)     d[name]=marks
7) while True:
8)     name=input("Enter Student Name to get Marks: ")
9)     marks=d.get(name,-1)
10)    if marks== -1:
11)        print("Student Not Found")
12)    else:
13)        print("The Marks of",name,"are",marks)
14)    option=input("Do you want to find another student marks[Yes|No]")
15)    if option=="No":
16)        break
17) print("Thanks for using our application")
```

### **Output**

D:\Python\_classes>py test.py  
Enter the number of students: 5

Enter Student Name: sunny  
Enter Student Marks: 90

Enter Student Name: banny  
Enter Student Marks: 80

Enter Student Name: chinny  
Enter Student Marks: 70

Enter Student Name: pinny  
Enter Student Marks: 60

Enter Student Name: vinny  
Enter Student Marks: 50

Enter Student Name to get Marks: sunny  
The Marks of sunny are 90



---

Do you want to find another student marks[Yes|No]Yes

Enter Student Name to get Marks: durga

Student Not Found

Do you want to find another student marks[Yes|No]No

Thanks **for** using our application

## Dictionary Comprehension:

Comprehension concept applicable for dictionaries also.

- 1) squares={x:x\*x **for** x **in** range(1,6)}
- 2) **print**(squares)
- 3) doubles={x:2\*x **for** x **in** range(1,6)}
- 4) **print**(doubles)

### Output

{1: 1, 2: 4, 3: 9, 4: 16, 5: 25}

{1: 2, 2: 4, 3: 6, 4: 8, 5: 10}