Coherent Association of Single Molecules from Single Atoms

A DISSERTATION PRESENTED

BY

Үіснао Үи

TO

THE DEPARTMENT OF PHYSICS

IN PARTIAL FULFILLMENT OF THE REQUIREMENTS
FOR THE DEGREE OF
DOCTOR OF PHILOSOPHY
IN THE SUBJECT OF
PHYSICS

Harvard University Cambridge, Massachusetts March 2021 ©2021 – YICHAO YU ALL RIGHTS RESERVED.

Coherent Association of Single Molecules from Single Atoms

Abstract

Contents

0	Introduction							
I	App	Apparatus						
	I.I	Cooling and Optical Pumping Beams	2					
	1.2	Tweezer and Imaging	3					
	1.3	Molecular Raman Frequency Generation	3					
2	Computer Control of the Experiment							
	2.I	Overall Structure	4					
	2.2	Frontend	4					
	2.3	Backends	5					
	2.4	Automation of Scan	5					
	2.5	Summary and Outlook	5					
3	Raman Sideband Cooling							
	3.I	Introduction	6					
	3.2	Theory	6					
	3.3	Setup	7					
	3.4	Challenge with Large Lamb-Dicke Parameter	7					
	3.5	Solution: High Order Sidebands	7					
	3.6	Solution: Simulation Based Optimization	9					
	3.7	Cooling Performance	9					
4	Inti	Interaction of Single Atoms						
	4. I	Scattering Length	13					
	4.2	Energy Levels of Two Interacting Atoms in an Anisotropic Trap	13					
	4.3	Interaction Shift Spectroscopy	14					
	4.4	Summary and Outlook	14					
5	Рно	otoassociation of Single Atoms	15					
	5.I	Energy Levels	ΙŞ					
	5.2	Effect of the Trap	15					
	5.3	Photoassociation Spectroscopy	16					
6	Twz	O-DHOTON SPECTBOSCOPY OF NACS GROUND STATE	1.5					

	6.1	Introduction	18
	6.2	Energy Level Structure for NaCs Ground State	18
	6.3	Raman Resonance on $v'' = -1$, $N = 0$ Ground State	18
	6.4	Raman Resonance on $v'' = -1$, $N = 2$ Ground State	18
7	Сон	ierent Optical Creation of NaCs Molecule	19
	7 . I	Introduction	20
	7.2	Raman Transfer Efficiency Model	20
	7.3	Excited State Selection	20
	7.4	Ground States Selection	20
	7.5	Raman Transition Results	20
8	Con	CLUSION	21
Aı	PPEND	IX A COMPUTER CONTROL APPENDEX	22
Aı	PPEND	IX B RAMAN SIDEBAND COOLING APPENDEX	23

Acknowledgments

,

Introduction

Apparatus

1.1 COOLING AND OPTICAL PUMPING BEAMS

(MOT, OP, fiber back reflection)

(Mention Na Raman beam to be covered in later chapter?)

- 1.2 Tweezer and Imaging
- 1.3 Molecular Raman Frequency Generation

(beam path, calibration)

Computer Control of the Experiment

- 2.1 OVERALL STRUCTURE
- 2.2 FRONTEND

(Abstraction) (Backward compatibility) (Flexibility) (Text based/version control friendly)

2.3	Backends
(comi	munication protocol) (IR)
2.3.1	FPGA Backend
(clock	generation) (pulse merging) (compression)
2.3.2	NiDAQ Backend
(Varia	ble clock)
2.3.3	USRP Backend
(SIM	D)
2.4	Automation of Scan
(Scan	requirement) (Combination of scans) (Scope/nested structure)
2.5	Summary and Outlook
(new	backend/SPCM) (native code generation, auto vectorization) (dynamic logic and dependency
tracki	ng/optimization)

Raman Sideband Cooling

3.1 Introduction

3.2 THEORY

3.1




Figure 3.1: Single Na atom Raman sideband cooling scheme. The Raman transitions between $|2,2;n\rangle$ and $|1,1;n+\Delta n\rangle$ have a one-photon detuning $\Delta=75$ GHz below the $3^2S_{1/2}$ to $3^2P_{3/2}$ transition. Two-photon detuning, δ , is defined relative to the $\Delta n=0$ carrier transition. For optical pumping, we use two σ^+ polarized transitions, one to pump the atom state out of $|1,1\rangle$ via $3^2P_{3/2}$ and one to pump atoms out of $|2,1\rangle$ via $3^2P_{1/2}$ to minimize heating of the $|2,2\rangle$ state.

3.3 SETUP

3.2

3.4 CHALLENGE WITH LARGE LAMB-DICKE PARAMETER

3.3

3.5 SOLUTION: HIGH ORDER SIDEBANDS

3.4




Figure 3.2: Geometry and polarizations of the Raman and optical pumping beams relative to the optical tweezer and bias magnetic field. Raman beams R1 and R4 address the radial x-mode. R1 and R2 address the radial y-mode. R3 and R4 address the axial z-mode, where the beams also couple to radial motion, but this coupling can be neglected when the atoms is cooled to the ground state of motion.




Figure 3.3: Optical pumping motional-state redistribution and Raman coupling for large LD parameters for the axial direction (z). The range plotted covers 95% of the initial thermal distribution. (A) Motional state distribution after one OP cycle for different initial states motion, $n_{\rm init}$. Due to photon-recoil and the large LD parameter, $\eta_z^{\rm OP}=0.55$, there is a high probability of n changing. (B) Matrix elements for Raman transition on the first order cooling sideband deviate from \sqrt{n} scaling with multiple minima.




Figure 3.4: Matrix elements for Raman transition including high order sidebands. During cooling, we utilize the fact that high motional states couple most effectively to sidebands with large $|\Delta n|$ in order to overcome the issue with variation and dead zone in the coupling strengths.

3.6 SOLUTION: SIMULATION BASED OPTIMIZATION

3.5

3.7 Cooling Performance

3.6 3.7




Figure 3.5: Schematic of the cooling pulse sequence. The tweezer is strobed at 3 MHz to reduce light shifts during optical pumping. Each cooling cycle consists of 8 sideband pulses. The four axial pulses address two sideband orders. The two pulses in each radial direction either address $\Delta n=-2$ and $\Delta n=-1$ or have different durations to drive $\Delta n=-1$, at the end of the cooling sequence when most of the population is below n=3. The Raman cooling and spectroscopy pulses have Blackman envelopes to reduce off-resonant coupling, while the measurement Rabi pulses in Fig. 3.7 have square envelopes to simplify analysis.




Figure 3.6: Raman sideband spectra for (A) x, (B) y, (C) z axis before (red circle) and after (blue square) applying Raman sideband cooling sequence. The height of the cooling sidebands (positive detuning) are strongly suppressed after cooling which suggests most of the atoms are cooled to the motional ground state in the trap.


Figure 3.7 (following page): Rabi flopping on radial axis x (A) carrier and (B) $\Delta n_x=1$ sideband, radial axis y (C) carrier and (D) $\Delta n_x=1$ sideband, axial axis z (E) carrier and (F) $\Delta n_x=1$ sideband, before (red circle) and after (blue square) Raman sideband cooling.

Solid lines (both red and blue) in all plots are fits to a Rabi-flopping that includes a thermal distribution of motional states as well as off-resonant scattering from the Raman beams.

The blue lines correspond to a ground state probability of (A-D) 98.1% along radial axis and (E-F) 95% along the axial axis after cooling. The red lines correspond to a thermal distribution of $80~\mu\text{K}$ before RSC. The horizontal dashed lines in all the plots correspond to the 4~% probability of imaging loss.

The green dashed line in (F) includes the additional decoherence due to a fluctuation of the hyperfine splitting of magnitude 3 kHz. We see that the decoherence effect is strongest for the post-cooling data on the axial $\Delta n_z=1$ sideband where the Rabi frequency is the lowest.

Figure 3.7: (continued)



Interaction of Single Atoms

4.1 SCATTERING LENGTH

(Importance/relation with binding energy etc.)

4.2 Energy Levels of Two Interacting Atoms in an Anisotropic Trap

(appendex?)

4.3 Interaction Shift Spectroscopy

(motional sideband, scattering length result)

4.4 Summary and Outlook

(Motional state selection)

Photoassociation of Single Atoms

- 5.1 Energy Levels
- 5.2 Effect of the Trap

(light shift, broadening)

5.3 Photoassociation Spectroscopy

(v=0, 12, 14, etc)

Two-photon Spectroscopy of NaCs

Ground State

- 6.1 Introduction
- 6.2 Energy Level Structure for NaCs Ground State
- 6.3 Raman Resonance on v'' = -1, N = 0 Ground State
- 6.4 Raman Resonance on v'' = -1, N = 2 Ground State

Coherent Optical Creation of NaCs

Molecule

	T
7. I	INTRODUCTION

- 7.2 RAMAN TRANSFER EFFICIENCY MODEL
- 7.2.1 BEYOND THREE-LEVEL MODEL
- 7.2.2 DIFFERENTIAL LIGHT SHIFT
- 7.2.3 SCATTERING
- 7.2.4 RAMAN TRANSFER VERSUS STIRAP
- 7.3 EXCITED STATE SELECTION
- 7.4 GROUND STATES SELECTION
- 7.4.1 FINAL MOLECULAR STATE
- 7.4.2 INITIAL ATOMIC STATE
- 7.5 RAMAN TRANSITION RESULTS

Conclusion



Computer control appendex

(Hardware spec)

B

Raman sideband cooling appendex

(Full sequence)