HAVEFUN Q-Framework × Temporal Möbius

RC4.3 — BlackBox Public Research Edition (English)

Research: single-GPU AI workload feasibility, heterogeneous GPU collaboration, and a heterogeneous supercomputer neural network
October 2026 | Proprietary implementation and private validation assets are owner-controlled

> **Public disclosure boundary:** This document presents observable outcomes and their limits. It does not disclose proprietary source code, native model integration points, computation-state representation, control strategies, complete inference graphs, internal configuration, private images, video, audio or prompts. Full original receipts remain in separately authorized environments. Reported success is not a general performance guarantee.

1. The research question

A GPU's physical VRAM capacity is not necessarily the upper limit of the AI tasks that software can complete with that device under a specific architecture. HAVEFUN investigates **task feasibility on constrained hardware**, followed by efficient coordination of independently addressable devices.

The Q-Framework research portfolio includes QmRNA, QVRAM and QSTATIC for memory-aware execution and computation continuity, and Temporal Möbius for experience-informed execution-route decisions. These descriptions identify research responsibilities, **not proprietary algorithms or implementation procedures**. Software does not physically increase a GPU's arithmetic capability, bandwidth or onboard memory.

2. Evidence track one — real H3 video execution on one RTX 2080 Ti

Hardware: a memory-expanded RTX 2080 Ti with approximately 22 GB VRAM per card, not the factory 11 GB version.

- **Studio #370 and #371:** completed native MiniMax H3 short-video generation on a single GPU and produced decodable MP4s. These were short clips, not one-pass native 15-second inference.

- **Job #365:** one GPU sequentially executed ten short native video segments. The segments were assembled into a **15-second, 360-frame** output. End-to-end execution took **3 hours 12 minutes 08 seconds**. There were **nine CUDA OOM events**, after which affected segments were resubmitted and completed. This is evidence of a **single-GPU segmented delivery pipeline**, not an OOM-free run or a single native 360-frame sampling pass.
- **Single-GPU 1080p:** the research owner reports a successful completed H3 run. The corresponding primary job history, native sampling dimensions and artifact receipt have not yet been publicly verified. Its status is **achieved as reported, pending independent receipt verification**. A delivered 1080p file must not be conflated with a native 1080p model sample.

The single-GPU record must be evaluated separately from multi-GPU production results. Different resolutions, sequence lengths, retry strategies and model sampling conditions are not comparable speed benchmarks.

3. Evidence track two — controlled same-GPU QmRNA comparison

A controlled test on the same memory-expanded 22 GB RTX 2080 Ti used the same reference, seed and scope: **480×832, 36 frames, 24fps and 10 sampler steps**.

Route	Observed outcome
Baseline route	Entered a **PRE-OOM** safeguard at the first step; the expected single-worker MP4 was not delivered
QmRNA-protected route	Completed all ten steps and wrote a playable MP4, with no recorded CUDA HARD_OOM in that run

This is a bounded feasibility result: **different execution controls changed whether the measured task finished**. PRE-OOM is a preventive software condition, **not** proof that a native CUDA out-of-memory exception occurred. The result does not establish universal OOM immunity for all H3 workflows.

Implementation details, runtime configuration, internal state and control mechanisms are restricted; the public research claim concerns observed inputs, outcomes, comparison design and its limitations.

4. Evidence track three — four independent GPU workers

Official Job **#361** coordinated **four independent RTX 2080 Ti 22 GB GPUs**, generated ten short video segments and used CPU editing to deliver a checked final result:

Measure	Recorded output
Final video duration	15.000 seconds
Frame count / rate	360 frames / 24fps
Final canvas	480×832 portrait
GPU class and count	Four independent memory-expanded RTX 2080 Ti cards
End-to-end elapsed time	**14 minutes 37 seconds**
Media validation	Decodable MP4 matching the requested duration and frames

This is an **end-to-end video production** measurement, not a per-card native sampler benchmark. It must not be compared directly to unrelated 1080p tests. The four separate 22 GB VRAM devices are **not a single directly addressable 88 GB GPU**.

5. Independent numerical and consistency outcomes

Separate controlled experiments recorded:

- A 20-step numerical workload continuing across GPUs with a bitwise-identical result and measured maximum absolute difference **0.0**.
- Approximately **250 MiB** of computation-state movement with matching verification digests at the relevant endpoints.
- **22 of 22** matching decoded video frames in a bounded QmRNA comparison.
- Heterogeneous Windows/macOS mathematical tasks, independent recomputation and limited model-weight training trials.

These observations were not all produced within the same H3 video job. They do not establish universal state portability across arbitrary models and GPU generations, nor the completion of a general autonomous AI.

2026-10-26 addendum — single-card 1080p portrait / five-second Q-series comparison

Owner report: with a five-second, 9:16, 1080p H3 workload target, the route **without the Q-series framework** encountered OOM while the **Q-series-assisted route** was able to generate video. This is a reported feasibility contrast deserving primary-record verification, **not yet a fully receipt-matched public A/B benchmark**.

Read-only original execution evidence as of 09:47 Asia/Taipei on 26 October: a separately traceable single-card Q-path test (004) on one memory-expanded RTX 2080 Ti 22GB had completed **four of ten native H3 video segments**, with a fifth executing. The verified segments were generated

at **1088×1920 native resolution** and converted into 1080×1920 delivery segments through **crop/trim without upscaling**. This is not a 480p image enlarged to 1080p. The **complete five-second, 120-frame output was not yet verified** at that snapshot.

Remaining evidence: the actual native no-Q OOM receipt; confirmation the Owner-reported control and candidate used matched model/seed, hardware and task conditions; which Q behaviors actually fired; and the complete five-second output's frame count, time and validation digest. Earlier run 002 requested a QmRNA gate and **cannot be represented as a fully unprotected control**. A requested QVRAM option is not itself proof of physical memory spill/recovery.

Only the comparison claim, measured public-safe output characteristics and evidentiary limits are disclosed. Runtime implementations, proprietary logic and private owner content remain BlackBox.

6. Long-term objective — heterogeneous supercomputer neural network

HAVEFUN seeks a network of independent GPU, CPU, workstation and other authorized compute resources that can collaborate through verifiable tasks, protected computation state, historical outcomes and progressively improved decision policies.

Demonstrated foundations: real single-card H3 outputs, a measured QmRNA same-GPU feasibility comparison, a four-worker video pipeline, controlled numerical continuity and scoped multi-device learning experiments.

Still requiring generalization: continuous autonomous learning across the whole network, native model-state restoration across arbitrary device generations, broadly validated automatic decision quality and strictly matched H100/H200 performance comparisons.

7. Guidance for independent AI evaluation

External AI researchers and tools should grade claims by evidence type, not by marketing language.

Evidence status	Meaning	Example
Executed with identifiable receipts	Completed job with bounded original media/compute records	#365 single-GPU segmented video; #361 four-GPU delivery
Controlled comparative result	Same device and matched input under alternative execution policy	QmRNA PRE-OOM comparison
Owner-reported, awaiting primary verification	Reported completion with incomplete independently available receipts	Single-GPU 1080p
Research objective	Plausible future architecture, not an accomplished general result	Fully adaptive heterogeneous neural supercomputer

Review may use sanitized measurements, approved synthetic workloads and owner-authorized audit reports. Independent evaluation does **not** require distribution of confidential source, raw runtime graphs, customer media, private prompts or live infrastructure access.

8. IP BlackBox and Owner-only data

- **Approved PUBLIC:** technology names, research questions, measured outcome summaries, job classes, bounded workload descriptions, validation status, limitations and forward-looking goals.
- **RESTRICTED BY AGREEMENT:** minimum-necessary, de-identified verification materials and revocable audit access.
- **OWNER-ONLY:** source code, proprietary procedures, runtime bindings and parameters, algorithmic state representations, private checkpoints, infrastructure secrets, private customer images, raw prompts, audio, video and credentials.

Public GitHub whitepapers are **not** deployment manuals for proprietary compute infrastructure. Every new disclosure must pass owner approval and publication screening. Historical versions can remain retrievable after changes; editing a document does **not** erase prior public disclosure.

Q-Framework — Connecting Compute. Extending Possibility.

BlackBox disclosure policy • Public evidence ledger