

## 4-31 实现考勤成功页面（移动端）

140.143.132.225:8000/project-1/doc-79

### 一、为超级管理员设置入职日期

因为在查询考勤结果的时候用到了员工入职日期，管理者创建员工记录的时候，要手动设置员工的入职日期，但是注册超级管理员的时候并没有填写入职日期，现在我们还没有做到员工管理页面，所以暂时手工在数据表里面设置超级管理员的入职日期。

开始事务	文本	筛选	排序	导入	导出						
id	open_id	nickname	photo	name	sex	tel	email	hiredate	role	root	
2	oNISI5C2Ih9Qw6kj	神思者	https://thirdwx.qlogo.cn/r	无名氏	(Null)	(Null)	(Null)	2021-01-13	[0]	1	

### 二、设置跳转到签到成功页面

员工签到成功以后，小程序要跳转到签到成功页面，所以代码应该写成如下的样子：

```
1. uni.showToast({
2.   title:"签到成功",
3.   complete:function(){
4.     uni.navigateTo({
5.       url: '../checkin_result/checkin_result'
6.     });
7.   }
8. })
```

### 三、设置全局请求路径

在发送Ajax请求之前，需要把后端Web方法的URL地址注册到main.js文件里边。

```
1. Vue.prototype.url = {
2.   .....
3.   searchTodayCheckin: baseUrl + "/checkin/searchTodayCheckin",
4. }
```

### 四、修改系统时间

因为Emos系统的签到时间是从08:30到09:30，为了实验签到功能，所以我们要修改系统时间在签到时间段之内。另外，如果你是周六、周日调试项目，需要在 `tb_workday` 表中加入当天日期，这样原本的周末就变成了工作日，可以考勤了。

### 五、编写代码发出Ajax请求

把模型层的数据都设置成空字符串，然后编写 `onShow` 回调函数，发出Ajax请求。

```
1. onShow: function() {
2.     let that = this;
3.     that.ajax(this.url.searchTodayCheckin, 'GET', null, function(resp) {
4.         let result = resp.data.result;
5.         that.name = result.name;
6.         that.photo = result.photo;
7.         that.deptName = result.deptName;
8.         that.date = result.date;
9.         that.attendanceTime = result.attendanceTime;
10.        that.closingTime = result.closingTime;
11.        that.checkinTime = result.checkinTime;
12.        that.status = result.status;
13.        that.risk = result.risk;
14.        that.address = result.address;
15.        that.checkinDays = result.checkinDays;
16.        that.weekCheckin = result.weekCheckin;
17.    });
18. }
```

