

# Lambda Calculus

---

# Announcements

[cs61a.org/extra.html](https://cs61a.org/extra.html)

## Church-Turing Thesis

## The Church-Turing Thesis

---

A function on the natural numbers is computable by a human following an algorithm, ignoring resource limitations, if and only if it is computable by a Turing machine.



# Representation

## Functions Can Represent Boolean Values

---

If all we have to work with are functions and call expressions, is there any way to represent other primitive values?

```
t = lambda a: lambda b: a
f = lambda a: lambda b: b
```

```
def py_pred(p):
    return p(True)(False)
```

```
def f_not(p):
    """Define Not.

    >>> py_pred(f_not(t))
    False
    >>> py_pred(f_not(f))
    True
    """
```

```
    return lambda a: lambda b: p(b)(a)
```

**Exercise:**

```
def f_and(p, q):
    """Define And.
```

```
    >>> py_pred(f_and(t, t))
    True
    >>> py_pred(f_and(t, f))
    False
    >>> py_pred(f_and(f, t))
    False
    >>> py_pred(f_and(f, f))
    False
    """
```

```
    return p(q)(f)
```

```
def f_or(p, q):
    """Define Or.
```

```
    >>> py_pred(f_or(t, t))
    True
    >>> py_pred(f_or(t, f))
    True
    >>> py_pred(f_or(f, t))
    True
    >>> py_pred(f_or(f, f))
    False
    """
```

```
    return p(t)(q)
```

## Functions Can Represent Boolean Values

---

If all we have to work with are functions and call expressions, is there any way to represent other primitive values?

```
t = lambda a: lambda b: a
f = lambda a: lambda b: b
```

```
def py_pred(p):
    return p(True)(False)
```

```
def f_not(p):
    """Define Not.

    >>> py_pred(f_not(t))
    False
    >>> py_pred(f_not(f))
    True
    """
    return lambda a: lambda b: p(b)(a)
```

```
def f_if(p, a, b):
    """Define If.

    >>> py_pred(f_if(t, t, t))
    True
    >>> py_pred(f_if(t, t, f))
    True
    >>> py_pred(f_if(t, f, t))
    False
    >>> py_pred(f_if(t, f, f))
    False
    >>> py_pred(f_if(f, t, t))
    True
    >>> py_pred(f_if(f, t, f))
    False
    >>> py_pred(f_if(f, f, t))
    True
    >>> py_pred(f_if(f, f, f))
    False
    """
    return _____
```

## Lambda Calculus Notation



## Lambda Calculus

---

**Variables:** single letters, such as  $x$

**Functions:** Instead of `lambda x: x`, write  $\lambda x.x$ ; Instead of `lambda x, y: x`, write  $\lambda xy.x$

**Assignment:** Write `var f = ...`

**Application:** Instead of  $f(x)$ , write  $(f\ x)$ ;  $f(x)(y)$  and  $f(x, y)$  are both written  $(f\ x\ y)$

**Follow along!** <http://chenyang.co/lambda/>

**To type  $\lambda$ , just type `\`**

`var I =  $\lambda x.x$`

Are  $(I\ I)$  and  $I$  the same?

Are  $(K\ I\ I)$  and  $(K\ I\ K)$  the same?

`var K =  $\lambda r.(\lambda s.r)$`

Are  $(K\ I)$  and  $I$  the same?

Are  $(K\ I\ K)$  and  $(K\ (I\ K))$  the same?

Are  $(K\ K\ I)$  and  $K$  the same?

What's  $((K\ K)\ (K\ K))$  the same as?

Can you construct a 4-argument function from  $K$  and  $I$ ?

## Boolean Values

---

**Variables:** single letters, such as `x`

**Functions:** Instead of `lambda x: x` , write `λx.x` ; Instead of `lambda x, y: x` , write `λxy.x`

**Assignment:** Write `var f = ...`

**Application:** Instead of `f(x)` , write `(f x)` ; `f(x)(y)` and `f(x, y)` are both written `(f x y)`

**Follow along! <http://chenyang.co/lambda/>**

**To type `λ`, just type `\`**

`var T = λab.a`

Define **and**, **or**, and **not**!

Define exclusive or:

`var F = λab.b`

```
xor(False, False) -> False
xor(False, True)  -> True
xor(True,  False) -> True
xor(True,  True)  -> False
```