

CS61B Lectures #29

Today:

- Lower bounds on sorting by comparison
- Distribution counting, radix sorts

Readings: Today: *DS(IJ)*, Chapter 8; Next topic: Chapter 9.


Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 1

Better than $N \lg N$?

- Can prove that *if all you can do to keys is compare them*, then sorting must take $\Omega(N \lg N)$.
- Basic idea: there are $N!$ possible ways the input data could be scrambled.
- Therefore, your program must be prepared to do $N!$ different combinations of data-moving operations.
- Therefore, there must be $N!$ possible combinations of outcomes of all the if-tests in your program, since those determine what move gets moved where (we're assuming that comparisons are 2-way).

Decision Tree
Height \propto Sorting time



Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 2

Necessary Choices

- Since each if-test goes two ways, number of possible different outcomes for k if-tests is 2^k .
- Thus, need enough tests so that $2^k \geq N!$, which means $k \in \Omega(\lg N!)$.
- Using Stirling's approximation,

$$N! \in \sqrt{2\pi N} \left(\frac{N}{e}\right)^N \left(1 + \Theta\left(\frac{1}{N}\right)\right),$$

$$\lg(N!) \in 1/2(\lg 2\pi + \lg N) + N \lg N - N \lg e + \lg\left(1 + \Theta\left(\frac{1}{N}\right)\right)$$

$$= \Theta(N \lg N)$$

- This tells us that k , the worst-case number of tests needed to sort N items by comparison sorting, is in $\Omega(N \lg N)$: there must be cases where we need (some multiple of) $N \lg N$ comparisons to sort N things.

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 3

Beyond Comparison: Distribution

- But suppose can do more than compare keys?
- For example, how can we sort a set of N integer keys whose values range from 0 to kN , for some small constant k ?
- One technique is *distribution sorting*:
 - Put the integers into N buckets; integer p goes to bucket $\lfloor p/k \rfloor$.
 - At most k keys per bucket, so catenate and use insertion sort, which will now be fast.
- E.g., $k = 2, N = 10$:

Start:

14 3 10 13 4 2 19 17 0 9

In buckets:

| 0 | 3 2 | 4 | | 9 | 10 | 13 | 14 | 17 | 19 |

- Now insertion sort is fast. Putting in buckets takes time $\Theta(N)$, and insertion sort takes $\Theta(kN)$. When k is fixed (constant), we have sorting in time $\Theta(N)$.

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 4

Distribution Counting

- Another technique: *count* the number of items $< 1, < 2$, etc.
- If $M_p = \# \text{items with value } < p$, then in sorted order, the j^{th} item with value p must be item $\#M_p + j$.
- Suppose that one has a set of numbers in the range $[0, 1000)$ and that exactly 15 of them are less than 50, which is also in the set. Then the result of sorting will look like this: *[corrected 4/7]*

result:

--

 \rightarrow

--	--

 \dots

50

 \dots

--

0 15 999

- In other words, the count of numbers $< k$ gives the index of k in the output array.
- If there are N items in the range $0..M-1$, gives another *linear-time* $\Theta(M+N)$ —algorithm (We include M and N here to allow for both duplicates and for cases where $M \gg N$).
- [Postscript on notation: the notations $[A, B]$, (A, B) , $[A, B)$, and $(A, B]$ above refer to *intervals*. The use of parentheses vs. square brackets reflects the distinction between *open* and *closed* intervals. Thus $x \in [A, B]$ iff $A \leq x \leq B$, while $x \in (A, B)$ iff $A < x < B$, etc.]

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 5

Distribution Counting Example

- Suppose all items are between 0 and 9 as in this example:

7 0 4 0 9 1 9 1 9 5 3 7 3 1 6 7 4 2 0 0

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

 Counts

0	3	6	7	9	11	12	13	16	16
<0	<1	<2	<3	<4	<5	<6	<7	<8	<9

 Running sum

0	0	0	1	1	1	2	3	3	4	4	5	6	7	7	7	9	9	9
0			3			6			9		11	12	13			16		

- "Counts" line gives # occurrences of each key.
- "Running sum" gives cumulative count of keys $<$ each value...
- ... which tells us where to put each key:
- The first instance of key k goes into slot m , where m is the number of key instances that are $< k$.

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 6

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Next positions

0		3		6		9		12		15		18						

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 7

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

0	3	6	7	9	11	12	14	16	16
0	1	2	3	4	5	6	7	8	9

Next positions

0		3		6		9		12		15		18						

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 8

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

1	3	6	7	9	11	12	14	16	16
0	1	2	3	4	5	6	7	8	9

Next positions

0																		
0		3		6		9		12		15		18						

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 9

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

1	3	6	7	10	11	12	14	16	16
0	1	2	3	4	5	6	7	8	9

Next positions

0																		
0		3		6		9		12		15		18						

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 10

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	3	6	7	10	11	12	14	16	16
0	1	2	3	4	5	6	7	8	9

Next positions

0	0																	
0		3		6		9		12		15		18						

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 11

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	3	6	7	10	11	12	14	16	17
0	1	2	3	4	5	6	7	8	9

Next positions

0	0																	
0		3		6		9		12		15		18						

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 12

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	4	6	7	10	11	12	14	16	17
0	1	2	3	4	5	6	7	8	9

Next positions

0	0	1				4			7		9		
0		3		6		9		12	15		18		

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 13

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	4	6	7	10	11	12	14	16	18
0	1	2	3	4	5	6	7	8	9

Next positions

0	0	1				4			7		9	9	
0		3		6		9		12	15		18		

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 14

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	5	6	7	10	11	12	14	16	18
0	1	2	3	4	5	6	7	8	9

Next positions

0	0	1	1			4			7		9	9	
0		3		6		9		12	15		18		

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 15

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	5	6	7	10	11	12	14	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0	1	1			4			7		9	9	9
0		3		6		9		12	15		18		

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 16

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	5	6	7	10	12	12	14	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0	1	1			4	5		7		9	9	9
0		3		6		9		12	15		18		

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 17

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	5	6	8	10	12	12	14	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0	1	1		3	4	5		7		9	9	9
0		3		6		9		12	15		18		

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 18

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	5	6	8	10	12	12	15	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0		1	1			3		4		5		7	7		9	9	9
0			3			6		9			12		15		18			

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 19

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	5	6	9	10	12	12	15	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0		1	1			3	3	4		5		7	7		9	9	9
0			3			6		9			12		15		18			

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 20

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	6	6	9	10	12	12	15	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0		1	1	1		3	3	4		5		7	7		9	9	9
0			3			6		9			12		15		18			

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 21

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	6	6	9	10	12	13	15	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0		1	1	1		3	3	4		5	6	7	7		9	9	9
0			3			6		9			12		15		18			

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 22

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	6	6	9	10	12	13	16	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0		1	1	1		3	3	4		5	6	7	7	7	9	9	9
0			3			6		9			12		15		18			

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 23

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	6	6	9	11	12	13	16	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0		1	1	1		3	3	4	4	5	6	7	7	7	9	9	9
0			3			6		9			12		15		18			

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 24

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

2	6	7	9	11	12	13	16	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0		1	1	1	2	3	3	4	4	5	6	7	7	7	9	9	9
0			3			6			9			12			15			18

Output

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 25

Distribution Counting Example (II)

7	0	4	0	9	1	9	1	9	5	3	7	3	1	6	7	4	2	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

3	3	1	2	2	1	1	3	0	3
0	1	2	3	4	5	6	7	8	9

Counts

0	3	6	7	9	11	12	13	16	16
0	1	2	3	4	5	6	7	8	9

Running sum of Counts

3	6	7	9	11	12	13	16	16	19
0	1	2	3	4	5	6	7	8	9

Next positions

0	0	0	1	1	1	2	3	3	4	4	5	6	7	7	7	9	9	9
0			3			6			9		12		15		18			

Output

Last modified: Tue Apr 7 14:20:47 2020

C561B: Lecture #29 26

Radix Sort

Idea: Sort keys *one character at a time*.

- Can use distribution counting for each digit.
- Can work either right to left (LSD radix sort) or left to right (MSD radix sort)
- LSD radix sort is venerable: used for punched cards.

Initial: set, cat, cad, con, bat, can, be, let, bet

Pass 1 (by char #2)

	be	cad	can	con	bat	can	be	let	bet
	///	///	///	///	///	///	///	///	///
	'u'	'd'	'n'	't'					

be, cad, con, can, set, cat, bat, let, bet

Pass 2 (by char #1)

	bat	bet							
	cat	let							
	can	set							
	cad	be	con						
	///	///	///						
	'a'	'e'	'o'						

cad, can, cat, bat, be, set, let, bet, con

Pass 3 (by char #0)

			con						
			cat						
			can						
			cad	let	set				
			///	///	///				
			'b'	'c'	'l'	's'			

bat, be, bet, cad, can, cat, con, let, set

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 27

MSD Radix Sort

- A bit more complicated: must keep lists from each step separate
- But, can stop processing 1-element lists

A	posn
* set, cat, cad, con, bat, can, be, let, bet	0
* bat, be, bet / cat, cad, con, can / let / set	1
bat / * be, bet / cat, cad, con, can / let / set	2
bat / be / bet / * cat, cad, con, can / let / set	1
bat / be / bet / * cat, cad, can / con / let / set	2
bat / be / bet / cad / can / cat / con / let / set	

Last modified: Tue Apr 7 14:20:47 2020
CS61B: Lecture #29 28

Performance of Radix Sort

- Radix sort takes $\Theta(B)$ time where B is *total size of the key data*.
- Have measured other sorts as function of #records.
- How to compare?
- To have N different records, must have keys at least $\Theta(\lg N)$ long [why?]
- Furthermore, comparison actually takes time $\Theta(K)$ where K is size of key in worst case [why?]
- So $N \lg N$ comparisons really means $N(\lg N)^2$ operations.
- While radix sort would take $B = N \lg N$ time with minimal-length keys.
- On the other hand, must work to get good constant factors with radix sort.

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 29

And Don't Forget Search Trees

Idea: A search tree is in sorted order, when read in inorder.

- Need *balance* to really use for sorting [next topic].
- Given balance, same performance as heapsort: N insertions in time $\lg N$ each, plus $\Theta(N)$ to traverse, gives

$$\Theta(N + N \lg N) = \Theta(N \lg N)$$

Last modified: Tue Apr 7 14:20:47 2020

CS61B: Lecture #29 30

Summary

- **Insertion sort:** $\Theta(Nk)$ comparisons and moves, where k is maximum amount data is displaced from final position.
 - Good for small datasets or almost ordered data sets.
- **Quicksort:** $\Theta(N \lg N)$ with good constant factor if data is not pathological. Worst case $O(N^2)$.
- **Merge sort:** $\Theta(N \lg N)$ guaranteed. Good for external sorting.
- **Heapsort, treesort with guaranteed balance:** $\Theta(N \lg N)$ guaranteed.
- **Radix sort, distribution sort:** $\Theta(B)$ (number of bytes). Also good for external sorting.