Does Graph Expansion Help Small Code Models Localize Bugs? A Pre-registered Study of Candidate Pools, Scorer Discrimination, and Test-Time Reasoning with Gemma 4 on SWE-bench Verified

Sultan Haikal
recrified@gmail.com

October 2026

Abstract

Deploying structural code graphs in local developer agents requires balancing topological expansion against language model discrimination. Evaluating open models across 344 held-out SWE-bench Verified tasks reveals naive Personalized PageRank expansion yields statistically indistinguishable localization from lexical retrieval alone (47.1% vs 45.1%, exact binomial McNemar $p = 0.287$; excluding true advantages $\geq +4.4$ pp, $p < 0.05$). This limitation is characterized by an expected-rank **Break-Even Discrimination Bound** ($\text{AUC}^* \geq 1 - \frac{k-1}{M-1}$), where Gemma 4 E2B pairwise discrimination degrades from AUC = 0.7966 on lexical seeds to AUC = 0.6596 on structural neighbors, turning expanded pools into distractor sets. Consistent with relational reasoning limits in transformers [18], an exploratory 2×2 factorial evaluation on all 131 un-named Stratum C defects reveals that test-time reasoning traces (`<thought>`) raise Top-1 accuracy from 2.29% (3 hits) to 9.92% (13 hits, exact binomial $p = 0.0063^*$, discordant pairs $n_{10} = 11, n_{01} = 1$) and increase Stratum C MRR@50 by +74.6% from 0.0778 to 0.1358. Combining textual call-path annotations with thinking (C_3, 9.16%) yields empirical parity with unguided thinking (C_0, exact McNemar $p = 1.0000$), indicating that allocated reasoning tokens allow model representations to trace relational dependencies directly. Pre-registered causal interventions (`PREREG-CAUSAL-v1`, $N = 58$) isolate the mechanism of this bottleneck: syntax-preserving AST α-renaming incurs only a -1.73 pp top-1 drop (12.07% $\rightarrow$ 10.34%, $p = 1.0000$), confirming that control-flow syntax provides a resilient structural baseline without surface names, while inline comment provenance co-locating call paths above symbol signatures doubles top-1 accuracy to 25.86% (+13.79 pp lift, exact McNemar $p = 0.0386^*$, Wilcoxon $p = 0.0103^*$), significantly outperforming disconnected global edge lists (15.52%) and adjacency maps (15.52%). To deliver scalable provenance extraction on consumer hardware, **Perron** provides an open-source CSR diffusion engine executing vectorized spectral convergence in 1.89–5.10 ms within ≤ 3 MB zero-copy array resident RAM (144.33 MB peak process RSS, reflecting baseline Python interpreter, PyArrow, and NumPy runtime overhead), preserving 91.9% reasoning headroom under a 3,480-token budget. Downstream evaluation demonstrates that AST surgical replacement achieves a 0.0% syntax error rate ($p < .001$ vs unified diffs), resolving patch generation fragility independent of retrieval depth.

1 Introduction

Autonomous developer agents designed for local execution must localize software defects inside a working context of a few thousand tokens ($K \leq 4,096$), eliminating dependence on costly cloud APIs and preventing source code leakage. Standard lexical search (e.g., Okapi BM25) reliably finds symbols explicitly named in issue text or error traces. To locate fault sites that the issue never mentions, existing agent architectures (including Aider's PageRank repository maps [5], RepoGraph [14], and LocAgent [3]) deploy random walks or graph traversal tools over AST dependency networks.

The working assumption underlying graph-augmented localization rests on two joint conditions: (1) **Recall Expansion**: Traversal along structural call edges must place gold defect targets into the candidate pool that lexical search misses; and (2) **Rank Discrimination**: A compact language model must rank those newly introduced targets above the distractors that graph expansion inevitably introduces.

Evaluating both assumptions on a 344-task held-out subset of SWE-bench Verified [9] using Perron and a frozen `gemma-4-e2b-it` scorer exposes a fundamental disconnect: while 1-hop graph expansion adds +7.3 percentage points candidate recall over seeds, downstream top-5 localization accuracy remains indistinguishable from depth-matched BM25 (47.1% vs 45.1%, Holm $p = 0.287$).

This paper investigates this disconnect through five interconnected acts:

1. **Act I: The Empirical Paradox**: Across 19,298 scored evaluations, naive Personalized PageRank expansion achieves zero statistical advantage over lexical retrieval under frozen small scorers, confirming candidate pool parity (RQ1, RQ2).
2. **Act II: The Mathematical Diagnosis**: I formalize the expected-rank **Break-Even Discrimination Bound** ($\text{AUC}^* \geq 1 - \frac{k-1}{M-1}$) and identify the **Lexical Abstraction Bottleneck**: Gemma 4's discrimination collapses from 0.7966 ROC-AUC on seeds to 0.6596 on graph neighbors, falling below the expected-rank threshold required to benefit from pool expansion (RQ3).
3. **Act III: The Cross-Architecture Scaling Surface**: Pre-registered protocol `PREREG-SCALING-v1` on Dual Tesla T4 GPUs demonstrates monotonic intra-family scaling within Gemma 4 ($0.8544 \rightarrow 0.9274$), proves Gemma 4 E4B achieves representational efficiency over larger controls (Phi-4-mini and DeepSeek-7B), and isolates the physical quantization boundary for sparse MoE architectures on consumer GPUs.
4. **Act IV: The Principled Resolution and Causal Dissection**: Consistent with relational reasoning limits in transformers [18] and graph verbalization theory [4], a complete 2×2 factorial evaluation on all 131 un-named Stratum C defects demonstrates that test-time reasoning traces (`<thought>`, C_0) raise Top-1 localization accuracy from 2.29% (3 hits) to 9.92% (13 hits; +7.63 pp, exact binomial McNemar $p = 0.0063^*$, discordant pairs $n_{10} = 11, n_{01} = 1$; MRR +74.6%). Factorial comparison against combined provenance prompting (C_3, 9.16%) reveals statistical parity ($\Delta = -0.76$ pp, exact McNemar $p = 1.0000$, $\Delta_{\text{interaction}} = -2.29$ pp). Pre-registered causal interventions (`PREREG-CAUSAL-v1`, $N = 58$) further establish that stripping surface lexical tokens via AST α-renaming reduces top-1 accuracy by only -1.73 pp ($p = 1.0000$), while inline comment provenance doubles top-1 accuracy to 25.86% (+13.79 pp lift, $p = 0.0386^*$, Wilcoxon $p = 0.0103^*$), resolving the graph verbalization hierarchy for code.
5. **Act V: The Enabling Resource**: I release **Perron**, an open-source C/Python Compressed Sparse Row (CSR) engine executing decoupled spectral diffusion (vectorized convergence in 1.89–5.10 ms, 0.024–0.075 ms per inner-loop iteration; 0.17–0.45 ms standalone API dispatch) within ≤ 3 MB zero-copy array resident RAM (144.33 MB peak process RSS), delivering compact provenance paths within consumer hardware limits.

1.1 Contributions

- **Matched-Control Evaluation Design**: Depth-matched BM25, same-file, and degree-preserving null-graph candidate pools are scored by the identical model under controlled prompt budgets, isolating what graph structure contributes beyond pool cardinality.
- **Empirical Loss Funnel and Truncation Curves**: A 4-stage loss decomposition separates candidate boundary ceiling, rank compaction, and reader error. Truncating matched pools at $M \in [10, 50]$ shows that adding depth lexical candidates is consistent with distractor accumulation (Acc@5 drops by 4 tasks, -1.16 pp, $p = 0.455$), whereas graph expansion plateaus flat (+3 tasks, +0.87 pp over seeds, $p = 0.549$).
- **Discovery of the Lexical Abstraction Bottleneck**: Empirical analysis demonstrates that open models evaluate code relevance primarily via surface token overlap, causing pairwise discrimination to collapse from 0.7966 ROC-AUC on seeds to 0.6596 on graph neighbors, falling below the expected-rank Break-Even Discrimination Bound.

- **Cross-Architecture Scaling Surface and MoE Hardware Boundary**: Protocol `PREREG-SCALING-v1` evaluates four model archetypes on Dual Tesla T4 GPUs, confirming monotonic scaling within Gemma 4 (0.8544 → 0.9274), demonstrating that Gemma 4 E4B outperforms Phi-4-mini (0.7836) and DeepSeek-7B (0.6489), and isolating the physical 44.0 GB VRAM quantization barrier for sparse MoE models.
- **Factorial Provenance and Reasoning Discovery**: A 2×2 factorial evaluation on un-named defects ($N = 131$) isolates the causal drivers of code localization: test-time reasoning traces raise Top-1 localization from 2.29% (3 hits) to 9.92% (13 hits; $p = 0.0063^*$, discordant pairs $n_{10} = 11, n_{01} = 1$) and increase MRR@50 by +74.6%. Comparing Condition C3 with C0 shows that passive prompt annotations provide zero incremental advantage over unguided thinking ($p = 1.0000$), indicating that intermediate thinking tokens allow model representations to trace relational dependencies directly.
- **Causal Lexical Dissection and Graph Serialization Hierarchy**: Pre-registered causal interventions (`PREREG-CAUSAL-v1`, $N = 58$) isolate the mechanism of the Lexical Abstraction Bottleneck: AST α-renaming shows that control-flow syntax alone sustains 10.34% top-1 localization without lexical identifiers (−1.73 pp vs natural code, $p = 1.0000$). Furthermore, evaluating graph serialization taxonomies [4] reveals that inline comment provenance co-locating call paths at function definitions achieves 25.86% Acc@1 (+13.79 pp lift, $p = 0.0386^*$, Wilcoxon $p = 0.0103^*$), whereas disconnected global edge lists and adjacency maps underperform inline comments by dispersing self-attention.
- **High-Throughput CSR Graph Engine**: An efficient, memory-mapped Compressed Sparse Row multigraph architecture with decoupled specificity ratio hub damping that executes vectorized convergence in 1.89–5.10 ms on consumer workstations without matrix mutation (spectral convergence proofs detailed in Appendix A).
- **Open-Source Ecosystem and Benchmark Toolkit**: I release the `scores.parquet` archive (19,298 scored candidate evaluations), the Apache 2.0 `perron-core` library, precomputed CSR multigraphs for 12 canonical repositories, and curated strata annotations across 800 tasks spanning the broader SWE-bench ecosystem (300 Lite tasks + 500 Verified tasks, with 344 callable Verified tasks forming the primary held-out confirmatory benchmark) under CC0-1.0.

1.2 Claims and Evidence Hierarchy

To maintain strict methodological transparency, the findings of this study are categorized into five evidential families:

1. **Confirmatory Family** ($N = 344$): The matched-control evaluation ($A_4 - A_2$, $A_4 - A_3$ on strict Acc@5) is hash-committed and pre-registered with family-wise error control (Holm $p = 0.287$). It formally confirms that 1-hop graph expansion is null-compatible with lexical retrieval under frozen small scorers, excluding true population advantages $\geq$ +4.4 pp ($p < 0.05$).
2. **Empirical Diagnostic Family** ($N = 344$): The expected-rank Break-Even Discrimination Bound ($\text{AUC}^* \geq 1 - \frac{k-1}{M-1}$), the empirical collapse of Gemma 4's discrimination on graph neighbors (0.7966 vs 0.6596, Mann-Whitney $U = 2993, p = 0.00358^*$), the 4-stage loss funnel (3.68× boundary vs compaction loss), and the continuous resolvent basis dose-response surface ($n^*_{\text{eff}} \approx 8.8$) are empirical diagnostic characterizations.
3. **Exploratory Factorial Family** ($N = 131$): The 2×2 factorial evaluation on Stratum C un-named defects (C_1, C_2, C_0, C_3) isolates the causal effect of test-time compute ($p = 0.0063^*$ for C_0 vs C_1, +7.63 pp) and demonstrates empirical parity between unguided thinking and provenance prompting ($p = 1.0000$ for C_3 vs C_0; $\Delta_{\text{interaction}} = -2.29$ pp, −3 hits).
4. **Pre-registered Causal and Multi-Encoding Family** ($N = 58$, `PREREG-CAUSAL-v1`): Pre-registered AST α-renaming isolates lexical vs structural contributions (−1.73 pp top-1 change, exact McNemar $p = 1.0000$), and five-way graph serialization benchmarking proves inline comment provenance dou-

bles top-1 accuracy (+13.79 pp, exact McNemar $p = 0.0386^{*}$, Wilcoxon $p = 0.0103^{*}$), establishing that code graph verbalization favors localized inline provenance over disconnected edge lists.

5. **Engineering Tooling Utility ($N = 30$ Archetypes)**: Perron's AST surgical replacement editor is evaluated as a syntax safety utility against indentation traps and hunk drift (0.0% syntax errors vs 50.0% for `git apply`, $p < .001$), with full benchmark execution scoped to future work.

Scope Invariant and Methodological Boundary This investigation explicitly addresses the retrieval, candidate localization, and context packing layer ($K \leq 4,096$) of local developer agents. In hierarchical agent architectures [14,21], defect localization establishes the strict mathematical upper bound on downstream patch resolution. We intentionally decouple candidate localization from multi-turn Docker benchmark execution to evaluate the representation bottleneck without confounding noise from tool formatting or environment setup.

1.3 Physical Hardware Envelope

Local developer agents must operate efficiently on consumer hardware. Perron bounds active per-turn working context to $K_{\text{effective}} = 3,480$ tokens ($K \leq 4,096$). On a reference developer machine (15.68 GiB RAM), the standalone CSR engine peaks at 144.33 MB resident memory (loading graphs via zero-copy memory mapping within a ≤ 3.0 MB array buffer resident footprint; 91.4 MB total benchmark process delta including PyArrow and NumPy allocations). Hierarchical AST skeleton breadcrumbs occupy an average of 283.8 tokens per task (median 264 tokens), preserving 91.9% reasoning headroom for model generation within the 3,480-token context budget. Live inference of `gemma-4-e2b-it` was evaluated with left-padded batching and `logits_to_keep=1` on an NVIDIA Tesla T4 GPU (scoring prompts averaging 423 tokens per candidate symbol), achieving mean Time-To-First-Token of 3505.0 ms and 11.7 tokens/sec decode throughput.

2 Related Work

Graphs and Agents for Code Localization Lexical search and dense bi-encoders struggle with vocabulary mismatch and structural execution paths. RepoCoder [23] demonstrated that iterative retrieval loops improve code completion but incur multi-turn token inflation. Aider [5] introduced repository maps using Tree-sitter AST tags ranked by PageRank. Graph-guided agents such as RepoGraph [14], CodexGraph [12], and LocAgent [3] equip frontier models with graph traversal tools to navigate codebases interactively. While LocAgent [3] fine-tunes specialized models for multi-turn graph traversal, Perron investigates zero-shot localization under compact open weights (Gemma 4 2B/4B), isolating the exact point where un-annotated graph expansion collapses into distractor accumulation. AutoCodeRover [24] navigates ASTs through iterative search queries. In SWE-agent [22], specialized agent-computer interfaces improve resolve rates. Conversely, Agentless [21] demonstrated that a simple two-phase pipeline (hierarchical localization followed by test-filtered patch generation) resolves 32% of SWE-bench Lite (FSE 2025) without an agent loop, highlighting that simple pipelines establish strong baselines. These systems employ large hosted models; this paper evaluates whether graph expansion assists a small 2B model in a single scoring pass.

Random-Walk Retrieval on Graphs Scalable diffusion on graphs builds on push-based approximate Personalized PageRank [1], decoupled propagation architectures such as APPNP [10], and scalable indexing frameworks like PPRGo [2]. In link prediction, rooted PageRank and stationary-normalized hitting times [11] discount popular nodes by global stationary reachability. While HippoRAG [6] demonstrated that Personalized PageRank over open-domain text knowledge graphs outperforms iterative retrieval (formulating node specificity as inverse passage frequency $s_i = |P_i|^{-1}$ applied as a pre-walk teleport multiplier), software call

graphs present static AST structures with high-in-degree utility hubs (logging routines, assertion helpers) that appear as unseeded intermediate nodes that absorb diffusion mass regardless of s_i. Perron extends this decoupled random-walk lineage (APPNP [10], PPRGo [2]) to static compiled CSR code multigraphs, replacing dynamic entity extraction with post-walk specificity ratio damping over static CSR matrices.

Program Slicing and Fault Localization Classical program slicing [20] computes backward executable slices on statement-level Program Dependence Graphs (PDGs), but conservative alias analysis often retains 50% to 80% of an application's codebase. Spectrum-Based Fault Localization (SBFL) [15, 25] evaluates test coverage matrices to score statement suspiciousness. Pearson et al. [15] showed that fault-localization findings on artificial faults do not reliably transfer to real-world software defects, motivating authentic issue evaluation on SWE-bench [9]. Perron extracts symbol-level AST multigraphs to pack relevant contexts into prompt budgets ($K \leq 4,096$) without requiring test execution during retrieval.

Graph Verbalization and Reasoning Complexity in Language Models How structured graphs are presented to language models critically governs their reasoning efficacy. Fatemi, Halcrow, and Perozzi [4] demonstrated that graph verbalization functions alter reasoning accuracy by +4.8% to +61.8%, with unannotated text dumps failing to convey relational topology. In repository-level engineering, RepoGraph [14] observed that directly flattening 2-hop code graphs degrades SWE-bench resolve rates from 28.3% to 26.0% (below baseline) due to distractor accumulation. Furthermore, Sanford, Fatemi, Perozzi et al. [18] proved that while single-layer transformers (Depth1) solve basic retrieval lookups, graph reachability and s-t connectivity are NL-complete, mathematically requiring logarithmic depth or extra test-time reasoning tokens (LogDepthPause). Consistent with Sanford et al.'s [18] finding that relational reasoning in transformers requires intermediate token steps, empirical evaluations show that injecting static provenance comments without reasoning tokens (C2) fails to separate candidates, while test-time thinking traces (`<thought>`) allow compact models to traverse topological paths. Consequently, compact open-weights models cannot resolve multi-hop code graph paths in a single forward pass without explicit provenance and intermediate reasoning traces.

Pointwise versus Listwise Reranking Pointwise language model scoring (e.g., MonoT5 [13]) evaluates each candidate independently. Under independent scoring, the expected number of distractors that outscore a gold target with score s^* scales with candidate pool cardinality: $\mathbb{E}[X \mid s^*] = \sum_{j=1}^{M-1}(1 - F_{\text{dist},j}(s^*))$. Consequently, expanding candidate pool size M under a compact pointwise scorer risks distractor accumulation unless model discrimination is near-perfect. In contrast, listwise and setwise architectures [16, 19] introduce direct cross-candidate attention competition, mitigating distractor dominance.

3 Theoretical Foundations and The Perron Graph Engine

Figure 1 outlines the architectural pipeline of Perron, decoupling graph traversal into an upstream memory-mapped sparse matrix diffusion engine and a downstream structural verbalizer that feeds local Gemma 4 language models.

3.1 Multiplex Transition Matrix Construction

A codebase is represented as a directed multigraph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, where $\mathcal{V}$ denotes AST code symbols (classes, functions, methods) and $\mathcal{E}$ spans relations $r \in \{\text{call}, \text{inherit}, \text{import}, \text{caller}\}$. Directed edges $(u, v) \in \mathcal{E}_{\text{call}}$ indicate that symbol u invokes v, while $(u, v) \in \mathcal{E}_{\text{inherit}}$ represent class C3 Method Resolution Order inheritance, $(u, v) \in \mathcal{E}_{\text{import}}$ represent module imports, and $(u, w) \in \mathcal{E}_{\text{caller}}$ denote reverse call invocations.




Figure 1: The Perron architecture and candidate provenance pipeline. Multigraph dependency indexing extracts typed AST relationships ($\mathcal{E}_{\text{call, inherit, import, caller}}$) into decoupled memory-mapped CSR arrays. Truncated SpMM power iteration computes personalized PageRank vectors with step latency (0.17–0.45 ms) with zero runtime convolution cost. Decoupled specificity ratio damping ($\gamma = 0.70$) suppresses utility hubs (HSI@10 = 99.5%) before candidate pool extraction. For un-named defect reports, context-budgeted breadcrumb packing bounds candidate functions within tight prompt budgets ($K \leq 3{,}480$), enabling local Gemma 4 test-time reasoning traces (`<thought>`) to raise top-1 localization accuracy from 2.29% (3 hits) to 9.92% (13 hits; exact binomial $p = 0.0063^*$).

Relations receive asymmetric static weights:

$$W_{uv} = \omega_{\text{call}} A_{uv}^{(\text{call})} + \omega_{\text{inherit}} A_{uv}^{(\text{inherit})} + \omega_{\text{import}} A_{uv}^{(\text{import})} + \omega_{\text{caller}} A_{uv}^{(\text{caller})}, \tag{1}$$

where $\boldsymbol{\omega} = [0.50, 0.25, 0.15, 0.10]$ and $A_{uv}^{(r)} = \mathbb{I}((u,v) \in \mathcal{E}_r)$. Let $D_u = \sum_v W_{uv}$ be the out-degree sum. The row-stochastic transition matrix $T \in \mathbb{R}^{|\mathcal{V}| \times |\mathcal{V}|}$ and dangling indicator $\mathbf{d} \in \{0,1\}^{|\mathcal{V}|}$ are defined as:

$$T_{uv} = \begin{cases} \frac{W_{uv}}{D_u}, & D_u > 0 \\ 0, & D_u = 0 \end{cases}, \quad d_u = \begin{cases} 1.0, & D_u = 0 \\ 0.0, & D_u > 0 \end{cases}. \tag{2}$$

Memory-mapped ingestion via `numpy.load(mmap_mode='r')` opens the CSR representation directly from disk. Post-walk specificity ratio evaluation requires only $O(|\mathcal{V}|)$ vector arithmetic, eliminating runtime edge mutations and memory reallocation.

3.2 Personalized PageRank Diffusion and Linear Algebraic Bounds

Random walk diffusion models the propagation of bug relevance across call hierarchies. The Google transition operator M with damping factor $\beta = 0.85$ is formulated as:

$$M = \beta \cdot (T + \mathbf{d}\mathbf{p}_0^\top) + (1-\beta) \cdot \mathbf{1}\mathbf{p}_0^\top. \tag{3}$$

By the rank-1 perturbation spectrum of the Google matrix [7], the second-largest eigenvalue is strictly bounded by $|\lambda_2(M)| \leq \beta = 0.85$, establishing an invariant spectral gap $1 - |\lambda_2(M)| \geq 1 - \beta = 0.15$ and ensuring geometric convergence $O(\beta^t)$ in L_1 total variation distance. Power iteration stops on residual $\|\boldsymbol{\pi}^{(t+1)} - \boldsymbol{\pi}^{(t)}\|_1 < 10^{-6}$, converging in at most 90 iterations on Requests (1.89 ms) and 66 iterations on

SymPy (5.10 ms). By the regenerative renewal property of Markov chains with teleportation, the stationary distribution of the closed operator M is algebraically identical to the normalized leaky resolvent $(1-\beta)\mathbf{p}_0(I-\beta T)^{-1}$ (discrepancy $< 2 \times 10^{-8}$). Full proofs of the Brauer spectral bound, barycentric linearity, and leaky resolvent equivalence are provided in Appendix A.

3.3 Decoupled Specificity Ratio Hub-Damping

Personalized PageRank concentrates probability mass on high-in-degree hub nodes. To suppress structural popularity without mutating the static matrix T, Perron computes a repository-wide stationary baseline $\boldsymbol{\pi}_{\text{global}}$ once per codebase using a uniform prior $\mathbf{p}_{\text{uniform}} = \frac{1}{|\mathcal{V}|}\mathbf{1}$. For any query, the Specificity Score is defined as:

$$\text{Specificity}(v) = \frac{\pi_{\text{query}}(v)}{(\pi_{\text{global}}(v) + \epsilon)^{\gamma}}, \tag{4}$$

where $\epsilon = 10^{-8}$ and $\gamma = 0.70$. Resistance to hub congestion is measured by the Hub Suppression Index at top 10 (HSI@10):

$$\text{HSI@10} = 1.0 - \frac{|\text{top-10} \cap \mathcal{H}_{25}|}{10}, \tag{5}$$

where $\mathcal{H}_{25}$ denotes the set of top-25 global in-degree hub nodes in the repository multigraph. The asymptotic Pointwise Mutual Information (PMI) decomposition and Neumann series analysis showing why pre-walk scaling cannot prevent sink absorption are detailed in Appendix A.

3.4 Hierarchical AST Breadcrumb Context Packing

To deliver localized code context within prompt budgets ($K \leq 4,096$), Perron packs candidate symbols using hierarchical AST breadcrumb skeletons. For each candidate function, the enclosing class definition, docstring, and signature are preserved while stripping irrelevant sibling function bodies. Breadcrumb skeletons bound the context footprint to < 100 tokens per symbol, keeping syntax parseable and variable bindings intact.

4 Study Design and Hash-Committed Protocol

4.1 Benchmark and Task Waterfall

SWE-bench Verified [9] contains 500 tasks across 12 canonical Python repositories. To establish an unbiased held-out benchmark and prevent data leakage, instances are filtered via a mutually exclusive, collectively exhaustive (MECE) waterfall:

$$\begin{aligned} \text{Total Verified (500)} - \text{Lite Overlap (93)} &= \text{Held-Out (407)}, \\ \text{Held-Out (407)} - \text{AST Drift (56)} - \text{Non-Callable (7)} &= \textbf{344} \text{ Callable Tasks}. \end{aligned} \tag{6}$$

The 344 callable tasks ($\mathcal{S}_{\text{func}}$) define the callable, AST-parsable evaluation cohort of SWE-bench Verified possessing identifiable reference function targets. The 56 AST drift exclusions reflect legacy repository commits with syntax errors (such as Python 2/3 transitions) that fail standard AST parsing uniformly across all methods prior to candidate generation. Hyperparameters ($\beta = 0.85, \gamma = 0.70, \tau = 0.15, K = 25$) were fixed on development data and frozen prior to evaluation.

Defect Accessibility Strata To evaluate whether graph traversal selectively assists un-named defect localization, tasks are partitioned into three mutually exclusive strata based on issue text lexical visibility: (1) **Stratum A (Named,** $N = 208$**, 60.5%)**, where issue text explicitly names the gold function, method, or qualified class identifier; (2) **Stratum B (Traceback,** $N = 5$**, 1.5%)**, where issue text includes a traceback or explicit file path pointing to the gold source file, but omits the function name; and (3) **Stratum C (Un-Named,** $N = 131$**, 38.1%)**, where issue text contains neither the function name nor a traceback pointing to the target file. Strata are annotated via a deterministic regex extraction pipeline (`perron.analysis.strata`), validated by a manual dual-pass verification audit across 50 randomly sampled tasks with 100% concordance, released in `swebench-strata-annotations` (CC0-1.0).

4.2 Hash-Committed Protocol

The study operates under two hash-committed protocol locks:

1. **Retrieval Protocol Lock**: Frozen and publicly pushed at Git commit `6908e78` on October 5, 2026 (protocol SHA-256: `89416e40`…; split SHA-256: `95c7ef3c`…).
2. **Gemma 4 Pointwise Protocol Lock**: Frozen in two cryptographic stages (`benchmarks/protocol/gemma4_protocol_v1.yaml`, raw SHA-256: `96af1621`…; Stage 2 lock `gemma4_lock_v1.json`, raw SHA-256: `dbbf2920`…) under Gate G0 protocol commits `a13ab34` (Stage 1 freeze) and `9abe405` (Stage 2 cryptographic lock) on October 6, 2026.

4.3 Candidate Pools and Matched-Control Arms

Candidate pools are generated per task, matched to size $M_t = 10 + \min(|E_t|, 40) \in [10, 50]$ (mean 24.5, median 22.0), where E_t denotes 1-hop out-neighbors of top-10 lexical seeds S passing Filter F (functions/methods only, excluding test nodes and top-25 hubs $\mathcal{H}_{25}$):

- **B0 (Unscored BM25)**: Lexical candidates in native Okapi BM25 score order.
- **A1 (Seeds Only)**: Top-10 lexical seeds S ($M = 10$).
- **A2 (Depth-Matched BM25)**: S followed by the next BM25 candidates passing Filter F up to M_t.
- **A3 (Same-File Control)**: S followed by symbols in seed files passing Filter F up to M_t.
- **A4 (Graph 1-Hop Expansion)**: S followed by E_t ordered by adjacency $a(u) = \sum_{s \in S} p_0(s) T_{su}$.
- **A5 (Null Graph Control)**: Degree-preserving relation-stratified null graph replicate up to M_t.
- **A6 (Perron Diffusion Pool)**: Candidates ordered by Perron specificity scores up to M_t.

Mechanism Explaining Pool Recall vs. Reachability (201 vs. 199 Tasks) A4 achieves candidate pool oracle recall on 201/344 tasks (58.4%), whereas unweighted 1-hop BFS reachability reaches 199/344 tasks (57.8%). This 2-task divergence is mechanistically explained by two counterbalancing operations in the pool builder: seed test-node masking replaces test-file seeds with source seeds, recovering 16 tasks (e.g., `sympy-13372`), while Filter F degree-capping and hub pruning drop 14 tasks (e.g., `sphinx-7590`), yielding a net difference of +2 tasks ($199 + 16 - 14 = 201$).

4.4 Pointwise Gemma 4 Scorer

Each candidate symbol is formatted into a prompt context averaging 423.1 tokens (issue description + AST breadcrumb + prompt instructions; breadcrumbs alone average < 100 tokens). A frozen `gemma-4-e2b-it` model (FP16, thinking disabled) scores each candidate in a single forward pass: $s(t, v) = \text{logsumexp}(z[Y]) - \text{logsumexp}(z[N])$ on prompt variant P0, chosen on disjoint development data ($N = 100$). The evaluation required 19,298 forward passes.

4.5 Statistical Analysis

A localization hit (Function Acc@k) is scored as 1.0 if at least one ground-truth modified function is present in the top-k retrieved symbols, and 0.0 otherwise. The confirmatory family comprises two pre-specified contrasts on strict Acc@5:

- **PC1**: $A_4 - A_2$ (Graph 1-hop vs. Depth-matched BM25).
- **PC2**: $A_4 - A_3$ (Graph 1-hop vs. Same-file matched).

Contrasts are evaluated using exact two-sided McNemar tests with step-down Holm–Bonferroni correction over family $\alpha = 0.05$. Paired 95% confidence intervals are estimated via repository-stratified bootstrapping ($B = 10{,}000$). Post-hoc Contrasts are evaluated with repository-stratified bootstrap confidence intervals and exact McNemar tests.

5 Empirical Results

5.1 Standalone Function Retrieval (RQ1)

Table 1 presents standalone retrieval on SWE-bench Verified ($N = 344$ callable tasks). Okapi BM25 hits 175/344 (50.9%), Perron Static hits 173/344 (50.3%), and Standard PPR reaches 172/344 (50.0%). The difference between Perron and BM25 is −0.6 pp (95% CI [−3.5, +2.3], Holm $p = 1.000$). At top-5, BM25 outperforms Perron Static (45.1% vs. 40.4%, $\Delta = -4.7$ pp). In addition, BM25 achieves 99.4% Hub Suppression Index (HSI@10) without graph machinery, because defect issue descriptions target specific identifiers rather than generic library utilities. External baselines illustrate these retrieval trade-offs: whole-repository tag PageRank (Aider-style repo maps) achieves 40.0% File Acc@5 across candidate files, but produces 0.0% Function Acc@10 because tag graphs index entire files without isolating symbol-level function definitions for edit localization. Dense bi-encoder semantic retrieval mitigates colloquial vocabulary mismatch on issue descriptions, but achieves 38.4% Function Acc@10 due to imprecise token matching across fine-grained code identifiers compared to sparse lexical search. On Stratum C ($N = 131$ tasks where the issue never names the target), BM25 hits 28 and Perron hits 27. Reciprocal Rank Fusion (RRF) attains 174/344 (50.6%), failing to beat standalone BM25. Call-graph diffusion provides no detectable lexical lift over BM25 on this benchmark.

Table 1: Standalone retrieval evaluation on SWE-bench Verified ($N = 344$ callable tasks). Evaluates top-10 function accuracy, 95% bootstrap confidence intervals ($B = 10{,}000$), top-5 function/file accuracy, and Hub Suppression Index (HSI@10). Bold row label denotes the primary evaluated graph method (reference baseline); bold numerical values indicate the highest score in each column. Holm p-values are computed against Perron Static.

Method	Fn Acc@10	95% CI	Fn Acc@5	File Acc@5	HSI@10	Holm p
Perron Static ($\gamma = 0.70$)	50.3% (173/344)	[45.1%, 55.5%]	40.4%	53.8%	**99.5%**	reference
Okapi BM25	**50.9%** (175/344)	[45.6%, 56.1%]	**45.1%**	**59.6%**	99.4%	1.000
RRF Fusion (BM25 + Perron)	50.6% (174/344)	[45.3%, 55.8%]	42.2%	55.5%	**99.5%**	1.000
Standard PPR ($\beta = 0.85$)	50.0% (172/344)	[44.8%, 55.2%]	40.4%	52.8%	90.8%	1.000
Degree-Normalized PPR	49.4% (170/344)	[44.2%, 54.7%]	40.1%	52.3%	**99.5%**	1.000
HippoRAG Prior Scaling	49.4% (170/344)	[44.2%, 54.7%]	40.4%	52.6%	91.1%	1.000
Aider Repo Map (Tag PageRank)	0.0% (0/344)	[0.0%, 0.0%]	0.0%	40.0%	92.4%	< 0.001
Dense Semantic Retrieval	38.4% (132/344)	[33.4%, 43.6%]	29.7%	44.8%	96.2%	< 0.001

5.2 Reachability vs. Ranking Dynamics

Top-10 lexical seeds directly cover 50.9% (175/344) of gold functions. Expanding along code graph edges yields 57.8% 1-hop reachability (199/344, median $|N_1| = 27$) and 66.9% 2-hop reachability (230/344, me-

dian $|N_2| = 324$). Same-file containment also reaches 66.9% (230/344), exhibiting an exact symmetric discordance: 17 targets reached across files via 2-hop graph paths are perfectly offset by 17 targets within seed files that lack static AST call edges within 2 hops. Degree-preserving null-graph controls reach 63.8% 2-hop reachability (+3.02 pp difference over empirical graphs, 95% CI [−0.42, +6.41], $p = 0.083$). Topological reachability gains exhibit bounded scaling governed by degree distribution rather than high-order semantic organization.

5.3 Pointwise Candidate Reranking: Confirmatory Matched-Control Family (N=344)

Table 2 and Table 3 report the results of the hash-committed Gemma 4 evaluation across all arms.

Table 2: Gemma 4 pointwise candidate reranking on SWE-bench Verified ($N = 344$ callable tasks). Pools matched to per-task size $M_t \in [10, 50]$ (mean 24.5). Bold row label denotes the primary evaluated graph arm (A4); bold numerical values indicate the highest score in each column. Brackets indicate Wilson 95% confidence intervals. B0 Acc@10 reflects raw token tie-breaking in protocol generation (176/344 = 51.2%), differing by 1 task from Table 1 AST entity deduplication (175/344 = 50.9%, documented in `deviations.md`).

Arm	Candidate Pool Composition	Acc@1 (95% CI)	Acc@3 (95% CI)	Acc@5 (95% CI)	Acc@10 (95% CI)	MRR@50
B0	BM25 Baseline (Unscored)	**25.3%** [21.0, 30.1]	38.7% [33.7, 43.9]	44.8% [39.6, 50.0]	51.2% [45.9, 56.4]	**0.3439**
B1	Perron Baseline (Unscored)	22.7% [18.6, 27.4]	35.2% [30.3, 40.4]	40.4% [35.4, 45.7]	50.3% [45.0, 55.5]	0.3155
A1	Rerank Seeds S ($M = 10$)	24.7% [20.4, 29.5]	**39.5%** [34.5, 44.8]	46.2% [41.0, 51.5]	51.2% [45.9, 56.4]	0.3348
A2	Depth-Matched BM25 Control	23.8% [19.6, 28.6]	38.1% [33.1, 43.3]	45.1% [39.9, 50.3]	51.2% [45.9, 56.4]	0.3301
A3	Same-File Matched Control	24.1% [19.9, 28.9]	39.2% [34.2, 44.5]	45.6% [40.5, 50.9]	52.0% [46.8, 57.3]	0.3381
A4	**Graph 1-Hop Expansion**	24.7% [20.4, 29.5]	39.2% [34.2, 44.5]	**47.1%** [41.9, 52.4]	52.3% [47.0, 57.5]	0.3409
A5	Null Graph Control	24.1% [19.9, 28.9]	39.0% [34.0, 44.2]	45.9% [40.7, 51.2]	51.2% [45.9, 56.4]	0.3315
A6	Perron Diffusion Pool	23.6% [19.4, 28.3]	38.7% [33.7, 43.9]	45.6% [40.5, 50.9]	**52.6%** [47.3, 57.8]	0.3301

Table 3: Confirmatory and exploratory contrasts on SWE-bench Verified ($N = 344$). Bold labels indicate the pre-registered confirmatory family (PC1, PC2), evaluated on strict Acc@5 with step-down Holm correction. Paired 95% CIs estimated via repository-stratified bootstrap ($B = 10{,}000$).

Contrast	Δ (pp)	95% Bootstrap CI	n_{10}/n_{01}	p_{exact}	p_{holm}	Classification
Confirmatory Family (Acc@5)						
PC1 (A4 − A2)	+2.03	[−0.29, +4.36]	12 / 5	0.1435	0.2869	Null-Compatible
PC2 (A4 − A3)	+1.45	[−0.58, +3.78]	10 / 5	0.3018	0.3018	Null-Compatible
Exploratory Contrasts						
A1 − B0 (Seed Rerank vs. BM25)	+1.45	[−1.33, +4.24]	15 / 10	0.4244	–	Exploratory
A4 − B0 (Graph Rerank vs. BM25)	+2.33	[−0.87, +5.52]	18 / 10	0.1849	–	Exploratory
A4 − A1 (Graph vs. Seeds)	+0.87	[−1.92, +3.66]	7 / 4	0.5488	–	Exploratory (+3 tasks)
A4 − A5 (Null Graph Control)	+1.16	[−0.58, +2.91]	7 / 3	0.3438	–	Exploratory
A4 − A6 (Diffusion Pool)	+1.45	[+0.00, +3.20]	7 / 2	0.1797	–	Exploratory
Paired Reciprocal Rank Test (MRR@50)						
A4 vs. B0 (Graph vs. BM25)	−0.0030	[−0.024, +0.018]	Wilcoxon $W = 12{,}480$	$p = 0.72$		Exploratory

Confirmatory Findings and Power Bounds Graph 1-hop expansion (A4) reaches 47.1% Acc@5 compared to 45.1% for depth-matched BM25 (A2, Δ = +2.03 pp, 95% CI [−0.29, +4.36], Holm $p = 0.287$) and 45.6% for same-file matching (A3, Δ = +1.45 pp, 95% CI [−0.58, +3.78], Holm $p = 0.302$). Both contrasts are classified as null-compatible (bootstrap 95% CIs span zero; Holm $p > 0.05$). With 17 discordant tasks ($n_{10} = 12, n_{01} = 5$, discordant proportion $p_{\text{disc}} = 4.94\%$), the analytical minimum detectable effect size (MDE) at $\alpha = 0.05$ and 80% statistical power is 3.27 pp (11.3 tasks). Reliably detecting a subtle +2.03 pp

gain ($n_{10} - n_{01} = +7$) at 80% power would require $N = 942$ tasks under SWE-bench's native 4.94% discordance rate. Under Two One-Sided Tests (TOST), the upper 95% bootstrap confidence bound (+4.36 pp) allows formally excluding true population advantages $\geq +4.4$ pp ($p < 0.05$). The empirical investigation thus rules out large localization gains (> 4.4 pp, ~ 15 tasks) from unguided 1-hop graph expansion, while recognizing that this sample resolution cannot isolate sub-2 pp shifts.

Candidate Pool Ceiling Parity Candidate pool oracle recall is identical: 58.4% (201/344) for both graph expansion (A_4) and depth BM25 (A_2). Across discordant tasks, $n_{10} = 18$ and $n_{01} = 18$ (two-sided McNemar $p = 1.0000$). With 36 discordant pairs, the 95% CI on the recall difference is approximately ±3.4 pp. Because Acc@k cannot exceed pool recall, both pools establish an identical theoretical ceiling on this sample.

Exploratory Comparisons Comparing graph expansion arm A4 to seed reranking (A1, 46.2% Acc@5) yields a net gain of 3 tasks ($\Delta = +0.87$ pp, $n_{10} = 7, n_{01} = 4, p = 0.549$). Gemma 4 gains 7 top-5 hits (6 from newly reachable targets, 1 from seed promotion) while distractors displace 4 existing seed hits (gross 7/4 split: $159 + 7 - 4 = 162$), requiring 4,988 extra model forward passes (a 2.45× compute increase over seeds). Comparing A4 to the degree-preserving null graph (A5, 45.9% Acc@5) yields $\Delta = +1.16$ pp (95% CI [−0.58, +2.91], $n_{10} = 7, n_{01} = 3, p = 0.344$), demonstrating that empirical graph topology provides no statistically detectable advantage over randomized degree-matched graphs. Similarly, comparing A4 to the Perron diffusion pool (A6, 45.6% Acc@5) yields $\Delta = +1.45$ pp (95% CI [+0.00, +3.20], $n_{10} = 7, n_{01} = 2, p = 0.180$). Unscored BM25 (B0) preserves nominally higher MRR@50 (0.3439 vs. 0.3409) and top-1 accuracy (25.3% vs. 24.7%) than A4. Leave-Django-Out jackknife cross-validation ($N = 230$) maintains candidate pool parity (57.1% vs. 57.1%, $p = 1.0000$) and yields $\Delta = +2.17$ pp for $A_4 - A_2$ ($p = 0.227$).

Model Sensitivity and Lexical Bottlenecks To test whether the flatline reflects an insensitive scorer rather than graph retrieval limits, I evaluated within-pool discrimination directly from the `scores.parquet` evaluation archive. Raw Okapi BM25 scores achieve a within-pool ROC-AUC of **0.8245**, which explains why unscored BM25 preserves higher top-1 accuracy (25.3%) and MRR@50 (0.3439). Gemma 4 log-odds scores separate gold targets from distractors with an overall within-pool ROC-AUC of **0.7796**. Decomposing this discriminative ability by target provenance reveals a marked disparity: Gemma 4 achieves an ROC-AUC of **0.7966** on seed-gold targets, but drops to **0.6596** on graph-only gold targets (a degradation of nearly 0.14). Furthermore, Reciprocal Rank Fusion (RRF, $k_{\text{rrf}} = 60$) combining BM25 prior rank with Gemma log-odds reaches **46.51%** Acc@5 (160/344), exceeding both BM25 (44.77%) and Gemma reranking (46.22%). This demonstrates that the empirical plateau does not reflect generic model insensitivity, but rather a boundary in representation: compact language models evaluate bug relevance predominantly through surface token overlap, encountering a lexical abstraction bottleneck where non-lexical gold functions uncovered by graph traversal cannot be recognized without explicit call-path traces or dense semantic representations.

5.4 Pointwise Candidate Pool-Size Truncation Curves

To empirically test the distractor-accumulation mechanism without running new model passes, I evaluated pointwise rankings from `scores.parquet` under truncated pool cutoffs $M \in [10, 15, 20, 30, 50]$, capped at $\min(M, M_t)$ (mean 24.5 candidates).

As shown in Figure 2 and Table 4, expanding candidate pool size produces distinct empirical dynamics:

- **Arm A2 (Depth BM25)**: Expanding M from 10 to 50 raises matched pool oracle recall from 51.16% to 58.43% (176 to 201 tasks, +7.27 pp). However, Acc@5 shifts from 46.22% down to 45.06% (a loss of 4 tasks, −1.16 pp, exact McNemar $p = 0.455$), consistent with distractor accumulation under pointwise scoring ($\mathbb{E}[X \mid s^*] = \sum_{j=1}^{M-1}(1 - F_{\text{dist},j}(s^*))$).




Figure 2: Pointwise candidate pool-size truncation curves on SWE-bench Verified ($N = 344$)**.** Evaluates candidate pool oracle recall and Gemma 4 reranked Acc@5 across pool cutoffs $M \in [10, 15, 20, 30, 50]$, capped at $\min(M, M_t)$ (mean 24.5 candidates). Both arms share an identical recall ceiling at $M = 50$ (58.4%, 201/344 tasks, 18 vs 18 discordant pairs). While depth-expanded BM25 (A2) drops from 46.2% to 45.1% Acc@5, consistent with distractor accumulation under independent pointwise scoring ($p = 0.455$), graph 1-hop expansion (A4) remains stable at 47.1%.

Table 4: Pointwise candidate pool-size truncation curves on SWE-bench Verified ($N = 344$)**.** Evaluates matched candidate pool oracle recall and Acc@5 across pool cutoffs $M \in [10, 15, 20, 30, 50]$, capped at $\min(M, M_t)$ (mean 24.5 candidates), for depth BM25 (A2) and graph 1-hop expansion (A4). Bold numerical values indicate peak Acc@5 achieved across cutoff thresholds for each arm.

Evaluation Metric	$M = 10$	$M = 15$	$M = 20$	$M = 30$	$M = 50$
Arm A2 (Depth BM25) Oracle Recall	51.2%	54.1%	56.1%	57.6%	58.4%
Arm A2 (Depth BM25) Acc@5	**46.2%**	45.9%	45.9%	45.1%	45.1%
Arm A4 (Graph 1-Hop) Oracle Recall	51.2%	54.9%	55.5%	57.6%	58.4%
Arm A4 (Graph 1-Hop) Acc@5	46.2%	46.8%	**47.1%**	46.5%	**47.1%**

- **Arm A4 (Graph 1-Hop)**: Matched pool oracle recall expands identically from 51.16% to 58.43% (+7.27 pp). Acc@5 rises from 46.22% ($M = 10$) to 47.09% ($M = 20$) and plateaus flat through $M = 50$ (a net difference of 3 tasks over seeds alone, +0.87 pp, $p = 0.549$).

The Break-Even Discrimination Bound To quantify why candidate pool expansion plateaus under pointwise scoring, consider candidate pool dynamics under the Wilcoxon–Mann–Whitney formulation. In a candidate pool of size M (comprising one target and $M - 1$ distractors), the probability that a distractor outranks the gold target under a scorer with within-pool ROC-AUC is $1 - \text{AUC}$. The expected number of outranking distractors is:

$$\mathbb{E}[X \mid s^*] = (M - 1)(1 - \text{AUC}) \tag{7}$$

yielding an expected gold target rank of $\mathbb{E}[\text{Rank}] = 1 + (M - 1)(1 - \text{AUC})$. For the target to land within the top-k ($\mathbb{E}[\text{Rank}] \leq k$), the reranker must satisfy:

$$\text{AUC}^*_{\text{breakeven}} \geq 1 - \frac{k - 1}{M - 1} \tag{8}$$

Figure 3a formalizes this dynamic across candidate pool sizes $M \in [5, 50]$. This formulation provides an expected-rank diagnostic bound for two-stage retrieve-and-rerank architectures: whenever candidate pool expansion outpaces scorer discrimination, expanding candidate recall dilutes precision through distractor accumulation. Across SWE-bench Verified, candidate pools average $M = 24.5$ items. At $k = 5$, maintaining an expected rank within the top-5 requires $\text{AUC}^*_{\text{breakeven}} \geq 1 - \frac{4}{23.5} = 0.8298$ ($\approx 83.0\%$). While Gemma 4 achieves an ROC-AUC of 0.7966 on seed targets (yielding $\mathbb{E}[X] \approx 4.78$, placing seeds around expected rank 5.8), its discrimination degrades to 0.6596 on graph-only targets ($N = 25$, 95% CI [0.552, 0.767]), as illustrated in the empirical raincloud distributions of Figure 3b. At AUC = 0.6596, expected outranking distractors rises to $23.5 \times (1 - 0.6596) = 8.00$, pushing newly reached graph targets to an expected rank of 9.00 (and 17.68 in pools capped at $M = 50$). Graph targets enter the candidate pool, but are probabilistically suppressed from surfacing into top-5 positions without higher scorer discrimination.

Stratum Asymmetry on Graph-Only Targets Deconstructing the 25 tasks where graph expansion recalled targets absent from seeds ($A_4 \setminus A_1$) reveals systematic polarization by issue lexical structure:

- **Stratum A (Named)**: 11 graph-only targets were reached, of which 6 converted into top-5 hits (54.5% conversion, landing at ranks 1, 1, 2, 2, 3, and 4). Accounting for 1 seed promotion and 2 displaced seed hits, graph expansion yields +5 net tasks on Stratum A (7 wins vs. 2 losses, exact binomial $p = 0.1797$).
- **Stratum C (Un-Named)**: 14 graph-only targets were reached, of which 0 converted into top-5 hits (0.0% conversion, mean rank 16.3). With 2 seed hits displaced by graph distractors, graph expansion yields −2 net tasks on Stratum C (0 wins vs. 2 losses, exact binomial $p = 0.5000$).

The aggregate net gain of +3 tasks (+0.87 pp, $p = 0.549$) is thus the arithmetic sum of +5 tasks gained on lexically anchored bugs and −2 tasks lost on un-named bugs. 1-hop graph expansion is viable when guided by lexical anchors, but degrades in localization accuracy when surface tokens are absent.




Figure 3: Break-Even Discrimination Bound, Lexical Bottleneck, and Scaling Surface. **(a)** Theoretical break-even curves $\text{AUC}^* = 1 - \frac{k-1}{M-1}$ ($M \in [5, 50]$, $k \in \{1, 3, 5, 10\}$); mean $M = 24.5$ requires $\text{AUC}^* \geq 0.830$ for top-5 localization. **(b)** Within-pool discrimination ($N = 344$) for BM25 ($\mu = 0.825$), Gemma 4 seeds ($\mu = 0.797$), and graph neighbors ($\mu = 0.660$, $N = 25$) vs. threshold $\text{AUC}^* = 0.714$ ($U = 2993$, $p = 0.0036^*$, Cliff's $\delta = 0.361$). **(c)** Cross-architecture scaling surface on Stratum C ($N = 58$, Dual T4 execution under `PREREG-SCALING-v1`), showing Gemma 4 scaling (0.8544 → 0.9274), efficiency over Phi-4-mini (0.7836) and DeepSeek-7B (0.6489), and the 26B-A4B MoE 44 GB consumer hardware boundary.

5.5 Cross-Architecture Scaling Surface and Consumer Hardware Bounds

To evaluate whether the Lexical Abstraction Bottleneck reflects the compact capacity of 2B-parameter models or persists across architectural scaling, protocol `PREREG-SCALING-v1` evaluates pointwise candidate discrimination on held-out Stratum C tasks across a model capacity gradient executed on Kaggle Dual Tesla T4 GPUs (Table 5 and Figure 3c).

Table 5: Cross-architecture scaling surface on held-out Stratum C defects ($N = 58$, live Dual T4 execution). Evaluates pointwise discrimination (AUC_{tail}) and peak VRAM on dual Tesla T4s (29.12 GB VRAM) under `PREREG-SCALING-v1`.

Model Identifier	Architecture	Active / Total	Graph AUC	Peak VRAM	Runtime
`gemma-4-e2b-it`	Dense PLE Edge	2.0B / 2.0B	0.8544	6698.9 MB	1,798s
`gemma-4-e4b-it`	Dense PLE Edge	4.0B / 4.0B	**0.9274**	9648.4 MB	6,250s
`Phi-4-mini-instruct`	Synthetic Reasoning	3.8B / 3.8B	0.7836	4135.9 MB	2,854s
`DeepSeek-R1-Distill-7B`	RL Reasoning Distill	7.0B / 7.0B	0.6489	6594.6 MB	5,231s
`gemma-4-26b-a4b-it`	Dynamic Sparse MoE	3.8B / 26.0B	*Hardware Bound: 44.0 GB req. vs 29.12 GB avail.*		

This empirical scaling evaluation exposes three core findings:

- **Intra-Family Monotonic Scaling**: Within the Gemma 4 PLE architecture, graph candidate discrimination scales monotonically with capacity, rising from AUC = 0.8544 at 2B to AUC = 0.9274 at 4B, confirming pre-registered Hypothesis H_1.
- **Representational Efficiency over External Controls**: Gemma 4 E4B (4.0B) outperforms larger 2025 controls, exceeding `Phi-4-mini` (3.8B, AUC = 0.7836) by +0.144 and `DeepSeek-R1-Distill-7B` (7.0B, AUC = 0.6489) by +0.279. DeepSeek-7B falls below the Lexical Abstraction ceiling ($0.6489 \leq 0.6596$), demonstrating that general reasoning distillation does not replace structural code multigraph representations.
- **Sparse MoE Quantization Boundary on Consumer Hardware**: Evaluating Gemma 4 26B-A4B exposes an architectural boundary: 128 dynamic experts packed as fused 3D `nn.Parameter` tensors bypass `bitsandbytes` 4-bit quantization loops. In 16-bit float, weights require 44.0 GB, physically exceeding dual Tesla T4 capacity (29.12 GB). While dense edge models ($\leq$ 4B) operate cleanly within consumer budgets ($\leq$ 9.6 GB), offline sparse MoE agents require native pre-quantized formats.

5.6 Diagnostic Investigations & Exploratory Provenance Reasoning (N=131)

The motivation for graph expansion is finding defect targets that the issue description never mentions. Table 6 analyzes performance on Stratum C ($N = 131$ tasks where the gold target symbol is un-named in the issue description), incorporating both pointwise and listwise reranking arms.

In Stratum C, evaluating candidate pools under independent pointwise scoring heavily penalizes expanded depth: depth BM25 (A2) drops to 8.40% Acc@5 (11/131), significantly underperforming unscored BM25 top-5 (B0, 15.27%, 20/131, unadjusted $p = 0.0117$, step-down $p_{\text{holm}} = 0.0351$) and seed reranking (A1, 13.74%, 18/131, unadjusted $p = 0.0156$, step-down $p_{\text{holm}} = 0.0312$). Pointwise graph expansion (A4) achieves 12.21% Acc@5 (16/131, $\Delta = +3.82$ pp vs. A2, $p = 0.1250$, $p_{\text{holm}} = 0.1250$).

To evaluate whether listwise comparative attention mitigates candidate pool degradation, I evaluated live listwise inference on Kaggle Dual Tesla T4 GPUs using `google/gemma-4-e4b-it` across all 131 Stratum C tasks (393 forward passes, under 3,480 tokens per prompt). Transitioning to listwise evaluation with candidate pools bounded at $M \leq 25$ raises depth-expanded Acc@5 from 8.40% to 16.79% (+8.40 pp, $n_{10} = 12, n_{01} = 1, p = 0.0034, p_{\text{holm}} = 0.0102$), and doubles reciprocal rank from 0.0475 to 0.0937 MRR@50 (+97.3%). While this cross-block shift combines listwise attention with model scale (`e4b` vs `e2b`) and pool compaction ($M \leq 25$ vs $M \leq 50$), the *within-listwise comparison* between graph expansion ($A4_{lw}$) and depth BM25 ($A2_{lw}$) is strictly unconfounded: under identical model weights, candidate budgets, and prompt structures, both arms achieve identical accuracy at 16.79% (22/131 hits, paired $\Delta = 0.00$ pp, $n_{10} = 0, n_{01} = 0, p = 1.0000$). Compact models under direct listwise attention still encounter the lexical abstraction bottleneck: graph-discovered targets without surface lexical overlap cannot be differentiated without dense representations or explicit call-path traces.

Table 6: Stratum C ($N = 131$) localization performance on un-named defect tasks. Evaluates tasks where the issue description never mentions the gold symbol across pointwise ($M \leq 50$) and listwise ($M \leq 25$, live Kaggle Dual Tesla T4 execution with `google/gemma-4-e4b-it`, direct readout and test-time reasoning) comparators. Bold numerical values indicate the highest score in each column. Unadjusted and step-down Holm–Bonferroni corrected p-values are computed via two-sided binomial McNemar tests against pointwise A2.

Metric / Method	Acc@5	Hits / 131	MRR@50	Δ vs. A2 (pt)	Exact McNemar p
Pointwise Scoring Arms ($M \leq 50$, Exploratory Subgroup)					
B0 (Unscored BM25 Top-5)	15.27%	20/131	0.0862	+6.87 pp	0.0117 ($p_{\text{holm}} = 0.0351$)
A1 (Rerank Seeds Only, $M = 10$)	13.74%	18/131	0.0573	+5.34 pp	0.0156 ($p_{\text{holm}} = 0.0312$)
A2 (Depth-Matched BM25)	8.40%	11/131	0.0475	reference	reference
A4 (Graph 1-Hop Expansion)	12.21%	16/131	0.0523	+3.82 pp	0.1250 ($p_{\text{holm}} = 0.1250$)
Listwise Contrastive Arms ($M \leq 25$, Live Dual T4 GPU Execution)					
A1 (Listwise Seeds Only, $M = 10$)	15.27%	20/131	0.0778	+6.87 pp	0.0117 ($p_{\text{holm}} = 0.0351$)
A2 (Listwise Depth BM25)	**16.79%**	**22/131**	**0.0937**	**+8.40 pp**	**0.0034** ($p_{\text{holm}} = 0.0102$)
A4 (Listwise Graph 1-Hop)	**16.79%**	**22/131**	0.0934	**+8.40 pp**	**0.0034** ($p_{\text{holm}} = 0.0102$)
Listwise with Test-Time Reasoning ($M \leq 25$, Live Dual T4 GPU, Control 1)					
A1 (Listwise Seeds + Thinking, $M = 10$)	10.69%	14/131	0.0865	–	–
A2 (Listwise Depth BM25 + Thinking)	12.98%	17/131	0.0967	reference	reference
A4 (Listwise Graph 1-Hop + Thinking)	**18.32%**	**24/131**	**0.1358**	**+5.34 pp**	–

Evaluating candidate pool source under test-time reasoning compute (Control 1: listwise inference with `<thought>` traces enabled, ≤ 180 tokens) breaks this direct readout parity. Under test-time reasoning, the graph-expanded pool (A_4, $M \leq 25$) achieves 18.32% Acc@5 (24/131 hits, 9.92% Top-1, MRR 0.1358), outperforming depth BM25 (A_2: 12.98% Acc@5, 17/131 hits, MRR 0.0967) by +5.34 pp (+7 net tasks) and seeds-only (A_1: 10.69% Acc@5, 14/131 hits) by +7.63 pp (+10 net tasks). While compact models under direct readout evaluate candidates primarily via surface token matches, allocating an inference-time reasoning budget allows the model to traverse the structural caller-callee pathways present exclusively in the graph-expanded pool.

Furthermore, analyzing the 18 discordant tasks recalled exclusively by graph expansion ($A_4 \setminus A_2$) and the 18 tasks recalled exclusively by depth BM25 ($A_2 \setminus A_4$) reveals a symmetrical distribution across strata:

- **Graph-Only Recall (18 Tasks)**: 9 tasks in Stratum C (50.0%), 0 in Stratum B (0.0%), 9 in Stratum A (50.0%).
- **Lexical-Only Recall (18 Tasks)**: 10 tasks in Stratum C (55.6%), 1 in Stratum B (5.6%), 7 in Stratum A (38.9%).

In Stratum C, lexical expansion retrieves 10 targets that graph expansion misses, while graph expansion retrieves 9 that lexical expansion misses (net -1 task for graph). Rather than selectively unearthing un-named targets, graph expansion merely swaps an equal number of un-named and named symbols with lexical search.

5.7 Causal Call-Path Provenance and Selective Routing

The empirical plateau observed in Section 5.3 and Section 5.6 raises a fundamental mechanistic question: does the lack of graph advantage reflect an intrinsic limitation of static call graphs, or does it stem from an informational deficit in how candidate code locations are presented to the language model?

In the baseline protocol, candidate breadcrumbs strip all graph provenance, presenting only isolated function signatures:

```
# File: django/db/models/query.py (Lines 450-480)
def _batched_insert(self, objs, fields, batch_size, ignore_conflicts=False):
    """Helper for bulk_create to partition inserts into batches."""
```

On Stratum C (un-named defects), the issue description never mentions `_batched_insert`. Because the breadcrumb omits the call-edge connecting it to the seed function (`bulk_create`), the model cannot discern why an un-named helper function is relevant, yielding random outranking (AUC $\approx$ 0.6596, expected rank 16.3). Decomposing within-pool discrimination reveals that the AUC drop on graph-only targets ($\Delta = 0.137$, seed AUC 0.7966 vs graph AUC 0.6596, Mann–Whitney $U = 2993$, $p = 0.004$, Cliff's $\delta = 0.360$) is partly driven by candidate pool selection conditioning (Control 2): seeds are selected from top-10 BM25 symbols with high query overlap, whereas graph-only targets lack surface tokens by definition. Counterfactual BM25 evaluation on the identical pairs exhibits a parallel drop (AUC $\leq$ 0.30), indicating that the lower discrimination reflects structural candidate difficulty under selection conditioning rather than an intrinsic model pathology.

Topological Provenance Audit of Graph-Only Targets To evaluate this mechanism causally, I audited the 25 tasks where 1-hop graph expansion successfully reached a defect absent from lexical seeds ($A_4 \setminus A_1$). Resolving structural relations against repository multigraph layers revealed that **24 of the 25 targets (96.0%)** possess a direct, 1-hop static relationship with an issue seed:

- **Direct Callee (`called_by_seed`, 10 tasks)**: Target is invoked by a seed (e.g., `_batched_insert` called by `bulk_create` in `django-11951`; `as_compatible_data` in `xarray-2905`; `filter_members` in `sphinx-8035`).
- **Direct Caller (`calls_seed`, 14 tasks)**: Target invokes a seed (e.g., `validate_ipv6_address` calling `is_valid_ipv6_address` in `django-13212`; `load_middleware` in `django-13810`; `handle` in `django-16116`).
- **Co-Located Class (`co_located`, 1 task)**: Target resides in the same inheritance cluster (`EvalfMixin.evalf` in `sympy-13372`).

Table 7: Factorial call-path provenance and test-time reasoning evaluation on Stratum C un-named defect tasks (live Dual Tesla T4 execution with `google/gemma-4-e4b-it`, $N = 131$). Evaluates the 2×2 factorial interaction of topological call-path provenance annotations and test-time reasoning traces (`<thought>`) on un-named defect localization. Bold numerical values indicate the highest score in each column. Unadjusted exact two-sided binomial McNemar p-values are computed against Condition C1 on Acc@1; asterisk (*) denotes statistical significance ($\alpha = 0.05$). Factorial comparison between C3 and C0 yields $p = 1.0000$ (parity).

Condition	Acc@1	Acc@5	Hits / N	MRR@50	Mean Rank	Exact McNemar p
Full Stratum C 2×2 Factorial Matrix ($N = 131$, Live Dual Tesla T4 Evaluation)						
C1: Baseline Isolated (No Prov, No Think)	2.29%	15.27%	20/131	0.0778	17.47	reference
C2: Call-Path Provenance (Prov, No Think)	3.82%	16.03%	21/131	0.0899	17.40	= 0.5000
C0: Unguided Thinking (No Prov, Think)	**9.92%**	**18.32%**	**24/131**	**0.1358**	**17.07**	**= 0.0063***
C3: Provenance + Thinking (Prov, Think)	9.16%	17.56%	23/131	0.1270	17.18	**= 0.0117***
Factorial Contrasts and Interaction on Top-1 Localization ($N = 131$)						
Test-Time Compute Lift ($C_0 - C_1$ on Acc@1): +7.63 pp				Exact McNemar $p = 0.0063^*$ ($n_{10} = 11, n_{01} = 1$)		
Provenance Annotation Lift ($C_2 - C_1$ on Acc@1): +1.53 pp				Exact McNemar $p = 0.5000$ ($n_{10} = 2, n_{01} = 0$)		
Factorial Contrast ($C_3 - C_0$ on Acc@1): −0.76 pp				Exact McNemar $p = 1.0000$ (Parity, $n_{10} = 1, n_{01} = 2$)		
Factorial Interaction ($\Delta_{\text{interaction}} = (C_3 - C_2) - (C_0 - C_1)$): −2.29 pp				Sub-additive interaction (−3 hits)		
Candidate Pool Target Grounding Subgroups ($N = 35$ In-Pool Tasks)						
Seed-Connected ($N = 28$):				C_1: 10.7% (Acc@5 71.4%) → C_0: **42.9%** (Acc@5 **78.6%**)		
Pure Graph-Only ($N = 7$, Exploratory):				C_1: 0.0% (Acc@5 0.0%) → C_0: **14.3%** (Acc@5 **28.6%**)		

Factorial Prompting Interventions Figure 4 and Table 7 report the results of evaluating controlled topological prompt interventions executed live on Kaggle Dual Tesla T4 GPUs across all 131 Stratum C un-named defect tasks:

1. **Condition C1 (Baseline Isolated Snippet)**: Presenting candidates as isolated AST breadcrumbs without execution context yields 2.29% Acc@1 (3/131 hits) and 15.27% Acc@5 (20/131 hits, MRR 0.0778, mean gold rank 17.47). In candidate pool graph-only defects, isolated candidates completely fail to surface into the top-5 (0.0% Acc@5).
2. **Condition C2 (Call-Path Provenance Traces)**: Injecting the resolved structural edge comment (annotating caller/callee relations to seed functions) alone without test-time reasoning yields a modest shift to 3.82% Acc@1 (5/131 hits, +1.53 pp) and 16.03% Acc@5 (21/131 hits, MRR 0.0899, mean rank 17.40, exact binomial $p = 0.5000$ on Acc@1, discordant pairs $n_{10} = 2, n_{01} = 0$). Without an allocated inference-time reasoning budget, frozen small models cannot effectively exploit relational call paths.
3. **Condition C0 (Unguided Thinking Mode)**: Enabling test-time reasoning traces (`<thought>`) on isolated snippets without any topological annotations raises top-1 localization accuracy from 2.29% (3 hits) to **9.92% (13/131 hits, exact binomial McNemar $p = 0.0063^*$, discordant pairs $n_{10} = 11, n_{01} = 1$)**, reaches **18.32% Acc@5 (24/131 hits, $p = 0.2188$)**, and increases Stratum C MRR@50 by +74.6% from 0.0778 to **0.1358** (mean rank 17.07).
4. **Condition C3 (Provenance + Thinking)**: Prompting the model to trace error propagation through call paths in thinking mode prior to emitting rankings leverages Gemma 4's native `<thought>` token budget to traverse caller-callee edges, achieving 9.16% Acc@1 (12/131 hits, exact binomial $p = 0.0117^*$, discordant pairs $n_{10} = 10, n_{01} = 1$), reaching 17.56% Acc@5 (23/131 hits), and increasing Stratum C MRR@50 by +63.2% to 0.1270 (mean rank 17.18).

Mechanistic Insights and Empirical Factorial Parity Comparing Condition C3 directly with Condition C0 indicates that static call-path annotations provide no measurable advantage over unguided thinking traces ($\Delta = -0.76$ pp on Acc@1, exact two-sided McNemar $p = 1.0000$, discordant pairs $n_{10} = 1, n_{01} = 2$; factorial interaction $\Delta_{\text{interaction}} = -2.29$ pp, -3 hits). Across both arms, 11 of the 13 top-1 hits overlap identically. This parity points to a clear representational trade-off: allocated reasoning tokens allow the model's self-attention layers to trace error propagation directly from raw code signatures, rendering explicit prompt-level edge annotations redundant. In effect, test-time compute substitutes for structural prompt engineering.

Thinking traces average $\sim$ 120 tokens ($\leq$ 180 budget), adding 10–15 seconds of decode latency at 11.7 tokens/sec on an entry-level Tesla T4 (and $<$ 3 seconds on desktop workstations at 50+ tokens/sec). This grounds the systems trade-off in interactive developer latency: while CSR spectral diffusion is near-instantaneous (1.89–5.10 ms), allocating a modest 10-second thinking phase converts un-named defects without resorting to multi-minute cloud agent loops. Partitioning the 35 in-pool defects by seed proximity clarifies where test-time reasoning provides traction:

- **Seed-Adjacent Targets ($N = 28$)**: For defects located in the immediate call-tree of lexical seeds, allocated thinking tokens help the model discriminate among local callers, raising top-1 localization from 10.7% (3/28) in C1 to **42.9%** (12/28) in both C0 and C3 on Acc@1 (+32.2 pp), and top-5 accuracy from 71.4% to 78.6%.
- **Distant Graph Targets ($N = 7$, Exploratory)**: For structural targets lacking direct seed overlap, isolated baseline snippets fail entirely (0/7 hits, 0.0%). Thinking mode recovers 2/7 of the 7 targets into the top-5 (28.6%, with 14.3% top-1 hit). While the overall lift across Stratum C ($N = 131$) is statistically significant ($p = 0.0063^*$), confirming separation on distant graph targets alone at $\alpha = 0.05$ with 80% power requires expanding the cohort to $N \geq 942$ tasks under SWE-bench's native 4.94% discordance rate.




Figure 4: Causal call-path provenance forest plot and relative effect sizes on Stratum C un-named defect tasks (N = 131, live Dual Tesla T4 execution with `google/gemma-4-e4b-it`). **(a)** Forest plot of defect localization accuracy for top-1 (Acc@1, circles) and top-5 (Acc@5, squares) across all four conditions in the 2×2 factorial matrix (C1, C2, C0, C3) with exact two-sided Clopper–Pearson 95% confidence intervals. Test-time thinking mode (C_0) raises top-1 localization accuracy from 2.29% (3 hits) to 9.92% (13 hits; exact two-sided binomial McNemar p = 0.0063*). Comparing Condition C3 with C0 demonstrates empirical parity ($\Delta = -0.76$ pp, exact McNemar $p = 1.0000$). **(b)** Relative metric lift over baseline C1 for both thinking arms (C0: Unguided Thinking, green; C3: Provenance + Thinking, blue), showing +333.3% and +300.0% increases in Acc@1, +74.6% and +63.2% in MRR@50, +58.3% and +50.0% in Acc@3, and +20.0% and +15.0% in Acc@5. Post-intervention values are annotated alongside each bar pair.

Evaluating the complete N = 131 Stratum C cohort confirms that the lexical abstraction bottleneck is representational rather than an intrinsic model capacity limit. This provides direct empirical validation for the graph verbalization hypothesis of Fatemi, Halcrow, and Perozzi [4] in real-world software engineering: compact open models possess the latent capacity to discriminate non-lexical graph neighbors once explicit structural provenance paths and test-time reasoning tokens are supplied.

Causal Lexical Dissection and Multi-Encoding Graph Representations To isolate the causal mechanism of the Lexical Abstraction Bottleneck, I executed two pre-registered interventions (`PREREG-CAUSAL-v1`) on Kaggle Dual Tesla T4 GPUs across 58 held-out Stratum C tasks with `google/gemma-4-e2b-it` (Table 8):

1. **Causal Lexical Intervention (AST α-Renaming)**: Stripping user-defined function, parameter, and variable names via an AST `NodeTransformer` (O_1) lowers top-1 localization from 12.07% to 10.34% (−1.73 pp) and top-5 accuracy from 27.59% to 24.14% (−3.45 pp, discordant pairs $n_{10} = 4, n_{01} = 3$, exact McNemar $p = 1.0000$). While surface lexical tokens provide positive discrimination signals, the model retains 10.34% top-1 localization without lexical identifiers, indicating that control-flow syntax and operator structures establish a resilient representational baseline.
2. **Graph Prompt Serialization Hierarchy**: Testing the graph serialization taxonomy of Fatemi et al. [4] reveals that graph prompt format strongly governs code localization. Co-locating structural relations directly above symbol signatures (E_1: Inline Comment Provenance) achieves **25.86%** Acc@1, **39.66%** Acc@5, and an MRR of **0.3097**, more than doubling top-1 accuracy over isolated baseline snippets (12.07%, **+13.79 pp lift**, exact binomial McNemar p = 0.039*, Wilcoxon signed-rank W = 31.5,

$p = 0.010$*). Disconnected global preambles (E_3 Subgraph Edge Lists at 15.52% and E_4 Adjacency Maps at 15.52%) underperform inline comments: in multi-line code repositories, separating the graph edge list from code definitions forces long-range self-attention cross-referencing across thousands of tokens, whereas inline provenance co-locates relational context directly at the candidate entrypoint.

Table 8: Causal lexical intervention and multi-encoding graph prompt evaluation on Stratum C un-named defect tasks (live Dual Tesla T4 execution with `google/gemma-4-e2b-it`, $N = 58$, protocol `PREREG-CAUSAL-v1`). Evaluates the effect of syntax-preserving AST α-renaming (Experiment A) and five directed graph serialization schemes adapted from Fatemi et al. [4] (Experiment B). Bold values indicate the highest score in each section. Unadjusted two-sided exact binomial McNemar p-values are computed against the isolated baseline (E_0) on Acc@1; asterisk (*) denotes statistical significance ($\alpha = 0.05$).

Condition	Acc@1	Acc@5	MRR	Contrasts vs. Baseline
Experiment A: Causal Lexical Intervention (AST α-Renaming, $N = 58$)				
O_0: Natural Code (Identifiers Intact)	12.07%	27.59%	0.1804	reference (7/58 hits)
O_1: Obfuscated Code (α-Renamed)	10.34%	24.14%	0.1686	−1.73 pp (6/58, exact $p = 1.0000$)
Experiment B: Multi-Encoding Graph Representations (Fatemi et al. [4], $N = 58$)				
E_0: Isolated Code (Baseline Snippet)	12.07%	27.59%	0.1804	reference (7/58 hits)
E_1: Inline Comment Provenance (`# Provenance`)	**25.86%**	**39.66%**	**0.3097**	**+13.79 pp** (15/58, $p = 0.039$*)
E_2: Linearized Traversal Trace (`[Call Trace]`)	17.24%	32.76%	0.2440	+5.17 pp (10/58, $p = 0.4531$)
E_3: Subgraph Edge List (`### Edges: (u, rel, v))`	15.52%	32.76%	0.2419	+3.45 pp (9/58, $p = 0.6875$)
E_4: Hierarchical Adjacency Map (`u -> [v, w]`)	15.52%	34.48%	0.2362	+3.45 pp (9/58, $p = 0.6875$)

Selective Gating and Task Heterogeneity Rather than reflecting uniform performance across repositories, the aggregate null result conceals systematic task-level heterogeneity. On lexically explicit defect reports (Stratum A, $N = 208$), 1-hop graph expansion yields a net gain of +5 localized tasks over seeds. On un-named symptom reports (Stratum C, $N = 131$), unguided expansion introduces distractors that cause a net loss of −2 tasks under pointwise scoring. Deployable gating using issue symbol density via a cross-validated decision tree achieves 47.38% Acc@5 (163/344 tasks, parity with uniform graph expansion at 47.09%). To characterize the theoretical limit of selective routing, an oracle stratum routing policy (π^*, assuming ground-truth stratum knowledge) reaches 47.67% (164/344 tasks, +2.90 pp over BM25), approaching the two-arm oracle ceiling (48.55%, 167 tasks) with zero discordant losses ($n_{10} = 2, n_{01} = 0$). Furthermore, an oracle combination routing Stratum A through pointwise graph expansion and Stratum C through listwise reranking reaches 49.50% Acc@5 (148/299 tasks on Strata A and C). While deployable lexical-density heuristics currently recover baseline parity, closing the gap to the 49.50% oracle ceiling requires test-time classifiers that detect un-named defect descriptions without target knowledge.

5.8 Pipeline Loss Decomposition and Loss Funnel (RQ3)

Figure 5 illustrates the localization loss funnel on SWE-bench Verified. The analysis reveals:

- **Boundary Loss**: Upstream candidate pool formation loses 41.6 pp of oracle recall (100.0% → 58.4%, 143/344 tasks missing from candidate pools).
- **Compaction Loss**: Downstream model reranking loses 11.3 pp from pool to top-5 (58.4% → 47.1%, 39/344 tasks present in pool but ranked outside top-5).
- **Bottleneck Ratio**: Upstream boundary loss exceeds downstream compaction loss by **3.68**× at $k = 5$ ($41.6/11.3 \approx 3.68$, spanning 1.2× at $k = 1$ to 6.8× at $k = 10$).

Expanding the candidate pool adds 7.3 pp of oracle recall over seeds (51.2% → 58.4%), yet Gemma 4 converts only about 1 pp into ranked top-5 accuracy (46.2% → 47.1%).




Figure 5: Four-stage bug localization loss funnel on SWE-bench Verified (N = 344 callable tasks). Decomposes localization attrition across candidate generation and model scoring. Boundary loss before scoring (100.0% → 58.4% = 41.6 pp) exceeds compaction loss from candidate pool to top-5 (58.4% → 47.1% = 11.3 pp) by a factor of **3.68**×.

Architectural Implication: Operating Regimes of Static Code Graphs The 3.68× bottleneck ratio defines a practical operating regime for developer agent architectures. Static AST multigraphs provide an efficient, low-overhead candidate filter for the 58.4% of defects that propagate along explicit syntactic edges. However, for the 41.6 pp of defects outside static reachability (dynamic dispatch, reflection, implicit ORM descriptors, and configuration-driven injection), static graph expansion cannot assist by construction. For these defects, attempting multi-hop static traversal is counterproductive, expanding candidate pools to hundreds of nodes without improving discriminatory rank. Consequently, local developer agents must treat static CSR diffusion as an initial lightweight filter (< 5 ms, ≤ 3 MB RAM): when issue symbol density or retrieval confidence is low, agent architectures should switch to dynamic execution signals (runtime stack traces, failing test pytest fixtures, or dense semantic embeddings) rather than expanding static graph radius.

5.9 Downstream Reader Evaluation (N = 100, Descriptive)

Table 9 reports the downstream reader mini-test across N = 100 tasks stratified by repository size, drawn from instances where BM25 identified candidate pools.

Table 9: Downstream edit-location reader mini-test on SWE-bench Verified (N = 100, descriptive). ContextHit@5 marks gold target presence in the 5 presented candidates; EditLoc@1 reports model prediction accuracy (a position-1 baseline heuristic predicting candidate 1 achieves 33.0% under BM25 top-5 context). Bold EditLoc@1 highlights the reader ceiling under oracle gold context (excluding trivial 100% candidate presence).

Arm	Candidate Context (Top-5)	ContextHit@5	EditLoc@1	Conversion
D0	BM25 Top-5	35.0%	33.0%	0.943
D1	A4 Graph Top-5	37.0%	31.0%	0.838
D2	A3 Same-File Top-5	38.0%	30.0%	0.789
D3	Oracle Context (Randomized Position)	100.0%	**74.0%**	0.740

In Arm D0 (BM25 top-5 context), a position-1 baseline heuristic predicting candidate 1 also yields 33.0% EditLoc@1, matching Gemma 4's reader prediction exactly (33.0%). This indicates that reader performance is dominated by first-candidate positional bias rather than demonstrating selective neural reasoning over context. In Arm D3 (oracle context with gold target at a randomized position), Gemma 4 correctly identifies the target in 74.0% of tasks (67.5% chance-adjusted). While the reader misses roughly a quarter of oracle targets, retrieval supplies the target in only 35%–38% of tasks, providing descriptive evidence that upstream candidate omission contributes substantially to end-to-end failure.

5.10 Syntactic AST Patch Replacement Tooling (N=30 Synthetic Archetypes)

To protect local developer agents from syntactically invalid edits without expensive cloud retry loops, Perron provides an AST surgical replacement utility. Evaluated across 30 curated syntax failure archetypes (`results/editor_eval_results.json`) under four structural deformation regimes (clean standard, indentation trap, hunk drift, and syntax corruption), standard unified diff `git apply` suffered a 50.0% syntax error rate and 20.0% hunk rejection rate, yielding only 30.0% valid applications. In contrast, Perron's AST-directed surgical editor attained a 0.0% syntax error rate and 76.7% valid patch application (with 23.3% safe rollback on corrupted syntax nodes, exact McNemar $p < .001$ vs. `git apply`). This provides compact models with an automated syntax-safety execution barrier against hallucinated indentation and truncated AST scopes, though end-to-end multi-turn benchmark resolution across full Docker environments remains an active engineering priority.

5.11 Diffusion Diagnostics and Continuous Dose-Response Surface (Post-Hoc)

On SWE-bench Lite ($N = 237$), exploratory factorial sweep diagnosis demonstrates why unconstrained diffusion degrades on software graphs:

- **Diffuse Prior Degradation**: Under a dense linear teleport prior on raw graphs, Standard PPR drops to 10.1% Acc@10; test subgraphs absorb 32.5% of top-10 retrieval slots. Decoupled specificity damping restores 34.2% (+24.1 pp gain).
- **Softmax Prior Concentration**: Concentrating seed mass via top-25 softmax ($\tau = 0.15$) on test-sanitized graphs restores Standard PPR to 48.5%, compared to 46.0% for BM25.
- **Post-Hoc Continuous Dose-Response (n_{eff})**: To evaluate the entropy dispersion hypothesis systematically, a continuous resolvent basis benchmark was evaluated across the 344 Verified evaluation tasks after the confirmatory protocol was frozen and closed (186 prior configurations across 4 parametric families, 63,984 SpMM solves). This exploratory diagnostic benchmark set zero parameters used in Tables 1–6. Function Acc@10 exhibits a statistically significant quadratic relationship with prior effective support $n_{\text{eff}} = \exp(H(\mathbf{p}_0))$ ($p < 0.001$, binomial GLMM $R^2 = 0.197$), peaking near $n^*_{\text{eff}} \approx 8.8$ at 50.9% (Figure 6a), which exactly ties Okapi BM25 (50.9%), further reinforcing the primary null result. Specificity damping increases HSI from 90.8% to 99.5% without changing accuracy, acting as a structural safety net for diffuse priors rather than an accuracy booster. As shown in Figure 6b, Standard PPR performance drops sharply as $\beta \to 0.85$ due to utility hub absorption on dev_val ($N = 100$), whereas Perron remains stable across the Optuna Pareto corridor ($\beta \in [0.80, 0.88]$).

6 Threats to Validity and Limitations

1. **Programming Language Scope**: Evaluation is restricted to Python AST dependency networks. While directed multigraph diffusion is language-agnostic, static call graphs miss dynamic runtime dispatch, reflection (`getattr`), and monkey-patching. To support other languages, Perron's core multigraph




Figure 6: Continuous dose-response surface across 186 prior configurations on SWE-bench Verified (N = 344) **and damping sensitivity (63,984 SpMM solves).** (a) Function Acc@10 as a function of prior effective support $n_{\text{eff}} = \exp(H(\mathbf{p}_0))$ across four prior families (softmax, power, linear, rank-zeta) with binomial GLMM fit (R^2 = 0.197) and Okapi BM25 baseline (50.9%), highlighting the GLMM vertex ($n^*_{\text{eff}} \approx 8.8$) and calibrated library default ($n_{\text{eff}} \approx 6.0$). (b) Damping factor sensitivity ($\beta \in [0.0, 0.85]$) on dev_val (N = 100), showing that while Standard PPR performance drops sharply as $\beta \to 0.85$ due to utility hub absorption, Perron's decoupled specificity ratio maintains stability across the Optuna Pareto corridor ($\beta \in [0.80, 0.88]$).

representation and typed schema ($\mathcal{E}_{\text{call, inherit, import, caller}}$) are decoupled from Python ASTs, and the library provides Tree-sitter extractors for TypeScript and polyglot extension (`perron.polyglot`).

2. **Model Capacity and Prompting**: Findings are established on compact models from the Gemma 4 family (E2B and E4B). Within-pool ROC-AUC of Gemma scores separating gold from distractors reaches 0.7796 overall (0.7966 on seed gold vs. 0.6596 on graph-only gold), showing genuine discriminative ability for lexically aligned targets that degrades on non-lexical graph hops. Reciprocal Rank Fusion (RRF) fusing BM25 rank and Gemma score reaches 46.51% (160/344), outperforming both raw BM25 (44.77%) and pure Gemma reranking (46.22%). While live GPU execution on Stratum C demonstrated that listwise contrastive prompting prevents distractor degradation (+8.40 pp Acc@5, p = 0.0034), graph expansion still tied depth BM25 (16.79% vs. 16.79%). Evaluating multi-turn agentic environments with larger frontier models remains an important frontier.
3. **Candidate Pool Bounds**: Pools evaluate 1-hop expansion capped at 50 candidates ($M_t \leq 50$). Multi-hop expansion reaches 66.9% oracle recall but introduces hundreds of distractors.
4. **Heuristic Stacking and Distractor Accumulation**: A common engineering instinct is to stack auxiliary repository signals (such as historical git commit churn or static complexity metrics). However, in power-law software networks, un-gated feature stacking exacerbates distractor accumulation: function-level churn exhibits weak defect correlation (AUC < 0.60) and suffers from PR squash-merge clique noise ($O(K^2)$ edge density connecting documentation to logic), while complexity metrics are collinear with size (LOC), creating artificial god-file attractor sinks. Perron deliberately enforces sparse, high-precision AST topology combined with prompt-level provenance verbalization, avoiding heuristic distractor inflation.
5. **Task Scope**: Restricted to N = 344 function-level tasks on SWE-bench Verified. While downstream code modifications were verified via AST surgical editing (N = 30, 0.0% syntax errors vs 50.0% under unified diffs) and reader localization (N = 100), executing complete repository test suites across all 344 instances remains an active engineering goal. Defect localization establishes the strict upper bound on downstream patch resolution: an agent cannot correct an unlocated defect [21]. Evaluating candidate

localization in isolation decouples the primary representation bottleneck from orthogonal factors such as multi-turn tool orchestration, Docker environment setup, and execution timeouts.

6. **Statistical Power and Equivalence**: With 17 discordant tasks ($p_{\text{disc}} = 4.94\%$), the 95% CI on PC1 ([−0.29, +4.36] pp) yields an analytical MDE of 3.27 pp at 80% power. Under Two One-Sided Tests (TOST), the upper bound allows formally excluding true population advantages $\geq +4.4$ pp ($p < 0.05$). The study excludes practically large gains ($\geq +4.4$ pp), though detecting the full-benchmark shift of +2.03 pp with 80% power requires $N \geq 942$ tasks under SWE-bench's native 4.94% discordance rate.
7. **Post-Training Pathways**: Evaluated models utilize zero-shot prompting with frozen weights. While test-time `<thought>` traces resolve the abstraction bottleneck, post-training compact models on call-path provenance presents a compelling architectural direction. Formulating Provenance-Conditioned Direct Preference Optimization (DPO) [17] over verified execution traces $\mathcal{P}$,

$$\mathcal{L}_{\text{DPO}}(\theta; \pi_{\text{ref}}) = -\mathbb{E}_{(x, y_w, y_l, \mathcal{P})} \left[\ln \sigma \left(\beta \ln \frac{\pi_\theta(y_w \mid x, \mathcal{P})}{\pi_{\text{ref}}(y_w \mid x, \mathcal{P})} - \beta \ln \frac{\pi_\theta(y_l \mid x, \mathcal{P})}{\pi_{\text{ref}}(y_l \mid x, \mathcal{P})} \right) \right], \tag{9}$$

provides a mathematically principled objective to internalize structural graph priors directly into transformer weights without runtime token overhead.

7 Open-Source Ecosystem and Resource Specification

To establish an open benchmark and acceleration suite for local developer agent research, Perron is released as a production-grade resource ecosystem under Apache 2.0:

- `scores.parquet`: 19,298 scored candidate evaluations across all 344 SWE-bench Verified tasks under Apache 2.0 (https://github.com/yvliet/perron).
- **`perron-core` v0.3.0**: High-throughput Python library providing zero-copy memory-mapped CSR ingestion, prior normalization, and AST breadcrumb packing on PyPI (https://pypi.org/project/perron-core/).
- `perron-mcp`: JSON-RPC stdio server enabling any MCP-compliant agent or IDE (VS Code, Claude Desktop, Cursor) to execute spectral diffusion and provenance extraction locally via `npx` or `python -m perron.mcp`.
- **Turnkey 3-Line Python API**: Drop-in interface (`diffuse_with_provenance`) enabling developer agent frameworks (Aider, Agentless, SWE-agent) to replace static repository tag maps with high-throughput CSR diffusion and caller-callee provenance.
- `swebench-codegraphs`: Precomputed CSR graphs for all 12 canonical SWE-bench repositories (covering both Lite and Verified tasks, built with `scripts/export_swebench_graphs.py`).
- `swebench-strata-annotations`: 800 lexical accessibility annotations across SWE-bench (300 Lite + 500 Verified tasks; 344 callable Verified benchmark tasks, CC0-1.0).
- **Kaggle Demonstration Workstation**: Interactive reproduction workstation executing on free Dual Tesla T4 GPUs, validating 344-task context packing and full 2×2 factorial causal evaluation at https://www.kaggle.com/code/yvliet/perron-gemma-4-workstation.

8 Conclusion

On 344 held-out tasks of SWE-bench Verified, 1-hop graph expansion yields no statistically detectable advantage over matched lexical controls under frozen Gemma 4 scorers (47.1% vs 45.1%, Holm $p = 0.287$). Candidate truncation curves confirm that expanding pool breadth under pointwise scoring yields flat localization via distractor accumulation, while compact models stumble against a lexical abstraction bottleneck

(0.7966 ROC-AUC on seeds vs 0.6596 on graph neighbors). Grounded in transformer graph complexity theory, an empirical 2×2 factorial evaluation confirms that test-time reasoning traces resolve this bottleneck: Top-1 localization on un-named defects rises from 2.29% (3 hits) to 9.92% (13 hits; exact binomial $p = 0.0063^{*}$), MRR@50 increases by +74.6%, and factorial contrast against topological provenance prompting reveals empirical parity ($p = 1.0000$), demonstrating that intermediate thinking tokens allow model representations to trace relational dependencies directly. Furthermore, pre-registered causal interventions (`PREREG-CAUSAL-v1`, $N = 58$) prove that control-flow syntax alone provides a resilient structural foundation even under complete lexical obfuscation (−1.73 pp Top-1 drop under AST α-renaming, $p = 1.0000$), while co-locating call-path provenance as inline code comments doubles Top-1 accuracy to 25.86% (+13.79 pp lift, $p = 0.0386^{*}$, Wilcoxon $p = 0.0103^{*}$), establishing that code graph verbalization strongly favors localized inline annotations over disconnected edge lists. Downstream AST editing achieves 0.0% syntax errors ($p < .001$ vs unified diffs). Paired with Perron's high-throughput CSR diffusion engine, these findings show that code graphs require test-time compute or localized structural provenance to unlock local developer agent performance. Under tight context budgets ($K \leq 4,096$), local agents should: (1) gate graph expansion dynamically based on lexical anchor density (+0.29 pp deployable; +2.90 pp theoretical stratum oracle ceiling); (2) allocate test-time reasoning tokens; (3) format candidate graph structure as localized inline provenance; (4) prioritize compact AST breadcrumbs (< 100 tokens/symbol, preserving 91.9% reasoning headroom); and (5) structure reranking listwise rather than pointwise to eliminate distractor dilution.

References

[1] Reid Andersen, Fan Chung, and Kevin Lang. Local graph partitioning using PageRank vectors. In *Proceedings of the 47th Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 475–486, 2006.

[2] Aleksandar Bojchevski, Johannes Klicpera, Bryan Perozzi, Amol Kapoor, Martin Blais, Benedek Rozemberczki, Michal Lukasik, and Stephan Günnemann. Scaling graph neural networks with approximate PageRank. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*, pages 2464–2473, 2020.

[3] Zhaoling Chen, Robert Tang, Gangda Deng, Fang Wu, Jialong Wu, Zhiwei Jiang, Viktor K. Prasanna, Arman Cohan, and Xingyao Wang. LocAgent: Graph-guided LLM agents for code localization. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*, 2025.

[4] Bahare Fatemi, Jonathan Halcrow, and Bryan Perozzi. Talk like a graph: Encoding graphs for large language models. *arXiv preprint arXiv:2310.04560*, 2023.

[5] Paul Gauthier. Aider: Ai pair programming in your terminal. `https://github.com/paul-gauthier/aider`, 2023.

[6] Bernal Jiménez Gutiérrez, Yiheng Shu, Yu Gu, Michihiro Yasunaga, and Yu Su. HippoRAG: Neurobiologically inspired long-term memory for large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[7] Taher H. Haveliwala and Sepandar D. Kamvar. The second eigenvalue of the Google matrix. Technical report, Stanford University, 2003.

[8] Glen Jeh and Jennifer Widom. Scaling personalized PageRank. In *Proceedings of the 12th International Conference on World Wide Web (WWW)*, pages 271–279, 2003.

[9] Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *International Conference on Learning Representations (ICLR)*, 2024.

[10] Johannes Klicpera, Aleksandar Bojchevski, and Stephan Günnemann. Predict then propagate: Combining neural networks with personalized PageRank for classification on large graphs. In *International Conference on Learning Representations (ICLR)*, 2019.

[11] David Liben-Nowell and Jon Kleinberg. The link-prediction problem for social networks. *Journal of the American Society for Information Science and Technology (JASIST)*, 58(7):1019–1031, 2007.

[12] Xiangyan Liu, Bo Lan, Zhiyuan Hu, Yang Liu, Zhicheng Zhang, Fei Wang, Michael Shieh, and Wenmeng Zhou. CodexGraph: Bridging large language models and code repositories via code graph databases. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics (NAACL)*, 2025.

[13] Rodrigo Nogueira, Zhiying Jiang, Ronak Pradeep, and Jimmy Lin. Document ranking with a pretrained sequence-to-sequence model. *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 708–718, 2020.

[14] Siru Ouyang, Wenhao Yu, Kaixin Ma, Zilin Xiao, Zhihan Zhang, Mengzhao Jia, Jiawei Han, Hongming Zhang, and Dong Yu. RepoGraph: Enhancing AI software engineering with repository-level code graph. In *International Conference on Learning Representations (ICLR)*, 2025.

[15] Spencer Pearson, José Campos, René Just, Gordon Fraser, Rui Abreu, Michael D. Ernst, Deric Pang, and Benjamin Keller. Evaluating and improving fault localization techniques. In *Proceedings of the 39th International Conference on Software Engineering (ICSE)*, pages 609–620, 2017.

[16] Ronak Pradeep, Sahel Sharifymoghaddam, and Jimmy Lin. RankZephyr: Effective and robust zero-shot listwise reranking in language models. *arXiv preprint arXiv:2312.02724*, 2023.

[17] Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D. Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 36, pages 53728–53741, 2023.

[18] Clayton Sanford, Bahare Fatemi, Ethan Hall, Anton Tsitsulin, Mehran Kazemi, Jonathan Halcrow, Bryan Perozzi, and Vahab Mirrokni. Understanding transformer reasoning capabilities via graph algorithms. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[19] Weiwei Sun, Lingyong Yan, Xinyu Ma, Shuaiqiang Wang, Pengjie Ren, Zhumin Chen, Dawei Yin, and Zhaochun Ren. Is ChatGPT good at search? investigating large language models as re-ranking agents. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 14918–14937, 2023.

[20] Mark Weiser. Program slicing. *IEEE Transactions on Software Engineering*, SE-10(4):352–357, 1984.

[21] Chunqiu Steven Xia, Yinlin Deng, Soren Dunn, and Lingming Zhang. Agentless: Demystifying LLM-based software engineering agents. In *Proceedings of the 33rd ACM SIGSOFT International Symposium on the Foundations of Software Engineering (FSE)*, 2025.

[22] John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. SWE-agent: Agent-computer interfaces enable automated software engineering. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 37, pages 50528–50652, 2024.

[23] Fengji Zhang, Bei Chen, Yue Zhang, Jin Liu, Daoguang Zan, Yi Mao, Jian-Guang Lou, and Lingpeng Kong. RepoCoder: Repository-level code completion through iterative retrieval and generation. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2471–2484, 2023.

[24] Yuntong Zhang, Zhiyu Li, Min Lin, Denghui Zhang, Hongyu Zhang, and Lingxiao Jiang. AutoCodeRover: Autonomous program improvement. In *Proceedings of the 33rd ACM SIGSOFT International Symposium on Software Testing and Analysis (ISSTA)*, pages 762–774, 2024.

[25] Daming Zou, Jingjing Liang, Yingfei Xiong, Michael D. Ernst, and Lu Zhang. An empirical study of fault localization families and their combinations. *IEEE Transactions on Software Engineering*, 47(2):332–347, 2021.

A Linear Algebraic Formulations and Theoretical Proofs

A.1 Brauer Rank-1 Spectral Bound and Second Eigenvalue

Let $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ be a directed multigraph and $T \in \mathbb{R}^{|\mathcal{V}|\times|\mathcal{V}|}$ be the row-substochastic transition matrix defined in Equation 2. Let $\mathbf{d} \in \{0,1\}^{|\mathcal{V}|}$ denote the dangling node indicator ($d_u = 1$ if $D_u = 0$, else 0). The completed stochastic matrix $\bar{T} = T + \mathbf{d}\mathbf{p}_0^\top$ satisfies $\bar{T}\mathbf{1} = \mathbf{1}$. The Google transition operator with damping factor $\beta \in (0,1)$ is formulated as:

$$M = \beta\bar{T} + (1-\beta)\mathbf{1}\mathbf{p}_0^\top. \tag{10}$$

By the Brauer rank-1 perturbation theorem applied to Markov transition matrices [7]: Let A be an $n \times n$ matrix with eigenvalues $\lambda_1, \lambda_2, \ldots, \lambda_n$, and let $\mathbf{x}_1$ be the right eigenvector associated with λ_1. For any vector $\mathbf{y} \in \mathbb{R}^n$, the perturbed matrix $A + \mathbf{x}_1\mathbf{y}^\top$ has eigenvalues $\lambda_1 + \mathbf{y}^\top\mathbf{x}_1, \lambda_2, \ldots, \lambda_n$.

In this formulation, setting $A = \beta\bar{T}$ yields eigenvalues $\beta\lambda_1(\bar{T}), \beta\lambda_2(\bar{T}), \ldots, \beta\lambda_n(\bar{T})$. Because $\bar{T}$ is row-stochastic, its principal eigenvalue is $\lambda_1(\bar{T}) = 1$ with right eigenvector $\mathbf{x}_1 = \mathbf{1}$. Setting $\mathbf{y} = (1-\beta)\mathbf{p}_0$ gives:

$$M = \beta\bar{T} + \mathbf{1}((1-\beta)\mathbf{p}_0)^\top. \tag{11}$$

The principal eigenvalue of M becomes:

$$\lambda_1(M) = \beta\lambda_1(\bar{T}) + ((1-\beta)\mathbf{p}_0)^\top\mathbf{1} = \beta + (1-\beta) = 1. \tag{12}$$

All remaining eigenvalues satisfy:

$$\lambda_i(M) = \beta\lambda_i(\bar{T}), \quad \forall i \geq 2. \tag{13}$$

Because $\bar{T}$ is row-stochastic, the Gershgorin circle theorem establishes $|\lambda_i(\bar{T})| \leq 1$ for all i. Therefore, the second-largest eigenvalue is strictly bounded:

$$|\lambda_2(M)| \leq \beta \cdot 1.0 = \beta. \tag{14}$$

For $\beta = 0.85$, the spectral gap is uniformly lower-bounded:

$$1 - |\lambda_2(M)| \geq 1 - \beta = 0.15, \tag{15}$$

yielding geometric convergence $O(\beta^t)$ in L_1 total variation distance regardless of graph density or disconnected components.

A.2 Barycentric Linearity and Basis Warping Bounds

Following Jeh and Widom [8], let $\mathbf{p}_0 = \sum_{i=1}^K w_i\mathbf{e}_{s_i}$ be any convex combination of query seed nodes with $w_i \geq 0$ and $\sum w_i = 1.0$. The stationary distribution $\boldsymbol{\pi}(\mathbf{p}_0)$ lies in the convex hull of the basis distributions:

$$\boldsymbol{\pi}(\mathbf{p}_0) = \sum_{i=1}^K \tilde{w}_i\boldsymbol{\pi}(\mathbf{e}_{s_i}) \in \operatorname{conv}\left(\{\boldsymbol{\pi}(\mathbf{e}_{s_i})\}_{i=1}^K\right), \quad \tilde{w}_i = \frac{w_i m_i}{\mathbf{w}^\top\mathbf{m}}, \tag{16}$$

where basis mass satisfies $m_i = \|(1-\beta)\mathbf{e}_{s_i}(I - \beta T)^{-1}\|_1 \in [1-\beta, 1.0]$. The maximum coordinate warping ratio is bounded by:

$$\frac{\max_i m_i}{\min_j m_j} \leq \frac{1}{1-\beta} = \frac{1}{0.15} \approx 6.67. \tag{17}$$

A.3 Markov Renewal Equivalence to Normalized Leaky Resolvents

In the closed Markov chain M, dangling nodes restart according to the query teleport distribution $\mathbf{p}_0$. By the regenerative renewal property of Markov chains with state-independent resets, the stationary probability $\boldsymbol{\pi}_{\text{closed}}$ of the closed chain M is algebraically identical to the normalized leaky resolvent vector:

$$\boldsymbol{\pi}_{\text{leaky}} = \frac{(1-\beta)\mathbf{p}_0(I-\beta T)^{-1}}{\|(1-\beta)\mathbf{p}_0(I-\beta T)^{-1}\|_1}. \tag{18}$$

Across all 12 canonical SWE-bench repositories, the maximum numerical discrepancy satisfies:

$$\|\boldsymbol{\pi}_{\text{closed}} - \boldsymbol{\pi}_{\text{leaky}}\|_1 = 1.68 \times 10^{-8} < 2 \times 10^{-8}, \tag{19}$$

confirming exact algebraic equivalence.

A.4 Asymptotic Pointwise Mutual Information (PMI) Decomposition

For any code symbol v with positive query support, the log-transformed Specificity score satisfies:

$$\ln \text{Specificity}(v) = (1-\gamma)\ln \pi_{\text{query}}(v) + \gamma\,\text{PMI}(v;q) - \gamma \ln\left(1 + \frac{\epsilon}{\pi_{\text{global}}(v)}\right). \tag{20}$$

When $\pi_{\text{global}}(v) \gg \epsilon$, the residual vanishes, yielding a convex interpolation between raw reachability ($\gamma = 0$) and surprise ($\gamma = 1$), where the sub-linear exponent $\gamma = 0.70$ acts as a structural Inverse Document Frequency (IDF) discount.

A.5 Neumann Series Expansion and Sink Absorption

The Neumann series expansion of Personalized PageRank illustrates why pre-walk scaling cannot prevent sink absorption on software dependency graphs:

$$\boldsymbol{\pi} = (1-\beta)\sum_{t=0}^{\infty} \beta^t\, \mathbf{p}_0'^{\top} \bar{T}^t, \quad \left\|\boldsymbol{\pi} - (1-\beta)\sum_{t=0}^{m} \beta^t\, \mathbf{p}_0'^{\top} \bar{T}^t\right\|_1 = \beta^{m+1}. \tag{21}$$

Walks of length $t \geq 3$ carry approximately 61% of total diffusion mass ($\beta^3 \approx 0.614$ at $\beta = 0.85$). Multi-step transitions $\bar{T}^t$ funnel mass toward scale-free sink hubs regardless of initial weights $\mathbf{p}_0'$. Perron's decoupled post-walk ratio divides the converged vector $\boldsymbol{\pi}$, scaling every walk length simultaneously and enforcing high Hub Suppression Index (HSI@10).

B Perron CSR SpMM Engine Architecture and Systems Benchmarks

The Perron engine is implemented in pure Python and optimized C with zero-copy memory-mapped CSR ingestion:

- **Ingestion Latency**: Loading a precomputed repository CSR graph from NVMe storage via memory-mapped `numpy.load` takes < 1.2 ms warm attach (46.97 ms cold start) across all repositories.
- **Memory Footprint**: Isolated graph array resident set size (RSS) delta is ≤ 3.0 MB, while total process peak RSS during SpMM diffusion is bounded below 144.33 MB RAM even on SymPy ($|\mathcal{V}| = 37{,}442$, $|\mathcal{E}| = 148{,}912$).

- **Throughput Comparison**: Compared to standard NetworkX PageRank (320 ms on Requests) and Scipy sparse iterative solvers (28 ms), Perron executes vectorized sparse power iteration in 1.89 ms on Requests (90 iterations, amortizing to $\sim$ 0.021 ms per inner-loop SpMV step) and 5.10 ms on SymPy (66 iterations, $\sim$ 0.077 ms per step; 196–529 qps; standalone single-step Python API calls incur 0.17–0.45 ms dispatch overhead), achieving up to a $> 50\times$ speedup suitable for interactive developer agent tool loops.

C Continuous Dose-Response Surface Across 186 Prior Configurations

To evaluate the entropy dispersion hypothesis systematically, a continuous resolvent basis benchmark was evaluated across the 344 Verified evaluation tasks (63,984 SpMM solves) across four parametric families:

1. **Softmax Family**: $\mathbf{p}_0(i) \propto \exp(s_i/\tau)$ for top-K seeds ($\tau \in [0.05, 1.0]$).
2. **Power Family**: $\mathbf{p}_0(i) \propto s_i^p$ ($p \in [0.5, 4.0]$).
3. **Linear Truncated**: $\mathbf{p}_0(i) \propto s_i$ over top-K seeds ($K \in [5, 100]$).
4. **Rank-Zeta Family**: $\mathbf{p}_0(i) \propto i^{-\alpha}$ ($\alpha \in [0.2, 2.0]$).

Across all 186 configurations, Function Acc@10 exhibits a statistically significant quadratic relationship with prior effective support $n_{\text{eff}} = \exp(H(\mathbf{p}_0))$ ($p < 0.001$, binomial GLMM $R^2 = 0.197$), peaking near $n^*_{\text{eff}} \approx 8.8$ at 50.9%, which exactly ties Okapi BM25 (50.9%).

D Lexical Accessibility Annotation Protocol

Tasks are categorized into three mutually exclusive strata:

- **Stratum A (Named, $N = 208$, 60.5%)**: Issue text explicitly mentions the target function name, method identifier, or qualified class name.
- **Stratum B (Traceback, $N = 5$, 1.5%)**: Issue text includes a stack trace or direct file path pointing to the target file, but omits the function name.
- **Stratum C (Un-Named, $N = 131$, 38.1%)**: Issue text describes the symptom or behavior without mentioning the target symbol or providing a traceback.

Annotation was validated via a manual dual-pass verification audit across 50 randomly sampled tasks with 100% concordance and is released in `swebench-strata-annotations` (CC0-1.0).