

# **Field Ionization and Field Emission with Intense, Single-cycle THz Pulses Need to replace with my own title**

by

© Yunxiao Wang

A thesis submitted to the  
School of Graduate Studies  
in partial fulfilment of the  
requirements for the degree of  
Anqing, Anhui, China

B.S. in Physics University of Science and Technology of China May 2009  
Memorial University of Newfoundland

Doctor of Philosophy

St. John's

Newfoundland

Department of Physics August, 2016

## Acknowledgements

Put your acknowledgements here...

*“Intellectual and practical assistance, advice, encouragement and sources of monetary support should be acknowledged. It is appropriate to acknowledge the prior publication of any material included in the thesis either in this section or in the introductory chapter of the thesis.”*

— MUN School of Graduate Studies

# Contents

<b>1</b>	<b>Introduction</b>	<b>ii</b>
1.1	Overview of Recent Target Development . . . . .	ii
1.2	New Generation Target Cells . . . . .	iv
1.3	Structure of This Thesis . . . . .	v
	<b>Acknowledgements</b>	<b>vii</b>
	<b>List of Tables</b>	<b>x</b>
	<b>List of Figures</b>	<b>xi</b>
<b>2</b>	<b>Development of Cells with Metal End Windows</b>	<b>1</b>
2.1	Overview . . . . .	1
2.2	Wall Relaxation of $^3\text{He}$ . . . . .	3
2.2.1	Relaxation on Glass Surfaces . . . . .	3
2.2.2	Relaxation on Metal Surfaces . . . . .	7
2.3	Test Cell Fabrication . . . . .	9
2.3.1	Overview . . . . .	9
2.3.2	Glass-Metal Seal . . . . .	10

2.3.3	Mechanical Polishing and Electropolishing . . . . .	12
2.3.4	Electroplating . . . . .	13
2.3.5	Final Assembly of the Cell . . . . .	14
2.4	Cell Fill Procedure . . . . .	16
2.4.1	Cell Fill Preparation . . . . .	17
2.4.2	Cell Fill . . . . .	18
2.5	Experimental Setup and Procedure . . . . .	19
2.5.1	Pickup Coils . . . . .	20
2.5.2	Gradient Coils . . . . .	20
2.5.3	Laser Setup . . . . .	23
2.5.4	PNMR Losses and Corrected Lifetime . . . . .	24
2.6	Relaxation Measurement Results and Discussion . . . . .	30
2.6.1	Gold Coated Spherical Cell . . . . .	31
2.6.2	Gold Coated Spool Pieces . . . . .	32
2.6.3	Vertical Cells . . . . .	33
2.6.4	Horizontal Cells . . . . .	36
2.6.5	GE180 Cells . . . . .	39
2.6.6	Titanium Tubes . . . . .	41
	<b>Bibliography</b>	<b>42</b>
	<b>A Appendix title</b>	<b>45</b>

# List of Tables

2.1	Shown are the fill information, design and maximum measured lifetime of the test cells. Fill type is the method used to clean the gas. <sup>†</sup> indicates the maximum lifetime was obtained at an elevated position. Although canary glass is not metal, it is listed in the column of metal for Tweety and Sylvester for the sake of keeping the structure of the table simple. . . . .	31
-----	--	----

# List of Figures

1.1	<b>A target cell. The dimensions of different parts of the cell are not to scale.</b> . . . . .	iii
1.2	A diagram of target cell with metal end windows. . . . .	v
2.1	Shown is a glass-metal-glass seal. The metal tube is 5" long by 1" outer diameter. The glass is wetted onto the knife-edge of copper on both ends. . . . .	11
2.2	Glass-metal seals survived pressure higher than 20 atm. . . . .	11
2.3	Electropolishing [8] . . . . .	13
2.4	Shown left is the inner surface of a gold coated OFHC copper tube. Shown right is a OFHC copper tube without coating. . . . .	14
2.5	Ultrasonic cleaner with 3 tubes being cleaned. . . . .	15
2.6	Shown is the design of a typical string for our test cells. . . . .	16
2.7	A diagram of a Pyrex string with a cell and a retort attached while connected to the gas system through the bellows. Adapted from Matyas [11].	17
2.8	Diagram of the coils. Adapted from Zheng [18]. . . . .	21
2.9	Optics for spin-exchange optical pumping. Adapted from Zheng [18].	25
2.10	<b>PNMR setup.</b> . . . .	26

2.11	<b>A PNMR signal taken with gold coated test cell.</b>	27
2.12	3 spindowns of the cell GoldenVec1 each with a different sampling rate.	28
2.13	A linear fit to extract lifetime corrected for relaxation due to PNMR losses.	29
2.14	A diagram of target cell with metal end windows.	30
2.15	A picture of Gold Maiden, generally referred to as the “spool piece”.	32
2.16	Design and picture of Goldfinger.	34
2.17	The observed degradation of lifetime for Goldfinger (left) and Cupid (right). Shown in each of the two plots were several spindowns at different stage during the tests. The initial amplitude of the spindowns were scaled to 1 for better comparison of lifetime.	35
2.18	A picture of GoldenEye, the only test cell made with a valve.	36
2.19	Four spindowns of Goldrush before elevating the cell. All four measurements display similar lifetime with no obvious sign of degradation.	37
2.20	Shown on the right is the inhomogeneities vs. vertical distance from the center of the field. Shown on the left is the cell Goldrush with relaxation time due to field inhomogeneities as displayed on the right.	38
2.21	Design of the horizontal cell GoldenVec.	38

# Chapter 1

## Introduction


### 1.1 Overview of Recent Target Development

Nuclear-polarized noble gases have been proven to be very useful in various applications, such as polarized targets for electron scattering experiments [?], magnetic resonance imaging [?] and neutron scattering experiments [?].  $^3\text{He}$  has been particularly useful for studying spin-dependent interactions involving neutrons because, to first order approximation, a  $^3\text{He}$  nucleus has a pair of protons with paired spins and a single neutron that contributes the most of the nuclear spin. Free neutrons are not used as targets because they decay with a lifetime of roughly 15 minutes.

The latest experiments run in JLAB prior to the 12GeV upgrade have been using cells polarized with Spin-Exchange Optical Pumping (SEOP). Fig. 1.1 shows what a typical target cell looks like. These cells were made of the GE180 glass and use a two-chambered design. The top chamber, known as the pumping chamber, is where  $^3\text{He}$  is polarized through SEOP. The bottom chamber, known as the target chamber, is



where electron scattering occurs. Great effort has been made in our lab to develop this generation of cells. Alkali-hybrid SEOP together with narrowband laser diode arrays have increased the  $^3\text{He}$  polarization from 37% to 70%. Among other things, we also carefully studied an additional spin relaxation mechanism that limits the maximum achievable  $^3\text{He}$  polarization, which is referred to as the "X Factor". Analysis of data accumulated through developing this generation of target cells were thoroughly discussed in Ref. [?], part of which will be presented in chapter 4.




**Figure 1.1:** A target cell. The dimensions of different parts of the cell are not to scale.

## 1.2 New Generation Target Cells

The future experiments planned during the 12GeV era after the upgrade will be much more demanding in terms of target cell performance. One challenge it brings is the high relaxation due to electron beam. We have designed and tested a new style cell that utilizes convection instead of diffusion to increase the rate at which the polarization in the target chamber is replenished by polarized gas from pumping chamber [?]. We have obtained over 50% polarization with controllable convection speed so far. Fig. ?? shows a picture of the prototype cell.

An additional problem that comes with higher beam current is that the glass end windows of traditional design are not likely to survive the experiments. Our group started exploring the option of using metal end windows from a decade ago. Fig [?] shows an example configuration of such a cell. The first problem to solve is to find out the correct material and the proper technique to incorporate metal without introducing significant spin relaxation and still being able to hold high pressure gas (12 atm) inside. This is a brand new technique that may have a profound impact of future cell designs once fully developed. Although no metal end windows have been tested so far, multiple glass cells with different kinds metal tubes (much larger in area compared to the end windows that will be used in JLAB experiments) attached were examined and were enough to convince us the extra spin relaxation is not likely to cause significant problems. The metals tubes were connected to Pyrex glass with knife-edge (houskeeper) seals and stayed intact through high pressure tests. After exploring options such as pure copper, gold coated copper, titanium, stainless steel, gold coated titanium, we have established that electroplating gold on copper substrate



**Figure 1.2:** A diagram of target cell with metal end windows.

yields the best result so far, we have achieved a 15.6 h relaxation time with a Pyrex cell that had a 5" long by 1" gold coated copper tube attached horizontally. By extrapolating the relaxation rate due to gold surface from this result, we believe the relaxation rate introduced by small metal windows in a target cell will be less than  $1/135 \text{ hr}^{-1}$ . To the best of our knowledge, our group was the first to have proved the potential of incorporating metal to target cells in the presence of alkali vapor.

### 1.3 Structure of This Thesis

This thesis focuses on both discussion on the development of high-performance polarized  $^3\text{He}$  targets that utilize spin-exchange optical pumping (SEOP) and the development of future target cells that incorporate metal end windows. Chapter 2 gives a general description of SEOP. Chapter 3 introduces polarimetry techniques used in our lab for target cell characterization. Chapter 4 discusses the result collected in

our lab from the over-a-decade development of  $^3\text{He}$  target cells, in which the spin-exchange rate constant for K and  $^3\text{He}$  is calculated and the so-called "X Factor" is studied. Chapter 5 presents the development process of target cells with metal parts that aims to incorporate metal end windows to future cells for the 12 GeV era experiments. Chapter 6 summarizes this thesis and suggests future directions.

# Bibliography

- [1] High-performance nuclear-polarized  $^3\text{He}$  targets for electron scattering based on spin-exchange optical pumping. *PhD thesis, University of Virginia*, 2010.
- [2] A. Abragam. *Principles of Nuclear Magnetism*.
- [3] E. Babcock, I. A. Nelson, S. Kadlecik, and T. G. Walker.  $^3\text{He}$  polarization-dependent epr frequency shifts of alkali-metal- $^3\text{He}$  pairs. *Phys. Rev. A*, 71:013414, Jan 2005.
- [4] F. Bloch. Nuclear induction. *Phys. Rev.*, 70:460–474, Oct 1946.
- [5] G. Breit and I. I. Rabi. Measurement of nuclear spin. *Phys. Rev.*, 38:2082–2083, Dec 1931.
- [6] G. D. Cates, S. R. Schaefer, and W. Happer. Relaxation of spins due to field inhomogeneities in gaseous samples at low magnetic fields and low pressures. *Phys. Rev. A*, 37:2877–2885, Apr 1988.
- [7] G. D. Cates, D. J. White, T.-R. Chien, S. R. Schaefer, and W. Happer. Spin relaxation in gases due to inhomogeneous static and oscillating magnetic fields. *Phys. Rev. A*, 38:5092–5106, Nov 1988.

- [8] I. Delstar Metal Finishing. <https://www.delstar.com/electropolishing>.
- [9] R. L. Gamblin and T. R. Carver. Polarization and relaxation processes in  $\text{he}^3$  gas. *Phys. Rev.*, 138:A946–A960, May 1965.
- [10] J. Jackson. *Classical Electrodynamics*.
- [11] D. Matyas. Characterizing  $^3\text{he}$  nuclear spin relaxation in vessels of glass and metal. *Master thesis, University of Virginia*, 2016.
- [12] I. I. Rabi, N. F. Ramsey, and J. Schwinger. Use of rotating coordinates in magnetic resonance problems. *Rev. Mod. Phys.*, 26:167–171, Apr 1954.
- [13] M. L. R.Barbe and F. Laloe. Experimental verifications - measurement of the  $\text{he}^3$  self-diffusion coefficient. 35:935–951, 1974.
- [14] M. V. Romalis and G. D. Cates. Accurate  $^3\text{He}$  polarimetry using the rb zee-man frequency shift due to the  $\text{Rb}-^3\text{He}$  spin-exchange collisions. *Phys. Rev. A*, 58:3004–3011, Oct 1998.
- [15] M. V. Romalis, E. Miron, and G. D. Cates. Pressure broadening of rb  $d_1$  and  $d_2$  lines by  $^3\text{he}$ ,  $^4\text{he}$ ,  $\text{n}_2$ , and  $\text{xe}$ : line cores and near wings. *Phys. Rev. A*, 56(6), 1997.
- [16] L. D. Schearer and G. K. Walters. Nuclear spin-lattice relaxation in the presence of magnetic-field gradients. *Phys. Rev.*, 139:A1398–A1402, Aug 1965.
- [17] T. G. Walker and W. Happer. Spin-exchange optical pumping of noble-gas nuclei. *Rev. Mod. Phys.*, 69:629–642, Apr 1997.

- [18] Y. Zheng. Low field mri and the development of polarized nuclear imaging (pni)-a new imaging modality, 2015.

# Appendix A

## Appendix title

This is Appendix A.

You can have additional appendices too (*e.g.*, `apdxb.tex`, `apdxc.tex`, *etc.*). If you don't need any appendices, delete the appendix related lines from `thesis.tex` and the file names from `Makefile`.