



Software Sharing for Structural Health Monitoring and Control

ASCE EMI Technical Committee on Structural Health
Monitoring and Control

May 3, 2023

Table of Contents

CHAPTER 1. Structural Response Analysis and Interpretation	1
1.1 Modal Toolkit: Operational Modal Analysis & Data Visualization Library	2
1.2 Measurement Data Interpretation using Uncertain Models (MeDIUM)	3
CHAPTER 2. Model Updating	4
2.1 SMU – an open-source MATLAB package for structural model updating	5
CHAPTER 3. Input Identification	6
3.1 BuildingVibe: Open-Source Codes for Occupant Localization, Identification, and Characterization Using Human-Induced Building Vibrations	7

CHAPTER 1. Structural Response Analysis and Interpretation

1.1 Modal Toolkit: Operational Modal Analysis & Data Visualization Library

Rodrigo Sarlo¹

¹ Dept. of Civil and Environmental Engineering, Virginia Tech, Blacksburg, VA, USA

Description: Modal Toolkit is a MATLAB software library for modal analysis, specially designed for long-term ambient vibration monitoring and large-scale data processing. It is built from published state-of-the-art algorithms. Its current capabilities include:

Operational Modal Analysis

Frequency Spatial Domain Decomposition (FSDD) [1]

Covariance Based Stochastic Subspace Identification (SSI-COV) [2,3]

Uncertainty Quantification for SSI-COV [4]


Advanced Plotting and Animation

3D mode shape plotting and animation (see figure)

Time series animation

Stabilization Diagrams

Phase diagrams



Custom Classes for Data Handling

Vibedat Class: A container class for time series

measurements and associated sensor metadata, with built in plotting and data manipulation functions (filters, decimation).

Modeobj Class: A container class for modal data, with built in functions for data manipulation.

Geoviz Class: A class for sensor geometry visualization. Easily import sensor layouts and visualize them, or plot and animate mode shapes.

Modal Selection and Tracking

Interactive stabilization diagrams for manual mode selection (SSI-COV)

Automated stabilization diagram interpretation via clustering (SSI-COV) [5]

Interactive Spectral Peak selection (FSDD)

Web Link to Software Repository: <https://code.vt.edu/vibes-lab/modal-analysis>

Specifications: MATLAB 2018b or later.

Applications: Operational Modal Analysis of Goodwin Hall Smart Building [6].

References

1. Zhang, L., Wang, T. & Tamura, Y. A frequency-spatial domain decomposition (FSDD) technique for operational modal analysis. *Proc. 23rd IMAC* (2005).
2. Peeters, B. & De Roeck, G. Reference-Based Stochastic Subspace Identification for Output-Only Modal Analysis. *Mech. Syst. Signal Process.* **13**, 855–878 (1999).
3. Van Overschee, P. & De Moor, B. *Subspace Identification for Linear System: Theory - Implementation - Applications*. (Kluwer Academic Publishers, 1996). doi:10.1109/IEMBS.2008.4650193
4. Döhler, M. & Mevel, L. Efficient multi-order uncertainty computation for stochastic subspace identification. *Mech. Syst. Signal Process.* **38**, 346–366 (2013).
5. Reynders, E., Houbrechts, J. & De Roeck, G. Fully automated (operational) modal analysis. *Mech. Syst. Signal Process.* **29**, 228–250 (2012).
6. Sarlo, R., Tarazaga, P. A. & Kasarda, M. E. High Resolution Operational Modal Analysis on a Five-Story Smart Building under Wind and Occupant Excitations. *Eng. Struct.* (2017).

1.2 Measurement Data Interpretation using Uncertain Models (MeDIUM)

Sai G.S. Pai¹, ZeZhou Wang^{1,2}, Ian F.C. Smith^{1,3}

¹ Singapore-ETH Centre, Singapore

² Dept. of Civil and Environmental Engineering, National University of Singapore, Singapore

³Dept. of Civil & Environmental Engineering, Swiss Federal Institute of Technology, Lausanne, Switzerland

Description: MeDIUM is software to support interpretation of monitoring data taken from civil infrastructure systems such as bridges, tunnels and excavations. Monitoring and interpreting this data using physics-based models helps improve understanding of system behavior. However, such data interpretation, particularly when used for extrapolation prediction, requires significant expertise and technical knowledge.

Error-domain model falsification (EDMF) has been demonstrated to provide accurate solutions for model-based data-interpretation tasks. However, the use of this methodology through bespoke coding is often arduous and this can lead engineers to use other less accurate methodologies. MeDIUM simplifies and automates the use of EDMF.

MeDIUM provides functionalities that support validation and what-if analyses of data-interpretation solutions. The data-enhanced behavior models that are identified with MeDIUM enable improved assessment of current and future infrastructure performance for safe and sustainable asset management.

Implementation and Algorithm

MeDIUM is a software implementation of EDMF. This methodology was developed by Goulet and Smith [1] and has been applied for evaluation of over twenty full-scale case studies [2], [3].

In EDMF, model instances that provide predictions incompatible with measurements are falsified (rejected). Compatibility is assessed using thresholds (tolerance) on residuals between model predictions and measurements. These threshold values are computed based on uncertainty associated with the interpretation task at each measurement location. EDMF is an-easy-to-understand implementation of Bayesian updating.

Web Link to Software Repository: <https://github.com/MeDIUM-FCL/MeDIUM>.

Specifications: Windows 7 or later and 2GB RAM (4GB preferable)

Acknowledgements: This work was funded by the Singapore-ETH Center (SEC) (Contract no. FI 370074011-370074016) and the Swiss National Science Foundation (Contract no. 200020-169026).

References

- [1] J. A. Goulet and I. F. C. Smith, "Structural identification with systematic errors and unknown uncertainty dependencies," *Comput. Struct.*, vol. 128, pp. 251–258, Nov. 2013, doi: 10.1016/j.compstruc.2013.07.009.
- [2] I. F. C. Smith, "Studies of Sensor Data Interpretation for Asset Management of the Built Environment," *Front. Built Environ.*, vol. 2, p. 8, Mar. 2016, doi: 10.3389/fbuil.2016.00008.
- [3] S. G. S. Pai and I. F. C. Smith, "Methodology Maps for Model-Based Sensor-Data Interpretation to Support Civil-Infrastructure Management," *Front. Built Environ.*, vol. 8, p. 1, Feb. 2022, doi: 10.3389/fbuil.2022.801583.

CHAPTER 2. Model Updating

2.1 SMU – an open-source MATLAB package for structural model updating

Yang Wang

School of Civil and Environmental Engineering, Georgia Inst. of Technology, Atlanta, GA, USA

School of Electrical and Computer Engineering, Georgia Inst. of Technology, Atlanta, GA, USA

Description: Field dynamic testing with an as-built structure usually provides modal properties that are different from these generated by a finite element (FE) model (Figure 1). To update the FE model parameters, optimization problems can be formulated toward minimizing the difference between experimental and simulated modal properties. Various FE model parameters can be selected as optimization variables for model updating, such as the elastic moduli of structural members, or the stiffness values of support springs.

In general, optimization problems in FE model updating are non-convex with unknown number of local optima. Figure 2 illustrates the non-convexity using an objective function of only one scalar variable, whereas practical model updating problems usually have much higher-dimensional vector variables. To initiate an optimization search, randomly generated starting values of the optimization variables should be adopted to increase the chance of achieving global optimality.

Named SMU, a Structural Model Updating package has been developed for FE model updating by researchers at the Georgia Institute of Technology. Besides automating the random searches, the current version supports three model updating formulations, namely (1) the MAC (modal assurance criteria) value formulation, (2) the eigenvector difference formulation, and (3) the modal dynamic residual formulation. For each updating formulation, analytical Jacobian derivative of the objective function is implemented, improving the gradient search efficiency. In addition, the package supports various optimization algorithms available in MATLAB optimization toolbox, such as the Levenberg-Marquardt algorithm, the trust-region-reflective algorithms, the interior point method, *etc.* Finally, the MATLAB package contains multiple structural example problems of different sizes, which help users learn how to use the package.

Web Link to Software Repository: The open-source software package is shared online at <https://github.com/ywang-structures/Structural-Model-Updating>.

Specifications: MATLAB Optimization Toolbox is required.

Acknowledgements: This research was partially funded by the National Science Foundation (CMMI-1150700 and CMMI-1634483). Any opinions, findings, and conclusions expressed in this publication are those of the authors and do not necessarily reflect the view of the sponsors.

References

- [1] Y. Wang, X. Dong, D. Li, and Y. Otsuki. SMU: MATLAB Package for Structural Model Updating, version 1.1. Available: <https://github.com/ywang-structures/Structural-Model-Updating>.



Figure 1. Finite element model updating




Figure 2. Illustration of a non-convex objective function with one scalar

CHAPTER 3. Input Identification

3.1 BuildingVibe: Open-Source Codes for Occupant Localization, Identification, and Characterization Using Human-Induced Building Vibrations

Shijia Pan¹, Mostafa Mirshekari², Jonathon Fagert³, Laixi Shi⁴, Tong Yu⁴, Pei Zhang⁴, Hae Young Noh²

¹Department Electrical and Computer Engineering, University of California Merced, Merced, CA, USA

²Department of Civil and Environmental Engineering, Stanford University, Stanford, CA, USA

³Department of Civil and Environmental Engineering, Carnegie Mellon University, Pittsburgh, PA, USA

⁴Department Electrical and Computer Engineering, Carnegie Mellon University, Pittsburgh, PA, USA

Description: BuildingVibe includes MATLAB codes to extract human occupant information (listed below) from their footstep-induced floor vibration data. Vertical velocity responses of the floor are collected using geophone sensors. The “Hardware” folder includes three iterations of the sensing nodes design and implementation documentation, as well as data acquisition codes. The “Software” folder includes:

1. Step Event Detection (BOES_Step_Event_Detection): Detect human footsteps from noisy floor vibration data [1]
2. Individual Person Identification (FootprintID): Identify each person using their gait patterns and gait-induced floor vibrations [2]
3. Single Person Localization: Locate individual footsteps of a single person passing by [3]
4. Multiple People Localization (MultiPeople_Singlestep_Localization): Locate each footstep for multiple people walking simultaneously [4]
5. Human Gesture Recognition (SurfaceVibe): Identify different types of gestures on the physical surface (e.g., table, wall, floor) through surface vibrations [5, 6]




Figure 1. Human Footstep-Induced Building Vibrations

Web Link to Software Repository: The open-source software package is shared online at <https://github.com/dandanpan/VibrationSensingDocumentation>

Specifications: MATLAB Toolboxes and third-party libraries requirements are clarified in the readme files.

Acknowledgements: This research was partially funded by the National Science Foundation (CMMI-1653550), Google, Intel, and Highmark. Any opinions, findings, and conclusions expressed in this publication are those of the authors and do not necessarily reflect the view of the sponsors.

References

- [1] Pan, Shijia, Amelie Bonde, Jie Jing, Lin Zhang, Pei Zhang, and Hae Young Noh. "Boes: building occupancy estimation system using sparse ambient vibration monitoring." In *Sensors and Smart Structures Technologies for Civil, Mechanical, and Aerospace Systems 2014*, vol. 9061, p. 90611O. International Society for Optics and Photonics, 2014.
- [2] Pan, Shijia, Tong Yu, Mostafa Mirshekari, Jonathon Fagert, Amelie Bonde, Ole J. Mengshoel, Hae Young Noh, and Pei Zhang. "Footprintid: Indoor pedestrian identification through ambient structural vibration sensing." *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies* 1, no. 3 (2017): 1-31.
- [3] Mirshekari, M., Pan, S., Fagert, J., Schooler, E. M., Zhang, P., & Noh, H. Y. (2018). Occupant localization using footstep-induced structural vibration. *Mechanical Systems and Signal Processing*, 112, 77-97.
- [4] Shi, Laixi, Mostafa Mirshekari, Jonathon Fagert, Yuejie Chi, Hae Young Noh, Pei Zhang, and Shijia Pan. "Device-free Multiple People Localization through Floor Vibration." In *Proceedings of the 1st ACM International Workshop on Device-Free Human Sensing*, pp. 57-61. 2019.
- [5] Pan, Shijia, Ceferino Gabriel Ramirez, Mostafa Mirshekari, Jonathon Fagert, Albert Jin Chung, Chih Chi Hu, John Paul Shen, Hae Young Noh, and Pei Zhang. "Surfacevibe: vibration-based tap & swipe tracking on ubiquitous surfaces." In *2017 16th ACM/IEEE International Conference on Information Processing in Sensor Networks (IPSN)*, pp. 197-208. IEEE, 2017.
- [6] Pan, Shijia, Mostafa Mirshekari, Jonathon Fagert, Ceferino Gabriel Ramirez, Albert Jin Chung, Chih Chi Hu, John Paul Shen, Pei Zhang, and Hae Young Noh. "Characterizing human activity induced impulse and slip-pulse excitations through structural vibration." *Journal of Sound and Vibration* 414 (2018): 61-80.