Page 1: Model Performance Analysis

UI & Data Controls:

- Title & Layout: The page is set up with a centered, wide layout. The left column contains controls and dropdowns while the right column displays the visualization and summary table.
- Controls:
 - o NLP Approach Dropdown: Options include LDA, GPT, COMBINED, and LIWC.
 - o Idiographic/Nomothetic Dropdown: Changes based on the NLP approach (for GPT, defaults to "Nomothetic" for data availability).
 - Outcome Dropdown: Selects the outcome (e.g., Negative Affect, Angry, Nervous, Sad). For GPT, outcome values are standardized (e.g., "negative affect" becomes "na") and filtered from the file.

Graph Details:

- Graph Type: Violin Plot
- Axes:
 - X-Axis: Represents the "ML Model." In GPT mode, it shows a single category ("GPT"), while in other cases it shows two categories: "Elastic Net (en)" and "Random Forest (rf)."
 - Y-Axis: Represents the R^2 values, showing the distribution of model performance.
- Data & Filtering:
 - o GPT: Loads from modelfit_gpt_all.csv filtered by outcome and (if available) the nomothetic/idiographic value.
 - Non-GPT Models: Loads separate CSV files for Elastic Net and Random Forest; these datasets are concatenated.
- Colors:
 - o GPT Mode: The violin is rendered in blue.
 - Non-GPT: Elastic Net is shown in red, and Random Forest is shown in blue. The
 colors help differentiate the model types and make it easier to visually compare their
 R² distributions.
- Additional Features: The violin plot includes boxplots and all data points are shown, offering insight into both central tendency and spread.

Summary Table:

- Content: A table summarizing key statistics per model including the mean (with standard deviation), count (N), range (min to max R²), and the count of p-values below 0.05.
- Calculation: Each metric is computed on the filtered dataset and then presented in a neat tabular format.

Page 2: Data Table View - Model Performance per Participant UI & Data Controls:

- Layout: The page uses a centered, wide layout with controls in the left column and a data table in the right column.
- Controls:
 - NLP Approach, Idiographic/Nomothetic, ML Model, and Outcome Dropdowns: These
 determine which CSV file is loaded. For GPT, the outcome is chosen from unique
 values in the file; otherwise, the outcome is standardized (e.g., "negative affect" to
 "na").

Data Table:

- Table Type: Interactive Data Table
- Displayed Columns: Typically includes id, participant, r, r2, rmse, and p_value.
- Purpose: Presents participant-level performance metrics from the selected file.
- Axes Explanation:
 - o Unlike a graph, the table shows rows for each participant and columns for each metric.
- Color and Formatting:

- No explicit colors are used in the table; however, column headers and data formatting help in quick reading.
- Interaction: The table is scrollable with a fixed height (600px) and width (1200px).

Page 3: True vs Predicted NA Levels

UI & Data Controls:

- Title & Refresh: The title "True vs Predicted NA Levels" is displayed along with a "Clear All" button that resets the session state.
- Dynamic Graph Sections: The user can add multiple graph sections; each section has its own controls for outcome, ML model, and participant selection.

Graph Details:

- Graph Type: Line Chart
- Axes:
 - o X-Axis: Represents time (the "time" column from the dataset).
 - Y-Axis: Represents NA levels; two lines are plotted—one for the actual (true) NA levels and one for the predicted estimates.
- Data & Filtering:
 - Data is loaded from a CSV file whose filename is constructed based on the selected ML model, outcome, and nomothetic/idiographic value.
 - After selecting a participant, the data is filtered to include only rows for that participant.
- Colors:
 - o Actual NA Levels: Plotted in teal with a solid line.
 - o Predicted NA Levels: Plotted in red using a dashed line.
 - Correlation Calculation: The correlation coefficient between the actual and predicted NA values is computed and displayed in the title.
- Additional Features:
 - The graph has fixed dimensions (900 px wide, 400 px high) to ensure consistency, and tooltips show detailed information when hovering.

Page 4: Best Model Performance per Participant

UI & Data Controls:

- Layout: The page features controls on the left (including checkboxes and dropdowns) and a results section on the right.
- Controls:
 - Checkbox: "Include both Elastic Net and Random Forest" when checked, both models are compared; when unchecked, a dropdown allows selection of one model.
 - Outcome Dropdown: Allows selection of an outcome (e.g., Negative Affect, Angry, Nervous, Sad).

Data Processing:

- Aggregation: Data from multiple CSV files (covering different NLP approaches and both idiographic and nomothetic cases) are merged and filtered.
- Selection: For each participant, the record with the highest R² is selected.

Displayed Elements:

- Data Table:
 - o Content: Shows the best performance for each participant, including Participant, ML Model (if both are included), Nomothetic/Idiographic, NLP Approach, R², RMSE, P Value, and Counts.
- Pie Charts:
 - o Graph Types: Pie Charts
 - Pie Chart 1 (Nomothetic vs. Idiographic):
 - Slices: Represent counts of participants per category.

- Colors: Use Plotly's default discrete colors to differentiate the groups.
- Pie Chart 2 (NLP Approaches):
 - Slices: Represent the frequency of each NLP approach; "comb" is re-labeled as "All text features combined."
 - Colors: Also use discrete color mapping.
- o Pie Chart 3 (ML Models):
 - Shown only if both models are included.
 - Slices: Represent the counts for Elastic Net and Random Forest.
 - Colors: Defined via a discrete map (Elastic Net in red, Random Forest in blue).
- Axes Explanation for Pie Charts:
 - o Pie charts do not have traditional axes; the slices' sizes represent proportions or counts.
- Legend & Layout:
 - The charts are arranged in columns with legends and centered titles for clarity.

Page 5: Feature Importance Heatmap (SHAP Values)

UI & Data Controls:

- Layout: The page uses a two-column layout with controls in the right column and the heatmap visualization in the left column.
- Controls:
 - Outcome and Model Dropdowns: Users select the outcome (e.g., Negative Affect, Angry, etc.) and the ML model (Elastic Net (EN) or Random Forest (RF)).
 - Participant Multi-select: Allows selection of specific participants, or an "All" option can select every participant.
 - Opynamic Symmetric Slider: A slider allows users to set a symmetric threshold for feature importance values. The slider is linked to a callback that forces the two handles to be opposites (e.g., if one is set to -0.005, the other becomes 0.005).
 - o Info Box: A message box below the slider explains which SHAP importance values will be included (those outside the threshold) and which will be filtered out.

Graph Details:

- Graph Type: Heatmap
- Axes:
 - X-Axis: Represents the selected participants. When "All" is chosen, the x-axis shows a single label ("All Participants"); otherwise, it shows individual participant names.
 - o Y-Axis: Represents the features (variables) that passed the importance threshold.
- Data Processing:
 - Data is loaded from a CSV (named by model and outcome). After grouping and averaging, the data is pivoted so that features form the rows and participants the columns.
 - The pivoted data is filtered based on the importance threshold.
- Colors:
 - Color Scale: A custom color scale is used:
 - Deep Blue represents strong negative SHAP values.
 - White represents neutral importance.
 - Deep Red represents strong positive SHAP values.
 - Feature Label Colors: Each feature label on the y-axis is colored according to its NLP method (using a predefined color map such as LIWC in red, GPT in blue, etc.).
- Layout Adjustments:
 - The heatmap's height and width are dynamically set based on the number of features and participants.
 - A legend below the graph (built using HTML) explains the color mapping for the NLP methods.

UI & Data Controls:

- Layout: Similar to Page 5, this page uses a two-column layout with controls in the right column and the visualization in the left column.
- Controls:
 - Outcome & Model Dropdowns: Allow the user to select the outcome and ML model (with outcome normalized).
 - Participant Dropdown: Enables the selection of a single participant from the loaded dataset.
 - Performance Metrics Loading: A secondary CSV is loaded to extract performance metrics (R² and RMSE) for the selected participant, which are later shown in the graph title.
 - O Dynamic Symmetric Slider: As on Page 5, a slider is provided for setting the threshold for feature importance. It uses a symmetric range and displays an info box.

Graph Details:

- Graph Type: SHAP Summary Scatter Plot with Vertical Lines
- Axes:
 - X-Axis: Represents the SHAP (feature importance) values.
 - Y-Axis: Represents features. The y-axis values are evenly spaced for each feature, and feature names are used as tick labels.
- Data Processing:
 - O Data is filtered for the selected participant and then filtered based on the chosen importance threshold.
 - The data is sorted by NLP method (and importance) and assigned evenly spaced y-axis positions.
- Colors:
 - Vertical Lines & Markers: Each feature's importance is shown with a line extending from 0 to the SHAP value, with a dot at the end. The color of the line and dot corresponds to the feature's NLP method (e.g., LIWC is red, GPT is blue, etc.).
 - o Legend: Additional dummy traces ensure every NLP method appears in the legend.
- Additional Features:
 - The plot title includes the participant's name along with their performance metrics (R² and RMSE).
 - A dashed vertical line at x=0 helps delineate positive from negative importance.

Page 7: Feature Importance Analysis

UI & Data Controls:

- Layout: The page is divided into a left column for controls and a right column for the graphs.
- Controls:
 - o Dropdowns:
 - ML Model & Outcome: Users select the model and outcome (with outcome standardized).
 - Checkbox: "Include the variable 'Time'" (default is checked).
 - Participant Filtering: A slider lets users select the percentage of participants in each group based on performance (R²).
 - o Minimum Variable Occurrence Slider: Sets a threshold for how many participants must have a feature for it to be included.
- Data Processing:
 - Performance Data: Loaded from a performance CSV, participants are split into high and low R² groups.
 - Feature Importance Data: Loaded from another CSV, with an option to exclude the "Time" variable.
 - Aggregation: The absolute mean importance for each feature is computed separately for high and low R² groups. The absolute mean difference is also calculated.

Graph Details:

- Graph Type: Bar Charts (two separate charts)
- First Bar Chart High vs. Low R² Groups:
 - o Axes:
 - X-Axis: Represents the absolute mean value for each group.
 - Y-Axis: Lists the features (sorted by the high R² group's values) with labels color-coded by NLP method.
 - o Bars:
 - Two sets of bars for each feature: one for the high R² group (colored red) and one for the low R² group (colored turquoise).
- Second Bar Chart Absolute Mean Difference:
 - Axes:
 - X-Axis: Represents the absolute mean difference between the high and low R² groups.
 - Y-Axis: Lists the top features (sorted by difference) with color-coded labels.
 - Bars:
 - A single set of gray bars represents the difference.
- Colors:
 - The bar colors (red, turquoise, and gray) are chosen to clearly contrast the groups, and the y-axis labels are enhanced with HTML to include NLP method colors.

Legend:

An HTML-based legend at the bottom explains the NLP method color coding.

Page 8: Common Top Predictive Features

UI & Data Controls:

- Layout: This page uses a sidebar layout.
 - Left Sidebar (Controls):
 - Model Selection Dropdown: Allows the choice between Elastic Net (EN) and Random Forest (RF).
 - Sliders:
 - Number of Features per Participant (determines how many top features per participant are selected).
 - Number of Variables in Figure (sets how many variables appear in the aggregate view).
 - SHAP Value Threshold (filters features based on a minimum absolute SHAP value).
 - Checkbox: "Use ABS values only" toggles the data source and indicates that only absolute values are considered.
- Data Processing:
 - For each emotion (na, sad, angry, nervous), a CSV file is loaded based on the selected model and whether ABS values are used.
 - Each participant's top features (based on the SHAP threshold) are aggregated. The count of participants selecting each feature is calculated, and the SHAP sign (Positive or Negative) is determined.
- Graph Details:
 - o Graph Type: Stacked Horizontal Bar Charts
 - Axes:
 - X-Axis: Represents the "count" (or percentage of participants) in which the feature is selected.
 - Y-Axis: Represents the feature names, with labels color-coded based on their associated NLP method.
 - Bar Colors:
 - Bars are split by SHAP sign:

- Positive Values: Shown in a teal-like color (rgb(0,182,185)). Negative Values: Shown in a red hue (rgb(255,79,82)).
- Layout of Graphs:
 - The four emotion-specific bar charts are arranged in a 2×2 grid in the main area.
- Legend:
 - A legend below the charts (rendered in HTML) explains the NLP method colors.