

Neural Adaptive Video Streaming with Pensieve

Hongzi Mao

Ravi Netravali Mohammad Alizadeh





Users start leaving if video doesn't play in 2 seconds


Dynamic Streaming over HTTP (DASH)



Video Client

Request:

next video chunk at bitrate r




Response:

video content




Video Server


Dynamic Streaming over HTTP (DASH)




Dynamic Streaming over HTTP (DASH)




Adaptive Bitrate (ABR) Algorithms




Why is ABR Challenging?



Why is ABR Challenging?




Why is ABR Challenging?



Network throughput
is variable & uncertain

Why is ABR Challenging?




Network throughput is variable & uncertain

Conflicting QoE goals

- Bitrate
- Rebuffering time
- Smoothness

Why is ABR Challenging?




Network throughput is variable & uncertain

Conflicting QoE goals

- Bitrate
- Rebuffering time
- Smoothness


Cascading effects of decisions

Our Contribution: Pensieve



Pensieve **learns** ABR algorithm **automatically** through experience

Our Contribution: Pensieve




1. First network control system using modern “deep” reinforcement learning
2. Delivers 12-25% better QoE, with 10-30% less rebuffering than previous ABR algorithms
3. Tailors ABR decisions for different network conditions in a data-driven way

Previous Fixed ABR Algorithms

- Rate-based: pick bitrate based on **predicted throughput**
 - FESTIVE [CoNEXT'12], PANDA [JSAC'14], CS2P [SIGCOMM'16]
- Buffer-based: pick bitrate based on **buffer occupancy**
 - BBA [SIGCOMM'14], BOLA [INFOCOM'16]
- Hybrid: use both throughput prediction & buffer occupancy
 - PBA [HotMobile'15], MPC [SIGCOMM'15]

Simplified inaccurate model leads to suboptimal performance


Example: Model Predictive Control



maximize $\text{QoE}(t, t + T)$
subject to system dynamics

Problem: Needs accurate throughput model


Example: Model Predictive Control




maximize $\text{QoE}(t, t + T)$
subject to system dynamics

Problem: Needs accurate throughput model


Example: Model Predictive Control



Example: Model Predictive Control



Reinforcement Learning




Goal: maximize the cumulative reward $\sum_t r_t$


Pensieve Design

State s_t


Past chunk throughput



Past chunk download time



Next chunk sizes




Current buffer size s_t

Remaining chunks c_t

Past chunk bitrate b_t

Agent



Reward r_t

$$+ q(b_t) - \mu T_t - \lambda |q(b_t) - q(b_{t-1})| \\ + (\text{bitrate}) - (\text{rebuffering}) - (\text{smoothness})$$

240P

360P

720P

1080P


Action a_t




Pensieve Design

State s_t


Past chunk throughput



Past chunk download time



Next chunk sizes



Current buffer size




Remaining chunks



Past chunk bitrate



Agent



Reward r_t


$$+ q(b_t) - \mu T_t - \lambda |q(b_t) - q(b_{t-1})|$$

+ (bitrate) - (rebuffering) - (smoothness)

Action a_t



How to Train the ABR Agent




Collect experience data: trajectory of [state, action, reward]

Training:
$$\theta \leftarrow \theta + \alpha \nabla_{\theta} \mathbb{E}_{\pi_{\theta}} \left[\sum_t r_t \right]$$

What Pensieve is good at



- Learn the dynamics **directly from experience**
- Optimize the high level QoE objective **end-to-end**
- Extract control rules from **raw high-dimensional** signals

Pensieve Training System





Trace-driven Evaluation

- **Dataset:** Two datasets, each dataset consists of 1000 traces, each trace 320 seconds.
- **Video:** 193 seconds. encoded at bitrates: {300, 750, 1200, 1850, 2850, 4300} kbps.
- **Video player:** Google Chrome browser **Video server:** Apache server




Trace-driven Evaluation

- **Dataset:** Two datasets, each dataset consists of 1000 traces, each trace 320 seconds.
- **Video:** 193 seconds. encoded at bitrates: {300, 750, 1200, 1850, 2850, 4300} kbps.
- **Video player:** Google Chrome browser **Video server:** Apache server




Pensieve improves the best previous scheme by 12-25%
and is within 9-14% of the offline optimal

QoE Breakdown



Reward/QoE \sim + Bitrate utility – rebuffering penalty – smooth penalty


QoE Breakdown




Pensieve reduces rebuffering by 10-32% over second best algorithm

Does Pensieve Generalize?

3G network trace




Synthetic trace



- Synthetic trace
- Covers a wide range of average throughput and network variation

Does Pensieve Generalize?



Train on **synthetic traces** then test on **real 3G network trace**

Only 5% degradation compared with Pensieve trained on real network trace

Summary

- Pensieve uses Reinforcement Learning to generate ABR algorithms
- Pensieve optimizes different network conditions through experience
- Pensieve outperforms existing approaches across a wide range of network environments and QoE preferences
- Policies generated by Pensieve have strong ability to generalize


<http://web.mit.edu/pensieve/>

My thoughts


- In addition to heuristics, reinforcement learning based on neural networks provides a new way to solve network problems.
- Neural networks trained with synthetic data in a simulation environment may also have good performance, as long as the data amount and diversity is enough.

Thank you.

Experiments in the Wild



How Close is Pensieve to Optimal?



- Simulate chunk download time $T_n = T_{n-1} (R_n / R_{n-1}) + \varepsilon$
- Use dynamic programming to obtain online/offline optimal
- Train a Pensieve agent with exactly the same setting as before

Multi-video extension

