

Student Information Name:蕭宜芳 Student ID:112034584 GitHub ID:yy223xiao Kaggle name:Xiaoooyifang Kaggle private scoreboard snapshot:

```
In [1]: from IPython.display import Image
Image(filename="C://Users//yuan//Desktop//DM2024-Lab2-Master-main//pic0.PNG",width=400,height=400)
```

```
Out[1]:
```

60 3 Xiaoooyifang 0.42573 5 4d

```
In [ ]: import pandas as pd
import json
```

1.Read Data:Load the tweet data from a JSON file. Each tweet is extracted and stored in a list, which is then converted into a DataFrame for further processing. 2.Load Data Identification:Import the data identification file, which contains metadata or unique identifiers for each tweet. 3.Merge the Emotion Labels and Data Identification Information:Combine the emotion labels and identification data with the main tweet dataset using the common tweet_id column. This ensures all necessary information is unified in one DataFrame. 4.Filter Rows That Have an Emotion Label:Remove rows that lack emotion labels (NaN) to focus on tweets with defined emotion categories.

```
In [ ]: tweets_data = []
with open('tweets_DM.json', 'r', encoding='utf-8') as f:
    for line in f:
        try:
            tweet = json.loads(line)
            tweets_data.append(tweet["_source"]["tweet"])
        except json.JSONDecodeError as e:
            print(f"Error decoding JSON: {e}")
tweets_df = pd.DataFrame(tweets_data)
```

```
In [4]: # Load emotion labels
emotion_df = pd.read_csv('emotion.csv')

# Load data identification
identification_df = pd.read_csv('data_identification.csv')

# Merge the emotion labels and data identification information
tweets_df = tweets_df.merge(emotion_df, left_on='tweet_id',
right_on='tweet_id', how='left')
tweets_df = tweets_df.merge(identification_df, left_on='tweet_id',
right_on='tweet_id', how='left')
```

```
# Filter rows that have an emotion label
labeled_tweets_df = tweets_df[~tweets_df['emotion'].isna()]
```

Reasons for Choosing the LightGBM Model: 1.Efficiency and Scalability:LightGBM is highly efficient, making it suitable for handling large, high-dimensional datasets like TF-IDF features from text. 2.Support for Multiclass Classification:LightGBM natively supports multiclass classification, essential for emotion recognition tasks. 3.Handling Sparse Data:It excels with sparse, high-dimensional data, which aligns well with text data represented as TF-IDF. 4.Regularization:Built-in regularization techniques (e.g., λ_1 , λ_2) help reduce overfitting, crucial for text data. 5.Fast Training:Its histogram-based algorithm ensures faster training and prediction, allowing for efficient experimentation.

1.Dataset Preparation:The dataset is split into training and testing subsets based on the identification column.Training data contains rows with identification == 'train'.Testing data contains rows with identification == 'test'. 2.Handling Missing Values:Ensure all text inputs are strings and handle any missing values by replacing None or NaN with an empty string. 3.Train-Validation Split:The training dataset is split into a training set and a validation set to evaluate model performance during training.The split is stratified to maintain the proportion of each emotion category. 4.Label Encoding;Encode categorical emotion labels into numerical format using LabelEncoder. 5.TF-IDF Vectorization:Convert text data into numerical feature representations using TF-IDF (Term Frequency-Inverse Document Frequency).The vectorizer is configured with: `max_features=10000`: Use up to 10,000 most relevant features.`ngram_range=(1, 2)`: Include both unigrams and bigrams.The vectorizer is applied to the training, validation, and test datasets. 6.Dataset Creation for LightGBM:Prepare datasets in the format required by LightGBM for training and validation. 7.Model Configuration: Set the parameters for the LightGBM model: `objective`: Multiclass classification. `num_class`: Number of emotion categories (from LabelEncoder). `boosting_type`: Gradient Boosted Decision Trees (gbdt). `metric`: Multi-class log loss (multi_logloss). `num_leaves`: Maximum number of leaves per tree (128). `learning_rate`: Learning rate (0.03). `max_bin`: Maximum number of bins for discretizing continuous features (255). `feature_fraction`: Use 70% of features for training. `bagging_fraction`: Use 60% of samples for training. `bagging_freq`: Perform bagging every 5 iterations. `min_data_in_leaf`: Minimum data points in each leaf (100) to avoid overfitting. `lambda_1` and `lambda_2`: Regularization parameters to reduce model complexity. `seed`: Random seed for reproducibility.

```
In [5]: #!pip install lightgbm
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.preprocessing import LabelEncoder
import lightgbm as lgb
import json
```

```
train_data = tweets_df[tweets_df['identification'] == 'train']
test_data = tweets_df[tweets_df['identification'] == 'test']
```

```
In [6]: X_train_text = train_data['text'].values
y_train_text = train_data['emotion'].values
X_test_text = test_data['text'].values
test_ids = test_data['tweet_id'].values
```

```
In [7]: import numpy as np
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.preprocessing import LabelEncoder

X_train_text = np.array(["" if x is None else str(x) for x in
X_train_text]) # Handle None/NaN and ensure strings
X_test_text = np.array(["" if x is None else str(x) for x in
X_test_text])
```

```
In [8]: X_train_text, X_val_text, y_train_text, y_val_text = train_test_split(
    X_train_text, y_train_text, test_size=0.2, random_state=42,
    stratify=y_train_text
)
```

```
In [9]: le = LabelEncoder()
y_train = le.fit_transform(y_train_text)
y_val = le.transform(y_val_text)

# TF-IDF vectorization
vectorizer = TfidfVectorizer(max_features=10000, ngram_range=(1, 2))
X_train_tfidf = vectorizer.fit_transform(X_train_text)
X_val_tfidf = vectorizer.transform(X_val_text)
X_test_tfidf = vectorizer.transform(X_test_text)
```

```
In [10]: train_dataset = lgb.Dataset(X_train_tfidf, label=y_train)
val_dataset = lgb.Dataset(X_val_tfidf, label=y_val,
reference=train_dataset)

params = {
    "objective": "multiclass",
    "num_class": len(le.classes_),
    "boosting_type": "gbdt",
    "metric": "multi_logloss",
```

```

    "num_leaves": 128,
    "learning_rate": 0.03,
    "max_bin": 255,
    "feature_fraction": 0.7, # 使用 70% 特徵
    "bagging_fraction": 0.6, # 使用 60% 樣本
    "bagging_freq": 5,
    "min_data_in_leaf": 100, # 增加最小葉子數據量
    "lambda_l1": 2.0, # 強化正則化
    "lambda_l2": 2.0,
    "seed": 42
}

```

Model Training 1. The `lgb.train()` function is used to train the LightGBM model: Parameters (params): Includes settings for multiclass classification and regularization. Training Data (train_dataset): The dataset used to fit the model. Validation Data (val_dataset): Used to monitor performance and avoid overfitting. 2. Predictions are made on the test data (X_test_tfidf) using the trained model: `model.predict()`: Generates probability predictions for each class. `argmax(axis=1)`: Converts probabilities to class labels by selecting the class with the highest probability. 3. Inverse Transform of Labels: Convert predicted numeric class labels back to their original emotion labels using the LabelEncoder. 4. Result Formatting: Combine test IDs with predicted emotions into a list of dictionaries for easier interpretation and saving.

```

In [11]: model = lgb.train(
    params,
    train_dataset,
    num_boost_round=2000,
    valid_sets=[train_dataset, val_dataset],
    callbacks=[
        lgb.early_stopping(stopping_rounds=100),
        lgb.log_evaluation(period=50) # 減少日誌顯示頻率
    ]
)

```

```
[LightGBM] [Info] Auto-choosing row-wise multi-threading, the overhead of testing
was 11.943399 seconds.
You can set `force_row_wise=true` to remove the overhead.
And if memory is not enough, you can set `force_col_wise=true`.
[LightGBM] [Info] Total Bins 542415
[LightGBM] [Info] Number of data points in the train set: 1164450, number of used
features: 9997
[LightGBM] [Info] Start training from score -3.597586
[LightGBM] [Info] Start training from score -1.765956
[LightGBM] [Info] Start training from score -2.347946
[LightGBM] [Info] Start training from score -3.124284
[LightGBM] [Info] Start training from score -1.037009
[LightGBM] [Info] Start training from score -2.018193
[LightGBM] [Info] Start training from score -3.396878
[LightGBM] [Info] Start training from score -1.957811
Training until validation scores don't improve for 100 rounds
[50]    training's multi_logloss: 1.35922      valid_1's multi_logloss: 1.36822
[100]   training's multi_logloss: 1.27209      valid_1's multi_logloss: 1.28754
[150]   training's multi_logloss: 1.22996      valid_1's multi_logloss: 1.25174
[200]   training's multi_logloss: 1.20395      valid_1's multi_logloss: 1.23185
[250]   training's multi_logloss: 1.18503      valid_1's multi_logloss: 1.21875
[300]   training's multi_logloss: 1.17009      valid_1's multi_logloss: 1.20954
[350]   training's multi_logloss: 1.1575       valid_1's multi_logloss: 1.20235
[400]   training's multi_logloss: 1.14664      valid_1's multi_logloss: 1.19685
[450]   training's multi_logloss: 1.13683      valid_1's multi_logloss: 1.1922
[500]   training's multi_logloss: 1.12799      valid_1's multi_logloss: 1.18839
[550]   training's multi_logloss: 1.11992      valid_1's multi_logloss: 1.1853
[600]   training's multi_logloss: 1.11246      valid_1's multi_logloss: 1.18263
[650]   training's multi_logloss: 1.10525      valid_1's multi_logloss: 1.18021
[700]   training's multi_logloss: 1.09857      valid_1's multi_logloss: 1.17826
[750]   training's multi_logloss: 1.09221      valid_1's multi_logloss: 1.17664
[800]   training's multi_logloss: 1.08618      valid_1's multi_logloss: 1.17527
[850]   training's multi_logloss: 1.08021      valid_1's multi_logloss: 1.174
[900]   training's multi_logloss: 1.07461      valid_1's multi_logloss: 1.17292
[950]   training's multi_logloss: 1.06901      valid_1's multi_logloss: 1.17183
[1000]  training's multi_logloss: 1.06377      valid_1's multi_logloss: 1.17098
[1050]  training's multi_logloss: 1.05858      valid_1's multi_logloss: 1.1703
[1100]  training's multi_logloss: 1.0535       valid_1's multi_logloss: 1.16959
[1150]  training's multi_logloss: 1.04853      valid_1's multi_logloss: 1.16895
[1200]  training's multi_logloss: 1.04374      valid_1's multi_logloss: 1.16844
[1250]  training's multi_logloss: 1.03911      valid_1's multi_logloss: 1.168
[1300]  training's multi_logloss: 1.03461      valid_1's multi_logloss: 1.16767
[1350]  training's multi_logloss: 1.03012      valid_1's multi_logloss: 1.16737
[1400]  training's multi_logloss: 1.02574      valid_1's multi_logloss: 1.16707
[1450]  training's multi_logloss: 1.02137      valid_1's multi_logloss: 1.16674
[1500]  training's multi_logloss: 1.01716      valid_1's multi_logloss: 1.16649
[1550]  training's multi_logloss: 1.01302      valid_1's multi_logloss: 1.16635
[1600]  training's multi_logloss: 1.0089       valid_1's multi_logloss: 1.16618
[1650]  training's multi_logloss: 1.00485      valid_1's multi_logloss: 1.16601
[1700]  training's multi_logloss: 1.00087      valid_1's multi_logloss: 1.16588
[1750]  training's multi_logloss: 0.996916     valid_1's multi_logloss: 1.16576
[1800]  training's multi_logloss: 0.99304      valid_1's multi_logloss: 1.16566
[1850]  training's multi_logloss: 0.989224     valid_1's multi_logloss: 1.16568
[1900]  training's multi_logloss: 0.985443     valid_1's multi_logloss: 1.16574
Early stopping, best iteration is:
[1837]  training's multi_logloss: 0.990204     valid_1's multi_logloss: 1.16562
```

```
In [12]: predictions_proba = model.predict(X_test_tfidf)
```

```
In [14]: predicted_classes = predictions_proba.argmax(axis=1)
predicted_emotions = le.inverse_transform(predicted_classes)
results = [{"id": id_, "emotion": emotion} for id_, emotion in
zip(test_ids, predicted_emotions)]

# 將結果保存為 JSON 文件
output_file = "predicted_emotionsv2.json"
with open(output_file, "w", encoding="utf-8") as f:
    json.dump(results, f, indent=4, ensure_ascii=False)

print(f"預測結果已保存到 {output_file}")
```

```
預測結果已保存到 predicted_emotionsv2.json
```

```
In [16]: input_file = "predicted_emotionsv2.json"
with open(input_file, "r", encoding="utf-8") as f:
    data = json.load(f)

# 將 JSON 數據轉換為 DataFrame
df = pd.DataFrame(data)

# 保存為 CSV 文件
output_file = "predicted_emotionsv2.csv"
df.to_csv(output_file, index=False, encoding="utf-8")

print(f"JSON 已成功轉換為 CSV，保存至 {output_file}")
```

```
JSON 已成功轉換為 CSV，保存至 predicted_emotionsv2.csv
```

```
In [17]: df = pd.read_csv('predicted_emotions.csv')
num_records = len(df)
print(f"CSV 文件共有 {num_records} 筆資料。")
```

```
CSV 文件共有 411972 筆資料。
```

Using common metrics like accuracy, precision, recall, and F1-score. This code assumes you have `y_val` (true labels) and `predictions_proba` (predicted probabilities) for the validation set.

```
In [ ]: from sklearn.metrics import accuracy_score, precision_score,
recall_score, f1_score, classification_report
import numpy as np

# Convert predicted probabilities to predicted classes for the
```

```
validation set
val_predicted_classes = model.predict(X_val_tfidf).argmax(axis=1)
val_predicted_emotions = le.inverse_transform(val_predicted_classes)
true_emotions = le.inverse_transform(y_val)

# Evaluate metrics
accuracy = accuracy_score(true_emotions, val_predicted_emotions)
precision = precision_score(true_emotions, val_predicted_emotions,
                             average='weighted')
recall = recall_score(true_emotions, val_predicted_emotions,
                       average='weighted')
f1 = f1_score(true_emotions, val_predicted_emotions, average='weighted')

# Detailed classification report
report = classification_report(true_emotions, val_predicted_emotions)

# Print evaluation results
print("Evaluation Results:")
print(f"Accuracy: {accuracy:.4f}")
print(f"Precision: {precision:.4f}")
print(f"Recall: {recall:.4f}")
print(f"F1 Score: {f1:.4f}")
print("\nClassification Report:\n")
print(report)

# Save evaluation results to a file
evaluation_results = {
    "accuracy": accuracy,
    "precision": precision,
    "recall": recall,
    "f1_score": f1,
    "classification_report": report
}

output_evaluation_file = "evaluation_results.json"
with open(output_evaluation_file, "w", encoding="utf-8") as f:
    json.dump(evaluation_results, f, indent=4, ensure_ascii=False)

print(f"Evaluation results saved to {output_evaluation_file}")
```