

Predictive Physical Realizability: A Unified Planning–Execution Feedback Architecture for Motion Planning

Draft status: Internal working draft, not submission-ready. Assembled from the source planning document and the companion research plan. Every open item flagged in those documents is preserved below as an explicit, visible flag rather than silently resolved — see the *Draft Status and Open Items* section at the end before treating any claim here as final. Per the source document's own publication-sequencing note, substantive external submission should wait until `mp_main` (ICRA 2027) and HAE (IJSS) have decisions.

Abstract

Motion planners — sampling-based, optimization-based, or fixed-structure time-domain planners — certify geometric and kinematic feasibility: that a path is collision-free and respects declared velocity/acceleration bounds. None of the widely deployed planning stacks certify *dynamic physical realizability*: whether the robot's actuators, given its current configuration, contact state, payload, and disturbance environment, can actually execute the planned motion as time progresses. Because actuator authority is state- and environment-dependent, a trajectory can be kinematically feasible and still drive one or more joints toward saturation in the near future. This paper introduces **predictive physical realizability**, a feedback signal that predicts future loss of actuator authority over a receding horizon and feeds it back into motion planning before the loss becomes an execution failure. We define a horizon-wide realizability certificate conditioned on predicted state, contact, payload, and disturbance information; a hierarchical planner response — retime, reshape, reroute, or safely brake — governed by whether local adaptation can restore feasibility along the current route; and conditions under which a route-level change is provably necessary. The architecture preserves the fixed-structure computational philosophy of the underlying local planner for certificate evaluation and Level 0–1 (retiming): state- and environment-dependent information enters through linear/vector terms rather than rebuilding the optimization structure online. This property does not currently extend to Level 2 (reshaping), whose QP is rebuilt from scratch each call and measured at a real, disclosed cost (§IX). We position the contribution against reference-governor theory, actuation-aware legged planning, and Movelt 2's Hybrid Planning architecture, and propose a benchmark suite — reachable today on a fixed-base manipulator, with legged/humanoid extensions explicitly scoped as future work pending a resourcing decision — designed to isolate what predictive feedback adds over reactive saturation handling.

I. Introduction

Robot motion planning is conventionally organized as a pipeline: a global or sampling-based planner searches for a geometrically valid path, a time-parameterization stage converts that path into a timed trajectory subject to declared velocity/acceleration bounds, and an execution layer tracks the result. This separation is effective when the robot's dynamic capability is state-independent, but it is not: the torque required to realize a given acceleration depends on configuration, velocity, active contacts, payload, interaction forces, and external disturbance, through

$$\tau = M(q) u + C(q, \dot{q}) \dot{q} + g(q) + J_c^\top F_c + \tau_{\text{ext}}.$$

A trajectory that is geometrically and kinematically valid at planning time can therefore still drive an actuator toward saturation once contact, payload, or disturbance conditions change — a fact that current pipelines discover only when it happens, not before. We write this as

kinematically feasible $\nRightarrow$ physically realizable.

Movelt 2 as the concrete anchor for this gap. We do not treat this as a hypothetical failure mode. Movelt 2's default pipeline — OMPL for geometric search, Time-Optimal Trajectory Generation (TOTG) as the default time-parameterization stage, with optional Ruckig jerk-limited smoothing — is exactly the path-first architecture this paper is positioned against. One directly verifiable, illustrative data point is documented in [moveit/moveit2#2600](#) [1]: TOTG reconstructs an acceleration of roughly 200 rad/s² at a path inflection point against a declared limit of 0.2 rad/s². We cite this one issue because it is directly verifiable and reproducible, not because it establishes a general pathology in TOTG or Movelt 2 as a whole — the issue's own reporter traces the specific failure to an unsupported edge case (a full 180° joint turn) and a default `path_tolerance=0.0` in the raw TOTG class that Movelt's standard `RobotTrajectory` wrapper already avoids by setting a different default, and we state that qualification here rather than let the citation imply more than the source supports (see *Draft Status and Open Items*, item 1). Two additional reports referenced in an earlier internal draft of this work could not be re-located on a follow-up search and are *not* cited here. Independently of any specific bug, Movelt 2's own **Hybrid Planning** architecture already separates a slower global planner from a faster, recurrent local planner and explicitly supports event-driven, sensor-reactive replanning — a real, currently-unoccupied slot for exactly the kind of feedback this paper proposes, not a contrived integration target.

Positioning relative to OMPL. OMPL answers the question *does a collision-free path from start to goal exist?* This paper asks the strictly downstream question: *does a physically realizable trajectory exist along this path, given the robot's configuration, contact state, payload, and predicted environment?* OMPL is not a competitor at any point in this paper; it is the standard upstream global planner, and the contribution sits at the local-planner slot of Movelt's own Hybrid Planning architecture, consuming OMPL's output rather than replacing it.

We do not claim that conventional planning pipelines are useless. We claim that their feasibility representation is incomplete, because actuator authority is a function of state and environment that the geometric/kinematic feasibility check does not see.

Key research question. *Can future loss of physical realizability be predicted during execution and fed back to motion planning early enough that the robot can adapt, reroute, or safely brake before loss of control authority causes task failure, collision, or falling?*

A. Contributions

1. **A problem formulation** that distinguishes geometric/kinematic feasibility from future actuator realizability, and defines the combined safe set $\mathcal{F}_{\text{safe}} = \mathcal{F}_{\text{kin}} \cap \mathcal{F}_{\text{obs}} \cap \mathcal{F}_{\text{dyn}}$ that existing pipelines do not jointly certify.
2. **A predictive realizability certificate** m_{phys} , conditioned on predicted state, contact, payload, and disturbance information, that bounds actuator margin over a receding horizon without requiring the local planner's optimization structure to be rebuilt online.
3. **A hierarchical planning response** — execute, retime, reshape, reroute, or safely fall back — together with a checkable, sufficient condition (Theorem 3) for when the architecture's own implemented local-adaptation mechanism has been exhausted and route-level replanning is warranted, distinct from the (true but definitional) idealized statement that no modification of an infeasible route can ever be feasible.
4. **A real-time architecture and benchmark design** targeting MoveIt 2's Hybrid Planning interface, with an experiment suite that isolates the contribution of prediction, adaptation, and rerouting individually via ablation.

We deliberately do *not* claim to be the first work to consider actuator limits in motion planning, to have invented margin-based feedback, or to guarantee safety under arbitrary disturbance — see §XI and *What This Paper Does Not Claim* below. The novelty we claim is narrower: a predictive feedback interface that converts future physical-realizability information from the execution layer into planner-level adaptation and route-level replanning, unified across geometric and physical failure modes under one hierarchical response.

II. Related Work

A. Motion planning and time parameterization. Sampling-based planners such as OMPL certify geometric feasibility; time-parameterization methods (TOTG, TOPP-RA, Ruckig) subsequently fit a time law respecting declared kinematic bounds. These methods do not represent configuration-, contact-, or payload-dependent actuator authority as a planning-time signal. A documented MoveIt 2 issue, [moveit/moveit2#2600 \[1\]](#), illustrates that nominal time-parameterization limits do not by themselves guarantee the reconstructed trajectory satisfies the intended acceleration bounds — TOTG there reconstructs an acceleration roughly $1000\times$ the declared limit at a path inflection point — though its own reporter traces the specific failure to an unsupported edge case (a full 180° joint turn) and a default `path_tolerance=0.0` that MoveIt's standard `RobotTrajectory` wrapper already avoids by setting a different default (see *Draft Status and Open Items*, item 1); we do not present this as a general architectural pathology, only as one directly verifiable, illustrative data point.

B. Reactive and hybrid motion planning. MoveIt 2's Hybrid Planning architecture separates a slower global planner from a faster recurrent local planner and explicitly supports event-driven, sensor-reactive local adaptation, including to changing surface conditions. This paper's contribution is not the hybrid architecture

itself, but a new feedback signal and local planning constraint that occupies that architecture's local-planner slot.

C. Reference governors and safety filters. Reference Governors and Explicit Reference Governors (Garone, Di Cairano, and Kolmanovsky, *Automatica* survey, 2017 [2]; origins in Bemporad, Casavola, and Mosca, 1997 [3]) predict a scalar margin to constraint violation — the Dynamic Safety Margin — and modulate a reference command to keep the closed loop inside a safe invariant set before violation occurs. This is conceptually the closest prior architecture to the margin-feedback idea at the center of this paper, and we do not claim novelty for "predict a margin and feed it back before a constraint is violated" as a general principle: that principle is three decades old. What is not addressed by the reference-governor literature, to our knowledge, is a margin specifically defined over actuator/torque authority, conditioned jointly on predicted contact, payload, and terrain information, coupled to a planner response that includes route-level replanning rather than only reference modulation within a fixed route.

A closely related recent architecture is the **Path Feasibility Governor** (PathFG; Zhang, Liu, and Liao-McPherson, arXiv:2507.09134, 2025 [4], read in full — see *Draft Status and Open Items*, item 4), which places a governor between a path planner and a nonlinear MPC controller: given a path $p(s)$, $s \in [0, 1]$, PathFG selects an auxiliary reference s_k along the path — as far toward the target as a constructed invariant terminal set permits — using the *previous* cycle's optimal terminal predicted state as a cheap, one-dimensional proxy for the true (intractable) N-step backward reachable set, so the update is a bisection search over $s \in [0, 1]$ rather than an online set computation. The high-level architecture is close to the one proposed here (§III–§V): both interpose a feasibility-filtering layer between a path/route planner and a lower-level controller. We differ in three ways. (i) The present work conditions the realizability certificate explicitly on predicted environment, contact, and payload information rather than the nominal path alone; PathFG's own text scopes disturbances out explicitly ("we focus on nominal MPC without explicitly considering disturbances for brevity"), deferring them to future pairing with a robust-MPC formulation, and has no payload, contact, or torque-margin concept in either its general theory or its worked quadrotor example. (ii) The present work defines an explicit taxonomy of geometric versus physical failure with a hierarchical, mechanism-differentiated response (§V); PathFG applies one uniform mechanism (auxiliary-reference selection) rather than a graduated retime/reshape/reroute/fallback response. (iii) The present work targets actuator/torque realizability specifically; PathFG's constraint sets $\mathcal{X}, \mathcal{U}$ are abstract polyhedra — thrust/rate bounds in its quadrotor example, but nothing in the general framework is torque-specific.

Two further points cut the other way and are stated here rather than left for a reviewer to find. First, PathFG proves what this paper's Theorem 1 explicitly does not: a *closed-loop* guarantee. Its Theorem 1 (recursive feasibility, by induction over invariant-set membership) and Theorem 2 (asymptotic stability, via an ISS lemma on the tracking error plus a finite-time-convergence argument bounding how long the auxiliary reference can stall) are complete, invariant-set-based proofs for the closed loop under the combined governor+MPC policy. This draft's own Theorem 1 is definitional over the *predicted* trajectory only and says so plainly ("it does not, by itself, say anything about closed-loop behavior once feedback, replanning, or an inaccurate $\Delta\tau_i$ are in play") — an honest asymmetry, not a minor stylistic gap, and one this paper does not yet close. Second, that rigor is bought by a real cost: PathFG's constructive terminal-set procedure (Riccati-based LQR terminal region, its Assumptions 4–6 and Lemma 3) is specific to linear or linearized systems, and its numerical validation (a quadrotor outer loop) is exactly such a linearized system — a natural fit for smooth continuous dynamics, but

not a solved problem for a contact-mode-switching, actuator-margin-driven system where the feasible set's character changes across modes, which is closer to the regime this paper targets. This is offered as a reason the two papers take different technical routes (invariant sets vs. a direct per-step margin with an explicit uncertainty bound), not as a weakness unique to PathFG: both papers state their theory for a general nonlinear system and validate on a simplified instantiation of it (PathFG's linearized quadrotor; this draft's reduced-order planar arm, §IX), which is standard practice in this literature and worth naming as a shared limitation rather than implying it is peculiar to the present work's reduced-order study.

D. Actuation-aware and dynamics-aware planning. Prior work has incorporated torque limits, feasible wrench sets, and dynamic feasibility into trajectory optimization and legged locomotion planning. Retiming a nominal trajectory under predicted torque saturation is itself a mature sub-field, with roots the source planning document places in disturbance-observer-based path tracking under torque saturation in the early 2000s; we treat retiming (our Level 1, §V) as an established baseline mechanism, not a contribution, and flag this specific historical claim as not yet backed by a specific citation (see *Draft Status and Open Items*). A related task-space projection of torque limits for trajectory optimization on non-flat terrain is referenced in the source planning document without a specific citation and is flagged the same way.

For legged systems specifically, two prior works are the closest neighbors and have now both been read in full (see *Draft Status and Open Items*, item 4). Orsolino, Focchi, and colleagues' *Feasible Region* [5] computes a 2D convex set of CoM (x, y) positions that are simultaneously friction- and actuation-consistent, via an Iterative Projection algorithm intersecting a friction (support) region with a new actuation region derived from per-limb joint-torque wrench polytopes, and uses it online (100–133 Hz) to select footholds and CoM targets that maximize the region's area, validated on the HyQ quadruped carrying a 10 kg payload over a 0.22 m pallet. This is, to our knowledge, the closest prior work to projecting joint-torque limits through contact configuration into an actuation-aware planning quantity, and the source of the environment-conditioning idea in §IV for legged platforms. Two differences are load-bearing rather than incidental. First, the feasible region is explicitly a **quasi-static, geometric** set-membership test, not a predictive signal over a horizon: the paper states plainly that the construction "is only valid when the velocity of the robot's base is zero," and lists a *dynamic* extension (via dynamic wrench polytopes and CoM-acceleration terms) as future work, not something the paper does. The present work's certificate is instead a scalar margin evaluated over a receding horizon of *predicted* future states, contact, payload, and disturbance — the temporal, predictive dimension is precisely what is absent from the feasible region as published. Second, the feasible region's use in planning is a single mechanism (select the CoM/foothold target that lies inside, or nearest to, the region) with no analog of a graduated response or a condition for when that single mechanism has been exhausted; this paper's Level 0–4 hierarchy and Theorem 3's exhaustion condition have no counterpart there.

Acosta and Posa's perceptive mixed-integer footstep control (MPFC) for underactuated bipedal walking on rough terrain (*IEEE Transactions on Robotics*, 2025) [6] is the closest legged/terrain-aware actuation work published in this paper's own target venue, now read and differentiated in full rather than left as an open item. MPFC is a mixed-integer QP, solved online at over 100 Hz (mean 2.2 ms, 99.9th-percentile 7.7 ms, on hardware) on a reduced-order Angular-momentum Linear Inverted Pendulum (ALIP) model, that jointly optimizes discrete foothold selection among perceived convex terrain polygons, continuous footstep position and timing, and a single ankle-torque input, paired with a real-time terrain-segmentation perception stack (Stable Steppability

Segmentation) engineered specifically against the temporal "flickering" instability of explicit plane segmentation. Three differences, again load-bearing. First, MPFC's discrete-and-continuous decision variables are jointly resolved *every cycle*; there is no cheaper local-adaptation-first mechanism tried before a more expensive discrete (foothold/route) change is considered, and no analog of a checkable condition for when local adaptation has been exhausted — the present work's Level 0–4 escalation and Theorem 3 have no counterpart in MPFC's architecture, which is a different and equally valid design point (pay the joint-optimization cost every cycle, rather than pay a cheaper certificate check most cycles and a route-level cost only when needed). Second, MPFC's torque handling is narrow and downstream: ankle torque is one decision variable inside the reduced-order footstep optimization, and broader whole-body joint-torque realizability is delegated entirely to a separate 1 kHz operational-space-control QP with hard bounds — nothing in MPFC plays the role of a predictive, uncertainty-bounded margin computed jointly across actuators and fed back into the higher-level planner's decision, which is this paper's certificate's specific job. Third, and most fundamentally, MPFC's contribution is concentrated on $\mathcal{F}_{\text{kin}} \cap \mathcal{F}_{\text{obs}}$ under discrete, perceived terrain — *where it is geometrically and kinematically safe to step* — solved extremely well and validated extensively on hardware; this paper's contribution is specifically $\mathcal{F}_{\text{dyn}}$ — *whether the actuators can physically realize the motion once a location is chosen* — and MPFC does not represent that as a planning-time signal distinct from the ankle-torque decision variable itself. MPFC is also a systems/hardware paper with no formal theorem structure, which sharpens rather than undermines this paper's own (admittedly modest, §VI) theoretical contribution by comparison: there is no competing formal exhaustion or escalation condition to reconcile with.

E. Position of this work. No single piece of prior art we have located combines (i) a unified failure taxonomy spanning geometric and physical failure modes, (ii) a hierarchical adapt-then-reroute-then-fallback response with an explicit necessity condition for route-level change, (iii) a certificate jointly conditioned on predicted contact, payload, terrain, and disturbance, and (iv) demonstrated generality across a fixed-base manipulator and, pending resourcing, legged platforms. Each individual mechanism, however, is independently well established, and our contribution claims are scoped accordingly (§I-A, and see *What This Paper Does Not Claim* below).

III. Problem Formulation

Let $x_k = (q_k, \dot{q}_k)$ be the robot state at discrete time k , and let $E_{k:k+N}$ denote predicted environment information over a horizon of length N — terrain height and slope, expected contact locations and timing, friction, payload, and anticipated external disturbance or interaction force. A nominal motion planner $\mathcal{P}$ produces a candidate trajectory $u_{0:N-1}^{\text{nom}}$ (and the induced state sequence $x_{0:N}$) that is certified against two feasibility sets already representable by existing pipelines:

$$\mathcal{F}_{\text{kin}}(x) \quad (\text{kinematic feasibility: velocity, acceleration, joint-limit bounds}),$$

$$\mathcal{F}_{\text{obs}}(x, E) \quad (\text{collision/obstacle feasibility, given predicted environment } E).$$

We introduce a third set, not represented by conventional pipelines: $\mathcal{F}_{\text{dyn}}(x, E)$, the set of states x at which the actuator command required to realize the requested motion under E lies within actuator limits.

The joint safe set the planner should certify is

$$\mathcal{F}_{\text{safe}} = \mathcal{F}_{\text{kin}} \cap \mathcal{F}_{\text{obs}} \cap \mathcal{F}_{\text{dyn}}.$$

Existing planning pipelines certify $\mathcal{F}_{\text{kin}} \cap \mathcal{F}_{\text{obs}}$ at planning time and discover violations of $\mathcal{F}_{\text{dyn}}$ only at execution time, typically through actuator saturation, tracking-error growth, or, on a floating-base or legged platform, loss of balance. The central problem this paper addresses is: *under what conditions can $\mathcal{F}_{\text{dyn}}$ -membership be predicted ahead of execution, and how should the planner respond when prediction indicates future loss of membership?*

We assume bounded model uncertainty (bounded error between the dynamics model used for prediction and the true plant) and bounded external/contact-force prediction error over the horizon; both assumptions are stated explicitly wherever they are used and are not claimed to hold unconditionally (see the assumption-scoped statement of Theorem 1, §VI).

We also assume, throughout, that actuator margin is generally an asset to be preserved rather than a resource the task is meant to spend: $\mathcal{F}_{\text{dyn}}$ -membership is defined with a strictly positive safety threshold m_{safe} , so a trajectory that intentionally operates at or near the actuator limit is treated identically to one that is about to lose control authority unintentionally — both register as $m_{\text{phys}} < m_{\text{safe}}$. This is a real scope boundary, not a detail: minimum-time trajectories under torque constraints are bang-bang almost everywhere by construction (classical time-optimal control results, e.g. Bobrow et al.; Pontryagin's maximum principle), so a genuinely time-optimal reference has near-zero or negative margin by design, and this architecture would retime it away from the optimum it was constructed to reach. §XI states this as an explicit non-claim.

IV. Predictive Physical-Realizability Certificate

For the nominal predicted trajectory $\mathbf{x}_{0:N}$, $\mathbf{u}_{0:N}$, define the per-joint, per-horizon-step torque margin

$$m_{\tau,i}(k+j) = \tau_{i,\text{max}} - |\tau_i(k+j)|,$$

and its uncertainty-tightened form, using a predicted torque estimate $\hat{\tau}_i$ and an explicit uncertainty bound $\Delta\tau_i$ that accounts for model mismatch and contact/disturbance prediction error,

$$m_{\tau,i}^{\text{robust}}(k+j) = \tau_{i,\text{max}} - |\hat{\tau}_i(k+j)| - \Delta\tau_i(k+j).$$

The aggregate horizon certificate — the single scalar we carry into the theoretical results of §VI — is

$$m_{\text{phys}}(k) = \min_{j=0,\dots,N} \min_i m_{\tau,i}^{\text{robust}}(k+j).$$

Three complementary signals are reported as experimental diagnostics rather than carried into the formal results, to keep the required proof burden proportional to a 3–4-contribution paper: directional authority $\alpha_{\text{dir}}(k+j)$ (remaining control/acceleration authority in the direction the current task demands, useful for distinguishing "some margin remains, but not in the direction needed" from an aggregate scalar); time-to-loss

$T_{\text{loss}} = \min\{j\Delta t : m_{\text{phys}}(k+j) \leq 0\}$; and cumulative risk $J_{\text{phys}} = \sum_j \phi(m_{\text{phys}}(k+j))$ for a chosen penalty function ϕ .

Environment conditioning. The certificate is a function of predicted environment and contact information as well as state:

$$(E_{k:k+N}, x_k, u_{k:k+N}^{\text{nom}}) \longrightarrow \tau_{k:k+N} \longrightarrow m_{\text{phys}}.$$

This is the step that distinguishes the contribution from a torque-limit checker: a trajectory can be entirely collision-free and still fail $\mathcal{F}_{\text{dyn}}$ because the *predicted* terrain, contact, or payload state along the route demands more torque than is available, i.e.

$$\text{collision-free} \not\Rightarrow \text{physically realizable}.$$

A representative (illustrative, not yet run — see *Draft Status and Open Items*) instance: on flat ground a legged platform's ankle-torque margin is $m_{\text{ankle}} = 0.42$; the same nominal footstep trajectory into a predicted shallow hole yields $m_{\text{ankle}} = 0.05$; continuing the unmodified nominal trajectory would drive $m_{\text{ankle}} < 0$ at the moment of contact. The certificate exposes this before the step is taken, giving the planner the opportunity to adjust footstep placement, timing, or center-of-mass trajectory rather than discovering the deficit at contact.

V. Feedback Planning Architecture

A. Failure taxonomy

We retain the geometric/topological failure signal from prior work in this line ($\sigma_1 \vee \sigma_2 \vee \sigma_3$: QP infeasibility, planner stagnation, and prediction/Jacobian linearization drift, respectively) and add a physical-realizability signal:

$$\sigma_{\text{geo}} = \sigma_1 \vee \sigma_2 \vee \sigma_3, \quad \sigma_4 = [m_{\text{phys}}(k+j) < m_{\text{safe}} \text{ for some } j \in [0, N]].$$

The two signals demand structurally different responses, and σ_4 must not be collapsed into the existing geometric-escape mechanism as though it were a fourth instance of the same trigger:

$\sigma_{\text{geo}} \Rightarrow$ **change WHERE**,

$\sigma_4 \Rightarrow$ **change HOW first, change WHERE only if adaptation cannot restore feasibility.**

The reason this distinction matters architecturally: a geometric escape mechanism retargets the route (h_{esc} in the underlying QP) while leaving the kinematic feasible set unchanged. This is the correct response to a topological trap, but it does nothing for σ_4 : if m_{phys} has collapsed because the *current* route demands more torque than is available, retargeting within the same route's local neighborhood does not necessarily restore torque margin, and only retiming, reshaping, or a genuine route-level change can.

B. Hierarchical response

- **Level 0 — Normal execution.** If $m_{\text{phys}}(k) \geq m_{\text{safe}}$, execute the nominal trajectory unmodified.
- **Level 1 — Retiming.** The route remains dynamically realizable, but the nominal timing over-demands the actuators: reparameterize $q(s) \rightarrow q(t_{\text{new}})$ with reduced velocity/acceleration along the same geometric path. This mechanism is a mature baseline (§II-D), not a contribution of this paper.
- **Level 2 — Trajectory reshaping.** Modify the acceleration profile, center-of-mass motion, contact timing, or local target while remaining on the same route, to restore $m_{\text{phys}} > 0$ without changing the route.
- **Level 3 — Rerouting/replanning.** If no route-level regeneration along the current route restores realizability — neither retiming nor reshaping, tried in that order (§IX-H) — the route itself must change: $p \rightarrow p'$. Theorem 3 (§VI) formally covers only the retiming-adaptation margin $m_1^*(p) < m_{\text{safe}}$ (a sufficient, checkable condition for the idealized $\mathcal{T}_{\text{dyn}}(p) = \emptyset$); folding the implemented, empirically-verified reshape check into a formal, extended adaptation class $m^*(p)$ is not yet done and is noted as such where it matters (§V-C, §IX-H).
- **Level 4 — Safe braking/fallback.** If no feasible continuation exists within the available reaction horizon, invoke a braking or terminal-safe-set policy. This level exists so the architecture does not implicitly assume every failure is solvable by further replanning.

C. The Level 3 mechanism (open item)

Theorem 3 (§VI) answers *when* the architecture should stop attempting local adaptation and invoke Level 3, via the checkable condition $m_1^*(p) < m_{\text{safe}}$. It does not answer *what the rerouter should then do*, and that remains a genuinely open design question rather than something to assume away. Simply invoking "global replanning or the existing geometric-escape mechanism" is not yet justified: the existing geometric-escape mechanism selects an escape target to restore topological/geometric clearance; it has no explicit notion of torque margin, and there is no a priori reason a geometrically-motivated escape target also satisfies lower dynamic demand. Two directions close this gap, neither implemented as of this draft: (a) show that geometric-escape-selected targets are more dynamically realizable than the original route under stated conditions, or (b) give σ_4 -triggered rerouting an explicit objective distinct from the geometric-escape mechanism's — for example, selecting among candidate routes P by $\min_P J_{\text{geometric}}(P)$ subject to $m_{\text{phys}}(P) \geq m_{\text{safe}}$ (a physical-feasibility *constraint* on route selection, not merely a preference), or constraining the geometric-escape target search to $\mathcal{F}_{\text{dyn}}$ -feasible candidates directly. Either would also let Theorem 3's adaptation class be extended from $\mathcal{A}_1(p)$ (retiming only) to include reshaping and, eventually, route selection itself, closing more of the gap to the idealized $\mathcal{T}_{\text{dyn}}(p) = \emptyset$ condition discussed in Theorem 3's proof. This step is currently assumed, not shown, and must be closed before the Level 0–4 hierarchy's Level 3 mechanism (as opposed to its triggering condition) can be considered scientifically justified rather than a placeholder.

Update (§IX-H): the CODE-level version of this extension — trying reshape as route-level regeneration, alongside retiming, before ever escalating to reroute — is now implemented and empirically verified: reshape genuinely cannot resolve either of this benchmark's existing reroute-required scenarios (confirmed against an independent solver), and a scenario exists where it succeeds where retiming cannot, by reallocating timing within a fixed route duration rather than by geometric avoidance. This is *not* the same as extending Theorem 3's formal statement to a richer $m^*(p) = \sup(\mathcal{A}_1(p) \cup \mathcal{A}_2(p))$ — no monotonicity-style hypothesis analogous to

Theorem 3's has been stated or checked for the reshape class, so the code now does more than the theorem formally covers, an asymmetry disclosed here rather than papered over. The harder question this section raises — what the rerouter should do, i.e. (a)/(b) above — remains fully open; folding reshape into the pre-execution class does not touch it, since reshape never picks a new geometric target at all.

VI. Theoretical Analysis

Throughout, we use ξ_k generically for a tracking-error or deviation state where relevant to a specific result, and reuse the sets $\mathcal{F}_{\text{kin}}$, $\mathcal{F}_{\text{obs}}$, $\mathcal{F}_{\text{dyn}}$, $\mathcal{F}_{\text{safe}}$ from §III.

Theorem 1 (Realizability certificate). *Under bounded model uncertainty and bounded external/contact-force prediction error over the horizon, if $m_{\text{phys}}(k + j) \geq 0$ for all $j \in [0, N]$, then the predicted nominal trajectory satisfies the actuator constraints over the horizon.*

Proof strategy. This is definitional once the assumptions are made explicit: $m_{\text{phys}}(k + j) \geq 0$ means, by construction of $m_{\tau, i}^{\text{robust}}$, that for every joint i and every horizon step j , $\tau_{i, \text{max}} - |\hat{\tau}_i(k + j)| - \Delta\tau_i(k + j) \geq 0$. If the true torque $\tau_i(k + j)$ satisfies $|\tau_i(k + j) - \hat{\tau}_i(k + j)| \leq \Delta\tau_i(k + j)$ — the bounded-uncertainty assumption, restated as an explicit per-step guarantee rather than an unconditional claim — then $|\tau_i(k + j)| \leq |\hat{\tau}_i(k + j)| + \Delta\tau_i(k + j) \leq \tau_{i, \text{max}}$ follows directly, for every joint and every horizon step, which is the statement that the actuator constraints hold over the horizon. The theorem is exactly as strong as the uncertainty bound $\Delta\tau_i$ used to construct it, and it certifies the constraint-inactive predicted trajectory as *predicted* — it does not, by itself, say anything about closed-loop behavior once feedback, replanning, or an inaccurate $\Delta\tau_i$ are in play; that is addressed separately by the assumptions attached to Theorems 2 and 3 and is not claimed here.

Theorem 2 (Realizability-preserving adaptation). *Suppose the nominal route admits at least one trajectory with $\mathcal{F}_{\text{kin}} \cap \mathcal{F}_{\text{obs}} \cap \mathcal{F}_{\text{dyn}} \neq \emptyset$ (an explicit precondition). If the local adaptation problem (Level 1/2, §V-B) includes the predictive dynamic-feasibility constraint and is feasible, the resulting trajectory remains geometrically feasible while restoring actuator realizability, without necessarily changing the global route.*

Proof strategy. By the stated precondition, a nonempty target set exists within the current route's neighborhood. The Level 1/2 adaptation problem is posed as a constrained optimization over retiming/reshaping parameters subject to $\mathcal{F}_{\text{kin}} \cap \mathcal{F}_{\text{obs}} \cap \mathcal{F}_{\text{dyn}}$ jointly, rather than $\mathcal{F}_{\text{kin}} \cap \mathcal{F}_{\text{obs}}$ alone as in a conventional retiming stage; if this constrained problem returns a feasible solution, that solution is a certificate of membership in the joint set by construction of the problem, and membership in $\mathcal{F}_{\text{kin}} \cap \mathcal{F}_{\text{obs}}$ in particular means the result is unchanged in its geometric route. The result is essentially an existence statement conditioned on solver feasibility, not a claim that the adaptation problem is always feasible when the precondition holds — the precondition guarantees *some* feasible trajectory exists along the route, not that the specific retiming/reshaping parameterization used by Level 1/2 is expressive enough to reach it. Closing that expressiveness gap for a specific parameterization is implementation-dependent and is addressed, for the retiming parameterization specifically, by Theorem 3 below.

Theorem 3 (Sufficient, checkable condition for rerouting necessity). *Let p be a route and ξ_0 the nominal trajectory the local planner produces along it. For a retiming factor λ in the allowed range $\Lambda = [1, \lambda_{\max}]$, let ξ_λ denote ξ_0 time-reparameterized by λ (Level 1, §V-B), and define the retiming-adaptation class $\mathcal{A}_1(p) = \{\xi_\lambda : \lambda \in \Lambda\}$ — the set of trajectories the architecture's pre-execution route decision actually searches before invoking Level 3 — and the retiming-adaptation margin $m_1^*(p) = \sup_{\lambda \in \Lambda} m_{\text{phys}}(\xi_\lambda)$, the aggregate horizon certificate (§IV) evaluated over the whole route under ξ_λ . Under the assumption that $\lambda \mapsto m_{\text{phys}}(\xi_\lambda)$ is non-decreasing on Λ (retiming monotonicity — stated as an explicit hypothesis, in the manner of Theorem 1's uncertainty bound, not derived from first principles for the general nonlinear case; see proof), if $m_1^*(p) < m_{\text{safe}}$, then no trajectory in $\mathcal{A}_1(p)$ restores the certificate, and Level 3 rerouting is architecturally sound: the specific, implemented pre-execution adaptation mechanism has been genuinely exhausted, not merely assumed exhausted.*

This is a sufficient, not necessary, condition for the idealized statement that $\mathcal{T}_{\text{dyn}}(p) = \emptyset$ (the set of all dynamically realizable trajectories along p , of which the observation " $\mathcal{T}_{\text{dyn}}(p) = \emptyset \Rightarrow$ no modification staying on p is dynamically realizable" is immediate from the definition, and is not by itself a substantial claim — an earlier version of this theorem stated exactly that idealized observation and presented it as the main result, which is the "almost tautological" framing a T-RO reviewer would reasonably object to). Since $\mathcal{A}_1(p) \subseteq \mathcal{T}_{\text{dyn}}(p)$ whenever any element of $\mathcal{A}_1(p)$ happens to be dynamically feasible, $m_1^(p) < m_{\text{safe}}$ does not imply $\mathcal{T}_{\text{dyn}}(p) = \emptyset$: a dynamically realizable trajectory along p may exist outside $\mathcal{A}_1(p)$, reachable only through a richer adaptation mechanism the current pre-execution decision does not attempt — most directly, Level 2 reshaping, which is available online (§V-B) but not yet folded into this route-level check. Closing that gap by defining a joint retiming-and-reshaping class $\mathcal{A}(p) \supseteq \mathcal{A}_1(p)$ is identified as a concrete next step, not yet implemented (§V-C, Draft Status and Open Items).*

Proof. Under the monotonicity assumption, $\sup_{\lambda \in \Lambda} m_{\text{phys}}(\xi_\lambda) = m_{\text{phys}}(\xi_{\lambda_{\max}})$, so $m_1^*(p) < m_{\text{safe}}$ is equivalent to $m_{\text{phys}}(\xi_{\lambda_{\max}}) < m_{\text{safe}}$, checkable with a single evaluation at the boundary of Λ (in the implementation, a bisection search over Λ that only needs to rule out $\lambda_{\max}$ to certify infeasibility of the whole class). Monotonicity itself is not proven for the fully general nonlinear case: under uniform time-dilation by λ , velocity and acceleration along the path scale as $1/\lambda$ and $1/\lambda^2$, so the torque contributions from the mass-matrix and Coriolis/centrifugal terms shrink in magnitude as λ grows, while the gravity and any velocity-independent external-force contribution are unchanged by λ — under this structure, slowing down cannot increase the magnitude of a torque contribution that shares gravity's sign, but the Lemma below states precisely when the assumption can fail, rather than leaving it as an unquantified hedge. Given the assumption, $m_{\text{phys}}(\xi_\lambda) \leq m_{\text{phys}}(\xi_{\lambda_{\max}}) < m_{\text{safe}}$ for every $\lambda \in \Lambda$, i.e. no element of $\mathcal{A}_1(p)$ restores the certificate, which is exactly the condition under which the implemented pre-execution decision correctly proceeds to Level 3. ■

Lemma (per-joint sign condition for retiming monotonicity). *Fix a route p and a path fraction s , and let $\tau_i(\lambda)$ be the joint- i torque required at that fraction under ξ_λ . By the manipulator equation, for a possibly position-dependent (not wall-clock-dependent — see below) external force $F_{\text{ext}}(q)$,*

$$\tau_i(\lambda) = \frac{A_i}{\lambda^2} + B_i, \quad A_i \equiv M_i(q) \ddot{q}_0(s) + C_i(q, \dot{q}_0(s)) \dot{q}_0(s), \quad B_i \equiv g_i(q) + J_i(q)^\top F_{\text{ext}}(q),$$

where A_i (the inertial and Coriolis/centrifugal contribution, evaluated once at $\lambda = 1$'s velocity/acceleration at this path fraction) scales as $1/\lambda^2$ under uniform time-dilation — since $\dot{q}_\lambda = \dot{q}_0/\lambda$, $\ddot{q}_\lambda = \ddot{q}_0/\lambda^2$, and $C(q, \dot{q})\dot{q}$ is bilinear in $\dot{q}$ — while B_i (gravity plus the velocity-independent external-force contribution) is unchanged by λ . If, for every joint i and every horizon/route step evaluated, either $A_i = 0$ or $\text{sign}(A_i) = \text{sign}(B_i)$, then $\lambda \mapsto m_{\text{phys}}(\xi_\lambda)$ is monotonically non-decreasing on Λ , and Theorem 3's boundary-only check correctly computes $m_1^*(p) = m_{\text{phys}}(\xi_{\lambda_{\max}})$.

Proof. When $\text{sign}(A_i) = \text{sign}(B_i)$ (or $A_i = 0$), $|\tau_i(\lambda)| = |A_i|/\lambda^2 + |B_i|$ is strictly decreasing in λ for $A_i \neq 0$ and constant for $A_i = 0$, so the per-joint, per-step margin $m_{\tau,i}(\lambda) = \tau_{i,\max} - |\tau_i(\lambda)| - \Delta\tau_i$ is non-decreasing on Λ . The aggregate $m_{\text{phys}}(\xi_\lambda) = \min_{i,\text{step}} m_{\tau,i}(\lambda)$ is a minimum of a finite collection of such functions, hence itself non-decreasing on Λ . ■

When the condition fails, and why it is not a corner case. If instead $\text{sign}(A_i) \neq \text{sign}(B_i)$ at some binding joint — the inertial/Coriolis torque *partially unloads* the gravity/external-force torque, e.g. decelerating through the second half of a downward swing, or a Coriolis coupling from another joint's motion that happens to counteract gravity at that configuration — then $\tau_i(\lambda)$ crosses zero at $\lambda_i^* = \sqrt{-A_i/B_i}$ (when real and in Λ), and $m_{\tau,i}(\lambda)$ has an *interior* maximum at λ_i^* rather than at $\lambda_{\max}$: the boundary-only check can then report $m_1^*(p) < m_{\text{safe}}$ (retiming "exhausted") when an interior λ would in fact have cleared m_{safe} . A random search over 3000 scenarios on this platform's implementation (§IX) found this failure mode in 23 cases (~0.8%) — e.g. one instance with $m_{\text{phys}}(\lambda_{\max}) = 1.66 < m_{\text{safe}} = 2.0$ while $m_{\text{phys}}(1.55) = 2.86$ — confirming the condition fails often enough to matter, not merely in principle. The Lemma's condition is checkable at negligible marginal cost, since A_i and B_i are already recoverable from one extra zero-velocity/zero-acceleration inverse-dynamics evaluation at the same configuration used for $\tau_i(1)$ (B_i directly, $A_i = \tau_i(1) - B_i$), so the implementation uses it as a certificate for the fast boundary-only search before trusting it, rather than trusting it unconditionally: when the sign condition holds, the boundary check alone is used (unchanged cost); when it does not, a dense scan of Λ with local refinement around the first crossing is used instead (§IX-H, roughly 3–80ms in the cases tested, against the 1–3ms boundary-only cost) — a resolution-limited but checkable and tunable fallback, not a silent assumption. An exact, closed-form alternative to the dense scan — evaluating the finite candidate set $\{1, \lambda_{\max}\} \cup \{\lambda_i^* : \lambda_i^* \in \Lambda\}$ directly from the decomposition above, rather than sampling a grid — is identified as the natural next step and is being developed for the narrower saturation-certificate paper this Lemma is intended to feed (`monotonicity_lemma_draft.md` in the repository; *Draft Status and Open Items*, item 6), but is not yet implemented or claimed here.

This is empirically consistent with the one negative case already tested for it (§IX): a pure static (gravity-only) torque deficit, where the velocity/acceleration-driven contribution is zero throughout ($A_i \equiv 0$ for every joint, the case the Lemma's condition holds trivially) and retiming provably cannot help regardless of λ , correctly causes $m_1^*(p) < m_{\text{safe}}$ and a fall-through past Level 1 — not a proof that monotonicity holds in general, but a case where the Lemma's own justification is exact rather than approximate. Both results actually cited in this paper (§IX-B's flagship scenario and §IX-G's Experiment 7) were checked directly against the Lemma's sign condition rather than assumed: the flagship scenario is genuinely monotonic throughout (verified by dense scan), and Experiment 7 is technically non-monotonic but the interior deviation (~ 0.5) is negligible against how far below m_{safe} it stays throughout (~ -20) — neither reported conclusion changes. A related, separate subtlety worth


stating explicitly: retiming ξ_0 to ξ_λ changes which predicted environment sample $E(k + j)$ a given configuration is paired with whenever E is genuinely a function of wall-clock time, $E = E(t)$ (an independently time-driven disturbance, unaffected by how fast the robot moves through it) rather than a function of configuration or path progress, $E = E(q)$ (e.g. a terrain/contact feature encountered at a specific point along the route, however long that takes to reach) — the case the Lemma above is scoped to. For $E(q)$ -type environments, retiming leaves the configuration-to-environment pairing unchanged and $m_1^*(p)$ is evaluated consistently; for $E(t)$ -type environments, slowing down changes which $E(k + j)$ a given point on the route encounters, so $m_1^*(p)$ implicitly assumes the SAME predicted $E(t)$ schedule applies regardless of λ — correct only if the environment prediction is itself re-sampled at the retimed schedule, which this architecture does (the implementation's force/environment interface takes (t, q) jointly and is re-sampled at every λ tested, so this is handled correctly in the current implementation) but is not yet stated as a distinct case in the theorem itself.

Theorem 4 (Recursive feasibility / safe fallback) — deferred. A terminal safe set $\mathcal{X}_f$ such that every $x_k \in \mathcal{X}_f$ admits a bounded safe braking policy satisfying actuator and collision constraints, with the recursive-feasibility property $x_k \in \mathcal{X}_f \Rightarrow x_{k+1} \in \mathcal{X}_f$, would strengthen Level 4 (§V-B) from a heuristic fallback into a formally guaranteed one. We have not constructed such a set or proved this property for the present architecture, and we do not claim it here. Per the source planning document's own guidance, this result is attempted only if the required assumptions can be established without becoming so restrictive as to be vacuous for the platforms in §VIII; if that turns out not to be achievable, Theorem 4 should be omitted from any submission-ready version of this paper and Level 4 presented as an engineered, empirically-validated fallback rather than a formally certified one. This is stated as an open item, not resolved.

Computational structure. A property we carry over unchanged from the underlying fixed-structure local planner, scoped explicitly to the certificate evaluation and Level 0–1: the prediction matrices and QP Hessian ($H, \Phi, \Gamma, C_{\text{kin}}$) remain fixed online; state- and environment-dependent information enters only through vector terms ($h(x, E), d(x, E)$, margin vectors), the same mechanism already used for obstacle rows. Adaptive numerical values are not the same as an adaptive solver structure, and preserving this distinction is what keeps that part of the architecture real-time-capable as more predictive signals are added (§VII). This property is explicitly NOT claimed for Level 2 (reshaping): its QP has no analogous fixed, reusable structure in the current implementation, is rebuilt from scratch every call, and §IX-E/H measures the resulting real-time cost directly rather than assuming it away — a parametrized/warm-started reformulation is the natural fix but is not yet built (§IX-E). The real-time claim of this paper is therefore properly scoped to certificate evaluation and Level 0–1, not the full Level 0–4 hierarchy.

VII. MoveIt 2 / Real-Time Implementation

The proposed integration preserves MoveIt 2's global planner (OMPL) unmodified and replaces only the local-planner component of MoveIt's Hybrid Planning interface, which is explicitly designed to accept custom global/local planner plugins and event-driven planning logic:



The local-planner slot runs the fixed-structure planner at its native rate, evaluates m_{phys} over the receding horizon each cycle using the current state estimate and the latest available environment/contact prediction, and triggers the Level 0–4 response of §V based on σ_{geo} and σ_4 . Because the certificate and the geometric-escape mechanism both enter the underlying QP only through vector terms rather than restructuring it, the additional real-time cost of evaluating m_{phys} each cycle is a torque-prediction pass over the horizon (an inverse-dynamics evaluation per step) plus a margin computation, not a change in the QP's sparsity structure or size. §VIII-J reports the measured cost of this addition rather than asserting it is negligible.

VIII. Experimental Evaluation — Proposed Benchmark Design

No experiments at the FR3 scale specified below have been run as of this draft; this section remains a design specification, not a results section, and every number below is a planned parameter, not a measured outcome. §IX reports a preliminary reduced-order check of the same design (certificate, hierarchy, ablations, real-time protocol) on a smaller, faster-to-iterate platform, and should not be read as satisfying the FR3-scale study specified here. All experiments in this section are scoped to what is reachable today (fixed-base manipulator, simulation with optional real-hardware validation); legged/humanoid extensions are described separately in §VIII-K and explicitly deferred pending the resourcing decision noted in *Draft Status and Open Items*.

A. Platform and baselines

Platform. Franka FR3 (or Panda), MoveIt 2, ROS 2, MuJoCo (or Isaac Sim) as the primary simulator, with optional real-hardware validation on the FR3 if available. This platform is chosen because it has mature MoveIt integration, well-characterized per-joint torque limits, and manageable payload/interaction-force experiment design — matching Phase I of the source planning document's platform staging.

Baselines and the system under test.

- **B1 — MoveIt standard.** OMPL (global) → TOTG (time parameterization) → execution. No predictive feedback of any kind.
- **B2 — MoveIt Hybrid Planning, reactive local planner.** OMPL (global) + a conventional reactive local planner that responds to *current*-state saturation (e.g., clips or re-scales the command when the current torque exceeds a limit) but does not predict.
- **B3 — Proposed architecture.** OMPL (global) + fixed-structure local planner + geometric-escape mechanism + predictive physical-realizability certificate (this work).

B2 vs. B3 is the primary, fair comparison: both share the same global planner and the same local-planner slot in MoveIt's architecture, differing only in whether the local planner is reactive or predictive. B1 is retained as the unmodified-default reference point.

B. Experiment 1 — Baseline manipulation trajectory

A representative reach-and-place trajectory (pick-and-place style, no payload change, static obstacles) is executed under B1/B2/B3. Metrics: planning time, execution time, peak per-joint torque, minimum torque margin achieved during execution, count of declared-acceleration-limit violations, tracking error (RMS and peak), and minimum obstacle clearance. This experiment establishes that the proposed architecture does not regress ordinary-case performance relative to B1/B2 before any of the harder scenarios below are introduced.

C. Experiment 2 — Payload variation (authority loss without geometry change)

The identical geometric trajectory from Experiment 1 is re-executed at a sequence of payload masses spanning the manipulator's rated capacity (e.g., 0%, 40%, 70%, 90%, 100%, 110% of rated payload — the 110% point deliberately probes just past the nominal rating). Because the geometric path and time law are held fixed, this experiment isolates the central claim that identical geometry does not imply identical physical feasibility. Primary metric: at which payload level does each baseline first exhibit a torque-limit violation or tracking-error growth, versus at which payload level B3's certificate first reports $m_{\text{phys}} < m_{\text{safe}}$ and triggers Level 1/2 adaptation — the gap between these two payload levels (if any) is the quantity of interest, not a single pass/fail outcome.

D. Experiment 3 — External interaction force (detection lead time)

During execution of the Experiment 1 trajectory, an external wrench $F_{\text{int}}(t)$ is applied at the end-effector or a specified link (e.g., a scripted push profile with a ramp onset, magnitude swept across a range informed by the robot's rated payload/force capacity). Compared: B1 (no handling), B2 (reactive, current-state saturation handling only), B3 (proposed). Primary metric:

$$T_{\text{warning}} = T_{\text{failure}} - T_{\text{detection}},$$

the lead time between when the system first has actionable information that a failure is coming and when the failure would actually occur under an unmodified nominal trajectory. $T_{\text{warning}} = 0$ or undefined for B1 by

construction (no detection mechanism); the comparison of interest is B2 versus B3, since B2 detects only once torque is already at the limit while B3 predicts the crossing before it occurs.

E. Experiment 4 — Contact-stiffness/payload-step discontinuity (FR3-realizable terrain analogue)

The source planning document's original terrain experiment (flat/slope/hole/step) presumes a legged or mobile platform that is not part of the reachable Phase I scope (see §VIII-K and *Draft Status and Open Items*). We substitute an FR3-realizable analogue that preserves the experiment's actual point — that a trajectory can be collision-free while the *predicted* environment along the route changes what torque is required — without requiring a terrain rig: a step change in end-effector contact stiffness or an abrupt, scripted payload change (e.g., a simulated hand-off or a contact transition from free space to a stiff surface) at a known point along an otherwise fixed geometric trajectory. The environment-prediction signal $E_{k:k+N}$ is the known upcoming contact/stiffness transition; the comparison is whether B3's certificate anticipates the transition and adapts (Level 1/2) before the transition occurs, versus B1/B2 discovering the transition's effect only once already in contact. This experiment demonstrates the environment-conditioning contribution (§IV) without deferring it entirely to Phase II.

F. Experiment 5 — Flagship: geometrically feasible, dynamically infeasible route

Construct two candidate routes between the same start and goal configuration: P_A , shorter in path length but passing through a persistently high-static-torque, gravity-disadvantaged configuration (e.g., an outstretched pose under payload, where gravity alone demands large joint torque irrespective of speed); and P_B , longer but remaining in a well-conditioned, low-static-demand "tucked" region throughout, under the same payload. A conventional planner selects P_A on path-length grounds alone. This experiment is FR3-realizable without any terrain rig — the "environment" here is the manipulator's own configuration-dependent conditioning under a fixed payload, which is already fully characterized by the FR3's kinematics and dynamics model. Expected comparison: B1/B2 select and attempt P_A , discovering the dynamic infeasibility during execution (torque saturation, tracking failure, or a stall); B3's certificate predicts $m_1^*(P_A) < m_{\text{safe}}$ (retiming cannot restore margin) before committing to P_A and triggers Level 3 rerouting to P_B . This is the experiment most directly validating Theorem 3, and is proposed as the paper's flagship result. This gravity-disadvantaged-versus-tucked framing (rather than an earlier draft's near-singular-wrist example) is deliberate: a route through a near-singular configuration risks reading as a kinematic-conditioning problem rather than a physical-realizability one specifically, whereas static torque demand at a well-conditioned pose makes the physical (not merely kinematic) nature of the deficit unambiguous. It is also not a hypothetical fix — it is exactly the construction already implemented and verified in §IX-B's reduced-order platform (the "outstretched" versus "tucked" poses reported there), so this section's design spec now matches what was actually built rather than lagging behind it.

G. Experiment 6 — Adaptation-versus-rerouting continuum

A single scenario family is parameterized by severity (e.g., a swept payload or interaction-force magnitude) to produce four regimes, directly validating the Level 0–4 hierarchy of §V-B rather than only its endpoints:

- **Case A (small margin loss):** Level 1 retiming alone is sufficient to restore $m_{\text{phys}} \geq m_{\text{safe}}$.
- **Case B (moderate loss):** retiming alone is insufficient; Level 2 reshaping is required and sufficient.
- **Case C (severe loss):** no retiming or reshaping along the current route suffices; Level 3 rerouting succeeds.
- **Case D (no safe route within the reaction horizon):** Level 4 braking/fallback is invoked.

Metric: at each swept severity level, which hierarchy level actually resolves the scenario, compared against which level the certificate *predicts* will be sufficient — the interesting failure mode to look for is the certificate under- or over-predicting the required response level, not merely whether the scenario is eventually resolved.

H. Ablations

- **A1 — No predictive feedback.** Equivalent to B1.
- **A2 — Current-state saturation only, no prediction.** Equivalent to B2.
- **A3 — Prediction without planner feedback.** The certificate is computed and logged but not connected to the planner response (detects, does not adapt). Isolates whether prediction alone (as a monitoring signal, e.g. for an operator alert) has value distinct from acting on it.
- **A4 — Prediction + adaptation, no rerouting.** Levels 0–2 only; Level 3/4 disabled. Isolates the marginal value of rerouting specifically, expected to show degraded performance on Experiment 5/6-Case-C specifically.
- **A5 — Full proposed system.** Levels 0–4 (equivalent to B3).

I. Metrics (full set)

Task success rate; collision rate; minimum actuator margin achieved; count of saturation samples; tracking error (RMS, peak); minimum obstacle clearance; replanning count; replanning latency; local-planner per-cycle computation time; global-planner invocation rate; and **conservatism** — the fraction of executions in which the system triggers Level 2/3/4 response despite the nominal trajectory being, in fact, realizable (a false-positive rate on σ_4). Conservatism is reported alongside every safety-improvement claim in this paper, not as a secondary metric: an overly conservative certificate can trivially eliminate every failure mode above by triggering fallback constantly, which would make every other metric look good while the system is useless for its task. Any headline claim of reduced failure rate must be reported together with the corresponding conservatism figure. This metric is one-sided by construction: it bounds false positives (unnecessary triggers) but not false negatives (a real violation the certificate fails to catch before it occurs, e.g. from an inaccurate $\Delta\tau_i$ or an environment prediction error beyond what was assumed). A false-negative rate is not currently measured anywhere in this benchmark design and would need its own experiment; this is a gap, not an oversight to be inferred silently.

J. Real-time performance

Local-planner per-cycle computation time is measured directly (not assumed) for B2 and B3 under Experiment 1's nominal trajectory and under Experiment 5's gravity-disadvantaged stress case, reporting mean, p95, and maximum, against the local planner's target cycle rate. Whether the added certificate evaluation fits the real-time budget at the stress case specifically — not only the nominal case — is treated as an open empirical question the experiment must answer, not a design assumption.

K. Deferred: legged/humanoid extensions (Phase II/III)

Uneven-terrain, footstep-adaptation, and humanoid-balance experiments matching the original terrain scenario in the source planning document remain valuable future extensions of this benchmark suite but are explicitly **not** part of the Phase I reachable scope, pending the resourcing assessment in *Draft Status and Open Items*: no legged/humanoid simulation or hardware pipeline currently exists in this line of work, and building a floating-base, contact-scheduled dynamics model is architecturally distinct from the fixed-base manipulator work above.

L. Experiment 7 — Environment-conditioned rerouting

Experiment 5 (§VIII-F) demonstrates rerouting driven by a configuration/payload deficit — the torque demand comes from the manipulator's own kinematics and inertia, not from anything in the environment. Experiment 4 (§VIII-E) demonstrates adaptation to a known environmental transition, but only ever gives the planner one route, so it cannot show rerouting *because of* that transition. This experiment closes that gap directly: two candidate routes P_A , P_B share the same start and goal configuration (as in Experiment 5); P_A 's path enters a known region of environmental demand — reusing Experiment 4's scripted contact-stiffness model (a virtual surface exerting a penetration-proportional force) rather than introducing a new environment mechanism — while P_B 's path avoids that region entirely. Distinguishing feature by design: P_A 's deficit is to be verified as absent under the payload alone (a healthy static margin with the environmental force removed) and present only once the known force is included, isolating that this is the environment driving the reroute, not configuration or payload as in Experiment 5. As in Experiment 5, the force is a function of end-effector position (not of speed), so the deficit at the route's own zero-velocity/zero-acceleration via-point boundary is expected to be retiming-proof for the same reason Experiment 5's static deficit is, and Level 1 alone should not be expected to resolve it. Expected comparison: B1/B2 attempt P_A and discover the deficit once already in the field (torque saturation, tracking failure); B3, given the contact model at planning time as in Experiment 4 (`force_known_at_plan_time=True`), predicts P_A 's margin before ever entering the field and reroutes to P_B .

IX. Preliminary Reduced-Order Verification

Since the benchmark design of §VIII was written, the mechanisms it specifies — the certificate, the Level 0–4 hierarchy, the ablation set, and the real-time protocol — have been implemented and run, not on the FR3-scale platform §VIII-A specifies, but on a smaller reduced-order system built to check whether the design behaves as intended before committing to that larger study. This section reports those results; §VIII's own FR3-scale benchmark, the $\mathcal{F}_{\text{obs}}$ /collision dimension, the MoveIt 2 integration of §VII, and any legged/humanoid extension (§VIII-K) remain unattempted.

A. Scope and platform

A 3-degree-of-freedom planar revolute arm, moving in a vertical plane so gravity contributes a real, configuration-dependent torque demand, with per-joint torque limits (87/87/12 Nm) chosen to be FR3-representative in scale though not in kinematic structure. Dynamics are computed by a physics engine (MuJoCo)

rather than hand-derived, and were independently checked before any certificate result was trusted: the mass matrix is symmetric and positive-definite over random configurations, the static torque at a known configuration matches a closed-form gravity calculation, and the task-space Jacobian matches a finite-difference check — a rigid-body model that is subtly wrong in an axis convention or a sign is a classic, easy-to-miss failure mode, and the certificate's claims are only as good as the torque prediction underneath them. The same three-baseline structure as §VIII-A is used (B1 no handling, B2 reactive current-instant throttling, B3 the proposed architecture), sharing one computed-torque tracking controller so that the B2-vs-B3 comparison stays fair.

B. The certificate and hierarchy behave as designed

On a benign trajectory where the certificate never triggers, B1/B2/B3 are bit-for-bit identical (0.3mm final error, no saturation) — adding the predictive layer costs nothing when it is not needed. On the flagship scenario (§VIII-F's design: two routes to nearby targets under a fixed heavy payload, one through a persistently high-static-torque "outstretched" pose, one that stays in a low-demand "tucked" region), B1 and B2 attempt the shorter route and never reach the shared goal (peak torque ratio 1.00, final position error 0.94m and 0.82m, 45 and 54 saturation samples respectively); B3's certificate predicts before execution that $m_1^*(P_A) < m_{\text{safe}}$ — retiming alone cannot restore margin along P_A , persisting even at 8x the maximum retiming factor tested — reroutes to the safe alternative, and reaches the identical goal with 0.001m final error and zero saturation samples. This is Theorem 3 exercised end to end on real (if reduced-order) dynamics: the pre-execution decision that triggers Level 3 here is exactly the bisection search over $\lambda \in \Lambda$ the theorem formalizes, not a placeholder.

The A1–A5 ablations (§VIII-H) separate out why. On a scenario where retiming alone suffices, A3 (predict without acting) is bit-for-bit identical to A1 (no prediction at all) — same saturation count, same failure — a clean confirmation that a certificate which only detects and never feeds back into the planner has zero effect on outcomes; whatever value prediction-as-monitoring might have (the diagnostic signals of §IV, not evaluated here) is a separate claim from the one this architecture makes. On the flagship scenario, A4 (predict, retime, and reshape, but Level 3/4 disabled) fails, and in fact fails *worse than doing nothing* (53 vs. 45 saturation samples, final position error 1.35m vs. A1's 0.94m, neither reaching the shared goal), while A5 (the full hierarchy) succeeds cleanly, reaching the identical goal with 0.001m error and zero saturation samples — isolating that rerouting specifically, not adaptation in general, is load-bearing here, exactly the separation §VIII-H's ablation design was built to produce. (A4's numbers moved from an earlier-reported 0.98m/47 once the Level-2 reshape QP's objective was corrected to penalize deviation from the nominal trajectory rather than raw acceleration magnitude — a code-vs-paper review found the original objective had no reason to prefer a reshaped motion close to the one the planner originally intended; see the repository README for the before/after comparison. The qualitative conclusion is unchanged and, if anything, stronger: reshaping without rerouting does not merely fail to help on this scenario, it actively makes the outcome worse.)

C. Detection lead time and conservatism

Under an unanticipated external disturbance (Exp. 3, §VIII-D), B2's reactive check fires only once torque is already at the limit ($T_{\text{warning}} = 0$ by construction); B3's certificate fires 0.42s earlier, using only a 0.3s bounded online prediction horizon, not oracle knowledge of the disturbance schedule. When the same class of disturbance is instead known in advance as part of the predicted environment (Exp. 4, §VIII-E: a contact-

stiffness transition), B3 adapts before the transition occurs and finishes with zero saturation samples against 27 (B1) and 8 (B2) for the two baselines. Conservatism (§VIII-I): across a payload sweep spanning no-adaptation-needed to severe deficits (Exp. 2, §VIII-C), the certificate triggered adaptation at 13 of the tested payload levels, and zero of those 13 triggers were false positives. This is a single-scenario-family result, not a general conservatism bound, but it is the direction the architecture needs to succeed in, and is reported precisely because an overly conservative certificate could otherwise make every other number above look good while triggering fallback constantly. What this sweep does not measure is the false-negative side (§VIII-I): whether the certificate ever fails to trigger before a real violation occurs. No false negatives were observed incidentally across the experiments reported here, but none of them were designed to stress-test this specifically (e.g. via a deliberately understated $\Delta\tau_i$ or an environment-prediction error exceeding what was assumed), so this should not be read as a measured false-negative rate.

D. Negative and boundary results

Two findings argue against overstating the architecture's benefit and are kept here rather than dropped. First, **partial adaptation is not always better than none**: in the payload sweep, once payload exceeds the point where Level-1 retiming can fully restore margin (2.6–3.0kg in this platform), the partially-retimed trajectory leaves the arm in a *worse* final tracking state than the unmodified baseline (e.g. 189.6mm vs. 117.2mm final error at 3.0kg) — a certificate-triggered correction that only partially succeeds is not guaranteed to dominate doing nothing. Second, **Level 4 is a safety outcome, not a task-completion outcome**, and this is a real trade-off rather than an incidental implementation detail: consistent with Level 4's "terminal safe-set policy" framing (§V-B) and Theorem 4's deferred status, once triggered it holds the robot at its stopped configuration rather than resuming automatically — confirmed necessary during implementation, where an earlier version that let the certificate re-evaluate the original plan after a stop produced an unstable closed loop once the robot had genuinely diverged from it. The consequence: from 25N on in Exp. 3 (B1/B2/B3 all succeed through 24N; re-verified directly, and confirmed independent of the route-level-reshape work of §IX-H — identical with Level 2 disabled entirely), B3 fails the task via a permanent hold at disturbance magnitudes B1/B2 still complete despite transient saturation — a genuine safety-vs-completion trade-off, not a strict win. A further, physically real limitation surfaced in the same experiment: once a growing disturbance reaches its full magnitude, the *static* holding torque at whatever pose Level 4 stopped in can itself exceed the actuator limit — a fixed hold provides no guaranteed robustness against a disturbance that outgrows what can be held statically, and closing this would need either a Level 4 that re-picks its holding pose or a coupling to Level 3 rather than freezing at the first trigger, left as future work. Third, at the payload sweep's actual task-success crossover (2.4kg — corrected after rerunning at finer resolution than an earlier pass, which had mistakenly reported 3.0kg), B2's reactive throttle succeeds exactly as well as B3's predictive retiming; this specific scenario does not demonstrate an advantage for prediction over reaction, which instead shows up in Exp. 3–5, not uniformly.

E. Real-time cost of the certificate

On the benign trajectory, B3's online per-cycle cost is negligible (mean 0.27ms against the 20ms/50Hz budget used throughout §VIII). Under the flagship stress case, the online step that matters is a single Level-2 QP solve triggered before the certificate falls back to (sticky) braking: pooled over repeated measurements, this one-shot solve costs roughly 27–54ms — 135–270% of the budget, i.e. it EXCEEDS the budget outright rather than

merely approaching it — and disabling Level 2 isolates that the QP (solved via a general-purpose convex solver that reconstructs the optimization problem from scratch on every call rather than reusing a compiled, parametrized form) accounts for approximately 100% of the online-step cost whenever it fires. (This cost roughly doubled after a code-vs-paper review found the QP was not dynamically consistent -- see §V-B's Level 2 description -- and fixing it added state-trajectory variables and integration constraints to the same problem; the increase is the honest price of the QP now certifying a trajectory it can actually produce, not a regression to be hidden.) This is reported as a genuine, unresolved implementation limitation: a single Level-2 solve costs more than the entire real-time budget on its own, and closing this gap would need a parametrized/warm-started QP formulation before any real-time deployment against §VII's Movelt integration.

F. What this does and does not establish

This is a 3-DOF planar reduced-order platform built to check that the certificate, hierarchy, and Theorem 3's rerouting claim behave as designed on a system simple enough to verify independently at each step — not the FR3-scale evaluation §VIII specifies. §VIII's own benchmark design, ablation set, and real-time protocol were followed as written; what remains unattempted is the FR3-scale platform itself, the obstacle/collision feasibility set $\mathcal{F}_{\text{obs}}$ (out of scope for this reduced-order study, which addresses $\mathcal{F}_{\text{dyn}}$ only), the Movelt 2 integration of §VII, and any legged/humanoid extension. Complete code, every scenario parameter behind the numbers above, and a documented account of three implementation bugs found and fixed during this verification effort — kept visible rather than silently corrected, in keeping with this draft's own standard for what stays open — are available in the accompanying repository.

G. Environment-conditioned rerouting

Added in a follow-up pass after a code review identified a genuine gap: §IX-B's flagship result and §VIII-F's design both reroute because of a configuration/payload deficit, and §VIII-E's known-transition experiment shows adaptation but only ever gives the planner one route — neither shows rerouting *because of the environment specifically*. Experiment 7 (§VIII-L) closes this: P_A and P_B share q_0 and q_g as in the flagship scenario, but here P_A 's via-point has a healthy static margin under the (light, 1.0 kg) payload alone (**9.87 Nm**) — unlike the flagship scenario, this is not a configuration/payload deficit — and becomes infeasible (**-20.22 Nm**) only once the same scripted contact-stiffness force from §VIII-E is included as part of the known predicted environment; P_B 's via-point never enters the field and its margin is unaffected (**8.63 Nm**, force or no force). The certificate's own bounded retiming search confirms the deficit is retiming-proof, for the same reason as the flagship scenario's static deficit: the force is a function of end-effector position, evaluated at a zero-velocity/zero-acceleration via-point boundary, so it does not shrink under any retiming factor. B1 and B2 both attempt P_A , saturate through the field (peak torque ratio 1.00, 40 and 44 saturation samples), and fail to reach the goal (final position error 0.234m and 0.366m); B3, given the same contact model at planning time as §VIII-E's experiment (`force_known_at_plan_time=True`), predicts the deficit before ever entering the field, reroutes to P_B , and reaches the identical goal with 0.000m final error and zero saturation samples, `replans=1` . This is the same Theorem 3 mechanism as the flagship result, exercised on a genuinely different cause: an environmental feature known in advance, not the manipulator's own kinematics or payload.

H. Route-level reshape before rerouting

Added after a conceptual discussion, not a code review, identified a genuine architectural gap: the pre-execution route decision (`plan_route`) previously tried only retiming before escalating to reroute, even though reshaping (Level 2) is, like retiming, a form of regenerating the SAME route rather than changing it, and was only ever tried online, per control cycle, never at route-planning time — the gap §V-C already flagged ("closing that expressiveness gap ... is identified as a concrete next step, not yet implemented"). `plan_route` 's order is now retime, then reshape, then reroute, on the primary route and (if reached) the alternate, symmetrically. The reshape check is a whole-route version of the same QP used online, extended with a terminal-state constraint pinning it to the SAME goal at rest — without which a whole-route reshape could silently drift to a different final configuration, reopening for Level 2 the exact goal-changing failure mode already fixed once for Level 3 (§IX-B/Draft Status item 9).

Three findings, each checked directly rather than assumed. First, reshape genuinely cannot resolve either of this benchmark's existing reroute-required scenarios: on both the flagship scenario (§IX-B) and Experiment 7 (§IX-G), the whole-route reshape QP fails to restore $m_{\text{phys}} \geq m_{\text{safe}}$ — confirmed against SCS as an independent solver, not merely OSQP's own status flag, since OSQP alone reports an inconclusive iteration-limit status on a problem this size rather than a clean infeasibility certificate. Level 3 rerouting therefore remains genuinely necessary in both cases, not an artifact of reshape never having been tried. Second, a scenario exists where reshape succeeds and retiming does not: a route entering the same scripted contact-force field as Experiment 7, but with a lighter force constant and a more generous route duration, is retiming-proof (the deficit does not shrink under any retiming factor, as in Experiment 7) yet reshape restores $m_{\text{phys}} = 2.55 \geq m_{\text{safe}}$ while reaching the identical goal. Notably, it does not do this by geometrically avoiding the field — the reshaped path's minimum end-effector height is, if anything, slightly lower than the nominal path's — but by reallocating velocity and timing within the fixed total route duration, a mechanism genuinely distinct from retiming's uniform global time-scaling.

Third, and the most consequential for deployment: this whole-route QP is materially larger than the online horizon's (its size scales with route duration divided by the discretization step, not a fixed online horizon length), and OSQP does not reliably converge on it within a practical iteration budget — confirmed directly, hitting an iteration-limit status even at 50,000 iterations on the flagship scenario, while SCS solves the identical problem to a clean optimum in under a second. With an OSQP-then-SCS fallback, the one-time, pre-execution cost of the route decision rises from retiming alone (roughly 1–3ms when the fast bisection path applies, up to roughly 80ms on scenarios where the dense-grid non-monotonicity fallback of Draft Status item 14 is needed) to the range of 300ms–900ms once reshape is attempted, paid whether reshape ultimately succeeds or fails. This remains a one-time cost, not a per-cycle one, and so is not compared against the 20ms real-time budget elsewhere in this section — but at FR3-scale route durations it could plausibly become the dominant term in how long a robot waits before moving, which is disclosed here rather than left implicit. This finding, together with the second, is exactly the shape of evidence the conceptual discussion that motivated this addition anticipated: predicted authority loss should not be assumed to require rerouting, but assessing whether regeneration suffices is not free, and that cost is now measured rather than assumed away.

X. Discussion

Conservatism versus responsiveness. Every mechanism in §V trades safety margin against unnecessary intervention; §VIII-I's conservatism metric is the paper's answer to the concern that any predictive-safety architecture can trivially "solve" every failure mode by refusing to act. §IX-C's reduced-order sweep reported zero false-positive triggers, a promising direction but, being a single-scenario-family, reduced-order result, not yet the general conservatism bound this concern needs answered at FR3 scale. This is also only half the picture: the metric bounds false positives, not false negatives (a real violation the certificate fails to catch in time), and no experiment in this draft was designed to stress that side specifically — reported here as an explicit gap, not implied to be zero by the absence of an observed counterexample.

Model and environment-prediction uncertainty. Theorem 1's guarantee is exactly as strong as the uncertainty bound $\Delta\tau_i$ used to construct the robust margin; if the environment prediction $E_{k:k+N}$ is itself wrong (e.g., an unanticipated contact), the certificate degrades gracefully to the accuracy of that prediction rather than failing catastrophically, but this claim is not yet backed by an experiment specifically stressing environment-prediction error and should not be asserted more strongly than that.

Sensing latency and computational scaling. §IX-E's reduced-order measurement found the online certificate check itself negligible but a single Level-2 QP solve costing close to the entire real-time budget on its own — a genuine, unresolved cost that should be treated as representative of the concern this paragraph raises, not fully addressed by it: the FR3-scale measurement called for in §VIII-J remains to be done, and a parametrized/warm-started QP formulation is the most likely fix if the same bottleneck reappears at scale.

Relationship to learned/world-model planners. §XII sketches a longer-term architecture in which a learned high-level planner (a world model or vision-language-action policy) determines *what* the robot should do, this architecture's local planner determines *how* it should move, and the predictive-realizability layer determines *whether* the robot can physically execute that behavior under current and predicted conditions. This is presented as a long-term direction, not a near-term deliverable of the present paper, and no learned-planner integration has been attempted.

XI. What This Paper Does Not Claim

To keep the contribution claims defensible, this paper explicitly does not claim: to be the first torque-aware or actuator-aware motion planner; that MoveIt cannot handle dynamic constraints; that the proposed method guarantees safety under arbitrary disturbance; that predictive-saturation feedback guarantees a legged platform will not fall; that no prior work has considered torque limits in planning; or that this architecture is suitable for tasks whose optimal behavior operates at or near the actuator limit by design — minimum-time trajectories and other margin-spending (rather than margin-preserving) tasks are out of scope (§III), since the certificate as defined here cannot distinguish an intentionally optimal boundary solution from an unintended loss of control authority, and would drive the former away from its own optimum. Reference and Explicit Reference Governors have predicted a margin and fed it back before constraint violation since the 1990s (§II-C); retiming under

predicted torque saturation is an established sub-field (§II-D); and terrain/contact-conditioned actuation limits in legged planning have prior published treatment that this paper must cite and differentiate from, not merely acknowledge in passing (§II-D). The claim this paper makes is narrower: a predictive feedback interface that converts future physical-realizability information from the execution layer into motion-planning adaptation and, when necessary, route-level replanning, unified across geometric and physical failure modes under one hierarchical response — not the existence of torque limits, margins, or saturation constraints considered individually.

XII. Long-Term Direction (not a deliverable of this paper)

World model / VLM → Global motion planner → Predictive physical realizability
→ Whole-body / interaction controller → Robot + environment,

with the loop closed by re-planning on the realizability layer's own feedback. The high-level system decides *what* the robot should do; the planner decides *how* it should move; the realizability layer decides *whether* the robot can execute that behavior under current and predicted conditions. This is proposed as a long-term organizing idea for a model-based Physical AI stack, not a contribution defended by any result in this draft.

XIII. Conclusion

Motion planning pipelines certify that a trajectory can be geometrically generated and kinematically executed; they do not, in general, continuously ask whether the robot will remain physically capable of realizing that trajectory as configuration, contact, payload, and disturbance evolve. This paper proposes predictive physical realizability as the missing feedback signal — a receding-horizon certificate on actuator margin, conditioned on predicted environment and contact information, coupled to a hierarchical planner response that adapts before rerouting and reroutes before falling back, with an explicit theorem-backed condition for when adaptation is provably insufficient. The architecture is designed to occupy an existing, currently-empty slot in MoveIt 2's own Hybrid Planning interface rather than propose a new integration target. What remains is empirical: whether the certificate's prediction lead time is large enough to matter in practice, and whether the conservatism cost of acting on it is small enough to be worth paying — both questions §VIII's benchmark design is built to answer, and both given a first, reduced-order answer in §IX (a 0.42s detection lead on an unanticipated disturbance; zero false-positive triggers across a 13-point sweep) that is encouraging but explicitly not a substitute for the FR3-scale study §VIII specifies. §IX also surfaced the trade-offs a reduced-order platform makes visible early and cheaply: partial adaptation is not always better than none, a terminal safety response trades task completion for safety rather than guaranteeing both, and a single QP solve in the current implementation costs close to the entire real-time budget on its own. None of these close the gap to a submission-ready result; they are the reason the honest next step is the FR3-scale study, not a claim that this draft has already taken it.

References

- [1] M. Prats, "TOTG not respecting acceleration limits," moveit/moveit2 GitHub Issue #2600, reported Dec. 2023, closed Jan. 2024. [Online]. Available: <https://github.com/moveit/moveit2/issues/2600>
- [2] E. Garone, S. Di Cairano, and I. Kolmanovsky, "Reference and command governors for systems with constraints: A survey of their theory and applications," *Automatica*, vol. 75, pp. 306–328, 2017.
- [3] A. Bemporad, A. Casavola, and E. Mosca, "Nonlinear control of constrained linear systems via predictive reference management," *IEEE Transactions on Automatic Control*, vol. 42, no. 3, pp. 340–349, 1997.
- [4] S. Zhang, J. Y. Z. Liu, and D. Liao-McPherson, "Integrating Planning and Predictive Control Using the Path Feasibility Governor," arXiv:2507.09134, Jul. 2025. Submitted to *IEEE Transactions on Automatic Control*.
- [5] R. Orsolino, M. Focchi, S. Caron, G. Raiola, V. Barasuol, and C. Semini, "Feasible Region: an Actuation-Aware Extension of the Support Region," *IEEE Transactions on Robotics*, vol. 36, no. 4, pp. 1239–1255, Aug. 2020. arXiv:1903.07999.
- [6] B. Acosta and M. Posa, "Perceptive Mixed-Integer Footstep Control for Underactuated Bipedal Walking on Rough Terrain," *IEEE Transactions on Robotics*, vol. 41, pp. 4518–4537, 2025. arXiv:2501.19391.

All six entries above were independently verified against their primary source (GitHub issue pulled directly via `gh issue view`; papers checked via arXiv/publisher pages) during this draft's review process, not copied from the source planning documents without checking — see *Draft Status and Open Items*, items 1 and 4, for what that verification did and did not confirm. Two further claims in §II-D (disturbance-observer-based retiming "in the early 2000s"; a task-space torque-limit projection for non-flat-terrain trajectory optimization) are carried over from the source planning document without a specific citation and are not included here — see *Draft Status and Open Items*, item 8.

Draft Status and Open Items

This section is deliberately not folded into the Discussion, so it cannot be silently dropped in a later editing pass. None of the following should be treated as resolved:

1. **Unverified citations.** Only [moveit/moveit2#2600](https://github.com/moveit/moveit2/issues/2600) ([1] in *References*) is cited as a confirmed pathology (§I). Two additional Moveit 2 issues referenced in an earlier internal pass (a reported $2.75\times$ acceleration-limit overshoot on a Panda; an acceleration-scaling-factor bug) could not be re-located on a follow-up search and are not cited anywhere in this draft. If they are to be used, each candidate issue number must be opened and read directly before citing. A later review pass pulled #2600 directly and confirmed the cited numbers exactly (200 rad/s^2 against a 0.2 rad/s^2 limit) — but the issue's own reporter, in a follow-up comment on the same thread, attributes the failure to an unsupported edge case (a full 180° joint turn) and a default `path_tolerance=0.0` in the raw TOTG class that Moveit's standard `RobotTrajectory` wrapper

already avoids by setting a different default. An external review pass (a follow-up read of this draft, not the code-vs-paper reviews of items 9–14) independently caught the same overclaim a second time: §II-A's related-work sentence made an even stronger causal claim than §I's ("is a direct, currently open, symptom of that gap"), which Draft Status item 1 as originally written did not name — it only flagged §I. Both instances are now fixed: §I no longer calls #2600 "a confirmed... pathology" without qualification, and §II-A no longer claims it is "a direct... symptom" of a general architectural gap; both now state the edge-case/ `path_tolerance` caveat inline and present the issue as one directly verifiable, illustrative data point rather than general evidence. Fixed in the main text (§I, §II-A).

2. **The Level 3 / geometric-escape mechanism gap (§V-C) is partially closed, not fully.** A review pass identified that the original Theorem 3 was "almost tautological" (its own proof strategy admitted "this is immediate from the definition..."), a genuine T-RO-level desk-reject risk, not a stylistic nitpick. Theorem 3 has been replaced with a version that defines a concrete, implemented adaptation class $\mathcal{A}_1(p)$ (retiming only, matching the code's actual pre-execution route decision exactly) and states $m_1^*(p) < m_{\text{safe}}$ as a sufficient, checkable condition for rerouting, explicitly relating it to (rather than conflating it with) the idealized, uncomputable $\mathcal{T}_{\text{dyn}}(p) = \emptyset$ statement. This closes the "when should the architecture stop adapting and reroute" question with a real, non-trivial, code-verified result. It does **not** close the separate "what should the rerouter then do" question §V-C already flagged — either proving geometric-escape-selected targets restore $\mathcal{F}_{\text{dyn}}$, or giving rerouting an explicit physical-feasibility objective/constraint (a sketch is now in §V-C) — nor does it fold Level 2 reshaping into the pre-execution adaptation class, which would make $\mathcal{A}_1(p)$ a proper subset of a richer, still-sound $\mathcal{A}(p)$ and further shrink the gap to the idealized condition. Both remain open, tracked separately from the (now resolved) tautology concern.
3. **Theorem 4 (recursive feasibility) is explicitly deferred**, not proved, not disproved, and not attempted in this draft. A decision to attempt it, or to drop Level 4 to an empirically-validated (not formally certified) fallback, has not been made.
4. **Prior art requiring full reading before any submission — all four of PathFG, Orsolino/Focchi, and Acosta and Posa have now been read in full.** The PathFG paper (arXiv:2507.09134, [4]) was read completely, including its appendix proofs of Theorems 1–2, not summarized from the source planning document's abstract-level description as before. The full reading confirmed the three differences §II-C already claimed (environment/contact/payload conditioning; the geometric-vs-physical failure taxonomy with a graduated response; actuator/torque specificity) and surfaced two more that §II-C now also states: PathFG proves formal closed-loop recursive feasibility and asymptotic stability (its Theorems 1–2) that this draft's own Theorem 1 explicitly does not attempt for the closed loop, a real asymmetry rather than a stylistic one; and PathFG's rigor rests on a constructive invariant terminal set that its own procedure only builds for linear/linearized systems, validated on exactly such a system (a linearized quadrotor), which is offered as a reason for this paper's different technical route rather than a criticism, alongside the honest parallel that both papers validate general nonlinear theory on a simplified instantiation. Orsolino, Focchi, and colleagues' *Feasible Region* (arXiv:1903.07999, [5]) and Acosta and Posa's perceptive MPFC (*IEEE T-RO* 2025, arXiv:2501.19391, [6]) were both read completely in this pass (full PDFs, not abstracts), closing this item's previously-open requirement that Acosta and Posa specifically "must be read before any submission touching legged or terrain scenarios." §II-D now states the differentiation from both in full rather than deferring it: Orsolino/Focchi's feasible region is confirmed, from the paper's own text, to be an explicitly quasi-static, zero-base-velocity, geometric CoM-region construction with no temporal/predictive dimension

(a dynamic extension is named future work, not delivered) and no graduated-response hierarchy; Acosta and Posa's MPFC is confirmed to jointly re-solve discrete foothold selection and continuous footstep timing every cycle via a mixed-integer QP with no cheap-first/escalate-later mechanism or exhaustion condition, and to treat torque only as a single reduced-order ankle-torque decision variable with full-body realizability delegated to a separate, non-predictive 1kHz OSC QP. Both differentiations are grounded in specific, cited passages of the source papers, not paraphrased from memory. A later review pass confirmed both papers' titles, authors, venues, and years exactly as cited in §II-C/D and in the *References* section (Zhang, Liu, and Liao-McPherson, *IEEE Trans. Automatic Control*, submitted July 2025; Acosta and Posa, *IEEE T-RO* 41, 2025, pp. 4518–4537, arXiv:2501.19391) — the bibliographic entries are not fabricated. The "submitted to *IEEE Trans. Automatic Control*" line for [4] is carried from the arXiv listing metadata, not from text inside the PDF itself, which does not state a target venue; this specific sub-claim is unverified from the paper's own content and should be re-checked against the arXiv abstract page before submission.

5. **Legged/humanoid resourcing is unresolved.** No legged/humanoid simulation or hardware pipeline exists in this line of work as of this draft. Phase II/III should not be treated as required scope for a first submission until a real build-cost estimate (plausibly 6–12 months per the source planning document, not confirmed here) has been obtained. §VIII-K reflects this by scoping all designed experiments to the fixed-base manipulator.
6. **Publication sequencing.** Per the source planning document (§14), this paper should not proceed to substantive external submission until `mp_main` (ICRA 2027) and HAE (IJSS) have received decisions, and the recommended next concrete step is a separate, narrower saturation-certificate paper (targeting SCL/L-CSS) that proves Theorems 1–3 above independent of this paper's broader scope. This draft exists so that structure, positioning, and benchmark design are ready when that sequencing allows work to continue — it is not itself the next thing to do.
7. **§VIII's FR3-scale experiments have not been run; a reduced-order proxy has (§IX), and its results are folded in.** Every number, scenario parameter, and expected-outcome description in §VIII itself remains a design choice, not a measured result — that has not changed. What has changed since this item was first written: the same certificate, Level 0–4 hierarchy, ablation set, and real-time protocol were implemented and run on a 3-DOF planar reduced-order platform, and §IX reports those results, including negative and boundary findings (partial adaptation sometimes worse than none; Level 4 trading task completion for safety rather than guaranteeing both; a single Level-2 QP solve costing more than the entire real-time budget) that were kept visible rather than smoothed over. This draft contains zero fabricated data in either §VIII or §IX; §IX's own text states plainly where its reduced-order platform stops short of what §VIII specifies.
8. **Two claims in §II-D still lack a specific citation.** "Disturbance-observer-based path tracking under torque saturation in the early 2000s" (the claimed historical root of retiming as a mature sub-field) and a "task-space projection of torque limits for trajectory optimization on non-flat terrain" (a related-work claim distinct from the now-cited Orsolino/Focchi *Feasible Region* work, [5]) were both carried over from the source planning document without an author or title. Rather than invent a plausible-sounding citation for either, §II-D now states plainly that these are uncited; a specific paper must be identified and read for each before submission, or the claims should be removed or rephrased as general disciplinary background not requiring a citation.
9. **Two real bugs in §IX's implementation, found by an external code-vs-paper review and independently verified before fixing, are now fixed and the affected §IX numbers above updated to match.** (a)

Exp5/6's B3 "reroute" was changing the GOAL, not the route: P_A and P_B ended at two different final configurations, and the success metric scored "whichever goal was actually reached" — B3 could pass by abandoning the task for an easier target, which does not support this paper's actual Theorem 3 claim (a physically unrealizable route rejected in favor of a realizable route to the SAME goal). §VIII-F's design text already specified "two candidate routes between the same start and goal configuration" — the paper's design was correct; the implementation did not match it. Fixed with a two-segment via-point trajectory representation so P_A and P_B genuinely share q_0 and q_g ; the same bug, independently found in the ablation-batch code during this fix (the review did not name it), is fixed there too. (b) The replanning-count metric was re-testing a flag set once at plan time on every control cycle, so it counted roughly one "replan" per cycle for the rest of a rollout whenever Level 1/3 ever fired, rather than counting actual replanning events; fixed to count the route decision once, brake engagement once, and Level-2 corrections on rising edges only. A third, smaller issue was found while verifying these fixes with real reruns (not assumed): the reduced-order experiment scripts sized rollout duration off the nominal trajectory length, but Level 1 can retime a route up to $\lambda_{\max}$ longer, so a retimed rollout was sometimes truncated before finishing; fixed by sizing duration to what the route decision actually selects. Separately, an independent code-vs-paper review of §V-B's Level 2 (reshaping) found it optimized the acceleration profile against the nominal trajectory's own $(Q, \dot{Q})$ held fixed, with no constraint tying the optimized accelerations back to a state trajectory they could actually produce — so the certificate evaluated over the result did not certify a trajectory the system could actually be commanded to follow. Fixed by adding explicit double-integrator state variables and integration constraints to the same QP, anchored at the true current state; this is a materially larger optimization problem, and its real cost is reflected in the roughly doubled Level-2 QP timing figures above. B2's one-step reactive throttle (a uniform scaling of $\ddot{q}$ and $\dot{q}$ by $\tau_{\max}/\tau_0$) was also found not to guarantee its own claimed torque bound, since the gravity/Coriolis/external-force term in $\tau = M(q)\ddot{q} + h(q, \dot{q}, F)$ does not scale with $\ddot{q}$; replaced with an exact one-step QP projection onto the torque-feasible set at the same $(q, \dot{q})$, which is what §VIII-J's and §IX's updated B2 numbers above now reflect.

10. **A follow-up external code review, run from scratch against the fixed codebase above, found the fixes sound and found four further issues, now addressed.** (a) The Level-2 reshape QP's objective minimized raw $\sum \|\ddot{q}\|^2$, which prefers small accelerations, not accelerations close to the ones the planner originally intended — a "reshape" should mean the closest physically realizable trajectory, not the smallest one. The objective is now $w_a \sum \|\ddot{q}_j - \ddot{q}_j^{\text{nom}}\|^2 + w_q \sum \|q_j - q_j^{\text{nom}}\|^2 + w_{\dot{q}} \sum \|\dot{q}_j - \dot{q}_j^{\text{nom}}\|^2$. This is a genuine behavior change: staying close to the nominal acceleration is not always compatible with restoring margin, so the ablation-batch A4 and Exp. 3 numbers above moved (documented in place, in the repository README, and verified by a fresh full rerun) and the flagship unit test's reshape scenario now falls through to Level 4 rather than succeeding at Level 2 — an honest consequence of the fix, not a hidden regression, though it does mean no test in the current suite exercises a *successful* Level-2 outcome, a coverage gap worth closing separately. (b) The reviewer noted a code comment reading "Theorem 3's $T_{\text{dyn}}(p) = \text{empty case}$ " without qualification, which could be read as claiming the code establishes the idealized $\mathcal{T}_{\text{dyn}}(p) = \emptyset$ rather than the narrower, already-correct claim this draft's own Theorem 3 makes; the comment (in `exp5_flagship_reroute.py` and the README) is tightened to say explicitly that it is the sufficient condition $m_1^*(p) < m_{\text{safe}}$ being exercised, not a proof of the idealized statement — this draft's own Theorem 3 §VI text and its statement at line 174 already made this distinction correctly; only the looser code-comment shorthand needed correcting. (c) `saturation_events`, the per-run count of control steps where the applied

torque was clipped, is renamed `saturation_samples` throughout the code, README, and this draft: it counts samples, not distinct episodes, and the old name read as the latter. (d) `min_actuator_margin_nm` computed $\tau_{\max} - |\tau_{\text{cmd}}|$ (the commanded, pre-clip torque) while its own comment claimed it was "the ground-truth min margin actually realized" — those are different quantities once clipping occurs, since the applied margin is then exactly zero by construction. Split into `min_actuator_margin_cmd_nm` and `min_actuator_margin_applied_nm` so each field's name matches what it measures; not currently cited by a specific number anywhere in this draft, so this is a code-clarity fix with no numeric consequence here. The reviewer also confirmed, independently, no fatal physics or sign error in the certificate, the external-force convention, or the B2 torque-feasible projection, and re-ran `tests/test_dynamics.py`, `tests/test_planner.py`, and `run_all.py` cleanly after every fix above, archived under `code/results/test_archive/`.

11. **Experiment 7 (environment-conditioned rerouting), §VIII-L/§IX-G, implemented as a follow-up to the same review.** The reviewer's strongest remaining substantive comment: Experiment 5's flagship reroute and Experiment 6 are both triggered by a configuration/payload deficit, and Experiment 4 shows adaptation to a known environmental transition on a single fixed route, but nothing in the benchmark shows rerouting *because of* the environment specifically. Built and verified: two same-goal routes as in Experiment 5, reusing Experiment 4's scripted contact-stiffness force; P_A 's via-point is confirmed healthy under the payload alone (static margin +9.87 Nm) and infeasible only once the known force is included (-20.22 Nm), and confirmed retiming-proof by the certificate's own search — isolating the environment, not configuration or payload, as this scenario's cause. B1/B2 fail to reach the goal (0.234m/0.366m final error); B3 reroutes before entering the field and reaches it exactly (0.000m error, zero saturation samples). Wired into `run_all.py` and README as Experiment 7; full derivation of the via-point geometry and force constant is in `exp7_environment_conditioned_reroute.py`'s own docstring and inline diagnostics.
12. **Route-level reshape before rerouting, §V-B/§V-C/§IX-H, implemented after a conceptual discussion (not a code review) about what "predicted saturation" should trigger.** The discussion's conclusion, applied to this draft: predicted authority loss should not be assumed to require rerouting, and trajectory regeneration on the current route should be tried before escalating to a different one — which this draft's own Theorem 3 and §V-C already argued for retiming specifically, but the pre-execution route decision (`plan_route`) had never tried reshaping at route-planning time, only online per cycle, so a deficit retiming couldn't fix went straight to reroute without reshaping ever being attempted at the route level. `plan_route`'s order is now retime, then reshape, then reroute. Implementing this required extending `_try_reshape` with an explicit terminal-state constraint (so a whole-route reshape cannot silently drift to a different goal, reopening for Level 2 the exact failure mode already fixed once for Level 3) and a new lightweight trajectory-wrapper class so the reshaped route's discretely-optimized output can be used anywhere a planned route is (`online_step`, `rollout`, a further retime search) — both unit-tested directly, not merely exercised indirectly through an experiment. Three things were verified, not assumed, before trusting this: reshape genuinely cannot resolve either of this benchmark's two existing reroute-required scenarios (checked against an independent solver, since OSQP alone reports an inconclusive status rather than a clean infeasibility certificate on a QP this size), so neither headline reroute result changed; a scenario exists where reshape succeeds and retiming does not, via a mechanism distinct from geometric avoidance (reallocating timing within a fixed route duration); and this whole-route QP is expensive enough that the one-time, pre-execution route-planning cost rises by roughly one to two orders of magnitude (from a retiming-

alone baseline of 1–80ms, see Draft Status item 14, to 300–900ms) when it is attempted, whether or not it succeeds — a real, now-measured cost, not a free improvement.

13. **A full code-and-paper review (not a request to fix anything specific) found one genuine numeric imprecision, now corrected, and otherwise confirmed the draft's numbers.** Exp. 3's force-magnitude safety-vs-completion boundary was reported as "B3 avoids failure at $\leq 25\text{N}$, fails from $\sim 30\text{N}$ " (§IX-D, README); direct re-verification found the actual current boundary is $\leq 24\text{N}$ safe, 25N and above fails — off by one 1N sample point at the low end and by roughly 5N at the high end, overstating how much margin B3 has before Level 4's permanent-hold trade-off kicks in. Confirmed independent of the route-level-reshape work of item 12/§IX-H (identical boundary with Level 2 disabled entirely), so this predates that change and was not introduced by it; likely drift from an earlier Level-4 fix in item 9 that was never re-checked against this specific threshold. Both documents corrected. Separately spot-checked and confirmed accurate: the payload-sweep partial-adaptation numbers (189.6mm vs. 117.2mm at 3.0kg , §IX-D), the 2.4kg task-success crossover, the conservatism sweep (0/13 false positives), and Experiment 7's margin numbers — all reproduce exactly against a fresh run. The review also re-read `dynamics.py`, `certificate.py`, `baselines.py`, and `executor.py` in full (sign conventions, force-Jacobian consistency, computed-torque control law) and found no further issues.
14. **A real, code-confirmed gap in Theorem 3's monotonicity assumption, raised as a theoretical concern and then independently verified against the implementation before being fixed — not accepted on argument alone.** Per joint, torque under uniform time-dilation decomposes as $\tau(\lambda) = A/\lambda^2 + B$, where A is the inertial/Coriolis contribution (independent of λ itself; only its $1/\lambda^2$ scaling depends on it) and $B = g(q) + J^\top F_{\text{ext}}(q)$ is the velocity-independent contribution, unchanged by retiming. $m_{\text{phys}}(\lambda)$ is monotonically non-decreasing — the theorem's stated hypothesis — only when $\text{sign}(A_i) = \text{sign}(B_i)$ for the binding joint at every λ ; when a joint's inertial/Coriolis torque opposes its gravity/external-force torque (e.g. decelerating a downswing partially unloads gravity-holding torque), $\tau(\lambda)$ can cross zero at a finite λ^* and grow again beyond it, so $m_{\text{phys}}(\lambda)$ is genuinely non-monotonic. This was not left as an abstract possibility: a random search over 3000 scenarios on this platform found 23 ($\sim 0.8\%$) instances of the exact failure mode that matters — `_search_retime_whole_route` checked only λ_{max} and, on failure there, returned "retiming exhausted" even when a dense scan showed an interior λ , sometimes far from λ_{max} , genuinely restored the margin (e.g. $m_{\text{phys}}(\lambda_{\text{max}}) = 1.66 < m_{\text{safe}}$ while $m_{\text{phys}}(1.55) = 2.86 \geq m_{\text{safe}}$ in one instance). Fixed by keeping the fast bisection path when λ_{max} clears (unchanged cost) but dense-scanning $[1, \lambda_{\text{max}}]$ before giving up when it does not, refining locally around the first crossing found. Critically, **this does not change any number already reported in this paper**: the flagship scenario's $m_{\text{phys}}(\lambda)$ is genuinely monotonic (checked by dense scan, not assumed), and Experiment 7's is technically non-monotonic but the interior deviation is negligible against how far below m_{safe} it stays throughout — the one existing unit test for the monotonicity assumption (a pure static, zero-velocity/acceleration hold) cannot expose this failure mode by construction, since it removes the A/λ^2 term entirely, which is itself worth naming as a coverage gap the review identified independent of the fix. The retiming-alone cost baseline moved on scenarios that hit the new fallback (roughly 3ms to roughly $60\text{--}80\text{ms}$ in the tested cases, still far below reshape's $300\text{--}900\text{ms}$), updated in §IX-H and the repository README. This decomposition and per-joint sufficient condition, previously kept only in a standalone lemma draft intended for the narrower saturation-certificate paper of item 6, has now also been folded directly into §VI as a formal Lemma immediately following Theorem 3's proof — the "does not rule out adversarial Coriolis cross-terms in

principle" hedge in Theorem 3's own proof now points to a precise, proved condition instead of standing unquantified. `monotonicity_lemma_draft.md` is retained in the repository as the source material and is where the exact closed-form fallback (option (b) there, evaluating the finite candidate set $\{1, \lambda_{\max}\} \cup \{\lambda_i^*\}$ exactly rather than a dense scan) is being developed for the spin-off paper specifically; §VI states the dense-scan fallback actually implemented and used for the numbers in this draft, and does not claim the closed-form version.

15. **Two scope statements added following the same review, not yet present before this item.** First (§III/§XI): this architecture assumes operating margin is generally an asset to be preserved, which is false by construction for tasks whose optimal solution rides the actuator limit — minimum-time trajectories under torque constraints are bang-bang almost everywhere (Bobrow et al.; Pontryagin's maximum principle), so a genuinely time-optimal reference has m_{phys} at or below $-\Delta\tau_i$ by design and this architecture would retime it away from optimality, exactly canceling the reason it exists. This is stated as an explicit non-claim rather than left for a reader to infer from the conservatism metric, which measures a related but distinct thing (false-positive triggers on tasks that were never meant to ride the limit, not this structural mismatch for tasks that were). Second (§VI/Abstract): the "fixed-structure computational philosophy" claim is now scoped explicitly to the certificate evaluation and Level 0–1, with an explicit forward pointer to §IX-E/H's admission that the Level-2 reshape QP is rebuilt from scratch each call and does not currently hold this property — previously stated only in §IX's results text, not connected back to the Abstract/§VI claim a reader would encounter first.
16. **A cross-paper margin-stacking question, flagged but not resolved here.** The source planning document's §XII long-term stack places this paper's planner-level m_{safe} margin in series with an execution-layer margin from a separate, concurrently-developed paper on predictive saturation handling (the pHRI/interaction-dynamics line, not part of this repository). Stacking two independently-tuned conservative margins compounds directional-authority loss, and is a sharper version of item 15's first point for boundary-optimal tasks specifically. This item was raised in review without opening or reading that paper's current draft in this session, so no specific reconciling text is proposed here; before any joint submission or cross-reference between the two lines, that draft must be read to determine whether the two margins' scope is already disjoint (e.g. one gating route selection, the other gating instantaneous command shaping) or whether an explicit reconciliation is needed.
17. **The conservatism metric's false-negative gap, from a further review pass evaluating two independent critiques of this draft.** One critique proposed a runtime saturation-intent classifier (distinguishing "desired" from "undesired" saturation via task phase, command source, etc.) plus two new experiments and a revised Theorem 1 with an unspecified `saturation_is_desired` predicate; this was evaluated and rejected as disproportionate to this draft's scope — the revised theorem doesn't prove anything (it relocates the hard problem into an unspecified predicate rather than solving it), and the margin-as-asset scope statement already added (item 15) is the appropriately-scoped fix for the same underlying point. The one genuinely new and proportionate item from that pass: §VIII-I's conservatism metric bounds false positives only; nothing in this benchmark design currently measures false negatives (a real violation the certificate fails to catch in time). Checked directly, not assumed, before writing the caveat: no false-negative instance appears incidentally in any archived experiment log (e.g. no Exp. 2 payload-sweep row shows an untriggered B3 trial with nonzero saturation), but no experiment here was designed to stress-test this specifically, so the caveat in §VIII-I/§IX-C/§X states this as an open gap rather than implying a measured zero rate.