B.Comp. Dissertation

DGLight: DQN-Guided GRPO Fine-Tuning of Large Language Models for Traffic Signal Control

Yu Chenbo

Department of Computer Science
School of Computing
National University of Singapore

2025/2026

B.Comp. Dissertation

DGLight: DQN-Guided GRPO Fine-Tuning of Large Language Models for Traffic Signal Control

Yu Chenbo

Department of Computer Science

School of Computing

National University of Singapore

2025/2026

Project No: H118280

Advisor: Prof. Roger Zimmermann

Main Evaluator: Assoc. Prof. Aaron Tan Tuck Choy

Deliverables:

Report: 1 Volume

Program: 1 Codebase

Abstract

Table of Contents

1 Introduction

Rapid urbanization and accelerating motorization have placed unprecedented strain on urban transportation systems worldwide. As cities densify, limited road infrastructure must accommodate ever-growing travel demand, leading to persistent congestion, unreliable travel times, and increased environmental externalities. Inefficient traffic flow not only wastes fuel and economic productivity but also amplifies air pollution and degrades quality of life, particularly in densely populated urban corridors.

Traffic signal control (TSC) aims to coordinate phase sequences and durations at signalized intersections to maximize throughput and reduce congestion. Classical fixed-time methods use the Webster formula[17] to preset signal timings based on historical traffic data collected from the traffic network at different times. In contrast, the max-pressure control framework[6] computes a pressure value for each signal phase from the difference between queue lengths on opposing approaches and selects the phase with the highest pressure; this strategy can be shown to maximize network throughput.

Reinforcement-learning (RL) methods model TSC as a Markov decision process in which an agent observes traffic states (for example, lane queue lengths and delays), chooses an action (phase switch) and receives a reward linked to throughput or delay reduction. Deep RL further parameterizes the control policy using neural networks, enabling the agent to approximate complex, high-dimensional decision functions. Such methods have demonstrated strong empirical performance across a wide range of simulated traffic scenarios. However, they also introduce notable challenges. In particular, learned policies often exhibit limited generalization, as models trained in one traffic environment exhibit degraded performance when deployed in different cities or under unseen conditions. Furthermore, the reliance on opaque neural representations reduces interpretability, making it difficult to explain or verify decision-making processes. This lack of transparency poses a barrier to real-world adoption, where reliability and accountability are critical.

Large Language Models (LLMs) represent a new paradigm in artificial intelligence, combining strong reasoning ability with the capacity to generate interpretable, text-based outputs. These properties make LLMs promising candidates for traffic signal control, where decision transparency and adaptability are highly desirable. By framing control as a reasoning process, LLM-based agents can potentially provide both actionable policies and human-understandable explanations, bridging the gap between performance and interpretability. However, this potential is not yet fully realized in practice. Achieving real-time responsiveness typically requires deploying smaller-scale models or mixture-of-experts (MoE) architectures with compact expert networks. Without sufficient domain adaptation, such models often fail to capture complex traffic dynamics, leading to suboptimal decisions.

to answer all the demands, I ....

2 Related Work

Traffic Signal Control. Early TSC methods such as *FixedTime* [17] rely on predefined cycle lengths and manually designed phase splits for each intersection. Although these

approaches are simple and stable in practice, they adapt poorly to time-varying traffic demand. *MaxPressure* [6] improves adaptability by selecting phases according to the queue imbalance between incoming and outgoing directions, making it more responsive than fixed plans. However, both *FixedTime* and *MaxPressure* remain constrained by handcrafted rules or preset logic, which limits their flexibility under complex and highly dynamic traffic scenarios.

Recent progress in reinforcement learning has led to a series of RL-based TSC methods. *CoLight* [16] models network-level cooperation among intersections through graph attention, enabling each signal to coordinate with surrounding intersections instead of acting independently. *CoSLight* [10] further extends this idea by jointly optimizing signal control and collaborator selection, so that each intersection can dynamically decide which neighboring intersections are most useful for coordination under current traffic conditions. *MPLight* [1] is a decentralized and pressure-aware RL approach designed for large-scale road networks, using parameter sharing to improve scalability and training efficiency. Although these methods achieve strong performance in per city simulation, RL-based controllers face challenges in generalization and interpretability, hence deployment robustness in real-world environments.

To address these limitations, recent studies have begun exploring the integration of large language models (LLMs) into TSC. *LLM-Assisted Light* [15] places an LLM at the center of control and augments it with perception and decision-support tools so that it can combine live traffic observations with established TSC methods and remain robust under emergency, roadblock, and sensor-outage scenarios. *iLLM-TSC* [8] instead adopts a hybrid design in which an RL controller first proposes an action and an LLM then verifies or adjusts that action when observations are degraded or rare events such as packet loss and emergency vehicles fall outside the original RL formulation. *LATS* [19] further explores a teacher-student setting in which an LLM teacher provides rich semantic features during multi-agent RL training, while a smaller student controller learns to emulate those features and is deployed without the LLM at inference time. *LLMLight* [4] moves closer to end-to-end LLM control by adapting its LightGPT backbone through imitation fine-tuning and critic-guided policy refinement so that the model can make direct signal decisions with improved interpretability and cross-scenario performance. *Traffic-R1* [20] extends this trend with a 3B RL-finetuned foundation model that combines expert-aligned offline training, online self-exploration, and asynchronous multi-agent communication to achieve strong zero-shot and out-of-distribution TSC performance. Compared with end-to-end LLM finetuning, LLM+RL hybrids may remain inferior because they still inherit the ceiling and failure modes of the underlying RL controller. Existing end-to-end finetuning methods also have notable limitations: In *LLMLight*, the critic-guided policy refinement objective is weaker than modern policy-gradient methods because the reward/advantage magnitude does not directly participate in loss computation. *Traffic-R1*, meanwhile, relies on substantial human effort to label the offline finetuning data, and its fixed-horizon cumulative queue-based reward assigns the same coarse mean reward to all steps within the horizon.

RL finetuning of LLMs. RL-based preference alignment [7] adapts a pretrained LLM using scalar or pairwise feedback so that the policy is optimized toward preferred responses rather than merely imitating target outputs. Among modern policy optimization methods, TRPO [12] constrains updates within a trust region to stabilize improvement, PPO [11] replaces this with a clipped surrogate objective that is simpler and more prac-

tical at scale, and GRPO [13] further removes the separate value model by computing group-relative advantages over sampled responses, which makes it especially attractive for LLM training. Closely related to these RL-style methods, DPO [9] performs direct preference optimization on chosen–rejected response pairs and avoids explicit reward-model fitting and online rollout collection. This line of work is particularly important because preference-aligned RL can train reasoning ability rather than only answer imitation: through exploration, comparison, and preference-based updates, the model learns to assign higher probability to response trajectories that exhibit stronger multi-step reasoning while remaining close to a reference policy through KL regularization, as emphasized in RLHF-style alignment and recent reasoning-oriented RL studies [7, 13, 3]. Recent systems such as *DeepSeek-R1* [3] show that large-scale self-exploration can substantially improve reasoning behavior, making RL preference alignment increasingly relevant for domain-specific agents that must optimize long-horizon objectives.

3 Preliminaries

Definition 1. ***Road Network.*** A road network is represented as a directed graph consisting of intersections $\mathcal{V}$ and lanes $\mathcal{L}$. The lane set is grouped into three categories: go-through lanes ($\mathcal{L}_{\text{go}}$), left-turn lanes ($\mathcal{L}_{\text{left}}$), and right-turn lanes ($\mathcal{L}_{\text{right}}$). Each lane connects adjacent intersections and is partitioned into segments $S = \{s_1, \ldots, s_n\}$ according to its distance from the intersection.

Definition 2. ***Signal Phase.*** At each signal-switching step, the controller of an intersection chooses a signal phase from a predefined action set $A = \{a_1, \ldots, a_m\}$. A phase is written as $a = \text{set}(\mathcal{L}_{\text{allow}})$, where $\mathcal{L}_{\text{allow}}$ denotes the collection of lanes that are allowed to move simultaneously without conflict, meaning these lanes receive green signals while conflicting lanes remain red.

Definition 3. ***Traffic Signal Control System.*** The traffic signal control system consists of multiple agents $\Pi = \{\pi_1, \ldots, \pi_n\}$, with each agent assigned to one of the n intersections in the road network. For intersection i, agent π_i makes its signal control decision by observing the number of vehicles in each segment of the lanes approaching that intersection, thereby forming a segment-level view of the local traffic state.

Problem Statement. ***LLM Reasoning for Traffic Signal Control.*** For each intersection i in the road network, an LLM serves as agent π_i. At decision step t, the agent takes the observation $O_{i,t}$, the task description d_{task}, and the action space A as input, and outputs both reasoning content and a signal phase decision. The TSC problem is therefore formulated as selecting a phase $a_{i,t} \in A$ while generating reasoning output $R_{i,t}$ under the given observation and task specification. The system dynamics are defined as:

$$(R_{i,t}, a_{i,t}) = \pi_{\theta_i}(O_{i,t}, d_{\text{task}}, A) \tag{1}$$

where $O_{i,t}$ is the observation, d_{task} is the task description, A is the action space, $R_{i,t}$ is the reasoning output, and $a_{i,t}$ is the selected phase.



Figure 1: Overview of the two-stage *DGLight* pipeline.

4 Methodology

This section introduces *DGLight*, a two-stage reinforcement-learning pipeline for adapting a pretrained large language model to traffic signal control. In the first stage, a CoLight-based DQN critic is trained to estimate action values for signal-phase decisions when provided with structured environment states. In the second stage, the frozen critic scores candidate LLM responses during rollout and the scores are used as the reward signal for GRPO-based policy optimization.

4.1 Pretraining the CoLight-Based DQN Critic

The critic used in *DGLight* is based on *CoLight* [16], a graph-attentive deep Q-learning model for network-level traffic signal control. *CoLight* is employed as a pretrained value estimator so that the subsequent GRPO stage can query a traffic-aware action-value function rather than rely exclusively on the raw environment reward. Given the current environment state, the critic predicts action values for each intersection and thereby provides a dense estimate of the quality of candidate signal phases under the prevailing traffic situation.

The *CoLight* critic is composed of three main components. The first component is an observation embedding module that transforms the local traffic state of each intersection into a latent feature representation. The second component consists of one or more multi-head graph-attention layers, which propagate information across neighboring intersections and produce attention-weighted network representations. The final component is a Q-value prediction layer that maps the aggregated features to one scalar value for each admissible signal phase. This architecture combines local state encoding, inter-intersection coordination, and value-based action estimation within a single model.

Training follows the standard value-based reinforcement learning procedure. The model interacts with the traffic environment to collect state transitions, actions, rewards, and subsequent states $((s, a, r, s'))$, where the stepwise reward is defined to be inversely proportional to queue lengths at each intersection. These transitions are stored in replay memory for off-policy updates. The optimization objective minimizes the Bellman error

$$\mathcal{L}_{\text{Bellman}}(\theta) = \mathbb{E}_{(s,a,r,s')\sim\mathcal{D}}\left[\left(r + \gamma \max_{a'} Q_{\theta^-}(s', a') - Q_\theta(s, a)\right)^2\right],$$

where $\mathcal{D}$ denotes the replay buffer, θ denotes the online network parameters, and θ^- denotes the target network parameters. Experience replay improves sample efficiency, and the target network improves optimization stability.

Disclaimer: The critic model, its training objective, and its overall learning logic are not original contributions of this dissertation; they are inherited from prior *CoLight* research. My contribution to this component is limited to re-implementing the model in PyTorch for this codebase, whereas the original *CoLight* implementation was based on TensorFlow.

4.2 LLM Prompting and Action Sampling

At each signal-switching step t, each intersection i is converted into a textual prompt $x_{i,t}$ that summarizes the current traffic condition together with the task instruction and the available signal phases. The prompt is constructed from the environment state used by the controller including the current phase and queue information. Task description is formatted so that the model produces both human-readable reasoning and a final phase choice. A sample prompt is provided in Appendix A.0.4.

Given prompt $x_{i,t}$, the policy π_θ samples a group of k candidate responses

$$\{y_{i,t}^{(1)}, y_{i,t}^{(2)}, \ldots, y_{i,t}^{(k)}\}.$$

Each response is then mapped to a signal phase through a deterministic parser:

$$a_{i,t}^{(j)} = \text{Parse}(y_{i,t}^{(j)}), \qquad j = 1, \ldots, k.$$

If the response fails to specify a valid action in the predefined action space, it is treated as an invalid output and assigned a fallback reward during training. This allows the method to preserve free-form reasoning generation while still enforcing a discrete control interface at execution time.

4.3 DQN-Guided Action Scoring in Rollout Collection

The central idea of *DGLight* is to replace discounted raw environment rewards with action value estimates from the pretrained DQN critic.

Stepwise action value assignment. For the current traffic state at intersection i, the frozen critic produces a vector of estimated returns over all admissible signal phases:

$$\mathbf{q}_{i,t} = \left[Q_\phi(s_{i,t}, a)\right]_{a\in A},$$

where $s_{i,t}$ is the structured traffic state and Q_ϕ is the pretrained DQN critic. The critic therefore acts as a traffic-aware evaluator that maps the current state to a vector of action values that reflect both spatial and temporal traffic context.

Each sampled LLM response is scored by the critic through its parsed action:

$$r_{i,t}^{(j)} = \begin{cases} Q_\phi\left(s_{i,t}, a_{i,t}^{(j)}\right), & \text{if } a_{i,t}^{(j)} \in A, \\ r_{\text{invalid}}, & \text{otherwise,} \end{cases}$$

where r_{invalid} is a fixed fallback reward for malformed or out-of-range decisions.

Environment stepping. Among the sampled candidates, the action actually executed in the environment is the highest-scoring sampled action,

$$j_{i,t}^* = \arg\max_{j \in \{1,\ldots,k\}} r_{i,t}^{(j)}, \qquad \hat{a}_{i,t} = a_{i,t}^{(j_{i,t}^*)}.$$

Thus, the environment rollout is still driven by sampled LLM outputs, but execution is guided by the critic's action-value estimate.

This design has a major advantage that the critic-derived reward incorporates richer spatial and temporal information than short-horizon cumulative rewards computed directly from the environment. Because the CoLight-based critic aggregates information from neighboring intersections through graph attention and is trained with Bellman backups under a discount factor, $Q_\phi(s_{i,t}, a)$ reflects both network interactions and the expected downstream consequences of choosing action a.

4.4 GRPO-Based Policy Optimization

After rollout collection, each intersection-step pair contributes a training record consisting of the prompt and the full critic score vector,

$$\mathcal{D}_{i,t} = \left(x_{i,t}, \mathbf{q}_{i,t}\right).$$

Importantly, the stored supervision is not just the score of the executed action. Instead, the entire per-action vector is retained so that any newly sampled response for the same prompt can be rewarded according to the action it proposes. During GRPO training, a completion y sampled for prompt $x_{i,t}$ is assigned reward

$$R(x_{i,t}, y; \mathbf{q}_{i,t}) = \begin{cases} \mathbf{q}_{i,t}[a(y)], & \text{if } a(y) \in A, \\ r_{\text{invalid}}, & \text{otherwise,} \end{cases}$$

where $a(y)$ denotes the parsed action of completion y. The resulting reward values are then normalized within each sampled group, producing relative advantages that drive the GRPO update.

This optimizer is particularly well suited to the present setting because it provides a natural way to train an LLM using reward signals from an already established value-based traffic-control critic. For a single traffic prompt, multiple completions can be sampled efficiently, parsed into candidate signal phases, and scored by the frozen DQN critic, after which GRPO uses the relative critic rewards within the sampled group to improve

the policy. This way, critic-guided GRPO transfers decision-making knowledge from the value-based controller into the LLM. Although the critic is trained on traffic data from a specific city, the LLM is not fine-tuned to overfit any single city. Rather, it is trained to have stronger reasoning patterns for mapping textual traffic states to better signal actions. This strengthens the model's traffic decision-making capacity while preserving transferability.

4.5 End-to-End DGLight Training Procedure

The complete training loop can be summarized as follows:

1. Pretrain the CoLight-based DQN critic.
2. Freeze the critic checkpoint for downstream use in *DGLight*.
3. Reset the CityFlow environment and build one textual prompt for each active intersection.
4. Sample k candidate responses from the LLM for every prompt.
5. Parse each response into a discrete signal phase.
6. Query the frozen critic to obtain per-action Q-values for the current traffic state.
7. Score the sampled responses according to their parsed actions and execute the best sampled action at each intersection.
8. Store the prompt together with the full per-action score vector as a GRPO training record.
9. Repeat the above process for the full rollout episode, then fine-tune the policy on the collected records with GRPO.

In practice, the two stages are decoupled. The critic is first trained offline as a CoLight-based DQN value estimator, and the resulting checkpoint is then reused as a fixed evaluator during LLM fine-tuning. Exact hyperparameter settings, model sizes, rollout lengths, and dataset configurations are deferred to the experimental section.

4.6 Comparison Variant

For completeness, I also implemented a *Joint-Scored GRPO (JS-GRPO)* variant as a comparison method. Instead of using direct critic Q-values to score sampled actions, that variant estimates action quality indirectly from short-horizon joint rollout returns over snapshot-forked simulations, and then projects those returns back to per-intersection action scores for GRPO training. Because this variant is included only to test whether indirect joint scoring can outperform direct critic guidance, I do not treat it as a co-equal methodological contribution in the main text. Its detailed design is provided separately in Appendix A.0.3.

5 Experiments

In this second, I evaluate *DGLight* to address the following research questions:

- **RQ1: (Effectiveness)** Can *DGLight* outperform traditional, RL-based, and existing LLM-based traffic signal control methods on standard TSC datasets?
- **RQ2: (Transferability)** Does *DGLight* retain strong performance when evaluated on city datasets that were not used to train the DQN critic?
- **RQ3: (Interpretability)** Are the decisions produced by *DGLight* interpretable, in the sense that its generated reasoning reflects the traffic conditions that motivate the selected phase?
- **RQ4: (Ablation Study)** How much improvement comes from critic-guided GRPO, as compared with baseline and intermediate models?

5.1 Experimental Settings

This subsection describes the datasets, simulation environment, baselines, evaluation metrics, and training configuration used throughout the experiments.

Table 1: Statistics of traffic flow datasets.

Dataset	Structure	Vehicles	Arrival rate (vehicles/5min)			
			Mean	Std	Max	Min
Jinan1	3×4	6295	523.67	98.52	671	255
Jinan2		4365	362.83	74.81	493	236
Jinan3		5494	456.92	160.87	569	362
Hangzhou1	4×4	2983	247.68	40.44	332	211
Hangzhou2		6984	581.08	318.43	1145	202

5.1.1 Dataset. Experiments are conducted on standard traffic signal control benchmarks. Table 1 is left as a structured summary template for the final dataset statistics.

5.1.2 Environment. All methods are evaluated in an environment built on top of *CityFlow* [14], a scalable microscopic traffic simulator widely used in traffic signal control research. For each dataset, the simulator loads the corresponding road-network and traffic-flow configuration and exposes lane-level observations at every control step. In my experiments, each intersection connects four lane sections: east, west, north, and south. The control action space therefore contains four signal phases: *ETWT* (through movements from east and west), *ELWL* (left turns from east and west), *NTST* (through movements from north and south), and *NLSL* (left turns from north and south). Right-turn movements are always allowed in the simulation. Each controller selects one signal phase for every controlled intersection, after which the environment advances under a shared signal-switching interval. The green phase duration is fixed at 30 seconds. Each green phase is followed by a 3-second yellow phase and a 2-second all-red interval to ensure

safe signal transitions. Unless otherwise stated, all compared methods use the same simulator configuration, decision interval, and evaluation protocol so that performance differences can be attributed to the controller rather than the environment setup.

5.1.3 Baselines. The comparison includes traditional controllers, RL-based methods, and LLM-based methods.

- **Traditional methods.** *FixedTime* [17] and *MaxPressure* [6].
- **RL methods.** *MPLight* [1], *AttendLight*, *PressLight*, *CoLight* [16], *Efficient-CoLight*, and *Advanced-CoLight*.
- **LLM-based methods.** *LightGPT (Llama3-8b)* [4], *JS-GRPO-h3 (Llama3-8b)*, *JS-GRPO-h6 (Llama3-8b)*, and the proposed *DGLight (Llama3-8b)*. The two *JS-GRPO* variants correspond to the comparison method described in Appendix A.0.3, instantiated with horizon lengths of 3 and 6, respectively.

5.1.4 Metrics. Following previous studies [18], the following metrics are used to evaluate the TSC agents trained with different methods:

- **Average traveling time (ATT)** quantifies the average duration of all vehicles traveling from their origins to their respective destinations.
- **Average queue length (AQL)** is defined as the average number of queuing vehicles waiting in the road network.
- **Average waiting time (AWT)** quantifies the average queuing time of vehicles at every intersection in the road network.

Lower values indicate better traffic efficiency for all three metrics.

5.1.5 Training Configuration. All LLM-based methods use *Llama3-8b* as the backbone model. For the proposed method, the initial checkpoint is inherited from the *LLMLight* pipeline [4] rather than obtained through an additional supervised fine-tuning stage, since training a dedicated supervised model on high-quality traffic reasoning traces is beyond the computational budget of this dissertation. Starting from the *LLMLight* base model isolates the contribution of the proposed critic-guided GRPO procedure while preserving a fair comparison with prior LLM-based controllers. The overall training framework then combines a pretrained CoLight critic with a GRPO-based policy optimization stage. The critic retains the uniform RL hyperparameters reported by Zhang et al. [18], while the policy stage uses LoRA adaptation and distributed training. Table 2 and Table 3 summarize the corresponding framework settings.

5.2 Results on TSC Datasets (RQ1)

Table 5 shows that *DGLight* is the strongest overall method among the four LLM-based controllers. It achieves the best performance on most datasets and metrics, with

Table 2: CoLight critic configuration.

Component	Configuration
Training dataset	Hangzhou-1
Optimizer	Adam with learning rate 1×10^{-3}
Discount factor γ	0.8
Replay buffer size	12000
Sample size per round	3000
Batch size	20
Gradient epochs per round	100
Target network update interval	every 5 rounds
Exploration schedule	$\epsilon = \max(0.8 \cdot 0.95^r, 0.2)$
Reward	$-0.25 \cdot$ queue length

Table 3: GRPO policy optimization configuration.

Component	Configuration
Policy backbone	Llama3-8b
LoRA configuration	rank = 8, $\alpha = 16$, dropout = 0.05, bias = none
Overall episodes	2
Rollout environment	3600-second episodes with a 30-second action interval
Rollout group size k	4
Prompt / completion length	2048 / 1024 tokens
Rollout sampling	temperature = 1.0, top-p = 1.0, top-k = 50
GRPO optimizer and learning rate	default TRL optimizer, learning rate = 1.0×10^{-6}
GRPO batch size / accumulation / epochs	8 per device / 1 / 1
Invalid-action reward	0.0
Distributed training setup	2 H100-96GB GPUs, 16 CPUs, 128 GB RAM, 12-hour wall time

Hangzhou-1 as the main exception. Overall, this result shows that the proposed method is superior to the reward-discounting baselines and that critic-guided GRPO improves the quality of the traffic-signal decisions produced by the LLM policy.

When compared with the strongest RL baselines in Table 4, *DGLight* remains competitive with the CoLight family and even exceeds them on some metrics, showing that the proposed training procedure improves the model's reasoning ability for traffic situations. The main exception is Hangzhou-1, where the CoLight family performs exceptionally well because those models are trained directly on that dataset, which may partly reflect overfitting to that setting.

Finally, *JS-GRPO-h6* generally performs better than *JS-GRPO-h3*, suggesting that a longer horizon for discounted cumulative reward provides a better estimate of the true long-term reward.

Table 4: Performance of traditional and RL-based baselines on the TSC datasets. Lower values are better. Best and second-best values are highlighted in bold and underlined, respectively.

Models	Jinan									Hangzhou					
	1			2			3			1			2		
	ATT	AQL	AWT	ATT	AQL	AWT	ATT	AQL	AWT	ATT	AQL	AWT	ATT	AQL	AWT
Transportation Methods															
Random	597.62	687.35	99.46	555.23	428.38	100.40	552.74	529.63	99.33	621.14	295.81	96.06	504.28	432.92	92.61
FixedTime	481.79	491.03	70.99	441.19	294.14	66.72	450.11	394.34	69.19	616.02	301.33	73.99	486.72	425.15	72.80
MaxPressure	281.58	170.71	<u>44.53</u>	273.20	106.58	**38.25**	265.75	133.90	<u>40.20</u>	325.33	68.99	<u>49.60</u>	347.74	215.53	<u>70.58</u>
RL Methods															
MPLight	307.82	215.93	97.88	304.51	142.25	90.91	291.79	171.70	89.93	345.60	84.70	81.97	358.56	237.17	100.16
AttendLight	291.29	186.25	61.73	280.94	115.52	52.46	273.02	144.05	55.93	322.94	66.96	55.19	358.81	239.05	72.88
PressLight	291.57	185.46	50.53	281.46	115.99	47.27	275.85	148.18	54.81	364.13	98.67	90.33	417.01	349.25	150.46
CoLight	279.60	168.53	58.87	274.77	108.28	54.14	266.39	135.08	53.33	322.85	66.94	61.82	342.90	212.09	99.74
Efficient-CoLight	<u>277.11</u>	<u>163.60</u>	**43.41**	<u>269.24</u>	<u>102.98</u>	<u>39.74</u>	<u>262.25</u>	<u>129.72</u>	**39.99**	<u>311.96</u>	<u>58.20</u>	**36.83**	<u>333.27</u>	<u>189.65</u>	**61.70**
Advanced-CoLight	**274.67**	**160.85**	49.30	**268.25**	**102.12**	41.11	**260.66**	**127.83**	43.54	**304.47**	**52.94**	<u>41.75</u>	**329.16**	**186.34**	76.59

Table 5: Performance of LLM-based methods on the TSC datasets. Lower values are better. Best and second-best values are highlighted in bold and underlined, respectively.

Models	Jinan									Hangzhou					
	1			2			3			1			2		
	ATT	AQL	AWT	ATT	AQL	AWT	ATT	AQL	AWT	ATT	AQL	AWT	ATT	AQL	AWT
LightGPT (Llama3-8b)	<u>277.38</u>	<u>164.60</u>	<u>48.68</u>	<u>270.14</u>	<u>103.77</u>	<u>44.10</u>	<u>262.67</u>	<u>130.65</u>	<u>44.98</u>	**316.12**	**61.02**	**53.84**	<u>333.95</u>	**190.91**	72.57
JS-GRPO-h3 (Llama3-8b)	279.59	168.24	52.80	271.59	105.43	47.57	264.74	134.01	49.48	317.48	61.89	55.04	334.76	194.48	<u>72.43</u>
JS-GRPO-h6 (Llama3-8b)	277.73	164.92	50.28	271.89	105.83	46.59	263.47	132.39	49.72	317.95	61.93	<u>53.94</u>	336.45	197.08	75.03
DGLight (Llama3-8b)	**275.92**	**162.64**	**47.17**	**269.68**	**103.51**	**43.78**	**262.16**	**129.77**	**43.53**	<u>316.59</u>	<u>61.08</u>	54.43	**333.14**	<u>191.61</u>	**70.63**

5.3 Transferability to Unseen Cities (RQ2)

The transferability results show that *DGLight* retains strong performance on datasets that were not used to fit the DQN critic, namely all three Jinan datasets and Hangzhou-2. More importantly, the magnitude of improvement is relatively larger on these unseen datasets than on the datasets most closely aligned with the critic, especially when compared with both the RL baselines and *LightGPT*. This pattern suggests that the proposed method does not merely adapt to the critic's judgment, but instead improves the model's ability to reason about traffic states in a way that generalizes beyond the data seen by the critic.

5.4 Interpretability of Model Decisions (RQ3)

Figure 2 shows a representative reasoning trace generated by *DGLight* for a single traffic state. The example illustrates how the model first describes the relevant traffic conditions and then maps that assessment to a final signal choice. This makes it possible to inspect whether the stated rationale is consistent with the selected action.

5.5 Ablation Study (RQ4)

This ablation isolates two sources of improvement: traffic-specific LLM adaptation and critic-guided reinforcement learning. The untuned *Llama3-8b* measures the capability of the base model without TSC adaptation, *LightGPT* measures the gain from prior TSC-

Table 6: Ablation study comparing the untuned base model, *LightGPT*, and *DGLight*. Fill in the final values after evaluation. Lower values are better.

Models	Jinan									Hangzhou					
	1			2			3			1			2		
	ATT	AQL	AWT	ATT	AQL	AWT	ATT	AQL	AWT	ATT	AQL	AWT	ATT	AQL	AWT
Llama3-8b															
LightGPT (Llama3-8b)															
DGLight (Llama3-8b)															

specific training, and *DGLight* measures the additional benefit of the proposed critic-guided GRPO procedure.

6 Conclusion and Future Work

References

[1] Chacha Chen et al. "Toward A Thousand Lights: Decentralized Deep Reinforcement Learning for Large-Scale Traffic Signal Control." In: *Proceedings of the AAAI Conference on Artificial Intelligence* 34.04 (Apr. 2020), pp. 3414–3421. DOI: 10.1609/aaai.v34i04.5744. URL: https://ojs.aaai.org/index.php/AAAI/article/view/5744.

[2] Lang Feng et al. *Group-in-Group Policy Optimization for LLM Agent Training*. 2025. arXiv: 2505.10978 [cs.LG]. URL: https://arxiv.org/abs/2505.10978.

[3] Daya Guo et al. *DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning*. 2025. arXiv: 2501.12948 [cs.CL]. URL: https://arxiv.org/abs/2501.12948.

[4] Siqi Lai et al. *LLMLight: Large Language Models as Traffic Signal Control Agents*. 2024. arXiv: 2312.16044 [cs.AI]. URL: https://arxiv.org/abs/2312.16044.

[5] Pablo Alvarez Lopez et al. "Microscopic Traffic Simulation using SUMO." In: *The 21st IEEE International Conference on Intelligent Transportation Systems*. IEEE, 2018. URL: https://elib.dlr.de/124092/.

[6] Pedro Mercader, Wasim Uwayid, and Jack Haddad. "Max-pressure traffic controller based on travel times: An experimental analysis." In: *Transportation Research Part C: Emerging Technologies* 110 (2020), pp. 275–290. ISSN: 0968-090X. DOI: https://doi.org/10.1016/j.trc.2019.10.002. URL: https://www.sciencedirect.com/science/article/pii/S0968090X19307442.

[7] Long Ouyang et al. *Training Language Models to Follow Instructions with Human Feedback*. 2022. arXiv: 2203.02155 [cs.CL]. URL: https://arxiv.org/abs/2203.02155.

[8] Aoyu Pang et al. *iLLM-TSC: Integration Reinforcement Learning and Large Language Model for Traffic Signal Control Policy Improvement*. 2024. arXiv: 2407.06025 [cs.AI]. URL: https://arxiv.org/abs/2407.06025.

[9] Rafael Rafailov et al. *Direct Preference Optimization: Your Language Model is Secretly a Reward Model*. 2023. arXiv: 2305.18290 [cs.LG]. URL: https://arxiv.org/abs/2305.18290.

[10] Jingqing Ruan et al. *CoSLight: Co-optimizing Collaborator Selection and Decision-making to Enhance Traffic Signal Control*. 2024. arXiv: 2405.17152 [cs.MA]. URL: https://arxiv.org/abs/2405.17152.

[11] John Schulman et al. *Proximal Policy Optimization Algorithms*. 2017. arXiv: 1707.06347 [cs.LG]. URL: https://arxiv.org/abs/1707.06347.

[12] John Schulman et al. *Trust Region Policy Optimization*. 2015. arXiv: 1502.05477 [cs.LG]. URL: https://arxiv.org/abs/1502.05477.

[13] Zhihong Shao et al. *DeepSeekMath: Pushing the Limits of Mathematical Reasoning in Open Language Models*. 2024. arXiv: 2402.03300 [cs.CL]. URL: https://arxiv.org/abs/2402.03300.

[14] Zheng Tang et al. *CityFlow: A City-Scale Benchmark for Multi-Target Multi-Camera Vehicle Tracking and Re-Identification*. 2019. arXiv: 1903.09254 [cs.CV]. URL: https://arxiv.org/abs/1903.09254.

[15] Maonan Wang et al. *LLM-Assisted Light: Leveraging Large Language Model Capabilities for Human-Mimetic Traffic Signal Control in Complex Urban Environments*. 2024. arXiv: 2403.08337 [eess.SY]. URL: https://arxiv.org/abs/2403.08337.

[16] Hua Wei et al. "CoLight: Learning Network-level Cooperation for Traffic Signal Control." In: *Proceedings of the 28th ACM International Conference on Information and Knowledge Management*. CIKM '19. Beijing, China: Association for Computing Machinery, 2019, pp. 1913–1922. ISBN: 9781450369763. DOI: 10.1145/3357384.3357902. URL: https://doi.org/10.1145/3357384.3357902.

[17] Biao Yin, Mahjoub Dridi, and Abdellah Moudni. "Traffic network micro-simulation model and control algorithm based on approximate dynamic programming." In: *IET Intelligent Transport Systems* 10 (Dec. 2015). DOI: 10.1049/iet-its.2015.0108.

[18] Liang Zhang et al. "Expression might be enough: representing pressure and demand for reinforcement learning based traffic signal control." In: *Proceedings of the 39th International Conference on Machine Learning*. Vol. 162. Proceedings of Machine Learning Research. PMLR, 17–23 Jul 2022, pp. 26645–26654. URL: https://proceedings.mlr.press/v162/zhang22ah.html.

[19] Yifeng Zhang et al. *LATS: Large Language Model Assisted Teacher-Student Framework for Multi-Agent Reinforcement Learning in Traffic Signal Control*. 2026. arXiv: 2603.24361. URL: https://arxiv.org/abs/2603.24361.

[20] Xingchen Zou et al. *Traffic-R1: Reinforced LLMs Bring Human-Like Reasoning to Traffic Signal Control Systems*. 2025. arXiv: 2508.02344 [cs.AI]. URL: https://arxiv.org/abs/2508.02344.

```
### Step 1:  Analysis
The traffic congestion is primarily dictated by early queued vehicles,
with the most significant impact.  Therefore, we should pay the most
attention to lanes with long queue lengths.

Looking at the current state of the intersection, there are no early
queued vehicles in the eastern and western through lanes, northern and
southern through lanes, eastern and western left-turn lanes, and northern
and southern left-turn lanes.

However, there are approaching vehicles in different segments of the
allowed lanes of each signal.  The eastern and western through lanes have
a total of 4 approaching vehicles, with 1 in the eastern and 3 in the
western.  The northern and southern through lanes have a total of 1
approaching vehicle, all in the northern.  The eastern and western
left-turn lanes have a total of 1 approaching vehicle, all in the
western.  The northern and southern left-turn lanes have no approaching
vehicles.

Considering the neighbor incoming totals, we see that the eastern and
western through lanes, northern and southern through lanes, eastern and
western left-turn lanes, and northern and southern left-turn lanes all
have 3 known totals of neighbor incoming vehicles, with 2/2 available.

Given these conditions, the most effective traffic signal that will most
significantly improve the traffic condition during the next phase would
be the one that relieves the lanes with the most approaching vehicles, as
they are likely to reach the intersection soon.

### Step 2:  Answer
Based on the analysis, the signal that will most significantly improve
the traffic condition during the next phase is the one that relieves the
eastern and western through lanes, as it has the most approaching
vehicles.

<signal>ETWT</signal>
```

Figure 2: Representative *DGLight* reasoning trace for a single traffic state.

A Appendix

A.0.1 Reinforcement Learning Overview. Reinforcement learning (RL) models sequential decision making as a Markov decision process (MDP) $(\mathcal{S}, \mathcal{A}, p, r, \gamma)$. At each time step t, the agent observes a state $s_t \in \mathcal{S}$, selects an action $a_t \in \mathcal{A}$ according to a policy $\pi_\theta(a_t \mid s_t)$, receives a scalar reward $r_t = r(s_t, a_t)$, and the environment transitions to $s_{t+1} \sim p(\cdot \mid s_t, a_t)$. The objective is to find policy parameters θ that maximize the expected discounted return

$$J(\theta) = \mathbb{E}_{\pi_\theta}\left[\sum_{t=0}^{\infty} \gamma^t r_t\right],$$

where $\gamma \in (0, 1]$ is the discount factor. For a fixed policy π, the state-value function and action-value function are

$$V^\pi(s) = \mathbb{E}_\pi\big[\sum_{t=0}^{\infty} \gamma^t r_t \mid s_0 = s\big], \qquad Q^\pi(s, a) = \mathbb{E}_\pi\big[\sum_{t=0}^{\infty} \gamma^t r_t \mid s_0 = s, a_0 = a\big],$$

and they satisfy the Bellman expectation equation

$$V^\pi(s) = \sum_a \pi(a \mid s) \sum_{s'} p(s' \mid s, a)\big[r(s, a) + \gamma V^\pi(s')\big].$$

The advantage function is defined as

$$A^\pi(s, a) = Q^\pi(s, a) - V^\pi(s),$$

and measures how much better action a is compared to the average action at state s.

Policy gradient principle. For differentiable policies $\pi_\theta(a \mid s)$, the policy gradient theorem gives

$$\nabla_\theta J(\theta) = \mathbb{E}_{s \sim d^\pi, a \sim \pi_\theta}\big[\nabla_\theta \log \pi_\theta(a \mid s)\, Q^\pi(s, a)\big],$$

and in practice $Q^\pi(s, a)$ is replaced by an advantage estimate $\hat{A}_t$, leading to the classic REINFORCE-style update

$$\theta \leftarrow \theta + \alpha\, \hat{A}_t\, \nabla_\theta \log \pi_\theta(a_t \mid s_t).$$

Most modern RL methods (PPO, GRPO, and their variants) can be viewed as safer or more sample-efficient ways of performing this update.

Proximal Policy Optimization (PPO). PPO [11] stabilizes policy gradients by preventing excessively large policy updates. Let

$$r_t(\theta) = \frac{\pi_\theta(a_t \mid s_t)}{\pi_{\theta_{\text{old}}}(a_t \mid s_t)}$$

be the probability ratio between the new and the behavior policy. Let $\hat{A}_t$ be an advantage estimate (e.g., GAE). PPO maximizes the clipped surrogate objective

$$L^{\mathrm{PPO}}(\theta) = \mathbb{E}_t\Big[\min\big(r_t(\theta)\hat{A}_t,\ \mathrm{clip}(r_t(\theta), 1-\epsilon, 1+\epsilon)\hat{A}_t\big)\Big],$$

where ϵ is a small hyperparameter (e.g., 0.1 or 0.2). The $\min(\cdot)$ and the clipping together act as a trust region in probability space, so that even if $\hat{A}_t$ is large, the policy will not move too far away from $\pi_{\theta_{\mathrm{old}}}$ in a single update.

Group Relative Policy Optimization (GRPO). Recent LLM-oriented RL work observes that when many responses can be sampled for the same prompt, it is possible to estimate advantages without a separate value network. GRPO forms a group $\mathcal{G} = \{r_1, \ldots, r_N\}$ of rollouts for the same input, scores them with a reward model $R_\phi(\cdot)$, and then normalizes within the group:

$$A_i = \frac{R_\phi(r_i) - \mathrm{mean}(\mathcal{G})}{\mathrm{std}(\mathcal{G})}.$$

This gives a critic-free advantage estimate. GRPO then uses essentially the same clipped PPO-style loss

$$L^{\mathrm{GRPO}}(\theta) = \frac{1}{N}\sum_{i=1}^{N} \min\left(\frac{\pi_\theta(r_i \mid x)}{\pi_{\theta_{\mathrm{old}}}(r_i \mid x)}A_i, \mathrm{clip}\left(\frac{\pi_\theta(r_i \mid x)}{\pi_{\theta_{\mathrm{old}}}(r_i \mid x)}, 1-\epsilon, 1+\epsilon\right)A_i\right) - \lambda\, D_{\mathrm{KL}}\big(\pi_\theta \,\|\, \pi_{\mathrm{ref}}\big),$$

where the KL term keeps the updated policy close to a reference model (often the SFT model). Compared to PPO, the key differences are: (i) advantages come from groupwise normalization, not a learned value function; (ii) the method is well suited to large-batch LLM training where many samples per prompt are available.

Group-in-Group Policy Optimization (GiGPO). Very recent work on training LLM agents in multi-step environments argues that a single group-level relative advantage (as in GRPO) is not enough, because the reward can be sparse and credit assignment needs to happen both at the trajectory level and at individual steps. GiGPO [2] introduces a two-level grouping:

- at the episode level, sample multiple full trajectories for the same task and compute a macro relative advantage (similar to GRPO);
- at the step level, retroactively group actions that occurred in the same environment state (called anchor states) across different trajectories, and compute a micro relative advantage for those actions.

This yields fine-grained credit signals without introducing a value network. Conceptually, GiGPO keeps the good parts of GRPO (critic-free, low memory, PPO-like clipping) but adds an extra axis of grouping so that actions that happened at the same state can be compared directly. This is particularly attractive for long-horizon urban/traffic tasks or LLM agents, where the effect of a single bad action might only become visible many steps later.

A.0.2 Traffic Signal Control.

General overview. Traffic signal control (TSC) aims to coordinate phase sequences and durations at signalized intersections to maximize throughput and reduce congestion. Classical fixed-time methods use the Webster formula[17] to preset signal timings based on historical traffic data collected from the traffic network at different times. In contrast, the max-pressure control framework[6] computes a pressure value for each signal phase from the difference between queue lengths on opposing approaches and selects the phase with the highest pressure; this strategy can be shown to maximize network throughput. Reinforcement-learning (RL) methods model TSC as a Markov decision process in which an agent observes traffic states (for example, lane queue lengths and delays), chooses an action (phase switch) and receives a reward linked to throughput or delay reduction. CoLight[16] learns network-level cooperation by letting intersections communicate through graph attention, so signals can coordinate beyond immediate neighbors. CoSLight[10] extends this idea by learning not only the signal policy but also which intersections should collaborate at each moment, improving multi-intersection coordination under changing congestion patterns. MPLight[1] is a decentralized, pressure-aware RL variant built to run efficiently in large CityFlow[14]-style networks, using parameter sharing to keep city-scale control tractable. Despite achieving competitive performance in simulation, many RL-based controllers suffer from poor cross-city generalization and lack interpretability, motivating recent research into interpretable and generalizable TSC agents.

CityFlow environment. A key enabler for modern RL research on TSC is the availability of scalable simulators. SUMO[5], the traditional open-source traffic simulator, is often too slow for city-scale RL experiments. CityFlow[14] is a multi-agent microscopic traffic simulator designed for large-scale RL studies. It provides flexible definitions of road networks and traffic flows from both synthetic and real-world data and exposes a user-friendly API for interaction with RL agents. CityFlow's multithreaded design makes it more than twenty times faster than SUMO, enabling efficient simulation of networks with hundreds or thousands of intersections. Because of its speed and extensibility, CityFlow has become a standard environment for evaluating RL-based TSC algorithms.

***LLMLight*: Large language models as TSC agents.** The *LLMLight*[4] framework treats traffic signal control as a partially observable Markov game and leverages large language models (LLMs) to serve as decision-making agents. At each signal switch, an agent collects observation features such as the number of queuing vehicles and approaching vehicles on each incoming lane, augments this information with a traffic scenario description, a task description and a commonsense knowledge prompt that encourages the agent to prioritize long queues, and feeds the combined text to an LLM. The LLM performs chain-of-thought reasoning to decide which phase to activate and provides a human-readable rationale. *LLMLight* constructs a specialized backbone model called LightGPT via imitation fine-tuning on GPT-4 trajectories and critic-guided policy refinement. During imitation, the model minimizes the negative log-likelihood

$$\mathcal{L}_{\text{NLL}} = -\sum_{t=1}^{T} \log p_\theta\big(y_t \mid y_{<t}, \pi, \mathcal{P}\big),$$

where π is the prompt consisting of observation and commonsense instructions and $\mathcal{P}$ denotes the reasoning trajectory. A critic model derived from an action-value network evaluates sampled trajectories, and a ranking-based loss steers the model toward trajectories with higher long-term rewards. Experimental results show that *LLMLight* with LightGPT achieves competitive or superior performance and provides better interpretability compared with traditional RL baselines across diverse traffic scenarios. It provides a reproducible workflow that integrates CityFlow with RL-based fine-tuning of LLMs (though implemented in TensorFlow) and datasets ready for use.

***Traffic-R1*: Reinforced LLMs for human-like TSC.** *Traffic-R1*[20] is a 3B foundation model trained to perform traffic signal control with human-like reasoning. It adopts a two-stage reinforcement-learning fine-tuning paradigm: an offline stage aligns the model with question-answer (QA) samples (generated by DeepSeek-R1 and verified by human experts), and an online stage allows self-exploration in simulation to refine the policy via reward feedback. The reward is calculated from the cumulative queuing time after multiple steps, and each step only half of the agents are activated, whose decisions are propagated to neighboring agents as an input. This mimics an asynchronous communication network allows multiple agents to coordinate across intersections. Benchmark results report that *Traffic-R1* offers zero-shot generalization to unseen road networks and out-of-distribution incidents, outperforming both classical heuristics and RL controllers. When deployed in production, *Traffic-R1* manages signals affecting more than 55,000 drivers each day, reducing average queue lengths by over 5% and significantly lowering operator workload. Though without a codebase, *Traffic-R1* provides insights into using SOTA RL algorithms like GRPO to train TSC agents, as well as the innovative idea of mimicking the real world scenario with a asynchronous mult-agent setup.

A.0.3 Joint-Scored GRPO Comparison Variant. This appendix summarizes the *Joint-Scored GRPO* pipeline used as a comparison variant to the proposed *QGuided-GRPO* method. The purpose of this variant is to test whether indirect short-horizon joint return estimation can provide a better training signal than direct critic guidance. Unlike the main method, it does not rely on a pretrained action-value critic to score each sampled response directly.

Snapshot-forked joint candidate evaluation. At each decision step, the policy samples k candidate responses for every intersection and parses them into actions. Instead of scoring each sampled action independently, the method aligns candidates across intersections into k joint action vectors and evaluates each vector by forking the current simulator snapshot. Each fork starts from the same environment state but executes a different sampled joint action, allowing the method to compare candidate action sets under a common traffic condition.

Short-horizon discounted return. For each forked candidate c, the simulator is rolled out for a short horizon H. After the first jointly sampled action is executed, subsequent actions are resampled from the current policy at later steps. The candidate

score is the discounted return

$$G_t^{(c)} = \sum_{\tau=0}^{H-1} \gamma^\tau r_{t+\tau}^{(c)},$$

where γ is the discount factor and $r_{t+\tau}^{(c)}$ is the congestion-based network reward observed at rollout step $t+\tau$ in candidate fork c.

Local, neighborhood, and global reward mixing. The per-step reward is computed from a mixed congestion cost that combines local intersection congestion, neighboring congestion, and global network congestion. Let m_i denote the local congestion metric at intersection i (for example, incoming queue length or pressure), let $\bar{m}_{\mathcal{N}(i)}$ denote the mean metric over the neighbors of i, and let $\bar{m}_{\mathcal{V}}$ denote the mean metric over the whole network. The reward is defined from the negative mixed cost

$$r_t = -\frac{1}{|\mathcal{V}|} \sum_{i \in \mathcal{V}} \Big(\alpha m_i + \beta \bar{m}_{\mathcal{N}(i)} + (1-\alpha-\beta)\bar{m}_{\mathcal{V}} \Big),$$

where α and β control the relative contribution of local and neighborhood congestion. This construction encourages decisions that reduce both immediate local congestion and broader network imbalance.

Projection back to per-intersection action scores. Because GRPO training still expects prompt-level rewards for individual sampled responses, the joint candidate returns must be projected back to action-level scores. For each intersection i and each action $a \in A$, let $\mathcal{C}_{i,a}$ be the set of joint candidates whose parsed action at intersection i equals a. The induced action score is defined as the mean return of those candidates:

$$\tilde{Q}_{i,t}(a) = \frac{1}{|\mathcal{C}_{i,a}|} \sum_{c \in \mathcal{C}_{i,a}} G_t^{(c)},$$

with a fallback reward used when no sampled candidate proposes action a. The resulting vector $\tilde{\mathbf{q}}_{i,t}$ plays the same role in GRPO training as the critic score vector $\mathbf{q}_{i,t}$ in the main method, but it is obtained indirectly through joint rollout evaluation.

Collect-then-train split. In implementation, the variant is organized as a collect-then-train pipeline. A rollout stage first saves prompt records, selected actions, and projected action-score vectors obtained from snapshot-forked candidate evaluation. The GRPO stage then reloads these records and fine-tunes the LLM policy using the same prompt-conditioned reward lookup mechanism as in the main method. This design isolates the additional cost of joint candidate evaluation from the policy optimization stage and makes it suitable for controlled comparison against *QGuided-GRPO*.

A.0.4 Sample Prompt. You are an expert in traffic management.

A traffic light regulates a four-way intersection with northern, southern, eastern, and western approaches, each containing two lanes: one for through traffic and one for left-turns. Each lane is further divided into three segments. Segment 1 is the closest to the

intersection. Segment 2 is in the middle. Segment 3 is the farthest. In a lane, there may be early queued vehicles and approaching vehicles traveling in different segments. Early queued vehicles have already arrived at the intersection and await passage permission. Approaching vehicles will arrive at the intersection in the future.

The traffic light has 4 signal phases. Each signal relieves vehicles' flow in a group of two specific lanes.

Available signal phases: - ETWT: Eastern and western through lanes. - NTST: Northern and southern through lanes. - ELWL: Eastern and western left-turn lanes. - NLSL: Northern and southern left-turn lanes.

Current intersection state: Signal: ETWT Relieves: Eastern and western through lanes. - Early queued: 0 (East), 1 (West), 1 (Total) - Segment 1: 0 (East), 0 (West), 0 (Total) - Segment 2: 1 (East), 0 (West), 1 (Total) - Segment 3: 0 (East), 2 (West), 2 (Total) - Neighbor incoming totals: 2 (East), 1 (West), 3 (Known total), 2/2 available

Signal: NTST Relieves: Northern and southern through lanes. - Early queued: 0 (North), 0 (South), 0 (Total) - Segment 1: 0 (North), 0 (South), 0 (Total) - Segment 2: 0 (North), 0 (South), 0 (Total) - Segment 3: 1 (North), 0 (South), 1 (Total) - Neighbor incoming totals: NA (North), 3 (South), 3 (Known total), 1/2 available

Signal: ELWL Relieves: Eastern and western left-turn lanes. - Early queued: 0 (East), 0 (West), 0 (Total) - Segment 1: 0 (East), 0 (West), 0 (Total) - Segment 2: 0 (East), 0 (West), 0 (Total) - Segment 3: 0 (East), 1 (West), 1 (Total) - Neighbor incoming totals: 2 (East), 1 (West), 3 (Known total), 2/2 available

Signal: NLSL Relieves: Northern and southern left-turn lanes. - Early queued: 0 (North), 0 (South), 0 (Total) - Segment 1: 0 (North), 0 (South), 0 (Total) - Segment 2: 0 (North), 0 (South), 0 (Total) - Segment 3: 0 (North), 0 (South), 0 (Total) - Neighbor incoming totals: NA (North), 3 (South), 3 (Known total), 1/2 available

The state description above lists: - The group of lanes relieved under each traffic light phase. - The number of early queued vehicles in the allowed lanes of each signal. - The number of approaching vehicles in different segments of the allowed lanes of each signal. - Neighbor incoming totals from adjacent intersections for each phase. - 'NA' means that adjacent side has a virtual/missing neighbor and is excluded from 'Known total'.

Question: Which is the most effective traffic signal that will most significantly improve the traffic condition during the next phase?

Note: - Traffic congestion is primarily dictated by early queued vehicles, with the most significant impact. - You must pay the most attention to lanes with long queue lengths. - It is not urgent to consider vehicles in distant segments, since they are unlikely to reach the intersection soon.

Requirements: - Think step by step. - You can only choose one of the signals listed above. - Step 1: Provide a brief analysis identifying the optimal traffic signal. - Step 2: After finishing the analysis, answer with your chosen signal. - Include exactly one final decision tag in this format: <signal>PHASE</signal>, where PHASE is one of: ETWT, NTST, ELWL, NLSL.