



## MYR7

### TP70/P5 DIP SWITCHES SETTING : 1(002/Pulse)

Supported bill MYR 1、2、5、10、20、50、100 ( Malaysia )

| DIP1 Function                            | SW1 | SW2 | SW3 | SW4 | SW5 | SW6 | SW7 | SW8 | SW9 | SW10 |
|------------------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| ★ 1 Pulse / MYR 1                        | OFF | OFF | OFF |     |     |     |     |     |     |      |
| 2 Pulse / MYR 1                          | OFF | OFF | ON  |     |     |     |     |     |     |      |
| 3 Pulse / MYR 1                          | OFF | ON  | OFF |     |     |     |     |     |     |      |
| 4 Pulse / MYR 1                          | OFF | ON  | ON  |     |     |     |     |     |     |      |
| 5 Pulse / MYR 1                          | ON  | OFF | OFF |     |     |     |     |     |     |      |
| 10 Pulse / MYR 1                         | ON  | OFF | ON  |     |     |     |     |     |     |      |
| 20 Pulse / MYR 1                         | ON  | ON  | OFF |     |     |     |     |     |     |      |
| 100 Pulse / MYR 1                        | ON  | ON  | ON  |     |     |     |     |     |     |      |
| Fast Output Pulse Lo= 50ms<br>Hi=100ms   |     |     |     | ON  |     |     |     |     |     |      |
| ★ Slow Output Pulse Lo= 50ms<br>Hi=300ms |     |     |     | OFF |     |     |     |     |     |      |
| Inhibit level Active Low                 |     |     |     |     | ON  |     |     |     |     |      |
| ★ Inhibit level Active High              |     |     |     |     | OFF |     |     |     |     |      |
| ★ Accept MYR 1 & 2                       |     |     |     |     |     | ON  |     |     |     |      |
| Reject MYR 1 & 2                         |     |     |     |     |     | OFF |     |     |     |      |
| ★ Accept MYR 5                           |     |     |     |     |     |     | ON  |     |     |      |
| Reject MYR 5                             |     |     |     |     |     |     | OFF |     |     |      |
| ★ Accept MYR 10                          |     |     |     |     |     |     |     | ON  |     |      |
| Reject MYR 10                            |     |     |     |     |     |     |     | OFF |     |      |
| ★ Accept MYR 20                          |     |     |     |     |     |     |     |     | ON  |      |
| Reject MYR 20                            |     |     |     |     |     |     |     |     | OFF |      |
| ★ Accept MYR 50 &100                     |     |     |     |     |     |     |     |     |     | ON   |
| Reject MYR 50 &100                       |     |     |     |     |     |     |     |     |     | OFF  |

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip Switch 1 to 5 are only for Pulse mode.

### DIP SWITCHS SETTING : 2

| DIP2 FUNCTION       | SW1 | SW2 | SW3 | SW4 |
|---------------------|-----|-----|-----|-----|
| ★ Pulse Normal High | ON  |     |     |     |
| Pulse Normal Low    | OFF |     |     |     |
| ★ Pulse Protocol    |     | ON  |     |     |
| RS232 Protocol      |     | OFF |     |     |
| Harness Disable     |     |     | ON  |     |
| ★ Harness Enable    |     |     | OFF |     |
| Manufacture Default |     |     |     | ON  |
| ★ System Default    |     |     |     | OFF |

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch

(2) Dip Switches 1 & 3 are only used for pulse protocol.

### Currency Assign Data

| Interface<br>Bill value | RS232 | Pulse |
|-------------------------|-------|-------|
| BV1                     | 1     | 1     |
| BV2                     | 2     | 2     |
| BV3                     | 5     | 5     |
| BV4                     | 10    | 10    |
| BV5                     | 50    | 50    |
| BV6                     | 100   | 100   |
| BV7                     | 20    | 20    |