

Ex. 1

A114290048

2026-09-29

```
print(uuid::UUIDgenerate())
```

```
## [1] "ea2dae35-93f3-43f0-8195-533ae903bc1a"
```

q1

```
1+1
```

```
## [1] 2
```

q2

```
3*4
```

```
## [1] 12
```

q3

```
set.seed(2026)

# Draw a sample of 10 students from 1 to 55
student_sample <- sample(1:55, size = 10)

# Calculate the mean of the sampled student numbers
sample_mean <- mean(student_sample)

# View the sample and the result
student_sample
```

```
## [1] 29 33 38 45 47 27 44 36 5 31
```

```
sample_mean
```

```
## [1] 33.5
```

q4

```
#
variables_df <- data.frame(
  Question = 1:4,
  Variable_Name = c(
    "1. Blood type of a patient",
    "2. Number of customers served in a day",
    "3. Ranking of a restaurant (5-star scale)",
    "4. Monthly rent of an apartment in New Taipei City"
  ),
  Variable_Type = c(
    "Qualitative",
    "Quantitative (Discrete)",
    "Qualitative",
    "Quantitative (Continuous)"
  ),
  Level_of_Measurement = c(
    "Nominal",
    "Ratio",
    "Ordinal",
    "Ratio"
  )
)

#
print(variables_df)
```

##	Question	Variable_Name
## 1	1	1. Blood type of a patient
## 2	2	2. Number of customers served in a day
## 3	3	3. Ranking of a restaurant (5-star scale)
## 4	4	4. Monthly rent of an apartment in New Taipei City
##	Variable_Type	Level_of_Measurement
## 1	Qualitative	Nominal
## 2	Quantitative (Discrete)	Ratio
## 3	Qualitative	Ordinal
## 4	Quantitative (Continuous)	Ratio

Note that the `echo = FALSE` parameter was added to the code chunk to prevent printing of the R code that generated the plot.