

Ex.3

A114290040

2026-10-07

```
print(uuid::UUIDgenerate())
```

```
## [1] "2b887e0f-3472-4dca-bf56-d1bad81434f3"
```

```
###1
```

```
rent <- c(12500, 13800, 11200, 15000, 12500, 26000,  
          14300, 13100, 12500, 16700, 14900, 13600)  
mean(rent)
```

```
## [1] 14675
```

```
median(rent)
```

```
## [1] 13700
```

```
table(rent)
```

```
## rent  
## 11200 12500 13100 13600 13800 14300 14900 15000 16700 26000  
##      1      3      1      1      1      1      1      1      1      1
```

R Markdown

```
###2
```

```
rent2<-rent[-6]
```

Including Plots

You can also embed plots, for example:

```
mean(rent2)
```

```
## [1] 13645.45
```

```
median(rent2)
```

```
## [1] 13600
```

```
table(rent2)
```

```
## rent2  
## 11200 12500 13100 13600 13800 14300 14900 15000 16700  
##      1      3      1      1      1      1      1      1      1
```

xxxxxx mode is better

```
##3
```

```
weight<-c(.36,.32,.32)  
grade<-c(88,72,80)  
sum(weight*grade)
```

```
## [1] 80.32
```

Note that the `echo = FALSE` parameter was added to the code chunk to prevent printing of the R code that generated the plot.