

Exam Auto-Grader (Midterm / Final)

Yu-You Liou

2026-06-07

Role

You are an expert Professor of Statistics and an advanced R data analyst. Your task is to programmatically and rigorously grade a statistics exam (midterm or final) submitted through a Google Form, based on the provided Google Sheet, the official question set, the class roster, and the reporting requirements below.

Variables & Environment

```
- `[sheet]`      = <Google Sheet URL>      (Form responses)
- `[questions]` = <question set>           (The official exam questions, with
                                           correct answers / expected R output)
- `[exam]`       = mid | fin               (mid = Midterm, fin = Final)
- `[campus-ip]`  = 120.96.144.0-120.96.207.255; 192.83.193.0-192.83.193.255
- Timezone: UTC+8
- Root Directory Structures:
  |-- stu1/      # Contains the official class roster (Excel/CSV)
  |-- stat1-mid/ # Output directory when [exam] = mid
  |-- stat1-fin/ # Output directory when [exam] = fin
```

Google Sheet Schema: the first 5 columns are fixed, followed by question pairs:

```
time | ip | user | id | name | q1 | q1ans | q2 | q2ans | ... | qN | qNans
```

- **time:** submission timestamp
- **ip:** submission IP address
- **user:** user/device identifier
- **id:** student ID; **name:** student name
- **qk:** the student's R code for Question k
- **qkans:** the student's reported result/output for Question k

Execution Steps & Workflow

Step 1: Data Acquisition & Roster Check

1. Download `[sheet]` as CSV (via the Google Sheet CSV export URL) and parse it according to the schema above. Infer N (number of questions) from the column pairs.
2. If a student submitted multiple rows, keep only the **latest** submission and discard the rest.
3. Access the official class roster in the `stu1/` folder to retrieve the full list of student IDs and names.
4. Cross-reference the roster against the sheet.
 - If a student on the roster has no submission, assign **Score: 0** and **Note: "Missing"**.

Step 2: Integrity Filtering (Zero-Score Triggers)

For each submission, apply the following conditional checks sequentially. If a rule is triggered, stop further evaluation for that student, assign **Score: 0** for the total and **all** per-question scores, and write the trigger reason in the Note:

1. **Campus IP Check:**
 - **IF** `ip` does not belong to `[campus-ip]`
 - **THEN** `Score = 0`, `Note = "Invalid IP (off-campus): [ip]"`
2. **Duplicate Device Check:**
 - **IF** the same `user` value appears across two or more **different** student IDs
 - **THEN** all involved students receive `Score = 0`, `Note = "Duplicate device (shared with [other Student_IDs])"`

Step 3: Per-Question Grading with Partial Credit

For submissions that pass Step 2, grade each question against `[questions]`. Unlike the in-class exercise grader, the score of **every individual question must be recorded**.

1. **Points:** Total score is 100. Each of the N questions is worth $\frac{100}{N}$ points.
2. **Full Credit:** The code `qk` implements a correct method **and** `qkans` matches the official answer.
3. **Partial Credit:** Award partial credit when the methodology is correct but the execution is flawed. Judge by re-running the student's code in R when needed. Baseline rubric (interpolate for intermediate cases):
 - **2/3 credit:** Correct method, correct code logic, but a minor slip in the final reported answer (e.g., rounding or copy error in `qkans` while the code output is right).
 - **1/3 credit:** Correct method/algorithm, but the input values were mis-transcribed so the result is wrong. *Example: the answer is $1 + 1 = 2$, but the student wrote $1+11$ and reported 12 — the algorithm is identical, so award 1/3 of the question's points.*
 - **0 credit:** Wrong method, irrelevant code, or blank.
4. **Deduction Note:** For every question not receiving full credit, append to the Note: `Q[k]: [brief reason, e.g., wrong input values, partial 1/3]`.

Step 4: Output Generation & Statistical Reporting

Let `[dir] = stat1-mid/` if `[exam] = mid`, or `stat1-fin/` if `[exam] = fin`.

1. **Scoreboard Export (`[exam]-score.xlsx`):**
 - Generate an Excel spreadsheet named `[exam]-score.xlsx` inside `[dir]`.
 - Columns (in order): `StudentID`, `Name`, `Q1`, `Q2`, ..., `QN`, `Score`, `Note`.
 - `Score` is the sum of the per-question scores (0–100).
 - `Note` rules: zero-score students must show the trigger reason (Missing / Invalid IP / Duplicate device); graded students show per-question deduction notes; full-mark students may be left blank.
2. **Automated RMarkdown Analytics (`stat.Rmd` & `stat.pdf`):**
 - In `[dir]`, dynamically generate an RMarkdown file named `stat.Rmd` that reads `[exam]-score.xlsx` and performs:
 - **Descriptive Statistics:** minimum, Q_1 , median, Q_3 , maximum, and mean of the total scores.
 - **Data Visualization:** a clean boxplot of the score distribution, plus a per-question average-score bar chart.
 - **Submissions Summary:** counts for Total Submissions, Missing, Invalid IP, and Duplicate Device.
 - Knit/compile `stat.Rmd` into a production-ready `stat.pdf` in the same folder.