











Comment	Description	Designator	Footprint	LibRef	Quantity
BS-06-B4AA002	·	BT2	BAT_CR1220	BAT_HOLDER	1
100nF	贴片电容, 25v	C1, C2, C4, C5, C7, C9, C11, C13, C14, C15, C16, C47, C51, C54, C55, C56, C57, C58, C63, C81	0402_C	Сар	20
10uF	25v, 贴片电容	C3, C6, C10, C25, C46, C50, C62, C79, C80	0603_C	Сар	9
12pF	25v	C8, C12, C52, C53	0402_C	Сар	4
47uF	贴片电容	C17	1206_C	Cap	1
1uF	25v	C78, C84	0402_C	Cap	2
HC-1.25-4PWT		CN1, CN3, CN4, CN5, CN6	SMD_4P-1.25	4P-1.25	5
HEADER_SMD_36P		CN2	HDR-SMD_40P- P2.54	HEADER_SMD_40P	1
HC-1.25-2PWT		CN7	CONN-SMD_2P- P1.25-HC-1.25- 2PWT	HC-1.25-2PWT	1
BAT54C	双肖特基二极管	D3	BAT54C215	BAT54C	1
MBR0520	肖特基二极管	D6	SOD2513X120N	SOD-123 B5819W SL	1
AT24C02_1	C688857	IC1	SOP-8	AT24C02_1	1
AMS1117-3.3	Integrated Circuit	IC2	SOT229P700X180- 4N	AMS1117-3.3	1
W25Q128JVSIQ		IC3	SOP-8	W25Q128JVSIQ	1
SP3485EN-L	Integrated Circuit	IC4	SOP-8	SP3485EN-L	1
USB_MICRO_DIP		J1, J2	MICRO_USB_5S	USB_MICRO_DIP	2
KEY-SMD-324225	KEY,SMD,324225	KEY1, KEY2, KEY3, KEY4	KEY-SOP324225	KEY-SMD-324225	4
4.7uH	电感	L5	L1008	L	1
LCD		P1	FPC0.5 2H-WS-40P	FPC40P_LCD	1
TF_Card_Holder		P2	SD-MICRO-TF	TF_Card	1
CapTouch		P5	FPC-SMD_P0.50-6P	FPC-6P	1
4.7ΚΩ	贴片电阻	R1, R2	0402_R	0402 4.7KΩ (4701) 1%	2
10K	贴片电阻	R3, R4, R5, R13, R14, R15, R36, R37, R39, R41, R42, R70	0402_R	Res	12
120R	贴片电阻	R6, R40, R43	0402_R	Res	3
OR	贴片电阻	R7, R44	0402_R	Res	2
N.C.	贴片电阻	R8, R45	0402_R	Res	2
1k	贴片电阻	R9, R10, R50, R51	0402_R	Res	4
33R	贴片电阻	R11, R12, R58, R59, R60, R61, R62, R63, R68	0402_R	Res	9
4.7K	贴片电阻	R53, R54, R55, R56, R57	0402_R	Res	5
5R	贴片电阻	R69	0603_R	Res	1
MP3302DJ	LCD背光IC	U1	SOT-23-5	MP3302	1
STM32H750IBK6_CO RE		U2	CORE	STM32H750IBK6_CO RE	1
TJA1051T	TJA1044GT,SO- 8,NXP,	U3, U5	SOP-8	TJA1044T	2
UT3232G-P16-R		U6	TSSOP-16	UT3232G-P16-R	1
CH340E		U_CH1	MSOP-10	CH340E	1