

Graph Contrastive Learning Automated

Yuning You¹, Tianlong Chen², Yang Shen¹, Zhangyang Wang²


¹Texas A&M University, ²University of Texas at Austin



TEXAS
The University of Texas at Austin


Background

➤ Data-structure of graphs




LoGaG cover

➤ Graph networks



GCN, ICLR'17




GAT, ICLR'18

➤ Self-supervised learning: Warming-up models with **unlabeled data**

Background

➤ Self-supervision on graphs

❖ Predictive task



E.g. Graph completion, ICML'20


AutoSSL, arXiv'21

❖ Contrastive learning

- **GraphCL**, NeurIPS'20
- **Augmentations** + perturbation invariance

Self-Supervised Learning of Graph Neural Networks: A Unified Review


Yaochen Xie, Zhao Xu, Jingtun Zhang, Zhengyang Wang, Shuiwang Ji, *Senior Member, IEEE*



Background

➤ Augmentation is crucial in GraphCL

Data augmentation	Type	Underlying Prior
Node dropping	Nodes, edges	Vertex missing does not alter semantics.
Edge perturbation	Edges	Semantic robustness against connectivity variations.
Attribute masking	Nodes	Semantic robustness against losing partial attributes.
Subgraph	Nodes, edges	Local structure can hint the full semantics.



➤ Reason: challenge of **heterogeneous** nature of graph data



Fig 1. Social networks




Fig 2. Polymers






Fig 3. Power grids

Background


➤ Data heterogeneity



➤ Ad-hoc choices of augmentations in GraphCL

Data augmentation	Type	Underlying Prior
Node dropping	Nodes, edges	Vertex missing does not alter semantics.
Edge perturbation	Edges	Semantic robustness against connectivity variations.
Attribute masking	Nodes	Semantic robustness against losing partial attributes.
Subgraph	Nodes, edges	Local structure can hint the full semantics.

➤ Rules derived from tedious tuning



➤ Question: Can we be more principled and automated?


Contributions

- Given a new and unseen graph dataset, can GraphCL **automatically select augmentations**, avoiding ad-hoc choices or tedious tuning?
- Joint augmentation optimization (JOAO)
 - ❖ A **principled** bi-level optimization framework
 - ❖ **Automatic**, free of human labor of trial-and-error
 - ❖ Adaptive, generalizing smoothly to handling diverse graph data
 - ❖ Dynamic, allowing for augmentation types varying at different steps

Method. JOAO

➤ GraphCL

❖ Enforcing perturbation invariance



Data augmentation	Type	Underlying Prior
Node dropping	Nodes, edges	Vertex missing does not alter semantics.
Edge perturbation	Edges	Semantic robustness against connectivity variations.
Attribute masking	Nodes	Semantic robustness against losing partial attributes.
Subgraph	Nodes, edges	Local structure can hint the full semantics.

$$\begin{aligned}
 & \min_{\theta} \mathcal{L}(G, A_1, A_2, \theta) \\
 &= \min_{\theta} \left\{ \underbrace{\left(-\mathbb{E}_{\mathbb{P}_G \times \mathbb{P}_{(A_1, A_2)}} \text{sim}(\mathcal{T}_{\theta,1}(G), \mathcal{T}_{\theta,2}(G)) \right)}_{\text{Positive pairs}} \right. \\
 & \quad \left. + \underbrace{\mathbb{E}_{\mathbb{P}_G \times \mathbb{P}_{A_1}} \log(\mathbb{E}_{\mathbb{P}_{G'} \times \mathbb{P}_{A_2}} \exp(\text{sim}(\mathcal{T}_{\theta,1}(G), \mathcal{T}_{\theta,2}(G'))))}_{\text{Negative pairs}} \right\}, \quad (1)
 \end{aligned}$$

➤ The unified framework, joint augmentation optimization (**JOAO**) as a bi-level optimization

$$\begin{aligned}
 & \min_{\theta} \mathcal{L}(G, A_1, A_2, \theta), \\
 & \text{s.t. } \boxed{\mathbb{P}_{(A_1, A_2)}} \in \arg \min_{\mathbb{P}_{(A'_1, A'_2)}} \mathcal{D}(G, A'_1, A'_2, \theta), \quad (2)
 \end{aligned}$$

Method. Instantiation of JOAO

- A min-max optimization instantiation

$$\begin{aligned} \min_{\theta} \quad & \mathcal{L}(G, A_1, A_2, \theta), \\ \text{s.t.} \quad & \mathbb{P}_{(A_1, A_2)} \in \arg \max_{\mathbb{P}_{(A'_1, A'_2)}} \left\{ \mathcal{L}(G, A'_1, A'_2, \theta) \right. \\ & \left. - \frac{\gamma}{2} \text{dist}(\mathbb{P}_{(A'_1, A'_2)}, \mathbb{P}_{\text{prior}}) \right\}, \end{aligned} \quad (3)$$

- Principles

- ❖ Exploiting **challenging** augmentations: model-based adversarial training

MBRDL, arXiv'20

- ❖ Regularization with prior

- Uniform distribution avoiding collapse
- Squared Euclidean distance

Ref 5. Wang et al., arXiv'19

- ❖ Trade-off by γ

$$\begin{aligned} \text{dist}(\mathbb{P}_{(A_1, A_2)}, \mathbb{P}_{\text{prior}}) &= \sum_{i=1}^{|\mathcal{A}|} \sum_{j=1}^{|\mathcal{A}|} (p_{ij} - \frac{1}{|\mathcal{A}|^2})^2, \\ p_{ij} &= \text{Prob}(A_1 = A^i, A_2 = A^j) \end{aligned}$$

Method. AGD for JOAO

➤ Alternating gradient descent (AGD) Wang et al., arXiv'19

- ❖ Upper-level minimization
- ❖ Lower-level maximization

$$\begin{aligned} \min_{\theta} \quad & \mathcal{L}(G, A_1, A_2, \theta), \\ \text{s.t.} \quad & \mathbb{P}_{(A_1, A_2)} \in \arg \max_{\mathbb{P}_{(A'_1, A'_2)}} \left\{ \mathcal{L}(G, A'_1, A'_2, \theta) \right. \\ & \left. - \frac{\gamma}{2} \text{dist}(\mathbb{P}_{(A'_1, A'_2)}, \mathbb{P}_{\text{prior}}) \right\}, \end{aligned} \quad (3)$$

❖ Upper-level minimization

- GraphCL optimization given sampling distribution

$$\theta^{(n)} = \theta^{(n-1)} - \alpha' \nabla_{\theta} \mathcal{L}(G, A_1, A_2, \theta), \quad (4)$$

where $\alpha' \in \mathcal{R}_{>0}$ is the learning rate.

Method. AGD for JOAO

- ❖ Lower-level maximization
 - Gradient is not intuitive
 - Analytical rewrite

$$\begin{aligned} \mathcal{L}(G, A_1, A_2, \theta) = & \sum_{i=1}^{|\mathcal{A}|} \sum_{j=1}^{|\mathcal{A}|} \underbrace{p_{ij}}^{\text{Targeted}} \left\{ -\mathbb{E}_{\mathbb{P}_G} \text{sim}(T_{\theta}^i(G), T_{\theta}^j(G)) \right. \\ & \left. + \mathbb{E}_{\mathbb{P}_G} \log \left(\sum_{j'=1}^{|\mathcal{A}|} \underbrace{p_{j'}}_{\text{Undesired}} \mathbb{E}_{\mathbb{P}_{G'}} \exp(\text{sim}(T_{\theta}^i(G), T_{\theta}^{j'}(G'))) \right) \right\}, \end{aligned} \quad (5)$$

$$\begin{aligned} \min_{\theta} \quad & \mathcal{L}(G, A_1, A_2, \theta), \\ \text{s.t.} \quad & \mathbb{P}_{(A_1, A_2)} \in \arg \max_{\mathbb{P}_{(A'_1, A'_2)}} \left\{ \mathcal{L}(G, A'_1, A'_2, \theta) \right. \\ & \left. - \frac{\gamma}{2} \text{dist}(\mathbb{P}_{(A'_1, A'_2)}, \mathbb{P}_{\text{prior}}) \right\}, \end{aligned} \quad (3)$$

- Undesired marginal probability $p_{j'}$ entangled in negative term

Method. AGD for JOAO

- A lower-bound approximation to decouple p_j ,

$$\begin{aligned} & \mathbb{E}_{\mathbb{P}_G \times \mathbb{P}_{A_1}} \log(\mathbb{E}_{\mathbb{P}_{G'} \times \mathbb{P}_{A_2}} \exp(\text{sim}(T_{\theta,1}(G), T_{\theta,2}(G')))) \\ & \geq \mathbb{E}_{\mathbb{P}_G \times \mathbb{P}_{A_1} \times \mathbb{P}_{A_2}} \log(\mathbb{E}_{\mathbb{P}_{G'}} \exp(\text{sim}(T_{\theta,1}(G), T_{\theta,2}(G')))) \\ & \approx \mathbb{E}_{\mathbb{P}_G \times \mathbb{P}_{(A_1, A_1)}} \log(\mathbb{E}_{\mathbb{P}_{G'}} \exp(\text{sim}(T_{\theta,1}(G), T_{\theta,2}(G')))), \end{aligned} \quad (6)$$

$$\begin{aligned} & \min_{\theta} \quad \mathcal{L}(G, A_1, A_2, \theta), \\ & \text{s.t.} \quad \mathbb{P}_{(A_1, A_2)} \in \arg \max_{\mathbb{P}_{(A'_1, A'_2)}} \left\{ \mathcal{L}(G, A'_1, A'_2, \theta) \right. \\ & \quad \left. - \frac{\gamma}{2} \text{dist}(\mathbb{P}_{(A'_1, A'_2)}, \mathbb{P}_{\text{prior}}) \right\}, \end{aligned} \quad (3)$$

- Approximated contrastive loss:

$$\begin{aligned} \mathcal{L}(G, A_1, A_2, \theta) & \approx \sum_{i=1}^{|\mathcal{A}|} \sum_{j=1}^{|\mathcal{A}|} \overbrace{p_{ij}}^{\text{Targeted}} \ell(G, A^i, A^j, \theta) \\ & = \sum_{i=1}^{|\mathcal{A}|} \sum_{j=1}^{|\mathcal{A}|} p_{ij} \left\{ -\mathbb{E}_{\mathbb{P}_G} \text{sim}(T_{\theta}^i(G), T_{\theta}^j(G)) \right. \\ & \quad \left. + \mathbb{E}_{\mathbb{P}_G} \log(\mathbb{E}_{\mathbb{P}_{G'}} \exp(\text{sim}(T_{\theta}^i(G), T_{\theta}^j(G')))) \right\}. \end{aligned} \quad (7)$$

Method. AGD for JOAO

- Rewrote lower-level optimization

$$\begin{aligned} \mathbb{P}_{(A_1, A_2)} &\in \arg \max_{\mathbf{p} \in \mathcal{P}, \mathbf{p}=[p_{ij}], i,j=1,\dots,|\mathcal{A}|} \{\psi(\mathbf{p})\}, \\ \psi(\mathbf{p}) &= \sum_{i=1}^{|\mathcal{A}|} \sum_{j=1}^{|\mathcal{A}|} p_{ij} \ell(G, A^i, A^j, \theta) - \frac{\gamma}{2} \sum_{i=1}^{|\mathcal{A}|} \sum_{j=1}^{|\mathcal{A}|} (p_{ij} - \frac{1}{|\mathcal{A}|^2})^2, \end{aligned} \quad (8)$$


- Projected gradient descent Boyd et al., 2004

$$\mathbf{b} = \mathbf{p}^{(n-1)} + \alpha'' \nabla_{\mathbf{p}} \psi(\mathbf{p}^{(n-1)}), \mathbf{p}^{(n)} = (\mathbf{b} - \mu \mathbf{1})_+, \quad (9)$$

where $\alpha'' \in \mathcal{R}_{>0}$ is the learning rate, μ is the root of the equation $\mathbf{1}^T(\mathbf{b} - \mu \mathbf{1}) = 1$, and $(\cdot)_+$ is the element-wise non-negative operator. μ can be efficiently found via the bi-section method.

$$\begin{aligned} \min_{\theta} \quad & \mathcal{L}(G, A_1, A_2, \theta), \\ \text{s.t.} \quad & \mathbb{P}_{(A_1, A_2)} \in \arg \max_{\mathbb{P}_{(A'_1, A'_2)}} \left\{ \mathcal{L}(G, A'_1, A'_2, \theta) \right. \\ & \left. - \frac{\gamma}{2} \text{dist}(\mathbb{P}_{(A'_1, A'_2)}, \mathbb{P}_{\text{prior}}) \right\}, \end{aligned} \quad (3)$$


❖ Empirical convergence



Method. JOAO Sanity Check

➤ Are JOAO selected augmentation reasonable?

❖ Selections
align with
“best practices”




Method. JOAOv2 Addressing Distortion

- JOAO selects automatic, adaptive and dynamic augmentations
- However, more diverse, aggressive and challenging
- Potentially **distorting** training distribution

SLA+AG, ICML'20
DistAug, ICML'20

Datasets	A.S.	JOAO	JOAOv2
NCI1	0.2	61.77±1.61	62.52±1.16
	0.25	60.95±0.55	61.67±0.72
PROTEINS	0.2	71.45±0.89	71.66±1.10
	0.25	71.61±1.65	73.01±1.02

- JOAOv2 = JOAO + augmentation-aware multi-projection heads



$$\begin{aligned}
 & \min_{\theta} \quad \mathcal{L}_{v2}(G, A_1, A_2, \theta', \Theta_1'', \Theta_2''), \\
 & \text{s.t.} \quad \mathbb{P}_{(A_1, A_2)} \in \arg \max_{\mathbb{P}_{(A'_1, A'_2)}} \left\{ \mathcal{L}_{v2}(G, A_1, A_2, \theta', \Theta_1'', \Theta_2'') \right. \\
 & \quad \quad \quad \left. - \frac{\gamma}{2} \text{dist}(\mathbb{P}_{(A'_1, A'_2)}, \mathbb{P}_{\text{prior}}) \right\}, \\
 & \quad \quad \quad \boxed{\mathbb{P}_{(g_{\theta_1''}, g_{\theta_2''})}} = \mathbb{P}_{(A_1, A_2)}. \tag{10}
 \end{aligned}$$

Experiments & Discussions

➤ Settings

- ❖ Semi-supervised
- ❖ Unsupervised
- ❖ Transfer

➤ Competitors

- ❖ Heuristic designed pretexts
- ❖ GraphCL with rules

➤ Datasets

- ❖ Across diverse fields
- ❖ On bioinformatics domains

➤ **Summary** of JOAO performance

	v.s. GraphCL	v.s. Heuristic methods
Across diverse fields	Comparable	Better
On specific domains	Better	Worse

Experiments & Discussions. Across Diverse Datasets

- JOAO performs on par with ad-hoc rules

- Augmentation-aware projection heads strengths JOAO

Semi-supervised learning

L.R.	Methods	NCI1	PROTEINS	DD	COLLAB	RDT-B	RDT-M5K	GITHUB	A.R.↓
1%	No pre-train.	60.72±0.45	-	-	57.46±0.25	-	-	54.25±0.22	7.6
	Augmentations	60.49±0.46	-	-	58.40±0.97	-	-	56.36±0.42	6.6
	GAE	61.63±0.84	-	-	63.20±0.67	-	-	59.44±0.44	4.0
	Infomax	62.72 ±0.65	-	-	61.70±0.77	-	-	58.99±0.50	3.3
	ContextPred	61.21±0.77	-	-	57.60±2.07	-	-	56.20±0.49	6.6
	GraphCL	62.55 ±0.86	-	-	64.57 ±1.15	-	-	58.56±0.59	2.6
	JOAO	61.97±0.72	-	-	63.71 ±0.84	-	-	60.35±0.24	3.0
	JOAOv2	62.52 ±1.16	-	-	64.51 ±2.21	-	-	61.05 ±0.31	2.0
10%	No pre-train.	73.72±0.24	70.40±1.54	73.56±0.41	73.71±0.27	86.63±0.27	51.33±0.44	60.87±0.17	7.0
	Augmentations	73.59±0.32	70.29±0.64	74.30±0.81	74.19±0.13	87.74±0.39	52.01±0.20	60.91±0.32	6.2
	GAE	74.36±0.24	70.51±0.17	74.54±0.68	75.09±0.19	87.69±0.40	53.58 ±0.13	63.89±0.52	4.5
	Infomax	74.86 ±0.26	72.27±0.40	75.78 ±0.34	73.76±0.29	88.66±0.95	53.61 ±0.31	65.21±0.88	3.0
	ContextPred	73.00±0.30	70.23±0.63	74.66±0.51	73.69±0.37	84.76±0.52	51.23±0.84	62.35±0.73	7.2
	GraphCL	74.63 ±0.25	74.17 ±0.34	76.17 ±1.37	74.23±0.21	89.11 ±0.19	52.55±0.45	65.81±0.79	2.4
	JOAO	74.48±0.27	72.13±0.92	75.69 ±0.67	75.30 ±0.32	88.14±0.25	52.83±0.54	65.00±0.30	3.5
	JOAOv2	74.86 ±0.39	73.31±0.48	75.81 ±0.73	75.53 ±0.18	88.79±0.65	52.71±0.28	66.66 ±0.60	1.8

Unsupervised learning

Methods	NCI1	PROTEINS	DD	MUTAG	COLLAB	RDT-B	RDT-M5K	IMDB-B	A.R.↓
GL	-	-	-	81.66±2.11	-	77.34±0.18	41.01±0.17	65.87±0.98	7.4
WL	80.01 ±0.50	72.92±0.56	-	80.72±3.00	-	68.82±0.41	46.06±0.21	72.30 ±3.44	5.7
DGK	80.31 ±0.46	73.30±0.82	-	87.44±2.72	-	78.04±0.39	41.27±0.18	66.96±0.56	4.9
node2vec	54.89±1.61	57.49±3.57	-	72.63±10.20	-	-	-	-	8.6
sub2vec	52.84±1.47	53.03±5.55	-	61.05±15.80	-	71.48±0.41	36.68±0.42	55.26±1.54	9.5
graph2vec	73.22±1.81	73.30±2.05	-	83.15±9.25	-	75.78±1.03	47.86±0.26	71.10±0.54	5.7
MVGRL	-	-	-	75.40±7.80	-	82.00±1.10	-	63.60±4.20	7.2
InfoGraph	76.20±1.06	74.44 ±0.31	72.85±1.78	89.01 ±1.13	70.65 ±1.13	82.50±1.42	53.46±1.03	73.03 ±0.87	3.0
GraphCL	77.87±0.41	74.39 ±0.45	78.62 ±0.40	86.80±1.34	71.36 ±1.15	89.53 ±0.84	55.99 ±0.28	71.14 ±0.44	2.6
JOAO	78.07 ±0.47	74.55 ±0.41	77.32 ±0.54	87.35 ±1.02	69.50 ±0.36	85.29 ±1.35	55.74 ±0.63	70.21±3.08	3.3
JOAOv2	78.36±0.53	74.07±1.10	77.40 ±1.15	87.67 ±0.79	69.33±0.34	86.42 ±1.45	56.03 ±0.27	70.83±0.25	2.8

Experiments & Discussions. Across Diverse Datasets

- JOAOv2 generally outperforms heuristic self-supervised pretext tasks

Semi-supervised learning

L.R.	Methods	NCI1	PROTEINS	DD	COLLAB	RDT-B	RDT-M5K	GITHUB	A.R.↓
1%	No pre-train.	60.72±0.45	-	-	57.46±0.25	-	-	54.25±0.22	7.6
	Augmentations	60.49±0.46	-	-	58.40±0.97	-	-	56.36±0.42	6.6
	GAE	61.63±0.84	-	-	63.20±0.67	-	-	59.44±0.44	4.0
	Infomax	62.72 ±0.65	-	-	61.70±0.77	-	-	58.99±0.50	3.3
	ContextPred	61.21±0.77	-	-	57.60±2.07	-	-	56.20±0.49	6.6
	GraphCL	62.55 ±0.86	-	-	64.57 ±1.15	-	-	58.56±0.59	2.6
	JOAO	61.97±0.72	-	-	63.71 ±0.84	-	-	60.35±0.24	3.0
	JOAOv2	62.52 ±1.16	-	-	64.51 ±2.21	-	-	61.05 ±0.31	2.0
10%	No pre-train.	73.72±0.24	70.40±1.54	73.56±0.41	73.71±0.27	86.63±0.27	51.33±0.44	60.87±0.17	7.0
	Augmentations	73.59±0.32	70.29±0.64	74.30±0.81	74.19±0.13	87.74±0.39	52.01±0.20	60.91±0.32	6.2
	GAE	74.36±0.24	70.51±0.17	74.54±0.68	75.09±0.19	87.69±0.40	53.58 ±0.13	63.89±0.52	4.5
	Infomax	74.86 ±0.26	72.27±0.40	75.78 ±0.34	73.76±0.29	88.66±0.95	53.61 ±0.31	65.21±0.88	3.0
	ContextPred	73.00±0.30	70.23±0.63	74.66±0.51	73.69±0.37	84.76±0.52	51.23±0.84	62.35±0.73	7.2
	GraphCL	74.63 ±0.25	74.17 ±0.34	76.17 ±1.37	74.23±0.21	89.11 ±0.19	52.55±0.45	65.81±0.79	2.4
	JOAO	74.48±0.27	72.13±0.92	75.69 ±0.67	75.30 ±0.32	88.14±0.25	52.83±0.54	65.00±0.30	3.5
	JOAOv2	74.86 ±0.39	73.31±0.48	75.81 ±0.73	75.53 ±0.18	88.79±0.65	52.71±0.28	66.66 ±0.60	1.8

Unsupervised learning

Methods	NCI1	PROTEINS	DD	MUTAG	COLLAB	RDT-B	RDT-M5K	IMDB-B	A.R.↓
GL	-	-	-	81.66±2.11	-	77.34±0.18	41.01±0.17	65.87±0.98	7.4
WL	80.01 ±0.50	72.92±0.56	-	80.72±3.00	-	68.82±0.41	46.06±0.21	72.30 ±3.44	5.7
DGK	80.31 ±0.46	73.30±0.82	-	87.44±2.72	-	78.04±0.39	41.27±0.18	66.96±0.56	4.9
node2vec	54.89±1.61	57.49±3.57	-	72.63±10.20	-	-	-	-	8.6
sub2vec	52.84±1.47	53.03±5.55	-	61.05±15.80	-	71.48±0.41	36.68±0.42	55.26±1.54	9.5
graph2vec	73.22±1.81	73.30±2.05	-	83.15±9.25	-	75.78±1.03	47.86±0.26	71.10±0.54	5.7
MVGRL	-	-	-	75.40±7.80	-	82.00±1.10	-	63.60±4.20	7.2
InfoGraph	76.20±1.06	74.44 ±0.31	72.85±1.78	89.01 ±1.13	70.65 ±1.13	82.50±1.42	53.46±1.03	73.03 ±0.87	3.0
GraphCL	77.87±0.41	74.39 ±0.45	78.62 ±0.40	86.80±1.34	71.36 ±1.15	89.53 ±0.84	55.99 ±0.28	71.14 ±0.44	2.6
JOAO	78.07 ±0.47	74.55 ±0.41	77.32 ±0.54	87.35 ±1.02	69.50 ±0.36	85.29 ±1.35	55.74 ±0.63	70.21±3.08	3.3
JOAOv2	78.36±0.53	74.07±1.10	77.40 ±1.15	87.67 ±0.79	69.33±0.34	86.42 ±1.45	56.03 ±0.27	70.83±0.25	2.8

Experiments & Discussions. On Bioinformatics Datasets

- JOAOv2 underperforms heuristic self-supervised pretext tasks, without incorporating domain expertise
- JOAOv2 generalizes better than GraphCL on unseen / domain specific datasets

Transfer learning

Methods	BBBP	Tox21	ToxCast	SIDER	ClinTox	MUV	HIV	BACE	PPI	A.R.↓
No pre-train.	65.8±4.5	74.0±0.8	63.4±0.6	57.3±1.6	58.0±4.4	71.8±2.5	75.3±1.9	70.1±5.4	64.8±1.0	6.6
Infomax	68.8±0.8	75.3±0.5	62.7±0.4	58.4±0.8	69.9±3.0	75.3 ±2.5	76.0±0.7	75.9±1.6	64.1±1.5	5.3
EdgePred	67.3±2.4	76.0 ±0.6	64.1 ±0.6	60.4±0.7	64.1±3.7	74.1±2.1	76.3±1.0	79.9 ±0.9	65.7 ±1.3	3.8
AttrMasking	64.3±2.8	76.7 ±0.4	64.2 ±0.5	61.0 ±0.7	71.8±4.1	74.7 ±1.4	77.2±1.1	79.3 ±1.6	65.2 ±1.6	3.1
ContextPred	68.0±2.0	75.7 ±0.7	63.9 ±0.6	60.9 ±0.6	65.9±3.8	75.8 ±1.7	77.3 ±1.0	79.6 ±1.2	64.4±1.3	3.4
GraphCL	69.68 ±0.67	73.87±0.66	62.40±0.57	60.53 ±0.88	75.99 ±2.65	69.80±2.66	78.47 ±1.22	75.38±1.44	67.88 ±0.85	4.6
JOAO	70.22 ±0.98	74.98±0.29	62.94±0.48	59.97±0.79	81.32 ±2.49	71.66±1.43	76.73±1.23	77.34±0.48	64.43±1.38	4.5
JOAOv2	71.39 ±0.92	74.27±0.62	63.16±0.45	60.49±0.74	80.97 ±1.64	73.67±1.00	77.51 ±1.17	75.49±1.27	63.94±1.59	4.3

Experiments & Discussions. On Large-Scale Datasets

- JOAOv2 achieves a better generalizability and scalability, outperforms on large-scale datasets

Semi-supervised learning
on large-scale datasets

L.R.	Methods	ogbg-ppa	ogbg-code
1%	No pre-train.	16.04±0.74	6.06±0.01
	GraphCL	40.81±1.33	7.66 ±0.25
	JOAO	47.19 ±1.30	6.84±0.31
	JOAOv2	44.30 ±1.67	7.74 ±0.24
10%	No pre-train.	56.01±1.05	17.85±0.60
	GraphCL	57.77±1.25	22.45 ±0.17
	JOAO	60.91 ±0.83	22.06±0.30
	JOAOv2	59.32 ±1.11	22.65 ±0.22

Conclusions

- Problem: Handling **heterogenous** graph data with **less manual efforts**
- Contributions:
 - ❖ JOAO, a unified automatic framework
 - ❖ An instantiation as min-max optimization, with AGD for solution
 - ❖ JOAOv2, addressing distortion with multi-projection heads
 - ❖ Thorough experiments verifying the rationale and performance advantage

Further Discussions

➤ Limitation:

- ❖ Automating augmentation selection, while requiring human to construct & config augmentation pool: “full” automation is still desired

➤ Potential:

- ❖ In parallel to the principled formulation of bi-level optimization, a meta-learning formulation can also be pursued

References & Figures



➤ References

- GCN: Semi-Supervised Classification with Graph Convolutional Networks
- GAT: Graph Attention Networks
- Graph completion: When Does Self-Supervision Help Graph Convolutional Networks?
- AutoSSL: Automated Self-Supervised Learning for Graphs
- GraphCL: Graph Contrastive Learning with Augmentation
- MBRDL: Model Based Robust Deep Learning
- Wang et al: Towards A Unified Min-Max Framework for Adversarial Exploration and Robustness
- Boyd et al: Convex Optimization
- DLA+AG: Self-Supervised Label Augmentation via Input Transformations
- DistAug: Distribution Augmentation for Generative Modeling

➤ Figures

- 1. <https://www.euroscientist.com/imagine-a-social-network-like-facebook-with-no-facebook/>
- 2. <https://www.thoughtco.com/what-is-a-polymer-820536>
- 3. <https://www.e-education.psu.edu/ebf483/node/643>

Thank you for listening!

Paper: <https://arxiv.org/abs/2106.07594>

Code: https://github.com/Shen-Lab/GraphCL_Automated