
GainForest: Scaling Climate Finance for Forest Conservation using Interpretable Machine Learning on Satellite Imagery

000
001
002
003
004
005
006
007
008
009
010
011
012
013
014
015
016
017
018
019
020
021
022
023
024
025
026
027
028
029
030
031
032
033
034
035
036
037
038
039
040
041
042
043
044
045
046
047
048
049
050
051
052
053
054
Anonymous Authors¹

Abstract

Designing effective REDD+ policies, assessing their GHG impact, and linking them with the corresponding payments, is a resource intensive and complex task. GainForest leverages video prediction with remote sensing to monitor and forecast forest change at high resolution. Furthermore, by viewing payment allocation as a feature selection problem, GainForest can efficiently design payment schemes based on the Shapley value.

1. Introduction

Climate change is arguably humanity's primary challenge, demanding urgent, decisive action in line with the Paris Agreement. Land use is a key component, accounting for approximately 25% of total greenhouse gases (GHG). Land use includes a wide range of critical issues, from deforestation and forest degradation through agriculture. The domain is particularly challenging, given that the world's growing population and rising standards of living exert an increasing pressure on food and consumer goods production, both of which may lead to conflicting objectives with climate change and biodiversity.

The REDD+ program (Reducing Emissions from Deforestation and Forest Degradation), is UNFCC's scheme for the reduction of emissions caused by forest protection measures. However, designing effective REDD+ policies and actions, assessing their GHG impact, and linking them with the corresponding payments, is a resource-intensive and complex task for which there is considerable room for improvement also with respect to private sector involvement.

There are delays in implementation, inconsistencies in the reported data, insufficient levels of transparency, and as a result a lack of actionable projects. Current efforts fall short for fully leveraging the process and technology options

available today. The net result is insufficient climate action in the land management domain (including biodiversity protection) and a collective failure to meet the climate targets set.

We propose GainForest, an interpretable machine learning system that addresses concrete needs to improve the efficiency and effectiveness of Measurement, Reporting and Verification (MRV) processes in relation to forest conservation efforts and climate finance instruments that rely on MRV in order to incentivise sustainable land-use practices, as well as Payment for Ecosystem Services and biodiversity schemes that promote public and private investment in sustainable land-use activities.

GainForest integrates large amounts of unlabeled satellite imagery with labelled authoritative data from forest zoning and plot ownership to predict land use change. Interpretable machine learning approaches can then be used to guide fair performance and model-based climate payments.

2. Predicting Forest Change




Figure 1. Given past deforestation (pink) patterns from Global Forest Watch (left image), a video prediction model is able to forecast in which regions a deforestation pattern is likely going to spread to in the near future (blue boxes, right image)

¹Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML). Do not distribute.

Remote sensing, such as satellite imagery, is getting increasingly important in ecosystem monitoring. Although it provides a huge supply of data and detailed resolutions (Digital Globe provides imagery up to 0.3m per pixel), many downstream tasks, however, are constrained by a lack of

055 labels. Thus, current forest change alert systems such as
 056 FORMA (Wheeler et al., 2018) are constrained to train shallow
 057 supervised classifiers on handcrafted features to detect
 058 clear cuts in low resolutions (250m per pixel). Furthermore,
 059 in humid regions where clouds are covering large parts of
 060 forests, it can sometimes take months until forest change is
 061 detected and an alert is raised. Assessment of forest change
 062 suitable for performance-based payments such as the UN’s
 063 REDD+ program is usually limited on a yearly basis (often
 064 leveraging a mosaic of numerous clear satellite imagery
 065 combined with on-site measurements).

067 2.1. Leveraging Spatial and Temporal Dependencies

068 Recent research demonstrated (Jean et al., 2018; Xie et al.,
 069 2016), that we can leverage spatial dependencies and transfer
 070 learning techniques to pre-train efficient representations
 071 with deep learning models that allow us to fully leverage
 072 the high resolutions of modern satellite imagery. Moreover,
 073 by additionally considering the temporal dependencies of
 074 remote sensing data we can reformulate land use change
 075 prediction as a video prediction task (Lee et al., 2018) (see
 076 Figure 1), enabling us to forecast the spread of deforestation
 077 up to a daily basis¹. Accurate image forecasting models can
 078 support MRV decisions under uncertainty (e.g. predicting
 079 deforestation areas in cloudy images) and can be combined
 080 with additional authoritative data such as forest zoning and
 081 plot ownership.

082 2.2. Local Stakeholder Engagement as Active Learning

083 Machine learning models predicting forest change in high
 084 resolutions offer a valuable opportunity to engage and
 085 reward local stakeholders for climate action. Local stakeholders
 086 in respective regions can be queried by the model (e.g.
 087 via a mobile app) and incentivized to confirm or deny (uncertain)
 088 predictions of the model on-site. Responses can
 089 then be queried and used as future labels by the model using
 090 active learning.


091 3. Performance-Based Payments Based on 092 Feature Value Contribution

093 One of the challenges of performance-based payments such
 094 as REDD+ is how to distribute the payment from investors
 095 and donors to the local stakeholders. A natural way of tackling
 096 the attribution problem is to adopt a game-theoretic
 097 viewpoint, where each stakeholder is modelled as a player
 098 in a coalitional game and the usefulness of a player from
 099 any subset of contributors is characterized via a utility
 100 function. The Shapley value (SV) (Shapley, 1953) is a classic
 101 method in cooperative game theory to distribute the total
 102

¹ Assuming we are leveraging Planet’s daily satellite imagery coverage

103 gains generated by the coalition of all players and has been
 104 applied to problems in various domains in environmental
 105 science. The reason for its broad adoption is that the SV
 106 defines a unique profit allocation scheme that satisfies a set
 107 of properties with appealing real-world interpretations, such
 108 as fairness, rationality, and additivity.

109 By defining our climate utility function as machine learning
 110 model and our stakeholders as feature input (see Figure 2),
 111 we can solve the payment allocation problem as a feature
 112 selection problem and leverage the efficient SV computation
 113 techniques that has been applied to ML feature selection (Cohen
 114 et al., 2005; Sun et al., 2012; Mokdad et al., 2015; Jia
 115 et al., 2019; Lundberg & Lee, 2017). Climate investors can
 116 then use the assigned SV for their investment decisions.



117 *Figure 2.* We can solve the payment allocation problem as feature
 118 selection problem

119 4. Discussion

120 Machine learning-based MRVs for forest change combined
 121 with the exponential data growth in remote sensing can scale
 122 forest conservation efforts by providing more fine-grained
 123 predictions under uncertainty. Additionally by leveraging
 124 techniques from interpretable machine learning such as ef-
 125 ficient SV calculation, we can reframe payment allocation
 126 problems as efficient feature selection problems, potentially
 127 guiding climate investors in their decision making.

128 References

- Cohen, S., Ruppin, E., and Dror, G. Feature selection based on the shapley value. *In other words*, 1:98Eqr, 2005.
- Jean, N., Wang, S., Samar, A., Azzari, G., Lobell, D. B., and Ermon, S. Tile2vec: Unsupervised representation learning for spatially distributed data. *CoRR*, abs/1805.02855, 2018. URL <http://arxiv.org/abs/1805.02855>.
- Jia, R., Dao, D., Wang, B., Hubis, F. A., Hynes, N., Gürel, N. M., Li, B., Zhang, C., Song, D., and Spanos, C. J. Towards efficient data valuation based on the shapley

110 value. *CoRR*, abs/1902.10275, 2019. URL <http://arxiv.org/abs/1902.10275>.

111
112 Lee, A. X., Zhang, R., Ebert, F., Abbeel, P., Finn, C., and
113 Levine, S. Stochastic adversarial video prediction. *arXiv*
114 *preprint arXiv:1804.01523*, 2018.
115

116 Lundberg, S. M. and Lee, S.-I. A unified approach to in-
117 terpreting model predictions. In *Advances in Neural*
118 *Information Processing Systems*, pp. 4768–4777, 2017.
119

120 Mokdad, F., Bouchaffra, D., Zerrouki, N., and Touazi, A.
121 Determination of an optimal feature selection method
122 based on maximum shapley value. In *Intelligent Systems*
123 *Design and Applications (ISDA), 2015 15th International*
124 *Conference on*, pp. 116–121. IEEE, 2015.

125 Shapley, L. S. A value for n-person games. *Contributions*
126 *to the Theory of Games*, 2(28):307–317, 1953.
127

128 Sun, X., Liu, Y., Li, J., Zhu, J., Liu, X., and Chen, H. Using
129 cooperative game theory to optimize the feature selection
130 problem. *Neurocomputing*, 97:86–93, 2012.
131

132 Wheeler, D., Guzder-Williams, B., Petersen, R., and
133 Thau, D. Rapid modis-based detection of tree cover
134 loss. *International Journal of Applied Earth Observation and Geoinformation*, 69:78 – 87, 2018. ISSN
135 0303-2434. doi: <https://doi.org/10.1016/j.jag.2018.02.007>. URL <http://www.sciencedirect.com/science/article/pii/S0303243418301399>.

136
137
138 Xie, M., Jean, N., Burke, M., Lobell, D., and Ermon, S.
139 Transfer learning from deep features for remote sensing
140 and poverty mapping. In *Thirtieth AAAI Conference on*
141 *Artificial Intelligence*, 2016.
142
143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164