### CS 615 - Deep Learning

### Assignment 3 - Convolutional Neural Networks Spring 2020 Xiangang Lai

#### 1 Theory

1. (2pts) Apply kernel K to data X. In other words, what is X \* K?:

$$X = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix} K = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

Its only valid value at the center: 165

2. Given the feature map filter output,  $F = \begin{bmatrix} 1 & 2 & 3 & 4 & 1 & 3 \\ 4 & 5 & 6 & 0 & 0 & 12 \\ 7 & 8 & 9 & 1 & 0 & 4 \end{bmatrix}$ , what is

the output from a pooling layer with width of 2 and stride of 2 if we are using:

• (3pts) Max-Pooling?

$$P = \begin{bmatrix} 5 & 6 & 12 \\ 8 & 9 & 4 \end{bmatrix}$$

• (3pts) Mean-Pooling?  

$$P = \begin{bmatrix} 3 & \frac{13}{4} & 4 \\ -\frac{185}{4} & -\frac{95}{2} & -49 \end{bmatrix}$$

3. (2pts) Given an image X, what would the kernel K be that can reproduce the image when convoluted with it? That is, what is K such that X \* K = X? K should be the identity matrix with dimension 1

1

### 2 CNN for LSE Classification

### What you will need for your report

1. Your hyperparameter choices.

K is generated randomly with integers from -10 to 10, by seed 2278965

learning rate: 0.0027

L2 regularization rate: 0.01

2. Image representations of your initial and final kernels.

## Initial K



Figure 1: Initial K

# Final K



Figure 2: Final K




Figure 3: Square error over number of iterations

### 3 CNN for MLE Classification

1. Your hyperparameter choices.

K is generated randomly with integers from -10 to 10, by seed 28

learning rate: 0.0006

L2 regularization rate: 0.001

2. Image representations of your initial and final kernels.

## Initial K



Figure 4: Initial K

# Final K



Figure 5: Final K




Figure 6: Log likelihood over number of iterations

### 4 CNN for LCE Classification

1. Your hyperparameter choices.

K is generated randomly with integers from -10 to 10, by seed 1153

learning rate: 0.01

L2 regularization rate: 0.0001

2. Image representations of your initial and final kernels.

## Initial K



Figure 7: Initial K

# Final K



Figure 8: Final K




Figure 9: Cross entropy loss over number of iterations

### 5 CNN With Multiple Kernels

1. Your hyperparameter choices.

K is generated randomly with integers from -10 to 10, by seed 32

learning rate: 0.01

L2 regularization rate: 0

2. Image representations of your initial and final kernels.




Figure 10: Initial K




Figure 11: Final K




Figure 12: Square error over number of iterations

### 6 Multi-Kernel CNN For Image Classification

#### Architecture 1

1. The architecture.

Activation function: linear

Objective function: square error

stride: 2

Width of kernels: 5 number of kernels: 4

2. The values of any additional hyperparameters that you chose (outside of the architecture decisions).

K is generated randomly with integers from -10 to 10, by seed 32

learning rate: 0.00007

L2 regularization rate: 0.001

3. Plot of iteration vs objective function evaluation.




Figure 13: Square error over number of iterations

4. Final training and testing accuracies.

train accuracy: 1 trst accuracy: 0.93

#### Architecture 2

1. The architecture.

Activation function: logistic

Objective function: log likelihood

stride: 2

Width of kernels: 19 number of kernels: 9

2. The values of any additional hyperparameters that you chose (outside of the architecture decisions).

K is generated randomly with integers from -10 to 10, by seed 354

learning rate: 3e-7

L2 regularization rate: 0.5

3. Plot of iteration vs objective function evaluation.




Figure 14: Square error over number of iterations

4. Final training and testing accuracies.

train accuracy: 0.08 trst accuracy: 0.07