

Markdown PDF



This VS Code extension converts Markdown files to pdf, html, png or jpeg files.

[Japanese README](#)

Table of Contents

- [What's New](#)
- [Breaking Changes](#)
- [Features](#)
- [Chromium](#)
- [Usage](#)
- [Extension Settings](#)
- [Options](#)
- [FAQ](#)
- [Known Issues](#)
- [Change Log](#)
- [License](#)
- [Special thanks](#)

What's New

User-visible additions and improvements. For changes that may require action on your side, see [Breaking Changes](#). For the full user-facing release notes including past versions, see [RELEASE_NOTES.md](#).

X.Y.Z

- Added support for ```plantuml` fenced code blocks as a PlantUML syntax, in addition to the existing `@startuml` / `@enduml` block markers. Both are supported on equal footing.
 - Details: [PlantUML / RELEASE_NOTES.md#xyz-yyyymmdd](#)
- Chromium auto-download now fetches the latest Chrome Stable build from the [Chrome for Testing API](#), instead of relying only on the build id pinned by `puppeteer-core`. A new `markdown-pdf.chromium.autoDownload` setting (default `true`) lets you opt out.
 - Details: [Where is Chromium downloaded? / RELEASE_NOTES.md#xyz-yyyymmdd](#)
- Added math rendering support via [KaTeX](#), matching VS Code's built-in Markdown preview. Supports inline $\dots$ / $\left(\dots\right)$, display $\dots$ / $\left[\dots\right]$, and ```math` fenced code blocks. Opt out via `markdown-pdf.math.enabled`.
 - Details: [Math / RELEASE_NOTES.md#xyz-yyyymmdd](#)

2.0.1

- Self-closing `<div class="page" />` now correctly triggers a page break ([#428](#)).
 - Details: [RELEASE_NOTES.md#201-20260414](#)

2.0.0

- Include `(: [label] (path.md))` now reports errors inline instead of aborting the whole export, so a missing or unreadable fragment no longer breaks the rest of the document.
 - Details: [RELEASE_NOTES.md#200-20260413](#)
- Image `src` rewriting now correctly handles quoted attributes, flexible whitespace, and raw-text contexts.
 - Details: [RELEASE_NOTES.md#200-20260413](#)
- Front matter parsing now supports BOM-prefixed files.
 - Details: [RELEASE_NOTES.md#200-20260413](#)

Breaking Changes

Some changes may affect existing behavior. See the [FAQ](#) section for details. For the full user-facing release notes including past versions, see [RELEASE_NOTES.md](#).

X.Y.Z

- To mitigate XSS-like risk ([#411](#)), raw HTML in Markdown is now sanitized by default following the [GFM Disallowed Raw HTML extension](#). Tags such as `<script>`, `<iframe>`, `<style>`, and `on*` / `javascript:` attributes are stripped from Markdown body content. The behavior is controlled by the new `markdown-pdf.sanitize` setting.
 - Details: [Why is my raw HTML being escaped or removed? / RELEASE_NOTES.md#xyz-yyyymmdd](#)

2.0.0

- Heading IDs now follow GitHub-compatible VS Code slug generation. Existing internal anchors in your documents may change.
 - Details: [Why did my heading anchors change? / RELEASE_NOTES.md#200-20260413](#)
- Highlight.js upgraded from v9 to v11. Some highlight style names have been renamed or removed.
 - Details: [Why did my syntax highlight style stop working? / RELEASE_NOTES.md#200-20260413](#)
- Front matter parsing is now stricter. Some previously accepted formats may be rejected.
 - Details: [Why is my front matter no longer parsed? / RELEASE_NOTES.md#200-20260413](#)
- Chromium is resolved from an installed Chrome/Edge browser first, or auto-downloaded on first use.
 - Details: [How is the Chromium browser selected? / Where is Chromium downloaded? / RELEASE_NOTES.md#200-20260413](#)

Features

Feature	Description	Example
Syntax highlighting	Code block highlighting via highlight.js	<code>```js</code>
Emoji	Emoji shortcodes	<code>:smile:</code>
Checkbox	GitHub-style task lists	<code>- [] / - [x]</code>
Heading IDs	GitHub-compatible heading anchors	<code># Heading → #heading</code>
Container	Admonition-like blocks	<code>::: warning</code>
Include	Embed Markdown fragments	<code>:[label](path.md)</code>
PlantUML	UML diagrams from code blocks	<code>@startuml ... @enduml</code>
Math	LaTeX math via KaTeX	<code>\$E = mc^2\$</code>
Mermaid	Diagrams from fenced code blocks	<code>```mermaid</code>

Sample files

- [pdf](#)
- [html](#)
- [png](#)
- [jpeg](#)

Heading IDs

Headings automatically receive GitHub-compatible anchor IDs. For example:

Heading	Generated ID
<code># My Heading</code>	<code>#my-heading</code>
<code># API Reference</code>	<code>#api-reference</code>
<code># 日本語見出し</code>	<code>#日本語見出し</code>

See [Why did my heading anchors change?](#) in the FAQ for details.

Checkbox

INPUT

- [] Task A
- [x] Task B

OUTPUT

```
<ul>
  <li><input type="checkbox" disabled> Task A</li>
  <li><input type="checkbox" disabled checked> Task B</li>
</ul>
```

Container

Admonition-like blocks via [markdown-it-container](#).

INPUT

```
::: warning
*here be dragons*
:::
```

OUTPUT

```
<div class="warning">
<p><em>here be dragons</em></p>
</div>
```

PlantUML

Render UML diagrams via [PlantUML](#) using [markdown-it-plantuml](#).

Two equivalent syntaxes are supported. Both produce the same `<img>` tag and share the same [markdown-pdf.plantumlServer](#) setting.

Fenced code block

A `````plantuml` fenced code block. This is the common fence convention used across the PlantUML ecosystem (for example, [GitLab renders this form natively](#) when the PlantUML integration is enabled).

```
```plantuml
Bob -[#red]> Alice : hello
Alice -[#0000FF]->Bob : ok
```
```


`@startuml` / `@enduml` block markers. The markers can be customized via `markdown-pdf.plantumlOpenMarker` and `markdown-pdf.plantumlCloseMarker`.

```
@startuml
Bob -[#red]> Alice : hello
Alice -[#0000FF]->Bob : ok
@enduml
```

```

sequenceDiagram
    participant Bob
    participant Alice
    Bob->>Alice: hello
    Alice-->>Bob: ok
  
```

Include markdown fragment files: `:[alternate-text](relative-path-to-file.md)`.



```
: [Changelog] (CHANGELOG.md)
```

OUTPUT

Content of README.md

Content of plugins/README.md

Content of CHANGELOG.md


Mermaid

Render diagrams from fenced code blocks via [Mermaid](#).

INPUT

```
```mermaid
stateDiagram
 [*] --> First
 state First {
 [*] --> second
 second --> [*]
 }
...
```
```

OUTPUT



Math

Render LaTeX math via [KaTeX](#). Uses [@vscode/markdown-it-katex](#) (the same plugin as VS Code's built-in Markdown preview) for $\cdots$, $\int_0^\infty f(x)dx$, and $\begin{env}\cdots\end{env}$, plus a small in-house plugin for $\langle \cdots \rangle$ and $\lceil \cdots \rceil$ bracket delimiters. Rendering runs in Node, so no network access is required.

Supported notations:

- Inline: $E = mc^2$, $\langle E = mc^2 \rangle$
- Display: $\int_0^\infty f(x)dx$, $\lceil \alpha \rceil$
- LaTeX environments: $\begin{aligned} a &= b \\ c &= d \end{aligned}$
- Fenced code block:

```


$$\sum_{i=1}^n i = \frac{n(n+1)}{2}$$


```

INPUT

Inline: $E = mc^2$

Display:

$\int_0^\infty e^{-x^2}dx = \frac{\sqrt{\pi}}{2}$

LaTeX environment:

```
\begin{aligned}
x + y &= 10 \\
x - y &= 4 \\
\end{aligned}
```

OUTPUT

Inline: $E = mc^2$

Display:

$$\int_0^\infty e^{-x^2} dx = \frac{\sqrt{\pi}}{2}$$

LaTeX environment:

$$\begin{aligned} x + y &= 10 \\ x - y &= 4 \end{aligned}$$

To disable math rendering (for example, when $\$X\$$ -style placeholders should stay as plain text), set `markdown-pdf.math.enabled` to `false`, set `math.enabled` to `false` in the document front matter, or escape the `$` as `\$`.

```
---
math:
  enabled: false
---
```

User-defined KaTeX macros can be passed via `markdown-pdf.math.katex.macros` or in the front matter:

```
---
math:
  katex:
    macros:
      "\\RR": "\\mathbb{R}"
---
```

Chromium

Markdown PDF uses a Chromium-based browser for PDF/PNG/JPEG export. It tries the following sources in order:

1. The path specified in `markdown-pdf.executablePath`
2. An installed Google Chrome, Microsoft Edge, or Chromium on your system
3. A managed Chromium automatically downloaded on first use (latest Chrome Stable; can be disabled with `markdown-pdf.chromium.autoDownload`)


See [How is the Chromium browser selected?](#) and [Where is Chromium downloaded?](#) in the FAQ for details.

If you are behind a proxy, set the `http.proxy` option in `settings.json` and restart Visual Studio Code.

Usage


Command Palette

1. Open the Markdown file
2. Press **F1** or **Ctrl+Shift+P**
3. Type **export** and select below
 - markdown-pdf: Export (settings.json)
 - markdown-pdf: Export (pdf)
 - markdown-pdf: Export (html)
 - markdown-pdf: Export (png)
 - markdown-pdf: Export (jpeg)
 - markdown-pdf: Export (all: pdf, html, png, jpeg)



Menu

1. Open the Markdown file
2. Right click and select below
 - markdown-pdf: Export (settings.json)
 - markdown-pdf: Export (pdf)
 - markdown-pdf: Export (html)
 - markdown-pdf: Export (png)
 - markdown-pdf: Export (jpeg)
 - markdown-pdf: Export (all: pdf, html, png, jpeg)




Auto convert

1. Add "`markdown-pdf.convertOnSave`": `true` option to **settings.json**
2. Restart Visual Studio Code
3. Open the Markdown file
4. Auto convert on save

Extension Settings

Visual Studio Code User and Workspace Settings

1. Select **File > Preferences > UserSettings or Workspace Settings**
2. Find markdown-pdf settings in the **Default Settings**
3. Copy `markdown-pdf.*` settings
4. Paste to the **settings.json**, and change the value



Options

List

| Category | Option name | Configuration scope |
|--------------------------|--|---------------------|
| Save options | markdown-pdf.type | |
| | markdown-pdf.convertOnSave | |
| | markdown-pdf.convertOnSaveExclude | |
| | markdown-pdf.outputDirectory | |
| | markdown-pdf.outputDirectoryRelativePathFile | |
| Styles options | markdown-pdf.styles | |
| | markdown-pdf.stylesRelativePathFile | |
| | markdown-pdf.includeDefaultStyles | |
| Syntax highlight options | markdown-pdf.highlight | |
| | markdown-pdf.highlightStyle | |
| Markdown options | markdown-pdf.breaks | |
| Emoji options | markdown-pdf.emoji | |
| Configuration options | markdown-pdf.executablePath | |

| Category | Option name | Configuration scope |
|-----------------------------|---|---------------------|
| Common Options | markdown-pdf.chromium.autoDownload | |
| | markdown-pdf.scale | |
| PDF options | markdown-pdf.displayHeaderFooter | resource |
| | markdown-pdf.headerTemplate | resource |
| | markdown-pdf.footerTemplate | resource |
| | markdown-pdf.printBackground | resource |
| | markdown-pdf.orientation | resource |
| | markdown-pdf.pageRanges | resource |
| | markdown-pdf.format | resource |
| | markdown-pdf.width | resource |
| | markdown-pdf.height | resource |
| | markdown-pdf.margin.top | resource |
| | markdown-pdf.margin.bottom | resource |
| | markdown-pdf.margin.right | resource |
| | markdown-pdf.margin.left | resource |
| PNG JPEG options | markdown-pdf.quality | |
| | markdown-pdf.clip.x | |
| | markdown-pdf.clip.y | |
| | markdown-pdf.clip.width | |
| | markdown-pdf.clip.height | |
| | markdown-pdf.omitBackground | |
| PlantUML options | markdown-pdf.plantumlOpenMarker | |
| | markdown-pdf.plantumlCloseMarker | |
| | markdown-pdf.plantumlServer | |
| markdown-it-include options | markdown-pdf.markdown-it-include.enable | |
| mermaid options | markdown-pdf.mermaidServer | |
| math options | markdown-pdf.math.enabled | |
| | markdown-pdf.math.katex.macros | |
| Sanitize options | markdown-pdf.sanitize | |

Save options

markdown-pdf.type

- Output format: pdf, html, png, jpeg
- Multiple output formats support
- Default: pdf

```
"markdown-pdf.type": [  
  "pdf",  
  "html",  
  "png",  
  "jpeg"  
],
```

markdown-pdf.convertOnSave

- Enable Auto convert on save
- boolean. Default: false
- To apply the settings, you need to restart Visual Studio Code

markdown-pdf.convertOnSaveExclude

- Excluded file name of convertOnSave option

```
"markdown-pdf.convertOnSaveExclude": [  
  "^work",  
  "work.md$",  
  "work|test",  
  "[0-9][0-9][0-9][0-9]-work",  
  "work\\test" // All '\\' need to be written as '\\\' (Windows)  
],
```

markdown-pdf.outputDirectory

- Output Directory
- All \ need to be written as \\ (Windows)

```
"markdown-pdf.outputDirectory": "C:\\work\\output",
```

- Relative path
 - If you open the **Markdown file**, it will be interpreted as a relative path from the file
 - If you open a **folder**, it will be interpreted as a relative path from the root folder
 - If you open the **workspace**, it will be interpreted as a relative path from each root folder
 - See [Multi-root Workspaces](#)

```
"markdown-pdf.outputDirectory": "output",
```

- Relative path (home directory)
 - If path starts with `~`, it will be interpreted as a relative path from the home directory

```
"markdown-pdf.outputDirectory": "~/output",
```

- If you set a directory with a **relative path**, it will be created if the directory does not exist
- If you set a directory with an **absolute path**, an error occurs if the directory does not exist

markdown-pdf.outputDirectoryRelativePathFile

- If `markdown-pdf.outputDirectoryRelativePathFile` option is set to **true**, the relative path set with `markdown-pdf.outputDirectory` is interpreted as relative from the file
- It can be used to avoid relative paths from folders and workspaces
- boolean. Default: false

Styles options

markdown-pdf.styles

- A list of local paths to the stylesheets to use from the markdown-pdf
- If the file does not exist, it will be skipped
- All `\` need to be written as `\\` (Windows)

```
"markdown-pdf.styles": [
  "C:\\Users\\<USERNAME>\\Documents\\markdown-pdf.css",
  "/home/<USERNAME>/settings/markdown-pdf.css",
],
```

- Relative path
 - If you open the **Markdown file**, it will be interpreted as a relative path from the file
 - If you open a **folder**, it will be interpreted as a relative path from the root folder
 - If you open the **workspace**, it will be interpreted as a relative path from each root folder
 - See [Multi-root Workspaces](#)

```
"markdown-pdf.styles": [
  "markdown-pdf.css",
],
```

- Relative path (home directory)
 - If path starts with `~`, it will be interpreted as a relative path from the home directory

```
"markdown-pdf.styles": [  
  "~/.config/Code/User/markdown-pdf.css"  
],
```

- Online CSS (<https://xxx/xxx.css>) is applied correctly for JPG and PNG, but problems occur with PDF [#67](#)

```
"markdown-pdf.styles": [  
  "https://xxx/markdown-pdf.css"  
],
```

markdown-pdf.stylesRelativePathFile

- If `markdown-pdf.stylesRelativePathFile` option is set to `true`, the relative path set with `markdown-pdf.styles` is interpreted as relative from the file
- It can be used to avoid relative paths from folders and workspaces
- boolean. Default: false

markdown-pdf.includeDefaultStyles

- Enable the inclusion of default Markdown styles (VSCode, markdown-pdf)
- boolean. Default: true

Syntax highlight options

markdown-pdf.highlight

- Enable Syntax highlighting
- boolean. Default: true

markdown-pdf.highlightStyle

- Set the current `highlight.js` style file name. Examples: `github.css`, `monokai.css`, `base16/solarized-dark.css`
- [file name list](#)
- demo site : <https://highlightjs.org/demo>

```
"markdown-pdf.highlightStyle": "github.css",
```

Markdown options

markdown-pdf.breaks

- Enable line breaks

- boolean. Default: false

Emoji options

markdown-pdf.emoji

- Enable emoji. [EMOJI CHEAT SHEET](#)
- boolean. Default: true

Configuration options

markdown-pdf.executablePath

- Path to a Google Chrome, Microsoft Edge, or Chromium executable to run instead of the bundled Chromium
- See [How is the Chromium browser selected?](#) in the FAQ for how this setting interacts with installed browser detection and the managed Chromium download
- All \ need to be written as \\ (Windows)
- To apply the settings, you need to restart Visual Studio Code

```
"markdown-pdf.executablePath": "C:\\Program Files  
(x86)\\Google\\Chrome\\Application\\chrome.exe"
```

markdown-pdf.chromium.autoDownload

- Automatically download a managed Chromium when no installed browser is found
- boolean. Default: true
- When `false`, Markdown PDF does not download Chromium and relies only on [markdown-pdf.executablePath](#) or an installed Google Chrome / Microsoft Edge / Chromium. Export fails if none is available.
- See [How is the Chromium browser selected?](#) in the FAQ for the full resolution order

```
"markdown-pdf.chromium.autoDownload": true
```

Common Options

markdown-pdf.scale

- Scale of the page rendering
- number. Default: 1

```
"markdown-pdf.scale": 1
```

PDF options

- pdf only. [puppeteer page.pdf options](#)

markdown-pdf.displayHeaderFooter

- Enables header and footer display
- boolean. Default: true
- Activating this option will display both the header and footer
- If you wish to display only one of them, remove the value for the other
- To hide the header

```
"markdown-pdf.headerTemplate": "",
```

- To hide the footer

```
"markdown-pdf.footerTemplate": "",
```

markdown-pdf.headerTemplate

- Specifies the HTML template for outputting the header
- To use this option, you must set `markdown-pdf.displayHeaderFooter` to `true`
- `<span class='date'></span>` : formatted print date. The format depends on the environment
- `<span class='title'></span>` : markdown file name
- `<span class='url'></span>` : markdown full path name
- `<span class='pageNumber'></span>` : current page number
- `<span class='totalPages'></span>` : total pages in the document
- `%%ISO-DATETIME%%` : current date and time in ISO-based format (YYYY-MM-DD hh:mm:ss)
- `%%ISO-DATE%%` : current date in ISO-based format (YYYY-MM-DD)
- `%%ISO-TIME%%` : current time in ISO-based format (hh:mm:ss)
- Default (version 1.5.0 and later): Displays the Markdown file name and the date using `%%ISO-DATE%%`

```
"markdown-pdf.headerTemplate": "<div style=\"font-size: 9px; margin-left: 1cm;\">  
<span class='title'></span></div> <div style=\"font-size: 9px; margin-left: auto;  
margin-right: 1cm; \">%%ISO-DATE%%</div>",
```

- Default (version 1.4.4 and earlier): Displays the Markdown file name and the date using `<span class='date'></span>`

```
"markdown-pdf.headerTemplate": "<div style=\"font-size: 9px; margin-left: 1cm;\">  
<span class='title'></span></div> <div style=\"font-size: 9px; margin-left: auto;  
margin-right: 1cm; \"> <span class='date'></span></div>",
```

markdown-pdf.footerTemplate

- Specifies the HTML template for outputting the footer
- For more details, refer to [markdown-pdf.headerTemplate](#)
- Default: Displays the {current page number} / {total pages in the document}

```
"markdown-pdf.footerTemplate": "<div style=\"font-size: 9px; margin: 0 auto;\">  
<span class='pageNumber'></span> / <span class='totalPages'></span></div>",
```

markdown-pdf.printBackground

- Print background graphics
- boolean. Default: true

markdown-pdf.orientation

- Paper orientation
- portrait or landscape
- Default: portrait

markdown-pdf.pageRanges

- Paper ranges to print, e.g., '1-5, 8, 11-13'
- Default: all pages

```
"markdown-pdf.pageRanges": "1,4-",
```

markdown-pdf.format

- Paper format
- Letter, Legal, Tabloid, Ledger, A0, A1, A2, A3, A4, A5, A6
- Default: A4

```
"markdown-pdf.format": "A4",
```

markdown-pdf.width

markdown-pdf.height

- Paper width / height, accepts values labeled with units(mm, cm, in, px)
- If it is set, it overrides the markdown-pdf.format option

```
"markdown-pdf.width": "10cm",  
"markdown-pdf.height": "20cm",
```

markdown-pdf.margin.top

markdown-pdf.margin.bottom

markdown-pdf.margin.right

markdown-pdf.margin.left

- Paper margins.units(mm, cm, in, px)

```
"markdown-pdf.margin.top": "1.5cm",  
"markdown-pdf.margin.bottom": "1cm",  
"markdown-pdf.margin.right": "1cm",  
"markdown-pdf.margin.left": "1cm",
```

PNG, JPEG options

- png and jpeg only. [puppeteer page.screenshot options](#)

markdown-pdf.quality

- jpeg only. The quality of the image, between 0-100. Not applicable to png images

```
"markdown-pdf.quality": 100,
```

markdown-pdf.clip.x

markdown-pdf.clip.y

markdown-pdf.clip.width

markdown-pdf.clip.height

- An object which specifies clipping region of the page
- number

```
// x-coordinate of top-left corner of clip area  
"markdown-pdf.clip.x": 0,  
  
// y-coordinate of top-left corner of clip area  
"markdown-pdf.clip.y": 0,  
  
// width of clipping area  
"markdown-pdf.clip.width": 1000,
```

```
// height of clipping area
"markdown-pdf.clip.height": 1000,
```

markdown-pdf.omitBackground

- Hides default white background and allows capturing screenshots with transparency
- boolean. Default: false

PlantUML options

markdown-pdf.plantumlOpenMarker

- Opening delimiter for the `@startuml` / `@enduml` block marker syntax. Change this if you want to use a different start marker.
- Default: `@startuml`

markdown-pdf.plantumlCloseMarker

- Closing delimiter for the `@startuml` / `@enduml` block marker syntax. Change this if you want to use a different end marker.
- Default: `@enduml`

markdown-pdf.plantumlServer

- Plantuml server. e.g. `http://localhost:8080`
- Default: `http://www.plantuml.com/plantuml`
- For example, to run Plantuml Server locally [#139](#) :

```
docker run -d -p 8080:8080 plantuml/plantuml-server:jetty
```

[plantuml/plantuml-server - Docker Hub](#)

markdown-it-include options

markdown-pdf.markdown-it-include.enable

- Enable markdown-it-include.
- boolean. Default: true

mermaid options

markdown-pdf.mermaidServer

- mermaid server
- Default: `https://unpkg.com/mermaid/dist/mermaid.min.js`

math options

markdown-pdf.math.enabled

- Enable math rendering via KaTeX for $\cdots$, $\cdots$, $\cdots$, $\cdots$, and $\cdots$ fenced code blocks.
- Matches the behavior of VS Code's built-in Markdown preview.
- Set to `false` to keep the raw $\cdots$, $\cdots$, $\cdots$, and $\cdots$ text (use this if your document contains $\cdots$ -style placeholders that should not be parsed as math).
- Default: `true`

markdown-pdf.math.katex.macros

- User-defined [KaTeX macros](#) passed to the KaTeX renderer.
- Example: `{ "\RR": "\mathbb{R}" }`
- Default: `{}`

Sanitize options

markdown-pdf.sanitize

- Sanitization mode for raw HTML in Markdown
- `"gfm"`: Strip GFM's disallowed tags and dangerous attributes (default)
- `"gfm-allow-style"`: Same as `"gfm"` but keeps `<style>` elements
- `"none"`: Disable sanitization (legacy behavior, not recommended)
- Default: `"gfm"`

```
"markdown-pdf.sanitize": "gfm",
```

FAQ

How can I change emoji size ?

1. Add the following to your stylesheet which was specified in the `markdown-pdf.styles`

```
.emoji {  
  height: 2em;  
}
```

Auto guess encoding of files

Using `files.autoGuessEncoding` option of the Visual Studio Code is useful because it automatically guesses the character code. See [files.autoGuessEncoding](#)

```
"files.autoGuessEncoding": true,
```

Output directory

If you always want to output to the relative path directory from the Markdown file.

For example, to output to the "output" directory in the same directory as the Markdown file, set it as follows.

```
"markdown-pdf.outputDirectory" : "output",  
"markdown-pdf.outputDirectoryRelativePathFile": true,
```

Page Break

Please use either of the following to insert a page break.

```
<div class="page"/>
```

```
<div class="page"></div>
```

Why did my heading anchors change?

Starting with 2.0.0, Markdown PDF generates heading IDs using a custom `markdown-it-named-headers` implementation that follows GitHub-compatible VS Code slug generation. Compared to the previous implementation, the new slug generator preserves CJK characters and underscores while removing unsupported punctuation, which can cause existing internal anchors (e.g. `#some-heading`) to resolve differently.

If your Markdown relies on specific anchor strings (for example, a table of contents or cross-document links), re-check the generated anchors after exporting and update the links as needed.

Why did my syntax highlight style stop working?

Starting with 2.0.0, Markdown PDF uses `highlight.js` v11 (previously v9). Some style names from v9 have been renamed or removed. Markdown PDF maps legacy style names to current names where possible and shows a warning message when a configured style cannot be found. If no mapping is available, the extension falls back to `tomorrow.css`.

Please check the [available styles](#) and update your `markdown-pdf.highlightStyle` setting to a current style name.

Why is my front matter no longer parsed?

Starting with 2.0.0, Markdown PDF parses YAML front matter with a custom implementation instead of `gray-matter`. The new parser is stricter and rejects the following cases that the old parser may have accepted:

- Top-level YAML sequences (arrays) as front matter
- Front matter that does not parse into a plain object
- Malformed YAML structures

A valid front matter must be a YAML mapping (object) at the top level, for example:

```
---
title: My Document
"markdown-pdf":
  displayHeaderFooter: true
---
```

BOM-prefixed files are still supported.

Why is my raw HTML being escaped or removed?

Earlier versions of this extension passed all raw HTML in Markdown through to the renderer without validation. Tags such as `<script>` and `<iframe>` could therefore execute during preview or PDF rendering, creating XSS-like risk when opening untrusted Markdown files (#411).

Starting with X.Y.Z, raw HTML inside the Markdown body is sanitized by default per the [GFM Disallowed Raw HTML extension](#). Behavior is controlled by `markdown-pdf.sanitize`:

Mode	Behavior
"gfm" (default)	Strip GFM's disallowed tags and dangerous attributes. Recommended when opening Markdown files authored by others.
"gfm-allow-style"	Same as "gfm" but keeps <code><style></code> so you can embed CSS directly in a Markdown file to produce a self-contained PDF. Use only with content you trust — CSS itself can still exfiltrate data.
"none"	Disable sanitization. Legacy behavior. Not recommended.

What "gfm" removes

Tags (opening and closing forms are both escaped to visible text): `<title>`, `<textarea>`, `<style>`, `<xmp>`, `<iframe>`, `<noembed>`, `<noframes>`, `<script>`, `<plaintext>`

Attributes:

- `on*` event handlers (`onClick`, `onload`, ...)
- `href` / `src` whose value starts with `javascript:`

Migrating from inline `<style>`

If you used to customize PDF layout by writing `<style>` directly inside a Markdown file, move that CSS into a `.css` file and reference it via `markdown-pdf.styles`. External stylesheets are loaded from your VS Code settings, not from the Markdown body, so they are not affected by sanitization.

Caveats for external CSS:

- CSS can still make outbound network requests through `@import url(...)`, `background: url(...)`, attribute selectors with `url(...)`, etc. Only reference stylesheet files you trust.

- When `markdown-pdf.stylesRelativePathFile` is `true`, the stylesheet path is resolved relative to the opened Markdown file. Be cautious about opening Markdown from untrusted locations that may ship a malicious sibling `.css`.

Sanitization scope

Sanitized:

- Raw HTML written inside the Markdown body (rendered via markdown-it's `html_block` / `html_inline`)
- Content pulled in by the Include feature (`:[label](path.md)`) — it goes through the same renderer

Not sanitized:

- External CSS loaded via `markdown-pdf.styles` (by design — user-configured trust boundary)
- The extension's built-in stylesheets and HTML template
- HTML emitted by the extension itself (mermaid, highlight.js, emoji, PlantUML)

How is the Chromium browser selected?

Markdown PDF resolves a Chromium-based browser in the following order:

1. The path specified in `markdown-pdf.executablePath`, if the file exists.
2. An installed browser on your system. Google Chrome (stable) is detected via `@puppeteer/browsers` at its standard OS install location; Microsoft Edge and Chromium are probed at the fixed paths listed below.
3. A managed Chromium that Markdown PDF automatically downloads on first use.

The first match wins. The per-OS scan order for installed Edge and Chromium is:

Windows

1. Google Chrome (stable install, detected via `@puppeteer/browsers`)
2. `%LOCALAPPDATA%\Microsoft\Edge\Application\msedge.exe`
3. `%LOCALAPPDATA%\Chromium\Application\chrome.exe`
4. `%PROGRAMFILES%\Microsoft\Edge\Application\msedge.exe`
5. `%PROGRAMFILES%\Chromium\Application\chrome.exe`
6. `%PROGRAMFILES(X86)%\Microsoft\Edge\Application\msedge.exe`
7. `%PROGRAMFILES(X86)%\Chromium\Application\chrome.exe`

macOS

1. Google Chrome (stable install, detected via `@puppeteer/browsers`)
2. `/Applications/Chromium.app/Contents/MacOS/Chromium`
3. `/Applications/Microsoft Edge.app/Contents/MacOS/Microsoft Edge`

Linux

1. Google Chrome (stable install, detected via `@puppeteer/browsers`)
2. `/usr/bin/chromium-browser`
3. `/usr/bin/chromium`
4. `/usr/bin/microsoft-edge`
5. `/usr/bin/microsoft-edge-stable`

Where is Chromium downloaded?

If no installed browser is found, Markdown PDF downloads a managed Chromium on first use. The download is stored under the extension's VS Code global storage directory:

OS	Download path
Windows	%APPDATA%\Code\User\globalStorage\yzane.markdown-pdf\
macOS	~/Library/Application Support/Code/User/globalStorage/yzane.markdown-pdf/
Linux	~/.config/Code/User/globalStorage/yzane.markdown-pdf/

If you use VS Code Insiders or VSCodium, the base path changes accordingly (for example `Code - Insiders` or `VSCodium` instead of `Code`).

During the download, `Installing Chromium` is shown in the status bar.

Which Chromium build is downloaded?

Markdown PDF tries to fetch the latest Chrome Stable build id from the [Chrome for Testing API](#). If the API is unreachable, it falls back in this order:

1. The most recently cached build under the global storage directory shown above
2. The build id pinned by the bundled `puppeteer-core` (last-resort fallback)

Disabling the auto-download

Set `markdown-pdf.chromium.autoDownload` to `false` to skip the download entirely. Markdown PDF will then rely only on `markdown-pdf.executablePath` or an installed Google Chrome / Microsoft Edge / Chromium, and export will fail with an error if none is available.

Known Issues

markdown-pdf.styles option

- Online CSS (<https://xxx/xxx.css>) is applied correctly for JPG and PNG, but problems occur with PDF.
[#67](#)

Change Log

For a user-facing summary of changes, see [RELEASE_NOTES.md](#). For the detailed change history including developer-facing notes, see [CHANGELOG.md](#).

License

MIT

Special thanks

- [puppeteer/puppeteer](#)
- [markdown-it/markdown-it](#)
- [markdown-it/markdown-it-emoji](#)
- [HenrikJoreteg/emoji-images](#)
- [highlightjs/highlight.js](#)
- [markdown-it/markdown-it-container](#)
- [gmunguia/markdown-it-plantuml](#)
- [mermaid-js/mermaid](#)