

Unsupervised Learning

测验, 5 个问题

✓ 恭喜！您通过了！

下一项



1 / 1
分数

1.

For which of the following tasks might K-means clustering be a suitable algorithm? Select all that apply.



1 / 1
分数

2.

Suppose we have three cluster centroids $\mu_1 = \begin{bmatrix} 1 \\ 2 \end{bmatrix}$, $\mu_2 = \begin{bmatrix} -3 \\ 0 \end{bmatrix}$ and $\mu_3 = \begin{bmatrix} 4 \\ 2 \end{bmatrix}$. Furthermore, we have a training example $x^{(i)} = \begin{bmatrix} -1 \\ 2 \end{bmatrix}$. After a cluster assignment step, what will $c^{(i)}$ be?



1 / 1
分数

3.

K-means is an iterative algorithm, and two of the following steps are repeatedly carried out in its inner-loop. Which two?



1 / 1
分数

4.

Suppose you have an unlabeled dataset $\{x^{(1)}, \dots, x^{(m)}\}$. You run K-means with 50 different random initializations, and obtain 50 different clusterings of the data. What is the recommended way for choosing which one of these 50 clusterings to use?



1 / 1
分数

5.

Which of the following statements are true? Select all that apply.

Unsupervised Learning

测验, 5 个问题

