Q-BRIDGE: Verifiable Policy Queries over Joint Confidence Views

Zida Yang[1,†], Weiqing Zeng[2,†], Guquan You[3,†], Cong Wang[1,*], Jiexin Zheng[1,*]
[1]Guanghua School of Management, Peking University
[2]Southwest Jiaotong University
[3]Institute of Emergency Safety Innovations, Guangzhou University
2401111090@stu.pku.edu.cn, zengweiqing@my.swjtu.edu.cn, youguquan@gzhu.edu.cn
{wangcong,jiexinzheng}@gsm.pku.edu.cn
† Equal contribution. * Corresponding authors.

***Abstract*—Repeated policy analysis queries the same logs while changing candidate decisions. Q-BRIDGE separates source aggregation from subsequent queries through a materialized confidence view: outcome means allowed by observational and randomized data and declared assumptions. One view supports adaptive queries under one coverage event, without rescanning logs. For disjoint nonnegative groups, a direct three-step construction caps feasible means, allocates within the cap, and recovers an optimal policy with matching lower and upper certificates. An independent checker validates these against the original constraints. Fixed-policy queries reuse constraint weights and exact terms before resorting to a solver. The construction and a general exact linear program agree on all 2,160 distinct synthetic family requests. Holding information fixed, family optimization resolves 107 undecided cases into 86 above-threshold policies and 21 exclusions; exact reoptimization of the original three policies recovers none of the 86. Controlled comparisons isolate lower group-average execution cost from exact-term retention. Coat connects the query interface to concrete policy redesign and catalogue-level stopping.**

***Index Terms*—query processing, uncertain data, materialized views, causal inference, verifiable computation**

I. Introduction

On a production-log snapshot and a smaller randomized experiment, a recommendation analyst must decide whether to adopt a policy, redesign it, or stop searching for a guaranteed gain. A policy assigns action probabilities; rejecting one candidate cannot settle the other two decisions. Unrecorded preferences confound production exposure, and experimental information may transfer only for group averages.

Causal query systems [1], [2] and uncertainty-aware query processing [3] make statistical meaning part of data management. Here the challenge is to preserve joint uncertainty across changing objectives, reuse computation, and return checkable answers. Q-BRIDGE[1] materializes interval endpoints and group-moment constraints as a *confidence view*: one joint feasible set of means under fixed source assumptions. Without rescanning logs, queries test a policy, recover the best robust policy, or exclude all above-threshold guarantees. For disjoint groups, a direct construction returns an optimal policy and a proof using original constraints.

[1]Code and saved certificate examples: https://github.com/yzd2002/Q-BRIDGE-ICDE2027.

A running example. Figure 1 has one context, four actions and margin $\delta = .001 = 0.1\,\text{pp}$; m_A is success probability under A. The reference is uniform. Q1 uses policy $(.15, .15, .35, .35)$, hence contrast $c = (-.1, -.1, .1, .1)$. Observational information gives the displayed intervals; randomized information transfers only $(m_A + m_C)/2 = .65$ and $(m_B + m_D)/2 = .70$. Substitution yields

$$\Delta_1 = .27 - .2(m_A + m_B) \geq .01.$$

The vector $(.6, .7, .7, .7)$ attains this one-percentage-point guarantee in decimal arithmetic; interval-only and group-only bounds are $-.075$ and $-.13$. These constructed teaching inputs are not measured effects.

Q2 reuses Q1's constraint weights to prove 0.6375 pp, above the 0.1 pp margin. For Q3, inconclusive reuse triggers a solve proving 0.5 pp, not policy rejection (Section IV).

For the family, the group sums fix reference payoff at .675, and $m_A \leq .6$ forces $m_C \geq .7$. Choosing C guarantees $.025 = 2.5\,\text{pp}$; the feasible vector $(.6, .7, .7, .7)$ gives no policy more than $.7 - .675$. Matching bounds prove the optimal robust guarantee (Section IV-E).

Our contributions connect query semantics, construction and execution:

A reusable source-to-query interface (Sections II–III). Source assumptions and simultaneous intervals map to stored constraints without changing their statistical meaning. One event—all target means lying in the view—supports adaptive policies and margins on that fixed view.

Direct construction with an independently checkable proof (Section IV). For disjoint nonnegative moment groups, we prove that the minimum feasible cap preserves the optimum, then recover a policy with matching original-constraint lower and family-upper certificates. A general exact LP supplies the same contract and supports overlaps.

Evidence separating choice from execution (Sections V–VI). All 86 recovered synthetic gains require different policies. Paired studies identify lower group-average cost from exact-term retention across objectives, with answers and solver paths fixed; Coat connects family certificates to concrete policy changes and catalogue queries.




Fig. 1. One view, two query modes. (a) Intervals and group means jointly constrain four unknown success probabilities. (b) Q2 reuses evidence; Q3 needs a new solve. (c) Matching policy-lower and family-upper bounds certify the optimal robust guarantee, not the actual effect. All certificates are independently checked against original constraints. Teaching values are rounded; exported proofs retain exact represented inputs.

Table I separates the three questions and the evidence needed to answer each.

II. The Query and Its Statistical Contract

Here m describes uncertain means, c encodes a policy change, and a certificate proves its bound. We define the query, build its shared feasible set (Section III), then compute checkable answers (IV).

A. Target, tables, and declarations

Let $X \in \{1, \dots, K\}$ be a context, $A \in \{1, \dots, L\}$ an action, and $Y \in \{0, 1\}$ an outcome; $Y(a)$ is the outcome under assignment to a, and $d = KL$. Sources O and R are observational and randomized. Target means are $m^O_{xa} = \mathbb{E}_O[Y(a) \mid X = x]$; experimental means are $m^R_{xa} = \mathbb{E}_R[Y(a) \mid X = x]$. For context weights w, policy π and reference π_0, the target contrast is

$$\Delta(c) = \sum_{x,a} w_x(\pi_{xa} - \pi_{0,xa}) m^O_{xa} = c^\top m^O. \tag{1}$$

Here $c_{xa} = w_x(\pi_{xa} - \pi_{0,xa})$ is the weighted change in action probability. Each policy row and w is a probability distribution, specified by the caller. Queries ask whether gain exceeds δ (usually $.001 = 0.1$ pp) for every allowed m; proofs bind c and δ. Uncertainty in estimated weights is outside this contract.

Flatten the context–action pairs into coordinates $i = 1, \dots, d$. The view stores per-action intervals $\ell \le m \le u$ and J group constraints $a \le Tm \le b$. Each row of T weights an action group; a_j, b_j bound its weighted mean. In Fig. 1, the two rows average A/C and B/D. Thus a view is a feasible set, not a point prediction or a table of independent intervals.

Within each source, events (x, a, y) are iid; panels require user-level treatment (Section VI-D). Write N^s_{xay} for counts, $N^s_{xa} = \sum_y N^s_{xay}$ and $S^s_{xa} = N^s_{xa1}$. Randomization requires $A \perp Y(a) \mid X$ and known $q_{xa} = P_R(A = a \mid X = x) > 0$ on moment supports. A union bound permits dependence across sources and rows.

Fix contexts, target, source assumptions, moment rows, sensitivities and confidence allocation before inference, optionally using independent design data. Objectives and thresholds may adapt; new snapshots or confidence constructions require another guarantee.

B. Observational information without a fitted logger

Observed success $p_{xa} = P_O(Y = 1 \mid x, a)$ differs from target mean m^O_{xa}. Let U collect unobserved factors and e_O denote exposure probabilities. Consistency, ignorability conditional on (X, U) and latent overlap give the normalized outcome-conditional weight

$$r^*(x, a, y) = \mathbb{E}_O\left[\frac{e_O(a \mid x)}{e_O(a \mid x, U)} \middle| x, a, y\right],$$
$$m^O_{xa} = \mathbb{E}_O[r^* Y \mid x, a]. \tag{2}$$

Declare $1/\Lambda \le r^* \le \Lambda$, $\Lambda \ge 1$. Larger Λ permits more confounding and hence wider uncertainty. This bounds an outcome-conditional average, not propensity odds or every latent weight. No propensity model is supplied; data alone do not justify this sensitivity parameter [4].

For binary outcomes the conditional-weight relaxation has the known exact interval image [5, Eq. (9)]:

$$L_\Lambda(p) = \max\{p/\Lambda, 1 - \Lambda(1 - p)\},$$
$$U_\Lambda(p) = \min\{\Lambda p, 1 - (1 - p)/\Lambda\}. \tag{3}$$

TABLE I
THREE QUESTIONS OVER ONE FIXED VIEW. GUARANTEES CONCERN EVERY ALLOWED MEAN VECTOR; THEIR FAILURE DOES NOT ESTABLISH A NONPOSITIVE ACTUAL EFFECT.

Question	Returned answer	Independently checked evidence and route
Does this policy guarantee gain $> \delta$?	True, false, or unknown	A dual lower bound or feasible counterexample, obtained by reuse or a fixed-objective solve; overlapping groups allowed.
What is the best robust improvement?	Capacity $\mathcal{R}$ and an attaining policy	Matching policy-lower and family-upper certificates. Our direct construction handles disjoint nonnegative groups; a general exact LP also handles overlaps.
Can every such guarantee be ruled out?	Exclusion when a family upper bound is $\leq \delta$	One feasible point and its maximum contrast over all policies. Full optimization is unnecessary if this witness suffices.

Normalization gives $\mathbb{E}[r^* \mid x, a] = 1$, hence $r_1 = m/p$ and $r_0 = (1-m)/(1-p)$ for $0 < p < 1$. Bounding both yields (3), exact for this relaxation [6].

Consistency provides additional information. The same table also implies

$$P_O(A = a, Y = 1 \mid x) \leq m^O_{xa} \leq 1 - P_O(A = a, Y = 0 \mid x). \tag{4}$$

Both fusion and OBS must include these joint-count constraints. With exposure .8 and $p = .5$, they give $[.4, .6]$, versus $[.25, .75]$ from $\Lambda = 2$ alone, without fitting propensities. This changes a substantive baseline comparison (Section VI-C).

C. Which randomized information transfers?

An analyst may declare a jacket-type average stable across sources while individual item means change. Row j selects context x_j, actions S_j and nonnegative weights ν_{ja} summing to one. The normalized matrix H has $H_{j,(x_j,a)} = \nu_{ja}$ on this group and zero elsewhere. It is the exact row-normalization of stored T, fixed before inference (III-C). The declaration is

$$\tau_j = (Hm^R)_j, \qquad |(Hm^O)_j - \tau_j| \leq \rho_j. \tag{5}$$

The tolerance ρ_j permits source differences in a normalized group mean, separately from sampling error; zero requires equal group means. Within a two-action group with positive weights, individual means can change by $(h, -\nu_1 h/\nu_2)$ while preserving that average. Thus agreement on a group does not establish agreement for every action.

With exact population group means and zero tolerance, $c = H^\top v$ implies $c^\top m = v^\top \tau$: the query is a weighted sum of known group means. Finite samples replace τ by intervals. Components outside this row span can remain variable within the box. Full cell transport ($H = I_d$, $\rho = 0$) is stronger; Coat includes its direct-evaluation control.

III. BUILDING ONE CONFIDENCE VIEW

We intersect simultaneous source intervals into one set covering all target means together. Later policy choices reuse this statistical guarantee.

A. Observational intervals and an explicit budget

Here a confidence *budget* is permitted failure probability, not sample size. Split $\alpha = \alpha_O + \alpha_R$ between sources. Of α_O, half covers d two-sided Clopper–Pearson (CP) intervals [7] $[p^-_{xa}, p^+_{xa}]$, each at $\alpha_O/(2d)$. The other half covers $2d$ one-sided joint-event bounds in (4), each at $\alpha_O/(4d)$, with denominator $N^O_x = \sum_{a,y} N^O_{xay}$. Denote their lower endpoints g^1_{xa}, g^0_{xa}. Then

$$\begin{aligned} \ell_{xa} &= \max\{L_\Lambda(p^-_{xa}), g^1_{xa}\}, \\ u_{xa} &= \min\{U_\Lambda(p^+_{xa}), 1 - g^0_{xa}\}. \end{aligned} \tag{6}$$

Monotonicity makes propagation conservative. Conditional binomial coverage permits random stratum counts. Empty action cells contribute $[0, 1]$; empty contexts add no joint restriction. The union bound permits interval dependence.

B. Two prespecified randomized constructions

Allocate α_R to one route, chosen before outcomes: first bound individual experimental means and average their intervals, or directly bound the group's score average. The former is used in the synthetic primary comparison; Coat reports both.

Projected cell intervals. Construct simultaneous binomial intervals $[r^-_i, r^+_i]$ for every randomized cell appearing in H, splitting α_R across those cells. Nonnegativity of H gives normalized group intervals $[Hr^-, Hr^+]$. Only these *group* intervals enter (5); individual experimental means are not equated to target means. Selecting the tighter route after seeing data is not covered by either individual budget.

Group scores. Conditional on an event falling in (x_j, S_j), define $q_j(a) = q_{x_j a}/\sum_{b \in S_j} q_{x_j b}$ and $Z_j = \nu_{jA} Y/q_j(A)$. Then $\mathbb{E}[Z_j] = \tau_j$ and $0 \leq Z_j \leq B_j = \max_a \nu_{ja}/q_j(a)$. Its count, sum and squared sum are obtained from N^R_{xay}, since $Y^2 = Y$. If every score multiplier $\nu_{ja}/q_j(a)$ equals one on S_j, then $Z_j = Y$ and we use a binomial interval. Otherwise, for $n_j \geq 2$, the two-sided empirical Bernstein interval [8] has half-width

$$h_j = \sqrt{\frac{2\widehat{\mathrm{Var}}(Z_j)\log(4/\beta_j)}{n_j}} + \frac{7B_j \log(4/\beta_j)}{3(n_j - 1)}. \tag{7}$$

Here $\beta_j = \alpha_R/J$, and the sample variance uses $n_j - 1$. The two terms account for observed score variation and its bounded range. Clip the expectation interval to $[0, 1]$; insufficient observations use the full range. The union bound covers overlapping groups sharing events.

C. Preserving the statistical meaning in stored coefficients

The statistical model describes normalized averages; the checker receives stored numbers. These must describe the

same problem. It interprets every stored double-precision (binary64) coefficient as an exact rational. Five stored values of .2, for example, sum to $1 + 2^{-54}$, not one. Treating this row as exactly normalized would break the link to coverage.

For nonzero T_j, its exact mass $\kappa_j = \sum_i T_{ji}$ defines $H_{ji} = T_{ji}/\kappa_j$ and $T_j m = \kappa_j H_j m$; zero rows impose deterministic zero constraints. Assignment probabilities are either exact or explicitly normalized nonnegative design weights. Their match to the data-generating assignment law is assumed, not established by normalization.

For a covered normalized interval $[\tau_j^-, \tau_j^+]$ and a normalized transport tolerance ρ_j, store

$$a_j = \operatorname{down}\big[\kappa_j(\tau_j^- - \rho_j)\big], \quad b_j = \operatorname{up}\big[\kappa_j(\tau_j^+ + \rho_j)\big]. \tag{8}$$

Projected intervals use exact $T_j r^-$ and $T_j r^+$, expanded by $\kappa_j \rho_j$. Observational endpoints, complements, score moments and normalization are computed rationally and rounded outward once at the endpoint. Exact empty intervals are refused before rounding. CP quantiles and the entire floating-point Bernstein half-width kernel (arithmetic, logarithms and square roots) remain trusted; neither these routines nor the scientific declarations are formally verified.

Policy encoding is separate. If ideal rational c^* is stored as c, let $e = c^* - c$. For a checked bracket $[L, U]$ on the stored *minimum* gain, $0 \le m_i \le 1$ gives the conservative ideal-policy bracket

$$[L + \sum_i \min(e_i, 0),\ U + \sum_i \max(e_i, 0)]. \tag{9}$$

The additions and threshold test are exact; a positive stored bound need not certify an ideal zero-margin query. Fixed-query timings (V-D) use stored contrasts, family queries (V-B) exact probabilities, and Coat (VI-D) both with (9) as needed.

D. Coverage and permitted reuse

Choose $\alpha_O + \alpha_R = \alpha$; fusion uses equal halves in our studies. With endpoints mapped as in (8), save

$$\widehat{\mathcal{C}} = \{m : \ell \le m \le u,\ a \le Tm \le b\}. \tag{10}$$

The exact worst-case bound is $V(c) = \min_{m \in \widehat{\mathcal{C}}} c^\top m$: minimize the policy's gain over every mean vector the view permits. Statistical coverage concerns whether the true vector is in this set; exact checking concerns the optimization over the stored set.

Theorem 1 (One event, all objectives): Under the source and sampling conditions in Section II, $P(m^O \in \widehat{\mathcal{C}}) \ge 1 - \alpha$. On that event, every linear objective, including one chosen adaptively from previous answers, satisfies $V(c) \le c^\top m^O$. Any verified lower approximation to $V(c)$ shares this inequality. A method that cannot establish a usable view or bound makes no positive assertion.

Proof. Conditional on independent design information, interval coverage averaged over stratum counts and monotone mapping cover the box at $1 - \alpha_O$. Prespecified randomized intervals cover Hm^R at $1 - \alpha_R$; transport and outward mapping give target moments. A union bound covers m^O at $1 - \alpha$. On that event, minimizing over the view bounds every objective simultaneously, including adaptive choices. Weak duality extends this to checked lower bounds. □

Reuse retains the statistical design [9], [10]. View identity binds count digests, confidence allocation, assignment design, radius, tolerances and matrix; protocols retain provenance.

E. Separating information gain from confidence cost

Fusion narrows a fixed box but divides its confidence budget. Let $\mathcal{B}_\alpha \subseteq \mathcal{B}_{\alpha/2}$ be full-budget OBS and fusion's observational box, with minima $B_\alpha, B_{\alpha/2}$. For nonempty $\mathcal{C}_F = \mathcal{B}_{\alpha/2} \cap \{a \le Tm \le b\}$, its optimum obeys

$$V_F - B_\alpha = \underbrace{(V_F - B_{\alpha/2})}_{G \ge 0} - \underbrace{(B_\alpha - B_{\alpha/2})}_{P \ge 0}. \tag{11}$$

Fusion improves the full-budget observational bound exactly when its constraint gain G exceeds its budget cost P.

Proposition 1 (A checkable zero-gain condition): Let $F_c = \arg\min_{m \in \mathcal{B}_{\alpha/2}} c^\top m$. Then $G = 0$ if and only if F_c contains a point satisfying all randomized group constraints. If F_c is a singleton, checking its moment rows decides whether $G = 0$ or $G > 0$.

Proof. A feasible box minimizer attains the box bound in $\mathcal{C}_F$. Conversely, compactness of nonempty $\mathcal{C}_F$ gives an optimizer; equality places it in F_c, and disjointness forces a strict gap. □

Choose box endpoints by the signs of c and check the group rows. A feasible point proves zero constraint gain; if zero coefficients leave multiple minimizers, failure of one point is inconclusive. Section VI-C applies this fixed-view diagnostic to actual losses.

IV. Query Execution and Verification

Execution separates a materialized view, an evidence *producer*, and an independent *receiver*. Fixed-policy queries try reusable bounds before a persistent LP (A–C); family queries find the best robust policy or exclude gains above a threshold (D–E). The receiver checks proposed evidence against the caller's view. True certifies the requested gain; false exhibits an allowed case that fails it; unknown means the evidence cannot decide.

A. Materialization and lower evidence

For independent binary events, each source's $2d$ counters determine its score moments and, with fixed declarations, its constraints. Aggregation costs $O(n_O + n_R)$ work and $O(d)$ storage; new objectives require no rescan. User panels additionally require group-score variances (Section VI-D).

A usable view requires an exactly checked feasible point, proposed by the solver or slack maximization. Otherwise its status is `uncertain`: no certificate or decision (mathematically unknown). This gate prevents empty-view certification but neither proves emptiness nor reliably accepts zero-volume sets.

The certificate supplies nonnegative weights η_L, η_U for lower and upper group constraints. These *dual prices* reduce

the objective to a constant plus independent per-coordinate terms. With $z = c + T^\top(\eta_U - \eta_L)$, weak duality gives

$$D(c;\eta) = a^\top \eta_L - b^\top \eta_U + \sum_i \min\{z_i \ell_i, z_i u_i\} \le V(c). \quad (12)$$

Each minimum chooses the cheaper endpoint of one interval. Subtracting lower and adding upper constraints cannot increase a feasible objective, so this sum is a checked lower bound. Any nonnegative weights are valid; better weights tighten the answer [11].

The standard-library checker uses represented coefficients exactly and rounds the final bound downward. Proofs bind objective, threshold and view digest; the caller supplies the trusted view. Nonfinite or failed proposals cannot authorize success. Independent optimization certificates are established [12].

B. Reusing exact terms

Reuse retains nonnegative constraint weights, reinserting the new c into the box minimum. Scaling affects tightness, not validity; fixed group terms need not be recomputed. A bounded first-in, first-out (FIFO) bank stores each dual divided by its old objective's binary64 ℓ_1 norm; the new norm supplies scale s. Zero old norm skips insertion; zero new norm sets $s = 0$. Floating scores order candidates, but checking uses the exact saved base–scale product. Retain $k = a^\top \eta_L - b^\top \eta_U$ and $r = T^\top(\eta_U - \eta_L)$. For nonnegative represented s,

$$D(c; s\eta) = sk + \sum_i \min\{(c_i + sr_i)\ell_i, (c_i + sr_i)u_i\}. \quad (13)$$

Setup costs $O(\mathrm{nnz}(T) + d + J)$ rational operations, later checks $O(d)$, with coefficient-dependent bit costs. Separately rounded multipliers can change last bits. A fresh receiver reconstructs (13); view/base-bound state is reconstructed or bypassed on validation failure. Dual and bounded-Lagrangian reuse are established [13], [14], [15]; persistent LP reoptimization supplies a control [16].

In the decimal example, Q1 supplies $\eta_L = (.2, .2), \eta_U = 0$, so $k = .27$ and $r = (-.1, -.1, -.1, -.1)$. Q2 has $c = (-.105, -.09, .105, .09)$ and scale .975, yielding .006375 in (13); its optimum .0105 is unnecessary for the .001 test. Q3 has $c = (-.05, -.15, .15, .05)$ and scale 1, yielding $-.0225$; a new solve gives .005. Reuse transfers constraint weights, while feasible points provide upper bounds.

C. Thresholds, screening and fallback

A checked feasible point brackets the optimum [17, Sec. 5.5.1]:

$$L(c) \le V(c) \le U(c) = c^\top \widetilde{m}. \quad (14)$$

Return true for $L > \delta$, false for $U \le \delta$, and unknown otherwise. False exhibits failure permitted by the view, not failure of the actual effect; a nonpositive lower bound alone decides nothing. Artifact status `unresolved` means no positive lower certificate and can accompany either false or unknown; the decision field distinguishes them. View witnesses and previous solver points remain feasible after objective changes. Check global feasibility before retention, round later dot products upward, and export the point bound to its view and objective for independent verification.

The path is: validate the view, check ordered reusable bounds, decide if possible, otherwise call the LP and check its evidence. Candidates start with zero dual, last native dual, initial feasible point and last native point. Histories retain at most 16 candidates of each enabled kind, including the last; reuse hits do not replace native last-result state. Native dual-simplex cutoff proposals [18] undergo exact checking; undecided requests resume without the cutoff and may remain unknown. Checked native duals update the bank; zero-dual answers are not dual reuse.

An objective cache reuses a result for the *same* c; the candidate bank reuses constraint weights for *new* c. Retention caches their exact k, r terms. Screening instead asks cheaply whether a candidate could decide the query, using outward binary64 intervals. It defers a lower candidate when its upper endpoint is $\le \delta$, or a primal candidate when its lower endpoint is $> \delta$. All operations expand outward; overflow or unbounded intervals take the exact path. Screening alone cannot authorize an answer.

True can bypass insufficient deferred lowers. Before false, replay all deferred lowers to preserve the best exported lower; before solving, replay all remaining candidates in order. Evidence, native state and solver paths must match the unscreened plan. Only zero dual before last-dual true, or initial primal before last-primal false, can be permanently omitted. Complete service cost determines whether these omissions pay.

Structural controls use box endpoints, continuous knapsack for single rows [19], or sparse HiGHS for overlaps [20]; only the reconstructed global dual is certified.

D. Certifying a whole policy family

We now optimize over policies. Here $\mathcal{C}$ is the fixed view; w^*, π_0^* mark exact input probabilities, while m^*, π^* will denote returned optimizers. The family Π contains all randomized policies on the available actions. Its *capacity* is the largest worst-case improvement attainable by any policy. Fix a nonempty compact convex view $\mathcal{C} \subseteq [0,1]^{KL}$, exact probability weights $w^* \ge 0$, $\sum_x w_x^* = 1$, and reference $\pi_0^* \in \Pi$. Define

$$\mathcal{R}(\mathcal{C}) = \max_{\pi \in \Pi} \min_{m \in \mathcal{C}} \sum_{x,a} w_x^* (\pi_{xa} - \pi_{0,xa}^*) m_{xa}, \quad (15)$$

$$F(m) = \sum_x w_x^* \left[\max_a m_{xa} - \sum_a \pi_{0,xa}^* m_{xa} \right]. \quad (16)$$

The inner minimum in (15) gives one policy's worst allowed case; the outer maximum chooses the best such policy. The reference makes $\mathcal{R} \ge 0$. At one allowed m, $F(m)$ chooses the best action per context. Every checked $m \in \mathcal{C}$ gives $\mathcal{R}(\mathcal{C}) \le F(m)$: each policy's minimum is at most its payoff at this point, whose policy maximum is $F(m)$. Thus $U(c)$ evaluates one policy, while $F(m)$ maximizes over policies

at that point. The latter bounds the best robust guarantee; $F(m) \le \delta$ excludes all guarantees above δ. The witness need not equal the true means; it does not bound actual effects.

Proposition 2 (Zero capacity in a fixed view): $\mathcal{R}(\mathcal{C}) = \min_{m\in\mathcal{C}} F(m)$. If all $w_x^* > 0$ and $\pi^*_{0,xa} > 0$, then $\mathcal{R}(\mathcal{C}) = 0$ exactly when $\mathcal{C}$ contains a vector constant across actions within every context.

Proof. Compact convex domains and a continuous bilinear payoff permit minimax exchange [21]; row maximization gives F. Its nonnegative summands, under strict positivity, vanish exactly at constant rows. Compactness attains the minimum. □

Without strict positivity, constant points remain sufficient for zero capacity, but the converse need not hold.

For nonnegative single-context moment rows, even overlapping ones, form

$$I_x = [\max_a \ell_{xa}, \min_a u_{xa}] \cap \bigcap_{j:x_j=x} [a_j/\kappa_j, b_j/\kappa_j].$$

Here $\kappa_j = \sum_i T_{ji} > 0$; zero rows require $a_j \le 0 \le b_j$. Choose one $v_x \in I_x$ per context, set every $m_{xa} = v_x$, and check the original constraints. This *constant-action witness* proves zero capacity without optimizing. Under the proposition's positivity conditions, an empty intersection proves $\mathcal{R} > 0$, not $\mathcal{R} > \delta$ for positive δ.

Partial evidence can bracket the family without full optimization. The maximum of checked lower bounds for any legal policies, together with the reference's zero, is $L_{\text{saved}} \le \mathcal{R}$. A nonempty set M_{saved} of checked points gives $U_{\text{saved}} = \min_{m\in M_{\text{saved}}} F(m) \ge \mathcal{R}$. Share them only for identical $\mathcal{C}, w^*, \pi_0^*$. Then $L_{\text{saved}} > \delta$ certifies existence, $U_{\text{saved}} \le \delta$ excludes it, and otherwise the family remains unresolved. Equation (18) separates certificate slack from restricted policy choice.

E. Exact capacity for partitioned moments

For one context, $F(m)$ is the largest action mean minus the reference payoff. Minimax therefore asks us to minimize $t - p^\top m$, with $m_i \le t$ and reference probabilities $p = \pi^*_{0,x}$. Our construction has two tasks: find the smallest family upper bound, then recover a policy attaining it. For disjoint groups, the first task reduces to capping means and allocating below that cap. The second recovers a proof using the *original* constraints, so the auxiliary cap cannot silently narrow the guarantee. Minimax and continuous allocation are classical ingredients [22], [23].

Theorem 2 (An attaining policy with an original-view certificate): Let $\mathcal{C}$ be a nonempty rational box-and-moment view with $0 \le \ell \le u \le 1$. Suppose every nonzero moment row is nonnegative, belongs to one context, and has positive support disjoint from every other row. For any rational probability weights w^* and reference policy π_0^*, including zero entries, the three-step construction returns $m^* \in \mathcal{C}$, $\pi^* \in \Pi$ and nonnegative original-row multipliers η_L, η_U such that, with $c^*_{xa} = w^*_x(\pi^*_{xa} - \pi^*_{0,xa})$,

$$D(c^*;\eta) = c^{*\top} m^* = F(m^*) = \mathcal{R}(\mathcal{C}).$$

The dense implementation uses $O(dJ + d^2)$ exact arithmetic/comparison operations; the independent receiver uses $O(dJ + d)$. These are unit-cost rational-operation counts, excluding coefficient-dependent bit costs, encoding and hashing.

The certificate closes the gap between a policy we can achieve and a family bound no policy can exceed: $D(c^*;\eta) \le \min_{m\in\mathcal{C}} c^{*\top} m \le \mathcal{R} \le F(m^*)$. Equal checked endpoints prove optimality independently of how the producer found them. Check the domain before construction; reject unsupported rows. Zero rows require $a_j \le 0 \le b_j$ and receive zero multipliers. Ties use index order. The following three steps establish the theorem.

Step 1: Find the smallest feasible cap.

Within this algorithm, $p = \pi^*_{0,x}$ is the reference distribution, distinct from observed success p_{xa}. Write $\ell \le m \le u$ and $a_j \le T_j m \le b_j$. Set

$$t_\ell = \max_i \ell_i, \qquad g_j(t) = \sum_i T_{ji} \min(u_i, t),$$
$$t_0 = \min\{t \ge t_\ell : g_j(t) \ge a_j \quad \forall j\},$$
$$h_i = \min(u_i, t_0).$$

For nonzero rows, g_j is piecewise linear between rational upper-box breakpoints. The largest required root, or t_ℓ, determines t_0; only lower moments force it upward. Nonemptiness gives $T_j\ell \le b_j$. Disjoint groups independently choose mass in $[\max(a_j, T_j\ell), \min(b_j, T_j h)]$, so $\mathcal{C} \cap [\ell, h]$ is nonempty. Every point in this intersection has maximum t_0 by minimality; the entire box need not be feasible.

Minimum-cap sufficiency. For feasible m with $t = \max_i m_i$, clipping to $v_i = \min(m_i, t_0)$ preserves lower boxes and upper moments. Restore violated lower moments within $[v, h]$ to $a_j \le b_j$. The cap permits these repairs; disjoint supports prevent interference, giving feasible $v' \ge v$. Since p sums to one, $p^\top(m - v) \le t - t_0$, hence

$$\max_i v'_i - p^\top v' \le t_0 - p^\top v \le t - p^\top m.$$

Thus maximizing $p^\top m$ within this cap minimizes the original gap.

Step 2: Allocate means within the cap. With the largest mean fixed at t_0, maximizing reference payoff $p^\top m$ minimizes the family upper bound. These are mean values, not policy probabilities. Increasing m_i by ϵ costs group mass $T_{ji}\epsilon$ and gains $p_i\epsilon$. Starting at ℓ, fill each nonzero row in decreasing p_i/T_{ji} order on $T_{ji} > 0$, to total mass $\min(b_j, T_j h)$; uncovered coordinates take h_i. Thus the added mass is $\min(b_j, T_j h) - T_j\ell$. Nonnegative weights justify filling even zero-ratio coordinates, and the total meets the lower bound.

The upper price λ_j is zero when $b_j \ge T_j h$, including equality. Otherwise, use the largest support ratio if $b_j = T_j\ell$, or the last ratio receiving positive mass, including exact boundary exhaustion. This covers fixed coordinates and zero probabilities. The residual $\xi = p - T^\top\lambda$ is reference payoff after these group charges. Allocation satisfies

$$\xi_i > 0 \Rightarrow m_i^* = h_i, \quad \xi_i < 0 \Rightarrow m_i^* = \ell_i,$$
$$\lambda_j(b_j - T_j m^*) = 0.$$

Step 3: Recover the policy and original-row prices. Steps 1–2 give a family upper bound, not yet a robust policy. B ties for best at $m^* = (.6, .7, .7, .7)$, yet the allowed vector $(.6, .6, .7, .8)$ gives pure B a $-.075$ gain. Step 3 must match the family bound with an original-constraint policy lower bound. We need a probability vector supported on maximizers of m^* and prices making the original-box bound (12) tight there. The initial policy cancels positive residuals at capped coordinates; a tight original constraint supplies missing probability mass. Initialize

$$\widetilde{\pi}_i = (\xi_i)_+ \mathbf{1}\{u_i \geq t_0\}, \qquad D_\pi = 1 - \sum_i \widetilde{\pi}_i \geq 0.$$

Here $0 \leq \widetilde{\pi}_i \leq p_i$, with positive mass only at maximum coordinates. The original-box coefficient $z_i^{\text{init}} = \widetilde{\pi}_i - \xi_i$ is positive only at ℓ_i and negative only at u_i: below the cap $h_i = u_i$; elsewhere policy mass cancels positive residuals.

If $t_0 = t_\ell$, add D_π to a coordinate with $\ell_i = t_0$ and set all lower prices η to zero; its box coefficient increases at this lower endpoint. Otherwise choose the first row attaining its lower bound at t_0. Since $T_j h = a_j$, its supported means must equal h_i, and zero-price priority gives $\lambda_j = 0$, even if its upper moment is also tight. Set

$$E = \{i : T_{ji} > 0,\ u_i \geq t_0\}, \qquad s = \sum_{i \in E} T_{ji} > 0,$$

where positivity follows because otherwise this row would attain its bound below t_0. Set $\eta_j = D_\pi / s$, with other lower prices zero. Add $\eta_j T_{ji}$ to $\widetilde{\pi}_i$ on E. Updated box coefficients are zero on E and $-p_i - \eta_j T_{ji} \leq 0$ elsewhere in this row, where $m_i^* = h_i = u_i$; other coefficients are unchanged. The non-strict $u_i \geq t_0$ includes roots at breakpoints.

The completed π sums to one and selects maximum coordinates. With $z = \pi - p + T^\top(\lambda - \eta)$, box signs and tight priced rows make (12) exact for $c = \pi - p$ and $(\eta_L, \eta_U) = (\eta, \lambda)$:

$$\begin{aligned} D(\pi - p; (\eta, \lambda)) &= (\pi - p)^\top m^* \\ &= t_0 - p^\top m^*. \end{aligned}$$

Scale each context's objective and both row-price types by the same w_x^*. Concatenation yields original-program lower $= F(m^*) = \mathcal{R}(\mathcal{C})$, including zero-weight contexts. Such contexts still require a feasible point and a legal policy; only their objective and multipliers vanish.

The receiver checks original constraints, legal policy probabilities, multiplier signs and lower/objective/upper equality against the caller's request. It trusts neither the artificial cap nor the producer's internal state. □

The running example, step by step. Using Fig. 1's decimal inputs, Step 1 gives $t_0 = .7$. Step 2 gives $m^* = (.6, .7, .7, .7)$ and $\lambda = (0, 0)$. Step 3 starts with $(0, .25, .25, .25)$, adds the missing .25 to C, and returns $\pi^* = (0, .25, .5, .25)$ with $\eta_L = (.5, 0)$ and $\eta_U = 0$. The lower bound $.65(.5) - .6(.5) = .025$ equals the family upper bound $.7 - .675 = .025$. Pure C in Fig. 1 is another optimal policy. This exact decimal illustration explains the construction; measured runs check their own represented inputs.

V. Evaluation Design

The evaluation asks three questions: which decisions complete family queries settle (VI-A), what repeated query execution costs with answers and evidence fixed (VI-B), and what information each source contributes (VI-C). The first is retrospective; the source comparison is registered. Coat tests concrete policy changes and an unchanged query catalogue (VI-D). Complete-solver and new Coat timings use an AMD EPYC 7763, Python 3.12.3 and one CPU/native thread.

A. Fresh worlds and policy design

The registered study draws 48 confounded worlds: $(K, L) \in \{(2, 4), (8, 8), (16, 16)\}$, uniform/skewed randomization and group drift $0/.02$, with four worlds per stratum and five inference samples per world. Twelve additional worlds test near-unit sensitivity. A latent binary factor affects exposure and rewards. Metadata $h_a \in [-.5, .5]$ are fixed without inference labels, but their designed positive reward association limits representativeness. Random groups allow individual shifts while controlling group drift; shifts are not optimized for the evaluation objective.

Inference uses $2{,}000d$ O events and $100d$ or $1{,}000d$ R events. Independent design data use $500d$ O and $100d$ R events. Against a uniform reference, the three policies are: $\mathrm{softmax}(1.5h)$; $\mathrm{softmax}(4\widehat{p}_x)$ with design-R $\widehat{p}_{xa} = (S_{xa} + .5)/(N_{xa} + 1)$; and the design-view choice with the largest checked positive lower bound among twelve tilts. The tilts use linear or alternating action scores and slopes $\{-2, -1, -.5, .5, 1, 2\}$; ties retain the first positive maximum, and otherwise the reference. Design outcomes never enter inference counts. We compare $\Lambda = 2$ with an oracle boundary computed from simulator truth and rounded upward. This diagnostic preserves counts and policy rules, but the design-selected policy can vary with radius; it does not isolate a radius effect or replace the registered comparison.

The primary endpoint compares projected fusion with certification by either full-α OBS or projected R, for the metadata policy, low R budget and $\Lambda = 2$. Average paired certification differences within each of 48 independent worlds. Their values lie in $[-1, 1]$, so the one-sided 95% Hoeffding lower bound is the mean minus $\sqrt{2\log(20)/48}$. The registered target requires this endpoint > 0.05. Other settings and the stratified t interval are descriptive; the standalone union is a comparator, not a jointly calibrated decision rule.

B. Whole-family queries on fixed views

The retrospective family study reuses the 48 main worlds and the stored threshold for .001. Its 24 comparison cells are three source constructions (OBS, projected R, projected Fusion) × two R sample budgets × two radii × finite/population information. Each cell retains 48 worlds × five repetitions, giving 5,760 comparison positions, not independent datasets. The underlying 2,880 finite and 288 population program records reduce to 2,160 distinct exact $(\mathcal{C}, w, \pi_0)$ requests. Both solvers run each request: 4,320 synthetic calls. Deduplication saves computation without dropping comparison positions.

We decode saved inputs exactly, normalize policy probabilities rationally and recheck each position's three saved duals. Among 240 primary finite-Fusion cases, 12 already have checked policy gains; 121 have checked witnesses constant across actions within each context, with $F(m) = 0$, constructed before complete family optimization. The remaining 107 are the fixed recovery set. This family-level uncertainty differs from a fixed policy lacking a positive lower bound. Theorem 1 permits selection on the inference view; this retrospective analysis is not a new confirmatory or out-of-sample learning test.

C. A complete exact solver and the source of recovery

SoPlex 8.1.0 in rational mode [24], [25], [26] solves the epigraph LP on identical $(\mathcal{C}, w, \pi_0)$, suppressing exact-input stars:

$$\min_{m\in\mathcal{C},t} \sum_x w_x\big(t_x - \pi_{0,x}^\top m_x\big), \qquad m_{xa} \le t_x, \quad t_x \text{ free.} \tag{17}$$

Stationarity of free t_x gives $\sum_a \mu_{xa} = w_x$ for its nonnegative epigraph multipliers. Thus $\pi_{xa} = \mu_{xa}/w_x$ is a policy when $w_x > 0$; use the reference row when $w_x = 0$. Original-row duals and a feasible point complete the partition method's certificate contract. Import/export and checking are exact; neither the construction's answer nor a saved point is supplied.

Two lowest hashes per size cell select 78 unique requests (72 cells, 144 memberships) for three paired rounds in alternating order. Service runs from post-initialization transmission through checked certificates, including construction, verification, serialization and transport; startup, diagnostics and batch totals are separate. Fresh models/workers use one CPU, ten-second service and 8 GiB address-space limits; all phase limits are archived. Failures retain costs and denominators; ratios require complete pairs. Rounds measure machine variation, not independent samples.

Exact optima L_i^* for three normalized contrasts separate certificate transfer from policy choice: 7,762 unique $(\mathcal{C}, c)$ requests and 17,280 slots. Set $L_3^+ = \max(0, L_1^*, L_2^*, L_3^*)$, with zero from the reference. Here L_{saved} is the maximum of zero and saved lower bounds for these same three policies. Then

$$\mathcal{R} - L_{\text{saved}} = \underbrace{L_3^+ - L_{\text{saved}}}_{\text{certificate-transfer gap}} + \underbrace{\mathcal{R} - L_3^+}_{\text{three-policy restriction}}. \tag{18}$$

Both terms are nonnegative. Saved duals solve their stored objectives, but exact policy normalization can loosen transferred bounds. Missing optima leave the decomposition unknown. The 107-case recovery set and threshold remain unchanged.

Natural metadata partitions. Coat gender, jacket type and color each partition 300 items. Separate row families preserve the original 31-row views' exact coefficients, endpoints and confidence allocation. The evaluation includes 144 natural-row subviews, twelve box-only OBS positions, the 60-view grid and one full-cell control: 217 memberships, 125 unique requests. The construction supports 95; the generic LP covers 30 overlapping-row requests too. Subviews relax their parents and cannot increase capacity. Coverage uses each parent's event, without a joint 95% guarantee over all memberships. A feasible common point may exclude every policy; this is not exclusively a family-optimization benefit.

D. Repeated fixed-policy queries

The 63 inputs are three primary 1,000-query streams sharing one connected 512-cell view, 54 geometry streams ($d = 64, 512, 2048$; disjoint/mixed/connected rows), and six source-derived streams. The latter use generated logs with 64 actions: one million O and four million R events, with uniform/skewed assignment. Broader streams have 100 queries each. Nearby queries perturb contrasts; unrelated directions preserve legal policies; $\delta = .001$ throughout. Primary streams emphasize reuse: one solve, 999 hits, all true; broader streams permit all three verdicts. These constructed workloads do not estimate online hit rates; source ingestion is excluded.

Four plans cross interval screening S with cross-query exact-term retention P, sharing native configuration, zero-dual/last-dual/primal order, proof format and receiver. $P = 0$ discards exactly the dual constants and residuals retained by $P = 1$. Optimized plans equally retain view decoding, primal state and within-request objective/box conversion; sparse residuals skip zeros. The nonfactorial last-first bridge uses S_0P_1 arithmetic, checking last before zero while preserving decisions and native opportunities; valid true certificates may differ.

Joint service includes fresh producer/receiver initialization, view validation, queries, failures, native fallback, serialization and persistent FIFO16 receiver verification; disk I/O, compression, network transfer and separate legacy/Fraction audits are excluded. Core plans must match decisions, evidence and native paths.

All inputs undergo one quality pass and five timing rounds (45,000/225,000 responses), with fresh arm-streams, one CPU/native thread and input-independent shuffled order. Equal-weight geometric means within each input group/round retain four conditional factor ratios, their log interaction and four bridge ratios. Input ratios, slow cases, absolute costs, receiver shares and prefixes are archived. Registered checks are descriptive: retention helps without screening; screening helps without retention but costs with retention. Five rounds measure machine variation, not independent workloads.

VI. Experimental Results

A. What complete family optimization adds

Broader policy search changes the fixed-view answer. The 107 previously unresolved primary finite Fusion cases split into 86 above-threshold and 21 at-most-threshold family answers. Exact reoptimization of the same three policies recovers none: all 86 gains require different policies, rather than tighter transferred certificates. The 21 exclusions have $0 < \mathcal{R} \le \delta$, so positivity alone would not justify continuing search. Together with the earlier 12 above-threshold and 121 zero-capacity cases, the totals are 98 and 142 out of 240. Across all 86 recovered cases, the attainable gain has median 0.991 pp, interquartile range $[0.583, 1.549]$ pp and range




Fig. 2. Checked cost and fixed-view recovery. Left: all 234 pairs (78 inputs, three rounds), after worker readiness through verification; startup/cleanup are separate. SoPlex uses the same receiver; offsets separate points. Right: all 107 undecided queries. Tightening rechecks existing policies at ideal objectives; additional family permits different policies. No failures or missing decompositions; rounds describe machine variation, not confidence intervals.

$[0.105, 3.632]$ pp. For every one, the three-policy optimum after including the reference is zero. These are robust guarantees under the same view; the changed input is the policy set, not the information.

Both methods agree on all 2,160 unique synthetic requests (5,760 memberships). Their 4,320 responses, 7,762 fixed-policy optima, 220 Coat calls and 468 timing calls pass independent verification: 12,770/12,770, without timeout or incomplete call (Fig. 2).

Exact answers with dimension-dependent cost. All 234 timing pairs succeed. Across three rounds, the construction/SoPlex geometric-mean service ratios are 0.808–0.835 at $d = 8$, 1.066–1.129 at $d = 64$, and 1.170–1.196 at $d = 256$. The construction is slower in 5/78, 55/78 and 54/78 pairs, respectively. These compare checked service for a Python rational construction and compiled rational LP. Pair costs, certificate sizes, memory observations and failure denominators are archived. Table II reports absolute costs. At $d = 256$, verification alone takes median 144.3/144.6 ms (Part/LP), with about 149.5 kB per certificate. These pooled medians describe evidence cost, not matched-call ratios.

Separating policy choice from source information. At the larger conservative budget, projected R passes 223/240 thresholds versus Fusion's 218/240; R has greater capacity in 128 pairs, Fusion in 100, with 12 ties. At the smaller oracle-boundary budget, OBS and Fusion both pass 239 thresholds, yet OBS has greater capacity in 219 pairs and Fusion in 21. Their full- and split-budget views are not nested. All 24 cells and exact decompositions remain available. In the partition study's 2,880 finite views, the generating means satisfy the view and every returned-policy assertion is correct against the stored truth. These retrospective checks do not establish uniform coverage or validate the source assumptions.

TABLE II
MEDIANS OVER 78 CALLS PER METHOD/DIMENSION. RESPONSE: AFTER WORKER INITIALIZATION THROUGH PROOF CHECKING; CHECK: PER-CALL RECEIVER SHARE; WHOLE: INCLUDES STARTUP/CLEANUP. PART: PARTITION CONSTRUCTION; LP: SOPLEX. KB: 1,000 BYTES.

d	Method	Response ms	Check %	Whole ms	kB
8	Part	4.66	24.4	122.2	3.47
8	LP	4.99	22.1	135.2	3.47
64	Part	53.58	23.2	172.2	20.93
64	LP	40.85	31.6	170.0	20.91
256	Part	648.13	22.8	770.3	149.51
256	LP	419.97	34.6	554.0	149.44

B. *The cost of answering repeated policy queries*

All 270,000 quality and timing responses pass the recorded independent exact replay; the four core plans agree on evidence, decisions and native paths. Figure 3 shows the five optimized rounds. On the three primary streams, retention's joint-cost ratios are 0.735–0.748 without screening and 0.766–0.791 with it. Screening costs 1.103–1.138 and 1.165–1.186 times the corresponding unscreened plans. It also loses in every engine and source-derived group-round mean. Its earlier benefit without retention therefore does not survive optimized arithmetic; only two of the three registered directions hold in every primary round.

The last-first bridge costs 0.833–0.882 times S_0P_1 on primary streams, but is slower in one of their 15 input-round pairs. The corresponding slower counts are 66/270 engine and 17/30 source-derived pairs. Retention also has adverse individual cases despite lower group means. These results




Fig. 3. Retention lowers group-average cost; screening does not. S: screening; P: cross-query retention. Dots: each round's equal-input geometric-mean cost ratio (below one favors enabling the factor). Lines: five-round range, not confidence intervals. All three input groups and four conditional comparisons appear; interaction and last-first comparisons are archived.

TABLE III
CONSERVATIVE, LOWER-BUDGET DIAGNOSIS; 240 QUERIES PER POLICY. FINITE: THE FINITE OPTIMUM FAILS BUT THE POPULATION OPTIMUM PASSES. POP.: THE TRUE EFFECT EXCEEDS δ BUT BOTH OPTIMA FAIL. NO QUERY IS MISSED SOLELY BY NUMERICAL OPTIMIZATION.

Policy	Cert.	Finite	Pop.	True $\leq \delta$
Metadata	12	33	195	0
R heuristic	4	43	190	3
Robust design	2	0	0	238

support retaining reusable exact terms, not default screening or universal speedups; the bridge's changed candidate order is a separate mechanism.

a) Auxiliary execution controls: Under fixed arithmetic, screening plus retention fails the registered joint-cost-ratio target ≤ 0.8 against each feature alone. Screening slows every broader-group round. A larger bank misses its speed target; changed decisions preclude isolated reuse attribution. Materialization helps ingestion, but preparation costs $1.580/1.619$ times hot execution under uniform/skewed assignment, respectively. Full controls remain in the artifact.

C. Source information and query guarantees

All 60 worlds and 1,200 inference configurations complete. Primary fusion certifies 12/240 versus six for the standalone union (OBS six, R zero): six additions, no losses, certification-rate difference 0.025 (2.5 pp). Hoeffding's lower endpoint -0.3283 misses the registered target; its finite-world penalty limits power for modest gains. The descriptive t interval is $[-0.0249, 0.0749]$. All additions occur in two zero-drift 2×4 worlds. This does not confirm the target or establish absence of benefit.

Larger-budget projected fusion certifies 15 metadata queries, 16 heuristic queries and two robust-design selections. More randomized traffic does not resolve transfer or radius uncertainty.

Sampling uncertainty versus ambiguity. Finite views include sampling intervals; population views use exact generating statistics, retaining ambiguity. Among 240 primary queries with true effects above δ, ambiguity blocks 195 and sampling width 33; exact optima exclude optimization failure (Table III). Six additional finite certifications comprise four with sufficient standalone population information and two requiring fusion. Robust design retains the reference in 238/240 lower-budget cases: true effect zero.

Oracle radii use simulator truth. Across four radius/budget settings, fusion adds/loses 6/0, 9/0, 0/2 and 3/1 certifications versus the standalone union. Low-budget oracle metadata achieved gain averages 0.0114 pp versus 0.0913 pp budget cost; their difference changes the bound, not the policy effect. Proposition 1 proves zero optimal gain for 193/240 queries, including both losses; the larger-budget loss has positive gain below cost. All three losses persist at exact optima. Budget streams differ and robust policies can change across radii; fixed-world diagnoses estimate neither sample-size effects nor complementarity frequencies. Full diagnostics remain in the artifact.

a) Standalone-source controls: Observational consistency (4) lets OBS certify 99/100 external 2×2 queries; other policy/view settings differ. KuaiRec's imposed exposures and query-directed randomized means [27] do not establish general complementarity: a 35-setting census finds no true-radius fusion-only case. 400 count/policy pairs remain in the artifact.

The broader audit includes 6,000 inference views: 60 worlds, five repetitions, two R sample budgets, two radii and five constructions. The family's 2,880-view subset uses 48 main worlds and only OBS/projected-R/projected-Fusion. All

14 set misses occur outside that subset; none yields a bound above its true contrast or a false certification. All 18,900 final-mapping proofs (18,000 synthetic, 900 thinned Coat) pass independent checking; seven group-score certifications are unresolved after mapping, while projected statuses are unchanged. Separate design views have one miss in 600. Empirical coverage checks do not prove Theorem 1's assumptions.

D. Real data: inference over user blocks

Coat has 290 users, each supplying 24 self-selected and 16 randomized ratings on 300 items [28]. With one context ($K = 1$), policies sample items for this population, without personalization. Success is rating at least four, not purchase; zero is unobserved. Users, not the 11,600 ratings, are independent. Potential ratings are assumed invariant to within-source order and panel composition; cross-source equality needs an additional assumption.

Gender, jacket type and color define three partitions totaling 31 rows; their combined view overlaps. The twelve declarations are $\Lambda \in \{1, 1.5, 2, 3\}$ and $\rho \in \{0, .02, .05\}$; the primary declaration is $(2, 0)$. Five binary indicators—front-page placement, men's items, fleece, waterproof and black—define fifteen policies $\pi_i \propto t^{h_i}$, $t \in \{.5, 1.5, 2\}$, relative to uniform $1/300$. The primary policy doubles front-page weights and renormalizes over all items. Only those three front-page contrasts lie outside the moment row space.

The main analysis keeps all ratings and assumes R16 simple random subsets independent of potential ratings. The release describes random/uniform selection; unavailable collection code prevents verification. A separate event-interface control samples one rating per source/user without using its value: $q_a = (16/300)/16 = 1/300$. Its 580 events leave 116 empty O and 124 empty R cells; all 900 queries and 15 full-cell controls are unresolved. This diagnoses the cost of discarding panel structure.

O conditional CP uses included users per item; joint CP uses $N = 290$. Uniform thinning divides marginal and latent inclusion propensities by 24, preserving their ratio and conditional ratings. Thus full inclusion strengthens consistency without changing Λ, not just reducing variance. Each active R user averages observed group ratings: under the subset design this is unbiased for their uniform group mean, with activity independent of potential ratings. Conditional on active count, these iid scores lie in $[0, 1]$. Equation (7) uses 72–290 users and variance denominator $n_j - 1$; item histograms cannot recover that variance. Projected intervals use per-item CP. Exact propagation follows (8), adding neither users nor transport evidence.

All 915 fixed-policy lower-bound queries are unresolved, with no refused view. At the primary declaration, group Fusion improves the bound over full-budget R group by 0.309 pp, but neither passes $\delta = .001$ (Table IV). Independent audit reconstructs user statistics, 61 views, 915 proofs and 15 direct controls; it does not establish the source assumptions.

Deciding beyond the tested policies. With the normalized ideal reference $1/300$, complete family optimization resolves all 60 original grid positions: 49 have $\mathcal{R} = 0$, four have $0 < \mathcal{R} \leq .001$, and seven have $\mathcal{R} > .001$. The seven positive declarations represent five unique mathematical requests: OBS at $\Lambda = 1$ repeats across three tolerances; group Fusion passes at $\Lambda = 1$ for all three tolerances and at $\Lambda = 1.5, \rho = 0$. These supply checked policies although the original fifteen-candidate evaluation certified none, conditional on the stated assumptions; there is no joint guarantee across declarations.

TABLE IV
COAT: PRIMARY FIXED-QUERY LOWER BOUNDS (PROBABILITY UNITS; $\Lambda = 2$, $\rho = 0$, $\alpha = .05$; 290 USERS) AND FAMILY COUNTS SUMMING TO TWELVE DECLARATIONS. POSITIVE FAMILY ANSWERS OCCUR OUTSIDE THE PRIMARY DECLARATION. FULL-CELL TRANSPORT IS A STRONGER CONTROL.

Construction	Primary LCB	$\mathcal{R} = 0$	$0 < \mathcal{R} \leq \delta$	$\mathcal{R} > \delta$
OBS	-0.03729	9/12	0/12	3/12
R group	-0.01502	12/12	0/12	0/12
R projected	-0.03402	12/12	0/12	0/12
Fusion group	-0.01193	7/12	1/12	4/12
Fusion projected	-0.03132	9/12	3/12	0/12
R full-cell control	-0.03077	1/1	0/1	0/1

A concrete policy decision. At $\Lambda = 1.5, \rho = 0$, the jacket-type certificate reallocates all 28 vests' uniform mass to item 0, a men's bomber: its probability rises from $1/300$ to $29/300$, the vests receive zero, and 271 items stay at $1/300$. All 15 original and 50 extended catalogue policies retain full support, so none makes this choice. The contrast is $(28/300)(m_0 - \overline{m}_{\text{vest}})$, with $\overline{m}_{\text{vest}}$ the uniform mean of the 28 vests. Its checked lower bound is $(28/300)(\ell_0 - b_{\text{vest}}/\kappa_{\text{vest}})$: the stored row mass κ converts the group constraint to its uniform mean. Only these two terms are nonzero, contributing 2.472638 pp and -2.226283 pp, respectively. Their sum guarantees 0.246355 pp in expected high-rating probability over uniform, exceeding 0.1 pp and matching the full overlapping view's capacity. Matched full-budget OBS and both R views have zero capacity. This retrospective answer assumes confounding no greater than $\Lambda = 1.5$ and no group-mean drift. It neither selects those assumptions from data nor measures purchase uplift; it does not imply every vest is worse.

All five primary $\Lambda = 2, \rho = 0$ views still have zero capacity. In group Fusion, every item mean can equal 0.2186 (rounded), tying every policy with the reference. A checked constant point already supplies this stopping answer; it is not an exclusive benefit of full optimization. The stronger full-cell control also has zero capacity.

The natural gender, jacket-type and color partitions supply 144 memberships: 10 exceed the threshold, 10 have positive capacity at most the threshold, and 124 have zero capacity. The construction and exact LP agree on all 95 unique supported requests across the full evaluation; the LP additionally resolves 30 overlapping requests. Every partition subview has capacity at most its parent's, as required by relaxation. These are dependent views of one dataset, not 144 independent experiments or new evidence for sampling assumptions.

Under full-cell transport, a separate direct control averages all 16 R ratings within each user and applies a one-sided Hoeffding bound ($N = 290$). The primary estimate is 0.00371, with lower bound -0.06452; none of 15 fixed queries passes. These per-query bounds neither support adaptive selection nor validate transport or a zero effect.

a) Catalogue queries with ordinary caching: For each primary Coat view, combine two of the five indicators: $\pi_i \propto t_1^{h_{1i}} t_2^{h_{2i}}$, with $(t_1, t_2) \in \{.5, 1, 2\}^2 \setminus \{(1, 1)\}$. Ten pairs give 80 policy positions at margins $0, .001, .01$ (0, 0.1, 1 pp): 240 requests, 50 distinct objectives and 150 objective–margin pairs. Prepared execution retains exact dual terms; optimized-exact adds sparse arithmetic and cached number conversions. Both share full objective caching and a persistent receiver. Native hot-start retains a solver basis without cross-objective certificate candidates. Quality checks precede three timing rounds.

Prepared and optimized-exact agree on all 1,200 requests, but cost ratios 0.960, 0.941, 0.953 miss the ten-percent target. Optimized-exact is slower in 3/15 view-rounds and retains more estimated exact-state payload in every view (not isolated RSS). Native hot-start changes 98 false answers to unknown and four unknown answers to false; it never reverses a Boolean answer. Thus overall service differs; on R projected, decisions agree and native is faster in all rounds. None certifies improvement, and neither fusion-only information target is supported. The five views have zero capacity, so a constant-action witness can already justify stopping.

b) The cost of family preprocessing: This experiment tests whether family evidence accelerates the unchanged catalogue. A useful policy outside it can coexist with false answers inside it. We repeat the 240 queries on two 16-row jacket-type Fusion views, $(\Lambda, \rho) = (1.5, 0)$ and $(2, 0)$, selected retrospectively with known capacities. Hot-start (Hot), optimized threshold execution (Opt), and Opt with partition (Part) or exact-LP (LP) preprocessing share objective caching, checked points and a rational receiver. Family certificates add only feasible points; a shared constant-action shortcut skips unnecessary family solves. Unresolved represented queries permit one producer attempt per objective–margin pair and one complete exact fallback per objective; ideal answers reuse this evidence without extra solves.

All 32 streams complete, each with 240 false answers under both semantics. On the nonzero-capacity view, Part adds 5.1–7.7% to Opt's full cost without reducing its two native and two exact calls (Table V); LP likewise saves no calls. The zero-capacity control skips family computation. Three rotations describe machine variation; execution positions are not fully balanced. Different optimal points compare complete preprocessing choices. Family answers enable redesign beyond the catalogue but do not amortize preprocessing here.

TABLE V
ORIGINAL COAT QUERIES. TIME: MEDIAN SECONDS OVER THREE ROUNDS, INCLUDING STARTUP, FAMILY WORK, EXTERNAL VERIFICATION AND CLEANUP. RATIO/OPT: PAIRED COST RANGE (ABOVE ONE IS SLOWER). N/E/F: NATIVE/FIXED-EXACT/FAMILY CALLS, IDENTICAL PER STREAM ACROSS QUALITY AND TIMING. BOTH VIEWS USE $\rho = 0$.

View	Plan	Time (s)	Ratio/Opt	N/E/F
$\Lambda = 1.5$	Hot	6.800	0.974–1.009	2/2/0
$\Lambda = 1.5$	Opt	6.934	1.000	2/2/0
$\Lambda = 1.5$	Opt+Part	7.312	1.051–1.077	2/2/1
$\Lambda = 1.5$	Opt+LP	7.276	1.042–1.079	2/2/1
$\Lambda = 2$	Hot	6.329	0.985–0.998	1/1/0
$\Lambda = 2$	Opt	6.390	1.000	1/1/0
$\Lambda = 2$	Opt+Part	6.431	0.999–1.024	1/1/0
$\Lambda = 2$	Opt+LP	6.359	0.990–1.002	1/1/0

VII. RELATED WORK AND SCOPE

Database queries. Causal systems adjust aggregates [1], implement matching [2], define units [29] and explain patterns [30]. Other approaches propagate uncertainty bounds [3] or certify semantic-view predicates from fresh draws [31]. Our source-constrained view supports adaptive objectives under one coverage event and whole-family stopping certificates.

Our view combines binary density-ratio and conditional-moment bounds [5], [6], without latent-model sharpness. Other fusion methods exploit overlap [32], impose experimental moments [33], or estimate sensitivity frontiers [34]. Propensity-odds policy learning [35], [36] makes different restrictions from our outcome-conditional weights. We add direct partition construction and original-constraint certificate recovery in one query interface.

Classical allocation. Continuous maximin sharing [37, Sec. 2.2] solves $\max_{0 \le z \le 1} \min_g \sum_{i \in G_g} v_i z_i$ under one resource budget, recovering capacities and allocations. Its groups partition profits; ours impose disjoint two-sided moments on means. We minimize $\max_i m_i - p^\top m$ per context and recover original-constraint certificates. The general exact LP supplies the same family answer and certificate contract.

Proofs and scope. Filtering [38], assignment caching [39], safe bounds and reuse are established; VIPR checks exact optimization derivations [12]. Unlike IntegriDB [40], our digests authenticate neither data nor freshness. Scope is binary outcomes, known target weights and trusted source/interval routines; continuous covariates, estimated weights and dependent interactions need extensions.

Data ethics. We reanalyze public benchmarks under their release terms, without recruiting or contacting participants. No institutional ethics review was undertaken or additional consent sought.

VIII. CONCLUSION

Q-BRIDGE's materialized confidence view supports repeated, checkable evaluation, redesign and stopping decisions. For disjoint groups, direct construction returns optimal policies and original-constraint certificates. Broader policy choice recovers guarantees unavailable to tested candidates; retaining exact terms reduces group-average execution cost on the tested streams.

Acknowledgments and AI Usage Declaration

OpenAI Codex assisted with drafting and mathematical exposition (Sections I–VIII), code and experiments (III–VI), figures, source retrieval and editing. Computational claims were checked against saved artifacts and citations against primary sources. The authors remain responsible for correctness, originality and the final submission.

References

[1] B. Salimi, J. Gehrke, and D. Suciu, "Bias in OLAP queries: Detection, explanation, and removal," in *Proceedings of the 2018 International Conference on Management of Data*. ACM, 2018, pp. 1021–1035. [Online]. Available: https://doi.org/10.1145/3183713.3196914

[2] B. Salimi, C. Cole, D. R. K. Ports, and D. Suciu, "ZaliQL: Causal inference from observational data at scale," *Proceedings of the VLDB Endowment*, vol. 10, no. 12, pp. 1957–1960, 2017. [Online]. Available: https://www.vldb.org/pvldb/vol10/p1957-salimi.pdf

[3] S. Feng, A. Huber, B. Glavic, and O. Kennedy, "Uncertainty annotated databases—a lightweight approach for approximating certain answers," in *Proceedings of the 2019 International Conference on Management of Data*. Association for Computing Machinery, 2019, pp. 1313–1330. [Online]. Available: https://www.cs.uic.edu/~bglavic/dbgroup/assets/pdfpubls/FH19.pdf

[4] J. Fawkes, M. O'Riordan, A. Vlontzos, O. Corcoll, and C. M. Gilligan-Lee, "The hardness of validating observational studies with experimental data," in *Proceedings of the 28th International Conference on Artificial Intelligence and Statistics*, ser. Proceedings of Machine Learning Research, vol. 258. PMLR, 2025, pp. 1819–1827. [Online]. Available: https://proceedings.mlr.press/v258/fawkes25b.html

[5] J. Dorn, K. Guo, and N. Kallus, "Doubly-valid/doubly-sharp sensitivity analysis for causal inference with unmeasured confounding," *Journal of the American Statistical Association*, vol. 120, no. 549, pp. 331–342, 2025. [Online]. Available: https://doi.org/10.1080/01621459.2024.2335588

[6] K. Ishikawa, N. He, and T. Kanamori, "A convex framework for confounding robust inference," *Journal of Machine Learning Research*, vol. 27, no. 62, pp. 1–53, 2026. [Online]. Available: https://jmlr.org/papers/v27/23-1434.html

[7] C. J. Clopper and E. S. Pearson, "The use of confidence or fiducial limits illustrated in the case of the binomial," *Biometrika*, vol. 26, no. 4, pp. 404–413, 1934. [Online]. Available: https://doi.org/10.1093/biomet/26.4.404

[8] A. Maurer and M. Pontil, "Empirical Bernstein bounds and sample variance penalization," in *Proceedings of the 22nd Annual Conference on Learning Theory*, Montreal, Canada, 2009. [Online]. Available: https://www.cs.mcgill.ca/~colt2009/papers/012.pdf

[9] R. Berk, L. Brown, A. Buja, K. Zhang, and L. Zhao, "Valid post-selection inference," *The Annals of Statistics*, vol. 41, no. 2, pp. 802–837, 2013. [Online]. Available: https://arxiv.org/abs/1306.1059

[10] D. Bertsimas, V. Gupta, and N. Kallus, "Data-driven robust optimization," *Mathematical Programming*, vol. 167, no. 2, pp. 235–292, 2018.

[11] A. Neumaier and O. Shcherbina, "Safe bounds in linear and mixed-integer linear programming," *Mathematical Programming*, vol. 99, no. 2, pp. 283–296, 2004. [Online]. Available: https://arnold-neumaier.at/ms/mip.pdf

[12] K. K. H. Cheung, A. Gleixner, and D. E. Steffy, "Verifying integer programming results," in *Integer Programming and Combinatorial Optimization*, ser. Lecture Notes in Computer Science, vol. 10328. Springer, 2017, pp. 148–160. [Online]. Available: https://arxiv.org/abs/1611.08832

[13] T. Marcucci and R. Tedrake, "Warm start of mixed-integer programs for model predictive control of hybrid systems," *IEEE Transactions on Automatic Control*, vol. 66, no. 6, pp. 2433–2448, 2021. [Online]. Available: https://groups.csail.mit.edu/robotics-center/public_papers/Marcucci19.pdf

[14] H. Kothari and J. R. Luedtke, "Accelerating Benders decomposition for solving a sequence of sample average approximation replications," *Mathematical Programming Computation*, 2026, published online May 23, 2026. [Online]. Available: https://link.springer.com/article/10.1007/s12532-026-00324-3

[15] A. Deza, F. Badilla, and S. S. Dey, "Mixed-integer program sensitivity analysis via branch-and-bound trees," 2026, preprint, version 1, submitted November 3, 2026. [Online]. Available: https://arxiv.org/abs/2611.04415v1

[16] HiGHS developers, "HiGHS documentation: Hot start and python interfaces," Official software documentation, 2026, accessed 2026-11-04; API cross-checked with HiGHS v1.12.0 source and local HiGHS 1.12.0 and 1.15.1 bindings. [Online]. Available: https://ergo-code.github.io/HiGHS/dev/guide/further/

[17] S. Boyd and L. Vandenberghe, *Convex Optimization*. Cambridge University Press, 2004. [Online]. Available: https://web.stanford.edu/~boyd/cvxbook/

[18] HiGHS developers, "HiGHS documentation: List of options," 2026, official documentation, accessed 2026-11-04; option semantics checked against local HiGHS 1.15.1. [Online]. Available: https://ergo-code.github.io/HiGHS/dev/options/definitions/

[19] S. Martello and P. Toth, *Knapsack Problems: Algorithms and Computer Implementations*, ser. Wiley-Interscience Series in Discrete Mathematics and Optimization. Chichester, UK: John Wiley & Sons, 1990. [Online]. Available: https://silvano333.github.io/kp.html

[20] Q. Huangfu and J. A. J. Hall, "Parallelizing the dual revised simplex method," *Mathematical Programming Computation*, vol. 10, no. 1, pp. 119–142, 2018. [Online]. Available: https://doi.org/10.1007/s12532-017-0130-5

[21] M. Sion, "On general minimax theorems," *Pacific Journal of Mathematics*, vol. 8, no. 1, pp. 171–176, 1958. [Online]. Available: https://msp.org/pjm/1958/8-1/pjm-v8-n1-p14-s.pdf

[22] H. A. Eiselt, "Continuous maximin knapsack problems with GLB constraints," *Mathematical Programming*, vol. 36, pp. 114–121, 1986.

[23] T. Kuno, H. Konno, and E. Zemel, "A linear-time algorithm for solving continuous maximin knapsack problems," *Operations Research Letters*, vol. 10, no. 1, pp. 23–26, 1991.

[24] Zuse Institute Berlin, "SoPlex 8.1.0," https://soplex.zib.de/, 2026, released September 2026. Accessed November 6, 2026.

[25] A. M. Gleixner, D. E. Steffy, and K. Wolter, "Iterative refinement for linear programming," *INFORMS Journal on Computing*, vol. 28, no. 3, pp. 449–464, 2016.

[26] A. Gleixner and D. E. Steffy, "Linear programming using limited-precision oracles," *Mathematical Programming*, vol. 183, pp. 525–554, 2020.

[27] C. Gao, S. Li, W. Lei, J. Chen, B. Li, P. Jiang, X. He, J. Mao, and T.-S. Chua, "KuaiRec: A fully-observed dataset and insights for evaluating recommender systems," in *Proceedings of the 31st ACM International Conference on Information & Knowledge Management*. ACM, 2022, pp. 540–550. [Online]. Available: https://kuairec.com/

[28] T. Schnabel, A. Swaminathan, A. Singh, N. Chandak, and T. Joachims, "Recommendations as treatments: Debiasing learning and evaluation," in *Proceedings of the 33rd International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 48. PMLR, 2016, pp. 1670–1679. [Online]. Available: https://proceedings.mlr.press/v48/schnabel16.html

[29] B. Salimi, H. Parikh, M. Kayali, L. Getoor, S. Roy, and D. Suciu, "Causal relational learning," in *Proceedings of the 2020 ACM SIGMOD International Conference on Management of Data*. ACM, 2020, pp. 241–256. [Online]. Available: https://doi.org/10.1145/3318464.3389759

[30] B. Youngmann, M. Cafarella, A. Gilad, and S. Roy, "Summarized causal explanations for aggregate views," *Proceedings of the ACM on Management of Data*, vol. 2, no. 1, pp. 71:1–71:27, 2024. [Online]. Available: https://doi.org/10.1145/3639328

[31] O. Hassanzadeh and D. Subramanian, "Semantic views: Certified reuse of LLM labels across semantic queries," 2026, preprint, version 1, submitted October 8, 2026. [Online]. Available: https://arxiv.org/abs/2610.12768v1

[32] K. Jiang, W. Hu, X. Lai, S. Yang, and X.-H. Zhou, "Improving sensitivity analysis by synthesizing randomized clinical trials with limited overlap," *Statistics in Medicine*, vol. 45, no. 18–19, p. e70637, 2026. [Online]. Available: https://onlinelibrary.wiley.com/doi/10.1002/sim.70637

[33] Y. Du, Z. Zhang, H. Li, C. Fang, J. Xu, Z. Peng, and J. Guo, "Feasible fusion: Constrained joint estimation under structural non-overlap," in *Proceedings of the 43rd International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 306. PMLR, 2026, pp. 26 851–26 885. [Online]. Available: https://proceedings.mlr.press/v306/du26s.html

[34] Q. Lanners, C. Rudin, A. Volfovsky, and H. Parikh, "Data fusion for partial identification of causal effects," in *Advances in Neural Information Processing Systems*, vol. 38. Curran Associates, Inc., 2025, pp. 150 638–150 702. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2025/hash/dd4e79c2228c43954cc074abf2f85a07-Abstract-Conference.html

[35] N. Kallus and A. Zhou, "Confounding-robust policy improvement," in *Advances in Neural Information Processing Systems*, vol. 31, 2018. [Online]. Available: https://proceedings.neurips.cc/paper/2018/hash/3a09a524440d44d7f19870070a5ad42f-Abstract.html

[36] K. Hess, D. Frauen, V. Melnychuk, and S. Feuerriegel, "Efficient and sharp off-policy learning under unobserved confounding," in *International Conference on Learning Representations*, 2026, pp. 57 552–57 587. [Online]. Available: https://proceedings.iclr.cc/paper_files/paper/2026/file/5e972fe492946fc7a02aef64d0f4fd7e-Paper-Conference.pdf

[37] T. Yamada, M. Futakawa, and S. Kataoka, "Some exact algorithms for the knapsack sharing problem," *European Journal of Operational Research*, vol. 106, no. 1, pp. 177–183, 1998. [Online]. Available: https://www.nda.ac.jp/~yamada/paper/98-2.pdf

[38] T. Bartels, V. Fisikopoulos, and M. Weiser, "Fast floating-point filters for robust predicates," *BIT Numerical Mathematics*, vol. 63, 2023, article 31. [Online]. Available: https://doi.org/10.1007/s10543-023-00975-x

[39] C. Cadar, D. Dunbar, and D. Engler, "KLEE: Unassisted and automatic generation of high-coverage tests for complex systems programs," in *USENIX Symposium on Operating Systems Design and Implementation*, 2008. [Online]. Available: https://static.usenix.org/event/osdi08/tech/full_papers/cadar/cadar_html/paper.html

[40] Y. Zhang, J. Katz, and C. Papamanthou, "IntegriDB: Verifiable SQL for outsourced databases," in *Proceedings of the 22nd ACM SIGSAC Conference on Computer and Communications Security*. Association for Computing Machinery, 2015, pp. 1480–1491. [Online]. Available: https://integridb.github.io/IntegriDB.pdf