

Reliable Robotic Manipulation Through Evidence-Grounded Control

Across identical simulation protocols, optimized PID produced the strongest aggregate reliability while no controller dominated every condition.

Problem and research question

Reliable manipulation requires more than nominal trajectory tracking: controllers must remain interpretable under payload, configuration, disturbance, noise, and actuator changes.

Method

A 2-link arm compares manual PID, Mamdani Fuzzy-PID, and bounded optimization-assisted PID under identical 0.001 s simulation, trajectory, torque-limit, threshold, and paired-seed protocols.

Key results

Evidence snapshot: 7.283% nominal objective reduction; 10/13 deterministic scenarios passed; 30/30 vs 0/30 isolated-noise vs combined-stress trials




Figure. Deterministic stress testing separates aggregate controller reliability while preserving failed cases.

Why this matters

The project supplies a transparent low-level execution layer that can sit beneath future perception, language, and task-planning systems.

Simulation scope

Simulation only; no hardware fidelity, collision avoidance, perception, online safety supervisor, or end-to-end embodied-AI implementation is claimed.

Limitations and next steps

Validate on hardware, add calibrated sensing uncertainty, and introduce runtime safety monitoring before deployment claims.

Sources: docs/report/technical_report.md | results/report/report_evidence.json | docs/report/PAPER_CLAIM_AUDIT.md