

PL032GE50K Planetary Gearbox

● General Information

- Ring material: Metal
- Max. Backlash at no-load: $\leq 2.5^\circ$
- Radial play of shaft: $\leq 0.07\text{mm}$
- Axial play of shaft: $\leq 0.3\text{mm}$
- Permissible Load Range: $0.5\text{Nm} \sim 5.0\text{Nm}$



● Specification

	Unit	PL032GE50K-1S	PL032GE50K-2S	PL032GE50K-3S	PL032GE50K-4S
Frame size	mm	$\phi 32$	$\phi 32$	$\phi 32$	$\phi 32$
Reduction ratio		1/3.7, 1/5.2	1/14, 1/19, 1/22 1/27, 1/35	1/49, 1/59, 1/68, 1/82 1/95, 1/115	1/181, 1/218, 1/253, 1/305 1/354, 1/426, 1/495, 1/596
Efficiency	%	90	81	73	66
Number of stages		1	2	3	4
Rated Continuous torque	Nm	0.5	2.0	4.0	5.0
Max. Momentary torque	Nm	1.5	6.0	10.0	12.0
Max. Radial load(10mm from flange)	N	100	100	100	100
Max. Axial load	N	50	50	50	50
Max. Shaft press fit force	N	100	100	100	100
Gearbox Length	mm	25.7	32.8	39.7	46.6
Weight	g	120	156	189	222
Max. Backlash at no-load	$^\circ$	2.5	2.5	2.5	2.5
Operating Temperature	$^\circ\text{C}$	-15 ~ +80			
Recommend input speed	rpm	<10000			

● Mechanical

