

PL042GF150K Planetary Gearbox

● General Information

- Ring material: Powder metal
- Max. Backlash at no-load: $\leq 2.5^\circ$
- Radial play of shaft: $\leq 0.06\text{mm}$
- Axial play of shaft: $\leq 0.3\text{mm}$
- Permissible Load Range: 1.5Nm~15.0Nm



● Specification

	Unit	PL042GF150K-1S	PL042GF150K-2S	PL042GF150K-3S	PL042GF150K-4S
Frame size	mm	$\phi 42$	$\phi 42$	$\phi 42$	$\phi 42$
Reduction ratio		1/3.7, 1/5.2	1/14, 1/19, 1/27	1/49, 1/59, 1/68, 1/82 1/95, 1/115	1/181, 1/218, 1/253, 1/305 1/354, 1/426, 1/495, 1/596
Efficiency	%	90	81	73	66
Number of stages		1	2	3	4
Rated Continuous torque	Nm	1.5	4.0	10.0	15.0
Max. Momentary torque	Nm	3.0	12.0	25.0	38.0
Max. Radial load(10mm from flange)	N	200	200	200	200
Max. Axial load	N	100	100	100	100
Max. Shaft press fit force	N	150	150	150	150
Gearbox Length	mm	31.5	42.1	52.5	62.9
Weight	g	244	314	433	519
Max. Backlash at no-load	$^\circ$	2.5	2.5	2.5	2.5
Operating Temperature	$^\circ\text{C}$	-15 ~ +80			
Recommend input speed	rpm	<8000			

● Mechanical

