

66 FRAME PMDC/BLDC GEAR MOTOR

● General information

- Encoder available : 2 PPR or 4 PPR.
- Epoxy coating on the surface.
- Protection class IP 65.
- Operating temperature -40℃ ~ +80℃.
- With protective vent valve to reduce condensation.



● Specification

Model	Voltage (v)	No Load		Rated Load		Torque (N.m)	Ratio	Stage	Power (W)	Length (mm)
		Current (A)	Speed (rpm)	Current (A)	Speed (rpm)					
MB/ME057FG100-PL0018	24	0.75	201	4.03	167	2.9	18	2	51	185
MB/ME057FG100-PL0029	24	0.75	125	4.03	103	4.7	29			
MB/ME057FG100-PL0036	24	0.75	100	4.03	83	5.8	36			
MB/ME057FG100-PL0079	24	0.83	46	4.03	38	11.5	79	3	46	185
MB/ME057FG100-PL0150	24	0.83	24	4.03	20	21.9	150			
MB/ME057FG100-PL0236	24	0.83	15	4.03	13	34.5	236			
MB/ME057FG100-PL0408	24	0.93	9	4.03	7	53	408	4	41	198
MB/ME057FG100-PL0531	24	0.93	7	4.03	6	69	531			
MB/ME057FG100-PL0837	24	0.93	4	4.03	4	108.8	837			

● Mechanical

