

L22008  
AL+PCL22009  
AL+PC22005-1/22005-2 E27  
SIZE:590x170x138mm  
Energy-saving light  
(ABS+PS)

## PRODUCT PARAMETERS

POWER	VOLTAGE	CCT RANGE	COLOUR	GRADE
20W/30W	AC100~260V/50~60Hz	3000K/6000K	Grey	IP65

L22007-20  
AL+PCL22006-20  
AL+PS22006-1/22006-2 E27  
Energy-saving light  
(ABS+PS)

## PRODUCT PARAMETERS

POWER	VOLTAGE	CCT RANGE	COLOUR	GRADE
20W	AC100~260V/50~60Hz	3000K/6000K	Grey	IP65



22006A-12/20/30



22006B-12



22007A-12/20/30



22007B-12



22006C-20



22007C-20



22008C-30



22008A-30/22008A-50

Hole Fix Ø 55


NO	MODEL	POWER	LUMEN	VOLTAGE	CCT RANGE	COLOUR	GRADE
1	22006A-12	0.2x60=12W	1080Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
2	22006A-20	0.5x40=20W	1600Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
3	22006A-30	0.5x60=30W	2400Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
4	22006B-12	0.2x60=12W	1080Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
5	22007A-12	0.2x60=12W	1080Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
6	22007A-20	0.5x40=20W	1600Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
7	22007A-30	0.5x60=30W	2400Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
8	22007B-12	0.2x60=12W	1080Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
9	22006C-20	1x20=20W	2000Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
10	22007C-20	1x20=20W	2000Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
11	22008C-30	1x30=30W	3000Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
12	22008A-30	1x30=30W	3000Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65
13	22008A-50	1x50=50W	5000Lm	AC100~260V/50~60Hz	3000K/6500K	GRAY	IP65



L22012-24



L22012-12



L22012-J20

L22012-36  
L22012-40  
L22012-50

L22012-J30




L22013



L22014

L22011  
AL+GLASS

22009C-30



## PRODUCT PARAMETERS

MODEL	POWER	LUMEN	VOLTAGE	CCT RANGE	PRODUCT SIZE(LxWxH)	THE SIZE OF POLE
L22012-24	24W	1920Lm	AC100~260V/50~60Hz	3000K/6500K	397x135x65mm	$\phi$ 40
L22012-12	12W	960Lm	AC100~260V/50~60Hz	3000K/6500K	350x103x60mm	$\phi$ 40
L22012-J20	20W	1400Lm	AC100~260V/50~60Hz	3000K/6500K	350x103x60mm	$\phi$ 40
L22012-J30	30W	2100Lm	AC100~260V/50~60Hz	3000K/6500K	388x143x65mm	$\phi$ 40
L22012-36	36W	2880Lm	AC100~260V/50~60Hz	3000K/6500K	498x220x85mm	$\phi$ 62
L22012-40	40W	3200Lm	AC100~260V/50~60Hz	3000K/6500K	498x220x85mm	$\phi$ 62
L22012-50	50W	4000Lm	AC100~260V/50~60Hz	3000K/6500K	498x220x85mm	$\phi$ 62
L22013-50	50W	5000Lm	AC100~260V/50~60Hz	3000K/6500K	520x228x75mm	$\phi$ 62
L22013-100	100W	10000Lm	AC100~260V/50~60Hz	3000K/6500K	625x290x75mm	$\phi$ 62
L22014-20	20W	2400Lm	AC100~260V/50~60Hz	3000K/6500K	325x156x70mm	$\phi$ 55
L22014-30	30W	3600Lm	AC100~260V/50~60Hz	3000K/6500K	325x156x70mm	$\phi$ 55
L22014-50	50W	6000Lm	AC100~260V/50~60Hz	3000K/6500K	361x172x70mm	$\phi$ 55
L22014-60	60W	7200Lm	AC100~260V/50~60Hz	3000K/6500K	532x240x73mm	$\phi$ 55
L22014-80	80W	9600Lm	AC100~260V/50~60Hz	3000K/6500K	532x240x73mm	$\phi$ 55
L22014-100	100W	12000Lm	AC100~260V/50~60Hz	3000K/6500K	532x240x73mm	$\phi$ 55
L22011-50	50W	4000Lm	AC100~260V/50~60Hz	3000K/6500K	527x280x130mm	$\phi$ 53
L22009C-30	30W	2400Lm	AC100~260V/50~60Hz	3000K/6500K	590x150x86mm	

# STREET LAMP LED

Application:  
Path, steps and ladders,  
building wall, garden.



## PRODUCT PARAMETERS

POWER	VOLTAGE	CCT RANGE	GRADE
7W/9W	AC100~260V/50~60Hz	3000/6500K	IP65

Application:  
Path, steps and ladders,  
building wall, garden.

# WALL LIGHT SERIES

## LED

Application:  
corridor, Square, park,  
outer wall

### L68060



### L68061



#### Material:

1. Whole stainless steel.


#### PRODUCT PARAMETERS

Power: 8W
Voltage: AC100~260V / 50~60Hz
Grade: IP 54
Colour:3000K/6500K

# WALL LAMP&BULKHEAD LAMP

## LED

Application:  
corridor, Square, park,  
outer wall



### L74016



### L74018

E27/LED
---------

#### Material:

1. Die-casting aluminum body powder spraying on the surface for the corrosion proof.

2. Silica gel gasket.

3. Lampshade PMMA(Opal)





#### PRODUCT PARAMETERS

Power: 6W/8W
Voltage: AC100~260V / 50~60Hz
Grade: IP 54
CCT range: 3000K / 6500k

# LAWN LIGHT SERIES

## LED

Application:  
Path, villa,Lawn,Garden





#### Material:

1. Die-casting aluminum body , powder spraying on the surface , for the corrosion proof.
2. Transparent glass flower design.
3. Transparent PC cover.
- Milky white PC cover

#### PRODUCT PARAMETERS

Power: COB 10W
Voltage: AC100~260V / 50~60Hz
Grade: IP 43
Colour:3000K/6500K



#### Material:

1. Whole stainless steel.
2. Milky white PC cover.

#### PRODUCT PARAMETERS

Power: 8W
Voltage: AC100~260V / 50~60Hz
Grade: IP 43
Colour:3000K/6500K



L83079



L83078



L83077



L83075



L83076



L83074



L83070



L61003



61005

MODEL	POWER	PRODUCT SIZE
L83079	E27/LED9W	240x167x110mm
L83078	E27/LED9W	225x185x150mm
L83077	E27/LED9W	225x185x150mm
L83075	E27/LED9W	198x110x90mm
L83076	E27/LED9W	230x185x130mm
L83074	E27/LED9W	250x165x110mm
L83070	E27/LED9W	250x165x110mm
L61003	7W/350Lm	<b>150x103X250mm</b>
61005	E27/40W	<b>150x103X250mm</b>

## FLOOD LIGHT SERIES



**L88001-1-S**  
10W  
185  
124



**L88001-2-S**  
2x10W  
221  
185  
124



**L88002-1-S**  
10W  
190  
124




**L88002-2-S**  
2x10W  
246  
190  
124

## PRODUCT PARAMETERS

POWER	VOLTAGE	CCT RANGE	COLOUR	GRADE
10W/20W	AC100-260V / 50-60Hz	3000/6500K	Grey	IP54



L61002



L61006



L61008



L61009

## Material:

1. Die-casting aluminum body powder spraying on the surface for the corrosion proof.
2. Silica gel gasket.
3. Opal glass

## PRODUCT PARAMETERS

Power: 8W
Voltage: AC100-260V / 50-60Hz
Grade: IP 65
CCT range: 3000K / 6500K



L74003



L74004



L74008



L74009

## PRODUCT PARAMETERS

Power: 6W/8W
Voltage: AC100-260V / 50-60Hz
Grade: IP 54
CCT range: 3000K / 6500K



76018



76019



76020



76021



76022



76023



76024



76034

## PRODUCT PARAMETERS

MODEL	POWER	PRODUCT SIZE
76018-6	15W	φ150x150mm
76018-8	25W	φ200x200mm
76018-10	40W	φ250x250mm
76018-12	60W	φ300x300mm
76019-6	15W	222x150x223mm
76019-8	25W	247x200x271mm
76020-6	15W	222x150x223mm
76020-8	25W	247x200x271mm
76021-6	15W	185x150x180mm
76022-6	15W	185x150x180mm

MODEL	POWER	PRODUCT SIZE
76023-6	15W	150x150x185mm
76024-6	15W	150x150x185mm
76023-8	25W	200x200x235mm
76024-8	25W	200x200x235mm
76034-6	15W	φ150x150mm
76034-8	25W	φ200x200mm
76034-10	40W	φ250x250mm
76034-12	60W	φ300x300mm



76025



76026



76038-S

76040  
(glass)

76034A



76018A



76027



76028

MODEL	POWER	PRODUCT SIZE
76025-6	15W	225x185x150mm
76025-8	25W	278x220x200mm
76026-6	15W	225x185x150mm
76026-8	25W	278x220x200mm
76034A-6	15W	φ150x272mm
76034A-8	25W	φ200x322mm
76018A-6	15W	φ150x272mm
76018A-8	25W	φ200x322mm
76027	15W	244x167x110mm
76028	15W	244x167x110mm
76038-S		φ118x120mm
76040-6 (Glass)	60W	150x150x195mm
76040-8 (Glass)	100W	180x180x225mm

**PRODUCT PARAMETERS**

Power: 6W & 8W  
 Voltage: AC100~260V / 50~60Hz  
 Grade: IP43  
 CCT range: 3000K / 6500K

**PRODUCT PARAMETERS**

Power : 6W & 8W

Input : 100~260V 50/60Hz

CCT Range:  3000~6500K

Material : AL+PS


Grade : IP43

# WALL LIGHT SERIES


LED

Application:  
corridor, Square, park,  
outer wall

L72018



L72002



## Material:

1. Die-casting aluminum body , powder spraying on the surface , for the corrosion proof.
2. Silica gel gasket.
- 3.High-strength tempered glass.


## PRODUCT PARAMETERS

Power:	COB 10W
Voltage:	AC100-260V / 50~60Hz
Grade:	IP 54
Colour:	3000K/6500K

L72019



L72004



## Material:

1. Die-casting aluminum body , powder spraying on the surface , for the corrosion proof.
2. Silica gel gasket.
- 3.High-strength tempered glass.

## PRODUCT PARAMETERS





Power:	COB 2x10W
Voltage:	AC100-260V / 50~60Hz
Grade:	IP 54
Colour:	3000K/6500K

L72036-01

L72036-02

L72037-01

L72037-02





JYZS-L652

JYZS-L653

JYZS-L654

JYZS-L655

JYZS-L656



JYZS-L657

JYZS-L658

JYZS-L659

JYZS-L660

JYZS-L661

## PRODUCT PARAMETERS

Power : 2x6W & 2x8W

Input : 100~260V 50/60Hz

CCT Range:  3000~6500K

Material : AL+PMMA

Grade : IP54

# LANTERN LIGHT SERIES

LED

Application:  
garden,villa,outer wall



L83018  
Hammer glass



L83068



## PRODUCT PARAMETERS

Power : 10W

Input : 100~260V 50/60Hz

CCT Range:  3000~6500K

Material : AL+Glass Grade : IP43

## PRODUCT PARAMETERS

Power : 6-10W

Input : 100~260V 50/60Hz

CCT Range:  3000~6500K

Material : AL+Glass Grade : IP43

## PRODUCT PARAMETERS

Power : 10W

Input : 100~260V 50/60Hz

CCT Range:  3000~6500K

Material : AL+Glass Grade : IP43

## PRODUCT PARAMETERS

Power : 6-10W

Input : 100~260V 50/60Hz

CCT Range:  3000~6500K

Material : AL+Glass Grade : IP43

## PRODUCT PARAMETERS

Power : 6 & 8W

Input : 100~260V 50/60Hz

CCT Range:  3000~6500K

Material : AL+Glass Grade : IP43

# LED T8 FIXTURE SERIES

LED



Application:  
Indoor , Super-Market



66008-2/66008-4

NO	MODEL	POWER	LUMEN	VOLTAGE	SIZE(MM)	CCT RANGE
1	66008-2	9W	600Lm	AC100~260V/50~60Hz	610x31x21	3000K/6500K
2	66008-4	18W	1200Lm	AC100~260V/50~60Hz	1220x31x21	3000K/6500K



66011-2/66011-4

NO	MODEL	POWER	LUMEN	VOLTAGE	SIZE(MM)	CCT RANGE
1	66011-2	9W	600Lm	AC100~260V/50~60Hz	610x33x13	3000K/6500K
2	66011-4	18W	1200Lm	AC100~260V/50~60Hz	1220x33x13	3000K/6500K



66012-2/66012-4

NO	MODEL	POWER	LUMEN	VOLTAGE	SIZE(MM)	CCT RANGE
1	66012-2	9W	600Lm	AC100~260V/50~60Hz	610x33x16	3000K/6500K
2	66012-4	18W	1200Lm	AC100~260V/50~60Hz	1220x33x16	3000K/6500K



66013-2/66013-4

NO	MODEL	POWER	LUMEN	VOLTAGE	SIZE(MM)	CCT RANGE
1	66013-2	9W	600Lm	AC100~260V/50~60Hz	610x33x18	3000K/6500K
2	66013-4	18W	1200Lm	AC100~260V/50~60Hz	1220x33x18	3000K/6500K

# LANTERN LIGHT SERIES

LED



Application:  
garden,villa,outer wall



L74019(E27orLED)



L83072(E27orLED)



L83073(E27orLED)



PRODUCT PARAMETERS	
Power :	12W
Product Size:	192x185x128mm

PRODUCT PARAMETERS	
Power :	20W
Input :	100~260V 50/60Hz
CCT Range:	3000~6500K
Material :	AL+PMMA Grade : IP43

PRODUCT PARAMETERS	
Power :	8W
Input :	100~260V 50/60Hz
CCT Range:	3000~6500K
Material :	AL+Glass Grade : IP43