



NANYANG TECHNOLOGICAL UNIVERSITY

EE6222 Machine Vision

Assignment 1: Dimensionality Reduction for Classification

MSc in Electrical and Electronic Engineering

Yan Ziming

G2507084J

October 20, 2025

Contents

1	Introduction	2
2	Dataset and Preprocessing	2
2.1	Dtaset Description	2
2.2	Normalization and Standarlization	2
2.3	Dataset Partition	3
3	Methodology	3
4	Results and Discussion	3
5	Conclusion	3

1 Introduction


In this Assignment, I selected the MINIST dataset for training and testing the performance of classifiers. As for the dimension of images are large, I explored several dimensionality reduction methods to reduce the dimension of data while trying to retain the most important features, including **PCA**, **LDA**, combined method (Fisherfaces), **LLE**, **Isomap**, and **PaCMAP**. I compared the effectiveness of these methods by plotting their performance with varying number of dimensions.

In addition, I establish several basic classifiers, like **MMD**, **KNN**, and include Logistic Regression Classifier with sklearn package. Therefore, I not only compare the effectiveness of different dimensionality reduction methods, but also access the accuracy of classify images for these classifier methods. I would describe the details of my experiment in the following sections.

2 Dataset and Preprocessing

2.1 Dataset Description

The MINIST dataset contains **70,000** images of handwritten digits (0-9) with a resolution of 28x28 pixels, which means there are **10** classes intotal. Each image had been saved with the format of vector with **784 in length**. In addition, the images are only have one channel, which means they are grayscale pixels. Because of the pre-shaped vectors, single channel, and easy to get features, I think MINIST dataset is suitable for this assignment. Therefore, I fetch the dataset from sklearn package directly 1.



```
mnist = fetch_openml('mnist_784', version=1)
```

Figure 1: Fetch Code

2.2 Normalization and Standarlization

Since the MINIST dataset had been well preprocessed and tested by plenty of researchers, I didn't do too much basic preprocessing, like outlier and missing value detection. However, I though normalization and standarlization arer still neccessary for the following basic classifiers, which may be affected intensely by the scle of features. So I rearrange the vectors to 0 mean and unit variance.

2.3 Dataset Partition

I found the number of samples (70,000) is too large, which may lead to many difficulties in my following experiment. Firstly, I will training several classifiers with many dimension reduction methods, meaning the number of training process will be big. If I train 50,000-70,000 for each training, the consumed time will be very long. Secondly, my classifiers which will be used are simple and basic, therefore, they are easy to converge with small scale of data. With these two reason, I decide to extract 7,000 samples from the origin dataset formly to reduce the expence of time.

After that, I split the dataset into training set and testing set through *train_test_split* function with ratio of 6:1 and finished the process of preparation of dataset 2.

```
Training Feature Dimension: (6000, 784)
Traing Label Dimension: (6000,)
Testing Feature Dimension: (1000, 784)
Testing Label Dimension: (1000,)
```

Figure 2: Dimension of practical dataset

3 Methodology

4 Results and Discussion

5 Conclusion

abc [1]

References

- [1] I. K. Fodor, "A survey of dimension reduction techniques," Tech. Rep. UCRL-ID-148494, Lawrence Livermore National Laboratory, Livermore, CA, USA, May 2002.