

Eliminating Double Amplifications of Hashing Indexes for Persistent Memory

Paper ID: 132

1 SUMMARY OF IMPLEMENTATIONS

We implement our proposed ElimDA with C++. We elaborate on the dependent software, representative hash indexes, and testing tools as follows.

Dependent softwares: the implementation of ElimDA relies on a suite of software, including ndctl, ipmctl, Intel PMWatch, and PMDK, which can be reached via the following URLs.

```
$ wget https://github.com/pmem/ndctl
$ wget https://github.com/intel/ipmctl
$ wget https://github.com/intel/intel-pmwatch
$ wget https://github.com/pmem/pmdk
```

Representative hash indexes: we use four representative hash indexes for comparison, namely CCEH [?], Dash [?], level hashing [?] and cleve hashing [?], which can be downloaded via the following URLs. Note that we used the PMDK version of the LEVEL hash implemented by Dash.

```
$ wget https://github.com/DICL/CCEH/tree/master/
CCEH-PMDK
$ wget https://github.com/pmdk/dash
$ wget https://github.com/chenzhangyu/Clevel-Hashing
```

Testing tools: we employ YCSB in our evaluation. It can be reached via the following URLs.

```
$ wget https://github.com/brianfrankcooper/YCSB/
releases/download/0.17.0/ycsb-0.17.0.tar.gz
```

2 EVALUATION DETAILS

Hardware configurations: We conduct extensive experiments on a single machine equipped with two 2.10 GHz Intel Golden 5318Y CPUs (with 24 cores in total), 128 GB of DRAM memory and four Optane PMem DIMMs of 200 series (128 GB per DIMM and 512 GB in total). The Optane PMem DIMMs are configured in interleaved App Direct Mode, which are connected to one processor. Figure ?? shows the major hardware configurations of our testbed and Figure ?? shows detailed information about the Optane PMem used in our evaluation.

We perform extensive testbed experiments, including (i) experiments to understand the properties of ElimDA; and (ii) experiments to understand the sensitivity of ElimDA.

Experiments with YCSB: We measure the access performance of ElimDA, CCEH, Dash, level hashing and cleve hashing using YCSB. We first generate the workloads through YCSB and then modify their format so that they can be used for testing. Finally, we use these workloads to test each hash index.

The following script is an example of how to generate an insert-only workload using YCSB:

```
#!/bin/bash
$ ycsb load basic -P uniformworkload > uniform/load.txt
$ ycsb run basic -P insertworkload > uniform/insert.txt
```

```
Architecture:          x86_64
CPU op-mode(s):        32-bit, 64-bit
Byte Order:            Little Endian
Address sizes:         46 bits physical, 57 bits virtual
CPU(s):                48
On-line CPU(s) list:   0-47
Thread(s) per core:    1
Core(s) per socket:    24
Socket(s):             2
NUMA node(s):          2
Vendor ID:              GenuineIntel
CPU family:            6
Model:                 106
Model name:            Intel(R) Xeon(R) Gold 5318Y CPU @ 2.10GHz
Stepping:               6
CPU MHz:               800.779
CPU max MHz:           3400.0000
CPU min MHz:           800.0000
BogoMIPS:              4200.00
Virtualization:        VT-x
L1d cache:             2.3 MiB
L1i cache:             1.5 MiB
L2 cache:              60 MiB
L3 cache:              72 MiB
```

Figure 1: Configurations of our testbed.

DimmID	Capacity	LockState	HealthState	FWVersion
0x0010	126.742 GiB	Disabled, Frozen	Healthy	02.02.00.1516
0x0210	126.742 GiB	Disabled, Frozen	Healthy	02.02.00.1516
0x0110	126.742 GiB	Disabled, Frozen	Healthy	02.02.00.1516
0x0310	126.742 GiB	Disabled, Frozen	Healthy	02.02.00.1516

Figure 2: The configurations of the Intel Optane PMem DIMMs of 200 series used in the evaluation.

We run the following script modify format of workloads.

```
#!/bin/bash
$ dir=./uniform/load.txt
$ sed -i '1,17d' $dir
$ sed -i 's/READ usertable user/r /' $dir
$ sed -i 's/INSERT usertable user/i /' $dir
$ sed -i 's/UPDATE usertable user/u /' $dir
$ sed -i 's/\[ field0=/ /' $dir
$ sed -i 's/\] /' $dir
```

After modifying the format, we measure the performance of all hash indexes. Due to space limitation, we present the following script which is used to evaluate ElimDA. The experiments with other hash indexes are similar.

```
#!/bin/bash
dir=/mnt/pmem1-node0/pool1
perf_dir=./insert_perf/
loadsize=50000000
runsize=50000000
FLAG='-mavx -mavx2 -mavx512f -mavx512bw -mavx512vl'

g++ -O3 -std=c++17 -I./ -lrt -c -o src/ElimDA.o -g \
src/ElimDA.cpp -DINPLACE -lpmemobj -lpmem \
$FLAG -lprofiler -lunwind
```

```

g++ -O3 -std=c++17 -I./ -lrt -o bin/run_all_ycsb \
-g src/run_all_ycsb.cpp src/ElimDA.o include/dlock.o \
-lpmemobj -lpmem -lpthread -DMULTITHREAD -lpqos

outdir=ycsb_all
for test in 1 2 3 4
do
    for oper in "w50r50.txt"
    do
        for num in 1 2 4 8 16 24
        do
            echo " " >> $outdir
            echo "test zipfian "$num" "$oper >> $outdir
            ycsb_dir="../../ycsb/zipfian/"$oper
            load_dir="../../ycsb/zipfian/load.txt"
            rm -rf $dir

            numactl -N 0 -m 0 \
            ./bin/run_all_ycsb $dir $loadsize $runsize
            $num $ycsb_dir $load_dir
            |grep -a -E "num|Ops|Start" >> $outdir
        done
    done
done

```

```

numactl -N 0 -m 0 \
./bin/multi_threaded_ElimDA $dir $loadsize $num \
|grep -a "Ops/sec" >> $outdir
done
sed -i '27d' ./src/ElimDA.h
sed -i '27i #define S_Bucket_Size 256' ./src/ElimDA.h
done

```

Experiments on Sensitivity: We also employ varying PMem Table Size as an example to clarify how we assess the performance of ElimDA. The experiments with other sensitivity are similar. To reduce experimental error, we measured the insert and positive search throughput five times in the following script:

```

#!/bin/bash
dir=/mnt/pmem1-node0/pool1
num=8
perf_dir=./insert_perf/
loadsize=500000000
FLAG='-mavx -mavx2 -mavx512f -mavx512bw -mavx512vl'
outdir=./sendata
srcdir=./sensitive.cpp
for testnum in 1 2 3 4 5
do
    for sbucketsize in 64 128 256 512 1024
    do
        sed -i '27d' ./src/ElimDA.h
        sed -i '27i #define S_Bucket_Size '\
        $sbucketsize' ./src/ElimDA.h
        rm -rf $dir

        g++ -O3 -std=c++17 -I./ -lrt -c \
        -o src/ElimDA.o -g src/ElimDA.cpp \
        -DINPLACE -lpmemobj -lpmem \
        $FLAG -lprofiler -lunwind

        g++ -O3 -std=c++17 -I./ -lrt \
        -o bin/multi_threaded_ElimDA -g \
        src/test.cpp src/ElimDA.o include/dlock.o \
        -lpmemobj -lpmem -lpthread \
        -DMULTITHREAD -lpqos
    done
done

```