

install.zsh(1)

NAME

install.zsh - a shell script

SYNOPSIS

Documentation automatically generated with `zsdoc'

FUNCTIONS

```
Ė. zi -at-eval
Ė. zi -compile-plugi n
Ė. zi -compini t
Ė. zi -download-fi le-stdout
Ė. zi -download-sni ppet
Ė. zi -extract
Ė. zi -forget-completi on
Ė. zi -get-cygwi n-package
Ė. zi -get-latest-gh-r-url -part
Ė. zi -get-package
Ė. zi -get-url -mtime
Ė. zi -instal l-completi ons
Ė. zi -mi rror-usi ng-svn
Ė. zi -parse-j son
Ė. zi -setup-plugi n-di r
Ė. zi -update-sni ppet
Ėzi cp
Ėzi extract
Ėzi mv
Ėzpextract
Ė°zi -atcl one-hook
Ė°zi -atpul l -e-hook
Ė°zi -atpul l -hook
Ė°zi -compile-plugi n-hook
Ė°zi -cp-hook
Ė°zi -extract-hook
Ė°zi -make-e-hook
Ė°zi -make-ee-hook
Ė°zi -make-hook
Ė°zi -mv-hook
Ė°zi -ps-on-update-hook
Ė°zi -reset-hook
AUTOLOAD compini t
```

DETAILS

Script Body

Has 3 line(s). No functions are called (may set up e.g. a hook, a Zle widget bound to a key, etc.).

Uses feature(s): *source*

zi-at-eval

~~~~

```
]]]
FUNCTION: .zi-at-eval [[[
```

Has 5 line(s). Calls functions:

```
.zi-at-eval
`-- zi.zsh/@zi-substitute
```

Uses feature(s): *eval*

Called by:

```
°zi-atpull-e-hook
°zi-atpull-hook
```

*zi-compile-plugin*

~~~~~

```
FUNCTION: .zi-compile-plugin [[[
Compiles given plugin (its main source file, and also an additional "...zsh"
file if it exists).
```

```
$1 - plugin spec (4 formats: user---plugin, user/plugin, user, plugin)
$2 - plugin (only when $1 - i.e. user - given)
```

Has 84 line(s). Calls functions:

```
.zi-compile-plugin
|-- side.zsh/.zi-compute-ice
|-- side.zsh/.zi-first
`-- zi.zsh/+zi-message
```

Uses feature(s): *eval, setopt, zcompile*

Called by:

```
°zi -compile-plugin-hook  
autoload.zsh/.zi -compile-uncompile-all  
zi.zsh/zi
```

zi-compinit

~~~~~

FUNCTION: `.zi-compinit` `[[[`  
User-exposed ``compinit`` frontend which first ensures that all completions managed by `! ZI "` are forgotten by Z-shell.  
After that it runs normal ``compinit``, which should more easily detect `! ZI "` completions.

No arguments.

Has 26 line(s). Calls functions:

```
.zi-compinit  
|-- compinit  
`-- zi.zsh/+zi-message
```

Uses feature(s): *autoload, compinit, setopt, unfunction*

Called by:

```
.zi-install-completions  
autoload.zsh/.zi-uninstall-completions  
autoload.zsh/.zi-update-or-status-all  
zi.zsh/.zi-prepare-home  
zi.zsh/zi
```

*zi-download-file-stdout*

~~~~~

FUNCTION: `.zi-download-file-stdout` `[[[`
Downloads file to stdout. Supports following backend commands:
`curl`, `wget`, `lftp`, `lynx`. Used by snippet loading.

Has 46 line(s). Calls functions:

```
.zi -download-file-stdout  
`-- zi .zsh/+zi -message
```

Uses feature(s): *setopt, trap, type*

Called by:

```
.zi -download-snippet  
.zi -get-cygwin-package  
.zi -get-package  
.zi -setup-plugin-dir
```

zi-download-snippet

~~~~~

```
FUNCTION: .zi -download-snippet []  
Downloads snippet either a file with curl, wget, lftp or lynx, or a directory,  
with Subversion when svn-ICE is active. Github supports Subversion protocol and  
allows  
to clone subdirectories. This is used to provide a layer of support for Oh-My-Zsh  
and Prezto.
```

Has 309 line(s). Calls functions:

```
.zi -download-snippet  
|-- side.zsh/.zi -store-ices  
`-- zi .zsh/+zi -message
```

Uses feature(s): *setopt, trap, zcompile*

Called by:

```
.zi -update-snippet  
zi .zsh/.zi -load-snippet
```

*zi-extract*

~~~~~

```
FUNCTION: .zi -extract() []
```

Has 22 line(s). Calls functions:

```
.zi-extract
|-- zi.zsh/+zi-message
`-- ziextract
Ê  `-- zi.zsh/+zi-message
```

Uses feature(s): *setopt*

Called by:

```
°zi-extract-hook
```

zi-forget-completion

~~~~~

```
]]]
FUNCTION: .zi-forget-completion [[
Implements alternation of Zsh state so that already initialized
completion stops being visible to Zsh.
```

```
$1 - completion function name, e.g. "_cp"; can also be "cp"
```

Has 20 line(s). Doesn't call other functions.

Uses feature(s): *setopt*, *unfunction*

Called by:

```
.zi-compi n i t
.zi-i nstal l -completi ons
autoload.zsh/.zi-uni nstal l -completi ons
zi.zsh/zi
```

### *zi-get-cygwin-package*

~~~~~

```
FUNCTION: .zi-get-cygwi n-package [[
```

Has 70 line(s). Calls functions:

```
.zi-get-cygwi n-package
`-- zi.zsh/+zi-message
```

Uses feature(s): *setopt*

Called by:

```
. zi -setup-plugi n-di r
```

zi-get-latest-gh-r-url-part

~~~~~

```
]]]
FUNCTION: . zi -get-latest-gh-r-url -part [[[
Gets version string of latest release of given Gi thub package.
Connects to Gi thub releases page.
```

Has 101 line(s). Calls functions:

```
. zi -get-latest-gh-r-url -part
`-- zi . zsh/+zi -message
```

Uses feature(s): *setopt*

Called by:

```
. zi -setup-plugi n-di r
autol oad. zsh/. zi -update-or-status
```

*zi-get-package*

~~~~~

```
]]]
FUNCTION: . zi -get-package [[[
```

Has 194 line(s). Calls functions:

```
. zi -get-package
|-- zi . zsh/+zi -message
|-- zi . zsh/@zi -substi tute
`-- zi extract
Ê    `-- zi . zsh/+zi -message
```

Uses feature(s): *eval*, *setopt*, *trap*

Called by:

```
zi .zsh/.zi-load
```

Environment variables used: zi.zsh ! ZPFX

zi-get-url-mtime

~~~~~

```
FUNCTION: .zi-get-url-mtime [[  
For the given URL returns the date in the Last-Modified header as a time stamp
```

Has 34 line(s). Doesn't call other functions.

Uses feature(s): *read, setopt, trap, type*

Called by:

```
.zi-download-snippet
```

*zi-install-completions*

~~~~~

```
FUNCTION: .zi-install-completions [[  
Installs all completions of given plugin. After that they are  
visible to 'compinit'. Visible completions can be selectively  
disabled and enabled. User can access completion data with  
'clist' or 'completions' subcommand.
```

```
$1 - plugin spec (4 formats: user---plugin, user/plugin, user, plugin)  
$2 - plugin (only when $1 - i.e. user - given)  
$3 - if 1, then reinstall, otherwise only install completions that aren't there
```

Has 61 line(s). Calls functions:

```
.zi-install-completions  
|-- side.zsh/.zi-any-colorify-as-uspl2  
|-- side.zsh/.zi-exists-physically-message  
|-- zi.zsh/+zi-message  
`-- zi.zsh/.zi-any-to-user-plugin
```

Uses feature(s): *setopt*

Called by:

```
.zi -download-snippet  
.zi -setup-plugin-dir  
zi .zsh/zi
```

zi-mirror-using-svn

~~~~~

FUNCTION: .zi-mirror-using-svn [[  
Used to clone subdirectories from Github. If in update mode (see \$2), then  
invokes `svn update`,  
in normal mode invokes `svn checkout --non-interactive -q <URL>`. In test mode  
only  
compares remote and local revision and outputs true if update is needed.

\$1 - URL  
\$2 - mode, "" - normal, "-u" - update, "-t" - test  
\$3 - subdirectory (not path) with working copy, needed for -t and -u

Has 27 line(s). Doesn't call other functions.

Uses feature(s): *setopt*

Called by:

```
.zi -download-snippet
```

### *zi-parse-json*

~~~~~

FUNCTION: .zi-parse-json [[
Retrieves the ice-list from given profile from the JSON of the package.json.

Has 102 line(s). Calls functions:

```
.zi -parse-json
```

Uses feature(s): *setopt*

Called by:

```
.zi -get-package
```


zi-setup-plugin-dir

~~~~~

```
FUNCTION: .zi-setup-plugin-dir [[[
Clones given plugin into PLUGIN_DIR. Supports multiple
sites (respecting `from' and `proto' ice modifiers).
Invokes compilation of plugin's main file.
```

```
$1 - user
$2 - plugin
```

Has 189 line(s). Calls functions:

```
.zi-setup-plugin-dir
|-- side.zsh/.zi-any-configure-as-uspl2
|-- side.zsh/.zi-store-ices
|-- zi.zsh/+zi-message
|-- zi.zsh/.zi-get-object-path
`-- ziextract
E  `-- zi.zsh/+zi-message
```

Uses feature(s): *setopt*, *trap*

Called by:

```
autoload.zsh/.zi-update-or-status
zi.zsh/.zi-load
```

## *zi-update-snippet*

~~~~~

```
]]]
FUNCTION: .zi-update-snippet [[[
```

Has 72 line(s). Calls functions:

```
.zi-update-snippet
|-- zi.zsh/+zi-message
|-- zi.zsh/.zi-get-object-path
`-- zi.zsh/.zi-pack-ice
```

Uses feature(s): *eval*, *setopt*

Called by:

```
autoload. zsh/. zi -update-or-status-snippet
```

zicp

```
]]]  
FUNCTION zicp [[
```

Has 28 line(s). Doesn't call other functions.

Uses feature(s): *setopt*

Called by:

```
zi mv
```

Environment variables used: `zi.zsh ! ZPFX`

ziextract

```
]]]  
FUNCTION: ziextract [[  
If the file is an archive, it is extracted by this function.  
Next stage is scanning of files with the common utility `file`,  
to detect executables. They are given +x mode. There are also  
messages to the user on performed actions.
```

```
$1 - url  
$2 - file
```

Has 274 line(s). Calls functions:

```
ziextract  
`-- zi .zsh/+zi -message
```

Uses feature(s): *setopt, unfunction, zparseopts*

Called by:

```
. zi-extract  
. zi-get-package  
. zi-setup-plugin-dir  
zpextract
```

zimv

```
]]]  
FUNCTION zimv [[[
```

Has 3 line(s). Calls functions:

```
zimv  
`-- zicp
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

zpextract

```
]]]  
FUNCTION: zpextract [[[
```

Has 1 line(s). Calls functions:

```
zpextract  
`-- ziextract  
Ē `-- zi.zsh/+zi-message
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

°zi-atclone-hook

```
FUNCTION: °zi-atclone-hook [[[
```

Has 4 line(s). Calls functions:

```
°zi-atclone-hook  
|-- side.zsh/.zi-countdown  
`-- zi.zsh/@zi-substitute
```

Uses feature(s): *eval*, *setopt*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° **zi-atpull-e-hook**

```
FUNCTION: °zi-atpull-e-hook [][]
```

Has 2 line(s). Calls functions:

```
°zi-atpull-e-hook  
`-- side.zsh/.zi-countdown
```

Uses feature(s): *setopt*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° **zi-atpull-hook**

```
FUNCTION: °zi-atpull-hook [][]
```

Has 2 line(s). Calls functions:

```
°zi-atpull-hook  
`-- side.zsh/.zi-countdown
```

Uses feature(s): *setopt*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° **zi-compile-plugin-hook**

```
FUNCTION: °zi-compile-plugin-hook [][]
```

Has 14 line(s). Calls functions:

```
°zi-compile-plugin-hook
```

Uses feature(s): *setopt*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° zi-cp-hook

```
FUNCTION: °zi -cp-hook [][]
```

Has 24 line(s). Calls functions:

```
°zi -cp-hook  
`-- zi . zsh/@zi -substitute
```

Uses feature(s): *setopt*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° zi-extract-hook

```
FUNCTION: °zi -extract-hook [][]
```

Has 4 line(s). Calls functions:

```
°zi -extract-hook  
`-- zi . zsh/@zi -substitute
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° zi-make-e-hook

```
FUNCTION: °zi -make-e-hook [][]
```

Has 5 line(s). Calls functions:

```
°zi -make-e-hook  
|-- side.zsh/. zi -countdown  
`-- zi . zsh/@zi -substitute
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° zi-make-ee-hook

```
FUNCTION: °zi -make-ee-hook [][]
```

Has 5 line(s). Calls functions:

```
°zi -make-ee-hook  
|-- si de. zsh/. zi -countdown  
`-- zi . zsh/@zi -substi tute
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° zi-make-hook

```
FUNCTION: °zi -make-hook [][]
```

Has 4 line(s). Calls functions:

```
°zi -make-hook  
|-- si de. zsh/. zi -countdown  
`-- zi . zsh/@zi -substi tute
```

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° zi-mv-hook

```
FUNCTION: °zi -mv-hook [][]
```

Has 21 line(s). Calls functions:

```
°zi -mv-hook  
`-- zi . zsh/@zi -substi tute
```

Uses feature(s): *setopt*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° zi-ps-on-update-hook

```
FUNCTION: °zi -ps-on-update-hook [][]
```

Has 14 line(s). Calls functions:

```
°zi -ps-on-update-hook  
`-- zi . zsh/+zi -message
```

Uses feature(s): *eval*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

° zi-reset-hook

```
]]]  
FUNCTION: °zi -reset-opt-hook [[[
```

Has 79 line(s). Calls functions:

```
°zi -reset-hook  
`-- zi . zsh/+zi -message
```

Uses feature(s): *eval*

Not called by script or any function (may be e.g. a hook, a Zle widget, etc.).

compinit

Initialisation for new style completion. This mainly contains some helper functions and setup. Everything else is split into different files that will automatically be made autoloaded (see the end of this file). The names of the files that will be considered for autoloading are those that begin with an underscores (like `_condition`).

The first line of each of these files is read and must indicate what should be done with its contents:

```
`#compdef <names ...>'
```

Has 549 line(s). Doesn't call other functions.

Uses feature(s): *autoload*, *bindkey*, *compdef*, *compdump*, *eval*, *read*, *setopt*, *unfunction*, *zle*, *zstyle*

Called by:

```
. zi -compinit
```