

直接去这里下载，Archeieve

[MySQL :: Download MySQL Community Server \(Archived Versions\)](#)

MySQL Product Archives

MySQL Community Server (Archived Versions)

Please note that these are old versions. New releases will have recent bug fixes and features!
To download the latest release of MySQL Community Server, please visit [MySQL Downloads](#).

Product Version: 5.7.26

Operating System: Linux - Generic

OS Version: Linux - Generic (glibc 2.12) (x86, 64-bit)

Compressed TAR Archive

Apr 13, 2019

615.0M

Download

(mysql-5.7.26-linux-glibc2.12-x86_64.tar.gz)

MDS: 08a3b385db2f151598017b63fbc6c43 | Signature

Compressed TAR Archive Test Suite

Apr 13, 2019

70.0M

Download

[Linux 安装 MySQL5.7_kali安装mysql5.7-CSDN博客](#)

1. 安装并上传mysql5.7.26安装包

```
(root@MiWiFi-RD04v2-srv) - [/home/z0reverse]
# ls
公共  文档  docker-compose-linux-x86_64  logs
模板  下载  JNDI-Injection-Exploit       marshalsec-master
视频  音乐  jndishell                    mysql-5.7.26-linux-glibc2.12-x86_64.tar.gz
图片  桌面  kali-archive-keyring.gpg     tmsl1demodb.sql
vulhub-master
```

2. 进行解压

```
(root@MiWiFi-RD04v2-srv) - [/home/z0reverse]
# tar -zxvf mysql-5.7.26-linux-glibc2.12-x86_64.tar.gz
mysql-5.7.26-linux-glibc2.12-x86_64/bin/myisam_ftdump
mysql-5.7.26-linux-glibc2.12-x86_64/bin/myisamchk
mysql-5.7.26-linux-glibc2.12-x86_64/bin/myisamlog
mysql-5.7.26-linux-glibc2.12-x86_64/bin/myisampack
mysql-5.7.26-linux-glibc2.12-x86_64/bin/mysql
```

3. 将其移动到usr/local/mysql文件夹下

```
mv mysql-5.7.26-linux-glibc2.12-x86_64 /usr/local/mysql
```

4. 创建mysql用户组并修改权限

```
groupadd mysql
```

```
useradd -r -g mysql mysql
```

5. 创建数据目录并授予权限

```
mkdir -p /data/mysql #创建目录
```

```
chown mysql:mysql -R /data/mysql #赋予权限
```

6. 配置/etc/my.cnf

```
vi /etc/my.cnf
```

```
[mysqld]
bind-address=0.0.0.0
port=3306
user=mysql
basedir=/usr/local/mysql
datadir=/data/mysql
socket=/tmp/mysql.sock
log-error=/data/mysql/mysql.err
pid-file=/data/mysql/mysql.pid
#character config
character_set_server=utf8mb4
symbolic-links=0
explicit_defaults_for_timestamp=true
```

7.进入mysql的bin目录下进行初始化

```
cd /usr/local/mysql/bin/
./mysqld --defaults-file=/etc/my.cnf --basedir=/usr/local/mysql/ --
datadir=/data/mysql/ --user=mysql --initialize
```

8.查看临时密码

```
cat /data/mysql/mysql.err
```

9.启动mysql并修改临时密码

先将mysql.server放置到/etc/init.d/mysql中

```
cp /usr/local/mysql/support-files/mysql.server /etc/init.d/mysql
systemctl start mysql
```

修改密码

```
mysql -u root -p(在bin目录下)
SET PASSWORD = PASSWORD('123456');
ALTER USER 'root'@'localhost' PASSWORD EXPIRE NEVER;
FLUSH PRIVILEGES;
```

```

—(root@MiWiFi-RD04v2-srv)-[/home/z0reverse]
—# /usr/local/mysql/bin/mysql -u root -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 2
Server version: 5.7.26

Copyright (c) 2000, 2019, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> SET PASSWORD = PASSWORD('123456');
Query OK, 0 rows affected, 1 warning (0.00 sec)

mysql> ALTER USER 'root'@'localhost' PASSWORD EXPIRE NEVER;
Query OK, 0 rows affected (0.00 sec)

mysql> FLUSH PRIVILEGES;
Query OK, 0 rows affected (0.00 sec)

mysql> use mysql;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> update user set host = '%' where user = 'root';
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> FLUSH PRIVILEGES;
Query OK, 0 rows affected (0.00 sec)

mysql> █

```

遇到该问题

1. libtinfo.so.5 缺失

```

/usr/local/mysql/bin/mysql -u root -p
ERROR:/usr/local/mysql/bin/mysql: error while loading shared libraries:
libncurses.so.5: cannot open shared object file: No such file or directory

```

因为 Kali Linux 默认可能未安装该兼容库

解决:

1. 安装ncurses5库

```
sudo apt install libncurses5
```

若提示版本不兼容或者没有, 安装开发库

```
sudo apt install libncurses5-dev
```

2. 创建软连接

检查系统中是否有更高版本的ncurses库

```
ls /lib/x86_64-linux-gnu/libncurses.so.*
```

```
# 假设存在libncurses.so.6, 创建软链接
```

```
sudo ln -s /lib/x86_64-linux-gnu/libncurses.so.6 /lib/x86_64-linux-  
gnu/libncurses.so.5
```

这个可能会很多lib这个库找不到，单都是一样的操作步骤，创建软连接就ing

```
```bash
```

```
使用ldd命令查看mysql客户端的依赖
```

```
ldd /usr/local/mysql/bin/mysq
```

然后对缺失的进行创建软连接

```
eg:
```

```
ls /lib/x86_64-linux-gnu/libncurses.so.1
```

```
sudo ln -s /lib/x86_64-linux-gnu/libncurses.so.6 /lib/x86_64-linux-
gnu/libncurses.so.1
```

## 2.命令配置

```
创建mysql命令软链接到系统路径
```

```
sudo ln -s /usr/local/mysql/bin/mysql /usr/bin/mysql
```

```
验证软链接
```

```
ls -l /usr/bin/mysql
```