

Tacit: Confidential Assets and DeFi on Bitcoin, Bridged by Zero-Knowledge Reflection

z0r0z
<https://tacit.finance>

Version 1 2026

Abstract

Bitcoin secures value without a trusted party, yet every way to issue assets on it, hide their amounts or trade them has brought one back: a proof courier, a federation, a rollup operator or a custodian. Tacit is a confidential asset layer for Bitcoin that needs none of them.

Tacit assets live on Bitcoin in Taproot envelopes, with amounts hidden in Pedersen commitments, and any indexer derives the same state from the chain alone. The same notes extend into an immutable pool on Ethereum that accepts private transactions only with an SP1 zero-knowledge proof. Each chain proves its state to the other, Bitcoin by proof-of-work and Ethereum by its light client, so value and calls cross between them with no signer, multisig or custodian.

In the pool, users send, swap, borrow and earn with amounts hidden, and never need ETH for gas. cBTC brings in real BTC from self-custody locks, and every balance recovers from a single key. The core is immutable, so nobody can change the rules under a user's funds, yet the protocol keeps improving, pool by pool, toward a V2 built on Bitcoin covenants.

1 Introduction

A useful asset layer on Bitcoin needs five properties:

1. its state is public data anyone can check;
2. amounts are hidden;
3. value can move to where computation is cheap without trusting a bridge;
4. BTC itself can back a fungible asset;
5. a user can recover everything from a key.

Existing designs each give up one:

Design	What it gives up
Ordinals, Runes	Amounts are public.
RGB, Taproot Assets	Validity moves off-chain, so losing a proof means losing the balance.
Liquid	Relies on a federation.
Rollups and Bitcoin L2s	Rely on an operator set.
Wrapped BTC	Relies on a custodian or a threshold group.

Tacit delivers all five by combining existing systems, with no new consensus:

Part	What it offers
Bitcoin metaprotocol (§2, §3)	Issue, send and trade Bitcoin assets with hidden amounts.
Confidential pool (§4, §6)	Private sends, swaps, loans and farms on Ethereum, gas-free.
Reflection (§5)	Notes and calls move between chains by proof, with no signer.
cBTC (§6)	Real BTC in self-custody locks, private on both chains.
Lineage (§8, §11)	An immutable core that improves by succession, toward covenants.

One property Bitcoin cannot yet enforce on its own: custody of the BTC behind cBTC. Tacit secures it economically until covenants make it absolute (§11).

2 A metaprotocol on Bitcoin

A Tacit op is a commit/reveal pair. The commit pays to a Taproot output whose only script leaf is:

$$\langle P \rangle \text{ OP_CHECKSIG OP_FALSE OP_IF "TACIT" 0x01 } \langle \text{payload} \rangle \text{ OP_ENDIF}$$

The reveal spends it, so the payload rides in witness data. Bitcoin nodes ignore it; indexers read it. A Tacit UTXO is valid iff the op that created it follows the rules and each of its inputs is itself valid.

The rules are deterministic, so every indexer that reads the same chain reaches the same state. There is no quorum, vote or leader, the same trust model as Ordinals and Runes. The reflection guest (§5) checks the rules a second time, under a verifying key that cannot change.

Ops cover issuance (TAC, the native asset, has a fixed supply of 21 million), transfers with optional stealth addresses, atomic trades against BTC, bids that fill while the buyer is offline, a native AMM, cBTC locks, and cross-chain burns, re-mints and calls. An unknown opcode creates no state, so the protocol grows by adding opcodes.

3 Confidential value

Every amount is a Pedersen commitment on secp256k1:

$$C = v \cdot H + r \cdot G,$$

where G is Bitcoin's generator and H is a second generator nobody knows the discrete log of. Commitments hide the value and add up. A transaction balances iff its excess

$$E = \sum C_{\text{out}} + b \cdot H - \sum C_{\text{in}}$$

has no H component, where b is any public burn. A Schnorr signature under E proves it: only someone who knows every blinding can sign, and nobody can sign for an excess that hides value.

Range proofs (Bulletproofs+) keep every amount in $[0, 2^{64})$. The recipient's blinding and encrypted amount come from a shared secret between sender and recipient, so a recipient finds every payment with its own key and the chain alone.

The Ethereum pool uses the same commitment, so value crosses between the chains unchanged.

4 The confidential pool

The pool is one immutable contract with no owner and no pause. It keeps Merkle trees of notes, locks and loan positions, a spent set for each, escrow for ETH and outside tokens, and the reflected state of Bitcoin.

Notes. A note is $(asset, C, owner)$. Spending one reveals its nullifier, which marks it spent. An owned note's nullifier uses the owner's secret key, so nobody can tell which note was spent: it hides among every owned note of its asset. Notes that came from Bitcoin stay bound to their Bitcoin key.

Entry and exit. `wrap` deposits ETH or any ERC-20, and one transaction can wrap and immediately send, swap, add liquidity or borrow. TAC, cBTC and cUSD have ERC-20s that only the pool mints: unwrapping mints them and wrapping burns them. A note can exit in full or in part, leaving hidden change.

Settlement. Every change to notes and positions is a batch of up to 256 ops proven by one SP1 program. The program checks membership, range proofs, balances and each op's rules, then commits only the public effects: nullifiers, new notes, payouts and fees. The contract verifies the proof and applies exactly those effects. Proofs never go stale, costs do not grow with use, and every proof is bound to one deployment.

5 Reflection: a bridge without signers

Bitcoin to Ethereum. Anyone may extend `BitcoinLightRelay`, a header relay that checks full proof-of-work and follows the heaviest chain. The reflection guest proves a run of blocks on top of it: it re-hashes every transaction, marks spent any input that spends a Tacit note, and re-verifies every Tacit envelope. The pool accepts the result once it is buried 24 blocks deep. Value then enters in two ways:

- **Bridge burn.** A note is destroyed on Bitcoin under an id naming the target pool, which mints it exactly once.
- **Fast lane.** A Bitcoin note bound to the pool is spent directly on Ethereum, with a signature from its Bitcoin key and proof that it is unspent on Bitcoin. Reflection then retires it on Bitcoin.

Ethereum to Bitcoin. A second guest, built on the `sp1-helios` light client, proves the pool's finalized state. The Bitcoin guest verifies that proof inside its own and acts on it: notes that left the pool are re-minted on Bitcoin, and fast-lane notes are retired.

Cross-chain calls. Reflection also carries calls, which move no value:

- **Bitcoin to Ethereum.** A Bitcoin key signs a `T_BTC_CALL`: a target contract and its calldata. The pool records it in an inbox, and `BtcCallExecutor` fires it once. The target sees which Bitcoin key signed, so a Bitcoin key can run an Ethereum smart account, vault or governance module with no Ethereum key.
- **Ethereum to Bitcoin.** Any Ethereum contract can post to `EthCallOutbox`. Reflection delivers the message to Bitcoin's inbox as a `T_ETH_CALL`, stamped with the sender's address, so an Ethereum DAO, timelock or oracle can direct Bitcoin-side applications.

The bridge rests on Bitcoin proof-of-work, the Ethereum sync committee and SP1. There is no multisig, attestor set or IOU. Anyone may run the provers, and Ethereum-side notes stay spendable

even if nobody does. A full round trip, from the pool to Bitcoin and back, has settled on mainnet.

6 Confidential DeFi

Swaps. Pools are constant-product curves with public reserves. `OP_SWAP_ROUTE` swaps a hidden note through up to four pools. `OP_SWAP` clears many hidden orders at one price, so nobody in a batch can be sandwiched. `TacitPublicAmm` trades the same reserves in the clear, so public and private liquidity share one curve.

Prover-blind swaps. `OP_SWAP_BLIND` hides trade sizes even from the SP1 prover. Traders commit to their inputs on a curve suited to a Groth16 circuit, which proves the batch's price and fills over hidden amounts; only the batcher that builds the proof sees them. The circuit's key comes from a public ceremony of over 5,000 contributions.

Trades without a pool. `OP_OTC` swaps two parties' notes directly. `OP_BID` is a limit order that fills while the buyer is offline. Adaptor locks give atomic swaps with the other chain.

Stealth payments. A payer locks a note to a one-time key only the recipient can derive. The recipient claims it, or the payer takes it back after a deadline.

cBTC. A user locks BTC on Bitcoin with a `T_CBTC_LOCK`, and the pool mints exactly that much cBTC, once. The locker keeps the lock's key. An escrow in wstETH worth at least $1.5\times$ the lock, which anyone may fund, makes spending the lock a loss: a lock spent without a redeem shows up in reflection and anyone can slash its escrow. The amount minted never depends on an oracle; a price feed only sizes the escrow. cBTC crosses to Bitcoin like any other Tacit note.

cUSD. A loan locks cBTC and mints cUSD, with 150% collateral to mint and liquidation below 130%. The borrower is hidden; the position's amounts are public so they can be priced. Policy lives in a governed `CollateralEngine` with on-chain caps, and a delay before a feed change or a stricter liquidation ratio applies.

Farms. LP shares bond into a receipt note that earns rewards. A running reward program can never be cut short or have its total rate lowered.

7 Gasless, self-sovereign, recoverable

Gasless. Any op may be relayed. The relayer's fee is bound inside the proof, so it cannot redirect a payout, raise the fee or act after the user's deadline. Once value is in the pool, a user never needs ETH. A Bitcoin-only user needs none at all: they enter and exit paying only BTC and act through relayers. Minting cBTC is the one exception, because its escrow is posted on Ethereum.

Self-sovereign. The relayer is optional. Anyone can call `settle`, proofs can be made locally, and all three guest programs rebuild byte for byte from source.

Recoverable. A wallet rebuilds every balance and position from its key and public chain data. There is no backup file to lose and no server to ask.

8 An immutable core that keeps improving

The pool, its guests and their verifying keys cannot be upgraded, so nobody can change the rules under a note that already exists. The protocol still improves in two ways.

At the edges. New Bitcoin opcodes, new tokens, new debt assets and reward programs, and better clients, relayers and provers all plug in without touching the core. V1 deepens as its market grows, with no migration.

By succession. The pool live today is the root of the V1 lineage. Each pool can deploy its successor once, through `createNextGen`, held by the ops multisig, which chooses the new code and nothing else: it cannot touch escrow, freeze an exit or redirect a payout. The successor continues the Bitcoin lane with no gap and keeps every asset’s identity. The old pool takes no new value but keeps every exit open, and users move on their own schedule.

9 Privacy

	Hidden	Public
Bitcoin	amounts; stealth recipients; batch trade sizes	addresses, the transaction graph, asset ids, burn amounts, AMM reserves
Pool	amounts; which owned note a spend consumes	deposits and withdrawals, AMM reserves, loan amounts
Relay	your key and blindings	the witness of the ops it proves

Proving locally keeps the witness on one device.

10 Trust and limits

Relied on:

- Bitcoin and Ethereum consensus;
- the soundness of SP1 and Groth16;
- the spl-helios sync committee;
- for the swap circuit only, one honest ceremony contributor;
- the `CollateralEngine` price feeds: BTC/USD for cUSD, and BTC per wstETH for cBTC escrow;
- the ops multisig (2-of-4, one-hour delay), within on-chain bounds;
- for walk-away bids on Bitcoin only, a watchtower holding a capped, dedicated key.

Not relied on: relayers, the hosted API, gateways and explorers.

Limits:

- Reflection halts, rather than rewrites, on a Bitcoin reorg deeper than 24 blocks.
- cBTC custody is economic until covenants.
- Bitcoin transfers carry a large witness, so Bitcoin suits settlement and the pool suits frequent activity.

11 Covenants, V2 and the road ahead

Bitcoin cannot yet restrict where an output may be spent. Once it can, through CTV, `OP_CAT`, `OP_CHECKSIGFROMSTACK`, `OP_VAULT` or an equivalent, Tacit’s reserved slots become fully trustless: cBTC locks whose sats can leave only through a redemption, bids escrowed on-chain instead of by a watchtower, and BTC split into fungible shares with no shared vault.

V2. V1 is built to hand off to this covenant generation, which it deploys through its own `createNextGen` and hands the Bitcoin lane to. cBTC then moves to enforced custody one lock at a time: a locker redeems a V1 lock, which frees its escrow, and re-locks the sats in a covenant vault that mints in V2 with no escrow. Every V1 note keeps its exits throughout.

A shielded pool on Bitcoin. The companion paper *Secret Sats* describes a shielded pool that lives on Bitcoin alone. It holds Tacit assets, not BTC, so nobody holds the pool. Each payment carries a small zero-knowledge proof, made on the payer’s own device, that hides the amount and unlinks sender from receiver, and every node checks it while replaying Bitcoin, with no Ethereum dependency. cBTC is its path to BTC, and sats also move in and out by atomic swap, and by covenant once Bitcoin allows one.

12 Conclusion

Tacit is an asset layer on Bitcoin with no bridge signer and no custodian:

- a metaprotocol with hidden amounts;
- an immutable, proof-gated pool that carries the same notes into confidential DeFi;
- a bridge of proofs in both directions, for value and for calls;
- cBTC, which carries real BTC into that DeFi and back to Bitcoin;
- a lineage of pools that improves as its market grows and hands off to V2 when Bitcoin gains covenants.

Where cryptography can enforce a property, it does. Where Bitcoin cannot yet enforce one, the gap is stated, bounded, and reserved for a covenant to close.

References

1. Rodarmor, C. *Ordinals* (2023); *Runes* (2024).
2. Pedersen, T.P. *Non-interactive and information-theoretic secure verifiable secret sharing*. CRYPTO 1991.
3. Jedusor, T.E. *Mimblewimble* (2016); Poelstra, A. *Mimblewimble* (2016).
4. Bünz, B. et al. *Bulletproofs*. IEEE S&P 2018. Chung, H. et al. *Bulletproofs+*. 2020.
5. Wuille, P.; Nick, J.; Ruffing, T.; Towns, A. *BIP-340, BIP-341*. 2020.
6. Groth, J. *On the size of pairing-based non-interactive arguments*. EUROCRYPT 2016.
7. Succinct. *SP1 zkVM; sp1-helios*.
8. Pertsev, A.; Semenov, R.; Storm, R. *Tornado Cash* (2019).
9. Walras, L. *Éléments d’économie politique pure* (1874); Gnosis Protocol (2019); Penumbrax ZSwap (2023).
10. Rubin, J. *BIP-119 (CTV); OP_CAT and OP_CHECKSIGFROMSTACK* proposals.
11. Tacit. *Secret Sats* (2026), companion paper.