

HW06 — AI-First API Testing Report

Submission identity

- Student: Nguyễn Đình Thái Hưng
- Student ID: 23127373
- SUT: EShop at `http://127.0.0.1:3000`
- Evidence status: official local Newman run with X-Student-Id: 23127373

1. API selection and collision check

Pool	Requirement	Chosen endpoint	Collision check
A	FR-03	POST /api/reset-password	Not selected by any listed friend
B	FR-09	POST /api/apply-coupon	Not selected by any listed friend
C	FR-16	POST /api/admin/import-products	Not selected by any listed friend

The selection deliberately avoids all nine endpoints reported by the three friends: login, checkout, admin order status, product listing, cart, admin coupon creation, registration, order cancelation, and category creation.

2. Method

For each endpoint I used a phased AI-first workflow: requirements decomposition → ambiguity correction → candidate generation → human audit → at least five student-added cases → data-driven Postman/Newman execution. Gemini was not allowed to inspect the implementation before generating candidates. Follow-up prompts explicitly corrected invented assumptions and unusable oracles. Full verbatim evidence is indexed in `ai-audit.md`.

The executable oracle distinguishes normative rules from unspecified behavior. ACCEPT/APPLY/COMMIT and REJECT/ROLLBACK cases assert requirements. OBSERVE cases assert only safety/stability and remain marked INCOMPLETE when the specification does not permit a binary verdict.

3. Test inventory and official execution result

API	AI candidates	VALID	INVALID	INCOMPLETE	Student-added	Executed	Passed	Failed
POST /api/reset-password	42	32	0	10	6	48	35	13
POST /api/apply-coupon	44	33	2	9	5	49	36	13
POST /api/admin/import-products	56	32	7	17	5	61	42	19

The official 158-case run used X-Student-Id: 23127373. Its 113 passing and 45 failing cases are not fabricated “green” evidence: failures are preserved because they reveal requirement violations.

4. Coverage

API	Domain partitions	State transitions	Security	Schema validation
reset-password	email, resetToken, newPassword	OTP active/reissued/old/used/email-bound	SEC-01, SEC-05, SEC-07; SQLi; leakage	Malformed/missing/null/type/extra fields
apply-coupon	code, total_amount, user_id, JWT	active/expired/disabled/usage threshold	SEC-02; missing/invalid/expired JWT; IDOR	Required numeric fields, formula and error stability
import-products	auth and every product property	commit/rollback, mixed batches, concurrency	FR-12/SEC-03 role gate; SQL/XSS literals; leakage	Top-level and row schema, malformed JSON, duplicate keys

The reset suite covers 42 AI candidates plus 6 extensions. Coupon uses 45 generated candidates, removes one invalid concurrency candidate, corrects three invalid candidates, and executes 44 corrected AI rows plus 5 extensions. Import uses 48 initial candidates plus 8 corrective supplemental candidates and 5 extensions. This keeps all three endpoints above the ≥35 target after audit.

5. Human audit decisions

- VALID: a traceable requirement and executable oracle exist.
- INVALID: the proposed case cannot establish its precondition or contradicts the endpoint contract; it is retained in the audit ledger but excluded or converted before execution.
- INCOMPLETE: useful exploratory input, but the specification leaves the expected result ambiguous; assertions are conservative.
- STUDENT_ADDED: a security, protocol, metamorphic, state, or white-box risk missed by Gemini.

Every row contains its label and reason in the Excel workbook and canonical case-definitions.mjs. Manual student sign-off remains required before submission; automated generation is not represented as personal review.

6. Postman/Newman implementation

Used features: collection folders; collection/environment/local variables; pre-request scripts; automatic X-Student-Id injection; dynamic unique users; bearer-token variables; data-driven JSON iterations; request chaining; setup/teardown fixtures; response-schema/formula/security assertions; CLI, JSON, JUnit, and HTML reporters. The local fixture API is limited to otherwise unreachable preconditions such as exact OTPs, coupon states, usage counts, and database snapshots. It is not the target API.

Not claimed: cloud workspace collaboration, Postman Monitor, or a hosted mock server. They are optional examples in the brief and were not necessary for deterministic local execution.

Reproduce from PowerShell in the repository root:

```
npm.cmd install
npm.cmd run generate:postman
npm.cmd run test:api -- --student-id 23127373
npm.cmd run verify:artifacts
```

7. Genuine defects

ID	Severity	Area	Finding	Evidence cases
BUG-01	Critical	Authentication	Passwords are stored in plaintext and login returns the full user record including password/reset_token/locked_until.	R-H-05, R-H-06

ID	Severity	Area	Finding	Evidence cases
BUG-02	High	Password reset	Reset accepts weak, missing, null, empty, and numeric passwords, contrary to FR-01.	R-AI-05..10, R-AI-35..38
BUG-03	High	OTP lifecycle	Forgot-password generates only four digits and stores no expiry timestamp; SEC-07 cannot be met.	Source review + R-AI-15
BUG-04	Critical	Coupon authorization	Apply-coupon has no JWT gate and trusts body user_id, enabling identity substitution and usage-limit bypass.	C-AI-02..06, C-AI-08..09
BUG-05	High	Coupon formula	Percent discount uses $\text{total} \times (1 - \text{discount_value})$, yielding negative discounts and inflated final totals.	C-AI-01, C-AI-19, C-AI-34
BUG-06	Medium	Coupon boundary	Minimum-order check uses $>$ instead of $\geq$, rejecting exact threshold values.	C-AI-18, C-AI-21, C-AI-22
BUG-07	Critical	Admin authorization	Import-products authenticates a JWT but never enforces <code>role=admin</code> .	I-AI-02, I-AI-56
BUG-08	High	Import validation	Rows validate only truthy name; invalid price/category/name-length values are inserted.	I-AI-21..33, I-H-04
BUG-09	High	Import atomicity	Mixed-invalid batches partially commit instead of rolling back the whole batch.	I-AI-40..42, I-AI-51, I-H-01
BUG-10	Medium	Error handling	Malformed JSON and null rows expose Express/Node stack details.	R-AI-40, C-AI-40, I-AI-45, I-H-01

Detailed reproduction steps, expected/actual results, and evidence references are in bug-reports.md. Source inspection supports root-cause analysis; the Newman failures remain the black-box evidence.

8. CI/CD

The workflow in api-tests.yml installs dependencies, regenerates artifacts, starts the local SUT, runs Newman, and uploads reports. The required all-pass versus one-fail pair is implemented as an explicit mutation-demonstration lane, separate from the diagnostic lane that preserves real SUT failures. Links and screenshots require the public GitHub push and are marked in ci-cd-report.md.

9. Agent Skill

The reusable skill under skills/eshop-api-test-generator decomposes specifications, classifies normative versus observational oracles, generates ≥ 35 candidates, audits them, adds human-risk prompts, and emits canonical rows/Postman data. Pseudocode is provided. The final diagram is intentionally not generated by AI because the brief explicitly requires it to be self-drawn; agent-skill-diagram-HUMAN-REVIEW.md is only a checklist for the student's own drawing.

10. Limitations and mandatory human review

OTP expiry and true concurrency need controlled time/parallel facilities not exposed by the published API. Identity and the official Newman rerun are complete. The student must still personally review/sign off rows, take the non-fabricated console screenshot, draw the diagram, record/upload the video, approve the final repository-visibility change, select the self-assessed grade, create the final ZIP, and submit it on Moodle. See manual-checklist.md.

11. AI declaration

I use AI tools for requirements analysis, test-candidate generation, critique, automation assistance, and report scaffolding. Full prompts, outputs, timestamps, corrections, and evidence paths are disclosed. Final correctness and submission responsibility remain with the student.