

# BUILDING A MODULARIZED SHINY APP WITH THE GOLEM AND HTML WIDGETS

**DR. CÉDRIC SCHERER**

Freelancing Data Visualization Designer  
Leibniz Institute for Zoo & Wildlife Research

 [cedricscherer.netlify.com](http://cedricscherer.netlify.com)

 [cedricphilippscherer@gmail.com](mailto:cedricphilippscherer@gmail.com)

 @CedScherer

 @Z3tt

Artwork by Benjamin Lacombe



[cedricscherer.netlify.com](http://cedricscherer.netlify.com)



[cedricphilipscherer@gmail.com](mailto:cedricphilipscherer@gmail.com)



@CedScherer



@Z3tt

# **CORRELAID X CHALLENGE 2020**



# MOVING THROUGH BERLIN BY BIKE

# **ANALYSING ACCIDENTS AND BICYCLE INFRASTRUCTURE IN BERLIN**

A CONTRIBUTION TO THE CORREL-AID X CHALLENGE 2020



# CORRELAID X CHALLENGE 2020

MOVING THROUGH BERLIN BY BIKE

**BERLINBIKES.CORRELAID.ORG**



[cedricscherer.netlify.com](http://cedricscherer.netlify.com)



[cedricphilipscherer@gmail.com](mailto:cedricphilipscherer@gmail.com)



@CedScherer



@Z3tt

# CORRELAID X CHALLENGE 2020




# ABOUT THE PROJECT


A Shiny app created with 🐾 and ❤️ for the CorrelAidX Challenge 2020  
*“Analysing and visualising German regional statistics with datenguidepy”*  
by Cédric Scherer, Andreas Neumann, Saleh Hamed & Steffen Reinhold




CorrelAidX Berlin, a local chapter of CorrelAid  
*Good Causes. Better Effects. Local Implementation.*

[Read more about our methodology](#)








Shiny is an R package that makes it easy to build interactive web apps straight from R.

[cedricscherer.netlify.com](http://cedricscherer.netlify.com)[cedricphilipscherer@gmail.com](mailto:cedricphilipscherer@gmail.com)

@CedScherer



@Z3t



**Shiny is an R package that makes it easy to build interactive web apps straight from R.**


You can host standalone apps on a webpage, build dashboards or embed them in R Markdown documents.

[cedricscherer.netlify.com](http://cedricscherer.netlify.com)[cedricphilipscherer@gmail.com](mailto:cedricphilipscherer@gmail.com)

@CedScherer



@Z3t



**Shiny is an R package that makes it easy to build interactive web apps straight from R.**

You can host standalone apps on a webpage, build dashboards or embed them in R Markdown documents.

You can extend your Shiny apps with CSS themes, htmlwidgets, and JavaScript actions.



# MASTERING SHINY

Hadley Wickham

👉 [mastering-shiny.org](https://mastering-shiny.org)

O'REILLY®

# Mastering Shiny

Build Interactive Apps, Reports & Dashboards  
Powered by R



Hadley Wickham



[cedricscherer.netlify.com](https://cedricscherer.netlify.com)



[cedricphilipscherer@gmail.com](mailto:cedricphilipscherer@gmail.com)



@CedScherer



@Z3tt

# Create a new directory and in this directory a file called app.R with the following content:

```
library(shiny)
ui <- fluidPage(
  "Hello, world!"
)
server <- function(input, output, session) {
}
shinyApp(ui, server)
```

Console Terminal Jobs

C:\Users\Balu\Work\Google Drive\Work\Stat\Personal\2020.Rstudio\TableContent

R version 4.0.2 (2020-06-22) -- "Taking Off Again"  
 Copyright (C) 2020 The R Foundation for Statistical Computing  
 Platform: x86\_64-w64-mingw32/x64 (64-bit)

R ist freie Software und kommt OHNE JEGLICHE GARANTIE.  
 Sie sind eingeladen, es unter bestimmten Bedingungen weiter zu verbreiten.  
 Tippen Sie 'license()' or 'licence()' für Details dazu.

R ist ein Gemeinschaftsprojekt mit vielen Beitragenden.  
 Tippen Sie 'contributors()' für mehr Information und 'citation()',  
 um zu erfahren, wie R oder R packages in Publikationen zitiert werden können.

Tippen Sie 'demo()' für einige Demos, 'help()' für on-line Hilfe, oder  
 'help.start()' für eine HTML Browserschnittstelle zur Hilfe.  
 Tippen Sie 'q()', um R zu verlassen.

&gt; |

Environment History Connections GT

Import Dataset

Global Environment

Environment is empty

Files Plots Packages Help Viewer

Run Shiny Application

runApp (shiny)

R Documentation

## Run Shiny Application

### Description

Runs a Shiny application. This function normally does not return; interrupt R to stop the application (usually by pressing Ctrl+C or Esc).

### Usage

```
runApp(
  appDir = getwd(),
  port = getOption("shiny.port"),
  launch.browser = getOption("shiny.launch.browser", interactive()),
  host = getOption("shiny.host", "127.0.0.1"),
  workerId = "",
  quiet = FALSE,
  display.mode = c("auto", "normal", "showcase"),
  ...)
```



# Modularizing Shiny app code

Last Updated: 17 Apr 2020

By: Winston Chang

As Shiny applications grow larger and more complicated, we use modules to manage the growing complexity of Shiny application code.



# Modularizing Shiny app code

Last Updated: 17 Apr 2020

By: Winston Chang

As Shiny applications grow larger and more complicated, **we use modules to manage the growing complexity** of Shiny application code.



[cedricscherer.netlify.com](https://cedricscherer.netlify.com)



[cedricphilipscherer@gmail.com](mailto:cedricphilipscherer@gmail.com)



@CedScherer



@Z3tt

## MOD.R

```
create_plot <- function(input, output, session, data) { ... }
```

```
create_plot_ui <- function(id) { ... }
```



## **SERVER.R**

```
callModule(create_plot, id = 'plotA', data = dataA)  
callModule(create_plot, id = 'plotB', data = dataB)  
callModule(create_plot, id = 'plotC', data = dataC)
```

## **UI.R**

```
create_plot_ui(id = 'plotA')  
create_plot_ui(id = 'plotB')  
create_plot_ui(id = 'plotC')
```

## **MOD.R**

```
create_plot <- function(input, output, session, data) { ... }  
create_plot_ui <- function(id) { ... }
```



## SERVER.R

```
callModule(create_plot, id = 'plotA', data = dataA)  
callModule(create_plot, id = 'plotB', data = dataB)  
callModule(create_plot, id = 'plotC', data = dataC)
```

## UI.R

```
create_plot_ui(id = 'plotA')  
create_plot_ui(id = 'plotB')  
create_plot_ui(id = 'plotC')
```

## MOD.R

```
create_plot <- function(input, output, session, data) { ... }  
create_plot_ui <- function(id) { ... }
```



## SERVER.R

```
callModule(create_plot, id = 'plotA', data = dataA)  
callModule(create_plot, id = 'plotB', data = dataB)  
callModule(create_plot, id = 'plotC', data = dataC)
```

## UI.R

```
create_plot_ui(id = 'plotA')  
create_plot_ui(id = 'plotB')  
create_plot_ui(id = 'plotC')
```

## MOD.R

```
create_plot <- function(input, output, session, data) { ... }
```

```
create_plot_ui <- function(id) { ... }
```



## SERVER.R

```
callModule(create_plot, id = 'plot', data = data)
callModule(create_map, id = 'map', data = data)
```

## UI.R

```
create_plot_ui(id = 'plot')
create_map_ui(id = 'map')
```

## MOD.R

```
create_plot <- function(input, output, session, data) { ... }
```

```
create_plot_ui <- function(id) { ... }
```

```
create_map <- function(input, output, session, data) { ... }
```

```
create_map_ui <- function(id) { ... }
```



## SERVER.R

```
callModule(create_plot, id = 'plot', data = data)
callModule(create_map, id = 'map', data = data)
```



## UI.R

```
create_plot_ui(id = 'plot')
create_map_ui(id = 'map')
```



## MOD\_PLOT.R

```
create_plot <- function(input, output, session, data) { ... }
create_plot_ui <- function(id) { ... }
```

## MOD\_MAP.R


```
create_map <- function(input, output, session, data) { ... }
create_map_ui <- function(id) { ... }
```



## MOD\_PLOT.R

```
create_plot_server <- function(input, output, session, data) {  
  ns <- session$ns  
  
  ...  
}  
  
create_plot_ui <- function(id) {  
  ns <- NS(id)  
  
  ...  
}
```





cedricscherer.netlify.com



cedricphilipscherer@gmail.com



@CedScherer



@Z3t




The `{golem}` package is an opinionated framework  
for building production-grade shiny applications.

# ENGINEERING PRODUCTION-GRADE SHINY APPS

Colin Fay, Sébastien Rochette,  
Vincent Guyader, Cervan Girard

👉 [engineering-shiny.org](https://engineering-shiny.org)



# If you haven't already installed {golem}:

```
install.packages("golem")
remotes::install_github("Thinkr-open/golem")
```



## New Project

 Back

## Project Type

R Package using RcppEigen &gt; ^

R Package using RcppParallel &gt;

 Book Project using bookdown >

R Package using devtools &gt;

 Package for Shiny App using golem > New Plumber API Project >

Simple R Markdown Website &gt; ✓

Create a new  
Package for Shiny  
App using golem

Cancel



cedricscherer.netlify.com



cedricphilipscherer@gmail.com



@CedScherer



@Z3tt

## # Building a Prod-Ready, Robust Shiny Application.

```
#  
# README: each step of the dev files is optional, and you don't have to  
# fill every dev scripts before getting started.  
# 01_start.R should be filled at start.  
# 02_dev.R should be used to keep track of your development during the project.  
# 03_deploy.R should be used once you need to deploy your app.
```



01\_START.R

```
#####
#### CURRENT FILE: ON START SCRIPT #####
#####
```

## Fill the DESCRIPTION ----

## Add meta data about your application

golem::fill\_desc(

pkg\_name = "golex", # The Name of the package containing the App

pkg\_title = "PKG\_TITLE", # The Title of the package containing the App

pkg\_description = "PKG\_DESC.", # The Description of the package containing  
the App

author\_first\_name = "AUTHOR\_FIRST", # Your First Name

author\_last\_name = "AUTHOR\_LAST", # Your Last Name

author\_email = "AUTHOR@MAIL.COM", # Your Email

repo\_url = NULL # The URL of the GitHub Repo (optional)

)

02\_DEV.R

03\_DEPLOY.R

Codes on GitHub:

**Z3TT/CORRELCON2020\_GOLEM\_HTML\_WIDGETS**



cedricscherer.netlify.com



cedricphilipscherer@gmail.com



@CedScherer



@Z3tt

## 01\_START.R

## 02\_DEV.R

## 03\_DEPLOY.R

```
#####
#### CURRENT FILE: ON START SCRIPT #####
#####

## Fill the DESCRIPTION ----

## Add meta data about your application
golem::fill_desc(
  pkg_name = "correlcon", # The Name of the package containing the App
  pkg_title = "A tutorial on the golem package and html widgets for nice looking
  Shiny apps", # The Title of the package containing the App
  pkg_description = "This Shiny app is build with the help of the {golem} framework
  and exemplary uses the html widgets {echarts4R}, {tmap}, and
  {shinycssloader}.", # The Description of the package containing the App
  author_first_name = "Cédric", # Your First Name
  author_last_name = "Scherer", # Your Last Name
  author_email = "cedricphilipscherer@gmail.com", # Your Email
  repo_url = NULL # The URL of the GitHub Repo (optional)
)
```



01\_START.R

## ## Set {golem} options ----

```
golem::set_golem_options()
```

## ## Create Common Files ----

## See ?usethis for more information

```
usethis::use_mit_license( name = "Cédric Scherer" ) # You can set another license here
```

```
usethis::use_readme_rmd( open = FALSE )
```

```
usethis::use_code_of_conduct()
```

```
usethis::use_lifecycle_badge( "Experimental" )
```

```
usethis::use_news_md( open = FALSE )
```

## ## Use git ----

```
usethis::use_git()
```

## ## Init Testing Infrastructure ----

## Create a template for tests

```
golem::use_recommended_tests()
```

02\_DEV.R

03\_DEPLOY.R



01\_START.R

## ## Use Recommended Packages ----

```
golem::use_recommended_deps()
```

## ## Favicon ----

# If you want to change the favicon (default is golem's one)

```
golem::remove_favicon()
```

```
golem::use_favicon("https://raw.githubusercontent.com/CorrelAid/xberlin/
master/inst/app/www/favicon.ico") # path = "path/to/ico". Can be an online file.
```

## ## Add helper functions ----

```
golem::use_utils_ui()
```

```
golem::use_utils_server()
```


## # You're now set! ----

```
# go to dev/02_dev.R
```

```
rstudioapi::navigateToFile( "dev/02_dev.R" )
```

02\_DEV.R

03\_DEPLOY.R



01\_START.R

02\_DEV.R

03\_DEPLOY.R

```
#####
##### CURRENT FILE: DEV SCRIPT #####
#####

# Engineering

## Dependencies ----
## Add one line by package you want to add as dependency
usethis::use_package("echarts4r")
usethis::use_package("tmap")

## Add modules ----
## Create a module infrastructure in R/
golem::add_module( name = "bars_echarts" ) # Name of the module
golem::add_module( name = "map_tmap" ) # Name of the module
```

01\_START.R

02\_DEV.R

03\_DEPLOY.R

```
#####
##### CURRENT FILE: DEV SCRIPT #####
#####

# Engineering

## Dependencies ----
## Add one line by package you want to add as dependency
usethis::use_package("echarts4r")
usethis::use_package("tmap")

## Add modules ----
## Create a module infrastructure in R/
golem::add_module( name = "bars_echarts" ) # Name of the module
golem::add_module( name = "map_tmap" ) # Name of the module
```



```
#' bars_echarts UI Function
#'
#' @description A shiny Module.
#'
#' @param id,input,output/session Internal parameters for {shiny}.
#'
#'
#' @noRd
#'
#'
#' @importFrom shiny NS tagList
mod_bars_echarts_ui <- function(id){
  ns <- NS(id)
  tagList(
    )
}
```

02. DEV.R

R/MOD\_BARS\_ECHARTS.R

01\_START.R

02\_DEV.R

03\_DEPLOY.R

R/MOD\_BARS\_ECHARTS.R

```
' #' bars_echarts Server Function
#'
#' @noRd
mod_bars_echarts_server <- function(input, output, session){
  ns <- session$ns

}

## To be copied in the UI
# mod_bars_echarts_ui("bars_echarts_ui_1")

## To be copied in the server
# callModule(mod_bars_echarts_server, "bars_echarts_ui_1")
```

## SERVER.R

```
callModule(mod_bars_echarts_server, "bars_echarts_ui_1")
callModule(mod_map_tmap_server, "map_tmap_ui_1")
```



## UI.R

```
mod_bars_echarts_ui("bars_echarts_ui_1")
mod_map_tmap_ui("map_tmap_ui_1")
```



## R/MOD\_BARS\_ECHARTS.R

```
mod_bars_echarts_ui <- function(id){
  ns <- NS(id)
  tagList()
}
mod_bars_echarts_server <- function(input, output, session){
  ns <- session$ns
}
```

## R/MOD\_MAP\_TMAP.R

```
mod_map_tmap_ui <- function(id){
  ns <- NS(id)
  tagList()
}
mod_map_tmap_server <- function(input, output, session){
  ns <- session$ns
}
```



01\_START.R

## ## Add helper functions ----

```
## Creates ftc_* and utils_*
golem::add_fct("helpers")
golem::add_utils("helpers")
```

02\_DEV.R

## ## External resources ----

```
## Creates .js and .css files at inst/app/www
golem::add_js_file("script")
golem::add_js_handler("handlers")
golem::add_css_file("custom")
```

03\_DEPLOY.R

## ## Add internal datasets ----

```
## If you have data in your package
usethis::use_data_raw(name = "my_dataset", open = FALSE)
```

## ## Tests ----

```
## Add one line by test you want to create
usethis::use_test("app")
```



01\_START.R

02\_DEV.R

03\_DEPLOY.R

## # Documentation

### ## Vignette ----

```
usethis::use_vignette("correlcon")
devtools::build_vignettes()
```

### ## Code coverage ----

```
## (You'll need GitHub there)
usethis::use_github()
usethis::use_travis()
usethis::use_appveyor()
```

### # You're now set! ----

```
# go to dev/03_deploy.R
rstudioapi::navigateToFile("dev/03_deploy.R")
```



01\_START.R

02\_DEV.R

03\_DEPLOY.R

```
#####
#### CURRENT FILE: DEPLOY SCRIPT #####
#####
```

```
# Test your app
```

```
## Run checks ----
```

```
## Check the package before sending to prod
devtools::check()
rhub::check_for_cran()
```

```
# Deploy
```

```
## RStudio ----
```

```
## If you want to deploy on RStudio related platforms
golem::add_rstudioconnect_file()
golem::add_shinyappsi_file()
golem::add_shinyserver_file()
```

## 03\_DEPLOY.R

## 02\_DEV.R

## 01\_START.R


## Docker ----

## If you want to deploy via a generic Dockerfile  
golem::add\_dockerfile()

## If you want to deploy to ShinyProxy  
golem::add\_dockerfile\_shinyproxy()

## If you want to deploy to Heroku  
golem::add\_dockerfile\_heroku()





cedricscherer.netlify.com



cedricphilipscherer@gmail.com



@CedScherer



@Z3tt



pagePiling.js meets Shiny!



## APP\_SERVER.R

```
#' The application server-side
#
#' @param input,output/session Internal parameters for {shiny}. #' @import shiny
#' @noRd
app_server <- function( input, output, session ) {
  # List the first level callModules here
  callModule(mod_bars_echarts_server, "bars_echarts_ui_1")
  callModule(mod_map_tmap_server, "map_tmap_ui_1")
}
```

## APP\_UI.R

## APP\_SERVER.R

```
'# The application server-side
#
#' @param input,output/session Internal parameters for {shiny}. #' @import shiny
#' @noRd
app_server <- function( input, output, session ) {
  # List the first level callModules here
  callModule(mod_bars_echarts_server, "bars_echarts_ui_1")
  callModule(mod_map_tmap_server, "map_tmap_ui_1")
}
```

## APP\_UI.R

## SERVER.R

```
callModule(mod_bars_echarts_server, "bars_echarts_ui_1")
callModule(mod_map_tmap_server, "map_tmap_ui_1")
```

APP\_SERVER.R

APP\_UI.R

```
#' The application User-Interface
#`@param request Internal parameter for `shiny}`.
#' @import shiny fullPage
#' @noRd
app_ui <- function(request) {
  tagList(
    # Leave this function for adding external resources
    golem_add_external_resources(),
    # List the first level UI elements here
    fullPage::pagePiling(
      sections.color = c('#f1f1f1', '#dddddd'),
      opts = list(easing = "linear", keyboardScrolling = TRUE),
      menu = c("interactive bar chart" = "bar",
              "interactive map" = "map"),
      fullPage::pageSection(center = TRUE,
                            menu = "bar",
                            mod_bars_echarts_ui("bars_echarts_ui_1")),
      fullPage::pageSection(center = TRUE,
                            menu = "map",
                            mod_map_tmap_ui("map_tmap_ui_1"))
    )
  )
}
```



## APP\_SERVER.R

## APP\_UI.R

```

#' The application User-Interface
#`@param request Internal parameter for `'{shiny}'`.
#`@import shiny fullPage
#`@noRd

app_ui <- function(request) {
  tagList(
    # Leave this function for adding external resources
    golem_add_external_resources(),
    # List the first level UI elements here
    fullPage::pagePiling(
      sections.color = c('#f1f1f1', '#dddddd'),
      opts = list(easing = "linear", keyboardScrolling = TRUE),
      menu = c("interactive bar chart" = "bar",
              "interactive map" = "map"),
      fullPage::pageSection(center = TRUE,
                            menu = "bar",
                            mod_bars_echarts_ui("bars_echarts_ui_1")),
      fullPage::pageSection(center = TRUE,
                            menu = "map",
                            mod_map_tmap_ui("map_tmap_ui_1"))
    )
  )
}

```


## UI.R

```

mod_bars_echarts_ui("bars_echarts_ui_1")
mod_map_tmap_ui("map_tmap_ui_1")

```









## Line


Basic Line Chart




Basic area chart




Smoothed Line Chart








Stacked area chart




Stacked Line Chart



Area Pieces




Try Dragging these Points




Line Easing Visualizing




Function Plot






Line Gradient




Custom Graphic Component




Line Chart in Cartesian Coordinate System



Click to Add Points



Two Value-Axes in Polar



Distribution of Electricity



Step Line



Line Style and Item Style



Tooltip and DataZoom on Mobile



Line Y Category



Multiple X Axes



# echarts4r



Interactive visualisations for R via [Apache ECharts \(incubating\)](#)

[GET STARTED](#)
[REFERENCE](#)
[TIMELINE](#)
[SHINY DEMO](#)


## New Features

"Use (almost) any chart serie as chart proxy, now on CRAN!"

[EXPLORE](#)
[CHANGELOG](#)

## Installation

The package is available on [CRAN](#). The full installation can be obtained with:

```
install.packages("echarts4r")
```

However, if you only want a *lite* version you can simply do, this is useful for a lighter version that installs faster if you do not want to use any of the geospatial features of the package:

```
install.packages("echarts4r", dependencies = c("Depends", "Imports"))
```

You can also install the *unstable* development version of echarts4r with `remotes` from Github, see [changes](#).

```
# install.packages("remotes")
remotes::install_github("JohnCoene/echarts4r")
```

如果您位于中国, 请安装

```
# install.packages("remotes")
remotes::install_github("https://gitee.com/JohnCoene/echarts4r")
```

## Links

Download from CRAN at  
[https://cloud.r-project.org/  
package=echarts4r](https://cloud.r-project.org/package=echarts4r)

Browse source code at  
[https://github.com/JohnCoene/  
echarts4r/](https://github.com/JohnCoene/echarts4r/)

Report a bug at  
[https://github.com/JohnCoene/  
echarts4r/issues](https://github.com/JohnCoene/echarts4r/issues)

Original library at  
<https://echarts.apache.org/>

## License

[Full license](#)

Apache License (>= 2.0)

## Community

[Code of conduct](#)

## Developers

[John Coene](#)

Author, maintainer, copyright holder

[All authors...](#)

## Support


Sponsor the project

[Sponsor](#)

[interactive bar chart](#)[interactive map](#)

## An interactive bar chart

■ Bikes ■ Cars ■ Pedestrians ■ Motorcycles




Source: Statistische Ämter des Bundes und der Länder via [Unfallatlas](#)


interactive bar chart

interactive map

## An interactive bar chart



Source: Statistische Ämter des Bundes und der Länder via [Unfallatlas](#)



## R/MOD\_BARS\_ECHARTS.R

```
mod_bars_echarts_server <- function(input, output, session){  
  ns <- session$ns  
  
  output$bars <- echarts4r::renderEcharts4r({  
    accidents_sum_bikes %>%  
    dplyr::group_by(type) %>%  
    echarts4r::e_charts(Gemeinde_name) %>%  
    echarts4r::e_bar(accidents) })  
}
```

## R/MOD\_BARS\_ECHARTS.R

```
mod_bars_echarts_server <- function(input, output, session){  
  ns <- session$ns  
  
  output$bars <- echarts4r::renderEcharts4r({  
    accidents_sum_bikes %>%  
    dplyr::group_by(type) %>%  
    echarts4r::e_charts(Gemeinde_name) %>%  
    echarts4r::e_bar(accidents)  
  })  
}
```

## RENDER CHART FOR UI



## R/MOD\_BARS\_ECHARTS.R

```
mod_bars_echarts_server <- function(input, output, session){  
  ns <- session$ns  
  
  output$bars <- echarts4r::renderEcharts4r({  
    accidents_sum_bikes %>%  
    dplyr::group_by(type) %>%  
    echarts4r::e_charts(Gemeinde_name) %>%  
    echarts4r::e_bar(accidents)  
  })  
}
```

### BAR CHART ACCIDENTS VS GEMEINDE\_NAME GROUPED BY TYPE



## R/MOD\_BARS\_ECHARTS.R

```
mod_bars_echarts_server <- function(input, output, session){  
  ns <- session$ns  
  
  output$bars <- echarts4r::renderEcharts4r({  
    accidents_sum_bikes %>%  
    dplyr::group_by(type) %>%  
    echarts4r::e_charts(Gemeinde_name) %>%  
    echarts4r::e_bar(accidents) %>%  
    echarts4r::e_x_axis(axisTick = list(interval = 0),  
                        axisLabel = list(rotate = 30),  
                        nameGap = 35) %>%  
    echarts4r::e_grid(bottom = 100, left = 150)  
  })  
}
```

**ROTATE LABELS  
TO SHOW ALL GEMEINDE\_NAMES**



## R/MOD\_BARS\_ECHARTS.R

```
mod_bars_echarts_server <- function(input, output, session){  
  ns <- session$ns  
  
  output$bars <- echarts4r::renderEcharts4r({  
    accidents_sum_bikes %>%  
    dplyr::group_by(type) %>%  
    echarts4r::e_charts(Gemeinde_name) %>%  
    echarts4r::e_bar(accidents) %>%  
    echarts4r::e_x_axis(axisTick = list(interval = 0),  
                        axisLabel = list(rotate = 30),  
                        nameGap = 35) %>%  
    echarts4r::e_grid(bottom = 100, left = 150) %>%  
    echarts4r::e_toolbox_feature(feature = "dataZoom") %>%  
    echarts4r::e_toolbox_feature(feature = "dataView") %>%  
    echarts4r::e_toolbox(bottom = 0)  
  })  
}
```

## ADD TOOLBOX



## R/MOD\_BARS\_ECHARTS.R

```
mod_bars_echarts_ui <- function(id){  
  ns <- NS(id)  
  fullPage::pageContainer(  
    h1("An interactive bar chart"),  
    br(),  
    echarts4r::echarts4rOutput(ns("bars"), height = "50vh")  
    br(), br(),  
    p("Source: Statistische Ämter des Bundes und der Länder via ",  
      tags$a(href = "https://unfallatlas.statistikportal.de/_opendata2020.html", "Unfallatlas"))  
  )  
}
```


## R/MOD\_BARS\_ECHARTS.R

```
mod_bars_echarts_ui <- function(id){  
  ns <- NS(id)  
  fullPage::pageContainer(  
    h1("An interactive bar chart"),  
    br(),  
    echarts4r::echarts4rOutput(ns("bars"), height = "50vh")  
    br(), br(),  
    p("Source: Statistische Ämter des Bundes und der Länder via ",  
      tags$a(href = "https://unfallatlas.statistikportal.de/_opendata2020.html", "Unfallatlas"))  
  )  
}
```



## R/MOD\_BARS\_ECHARTS.R

```
mod_bars_echarts_ui <- function(id){  
  ns <- NS(id)  
  fullPage::pageContainer(  
    h1("An interactive bar chart"),  
    br(),  
    echarts4r::echarts4rOutput(ns("bars"), height = "50vh")  
    br(), br(),  
    p("Source: Statistische Ämter des Bundes und der Länder via ",  
      tags$a(href = "https://unfallatlas.statistikportal.de/_opendata2020.html", "Unfallatlas"))  
  )  
}
```



# {shinycssloaders} - Add loading animations to a Shiny output while it's recalculating

[CRAN 1.0.0](#) [build](#) [passing](#)

When a Shiny output (such as a plot, table, map, etc.) is recalculating, it remains visible but gets greyed out. Using `{shinycssloaders}`, you can add a loading animation ("spinner") to outputs instead of greying them out. By wrapping a Shiny output in `withSpinner()`, a spinner will automatically appear while the output is recalculating.

You can choose from one of 8 built-in animation types, and customize the colour/size. You can also use your own image instead of the built-in animations. See the [demo Shiny app](#) online for examples.


## Table of contents

- [Example](#)
- [How to use](#)
- [Installation](#)
- [Features](#)
- [Sponsors](#) 

## Example

For interactive examples and to see some of the features, [check out the demo app](#).

Below is a simple example of what `{shinycssloaders}` looks like:



## Contributors 3

-  daattali Dean Attali
-  andrewsali
-  sTeamTraen Nick Brown

## Languages

- 
- CSS 65.6%
  - R 28.5%
  - JavaScript 5.9%



[cedricscherer.netlify.com](#)



[cedricphilipscherer@gmail.com](mailto:cedricphilipscherer@gmail.com)



[@CedScherer](#)



[@Z3tt](#)

# Single Element CSS Spinners

4

BG FG

[View Source](#)[View Source](#)[View Source](#)[View Source](#)[View Source](#)[View Source](#)[View Source](#)[View Source](#)

Created by @lukehaas



cedricscherer.netlify.com



cedricphilipscherer@gmail.com



@CedScherer



@Z3t

## R/MOD\_BARS\_ECHARTS.R


```
mod_bars_echarts_ui <- function(id){  
  ns <- NS(id)  
  fullPage::pageContainer(  
    pageContainer(  
      h1("An interactive bar chart"),  
      br(),  
      shinyCSSloaders::withSpinner(  
        echarts4r::echarts4rOutput(ns("bars"), height = "50vh")  
      ),  
      ),  
      br(), br(),  
      p("Source: Statistische Ämter des Bundes und der Länder via ",  
      tags$a(href = "https://unfallatlas.statistikportal.de/_opendata2020.html", "Unfallatlas"))  
    )  
}
```

## R/MOD\_BARS\_ECHARTS.R

```
mod_bars_echarts_ui <- function(id){  
  ns <- NS(id)  
  fullPage::pageContainer(  
    pageContainer(  
      h1("An interactive bar chart"),  
      br(),  
      shinyCSSloaders::withSpinner(  
        echarts4r::echarts4rOutput(ns("bars"), height = "50vh")  
      ),  
      ),  
      br(), br(),  
      p("Source: Statistische Ämter des Bundes und der Länder via ",  
        tags$a(href = "https://unfallatlas.statistikportal.de/_opendata2020.html", "Unfallatlas"))  
    )  
}
```

## APP\_UI.R

```
options(  
  spinner.type = 7,  
  spinner.color = "#11a579",  
  spinner.size = 1  
)
```



## tmap: get started!


- Hello World!
- Interactive maps
- Multiple shapes and layers
- Facets
- Basemaps and overlay tile maps
- Options and styles
- Exporting maps
- Shiny integration
- Quick thematic map
- Tips & Tricks

With the tmap package, thematic maps can be generated with great flexibility. The syntax for creating plots is similar to that of `ggplot2`, but tailored to maps. This vignette is for those who want to get started with tmap within a couple of minutes. A more detailed description of tmap can be found in an [article](#) published in the R Journal. The vignette is based on version 0.3.0 of the package, which is the latest version at the time of writing. Some minor changes have been made since then, which are described in `vignettes("tmap-changes")`. For more context on R's geographic capabilities we recommend the online version of the book [Geocomputation with R](#). The `Mapping maps with R` chapter of the book provides many more context and abundant code examples of map making with `tmap` and other packages. Other good resources are the vignettes of the `sf` package, and the website [rspatial.org](#).

### Hello World!

A good place to start is to create a map of the world. After [installing tmap](#), the following lines of code should create the map shown below.

```
library(tmap)
data("world")
tm_shape(world) +
  tm_polygons("HPI")
```




The object `world` is a spatial object of class `sf` from the `sf` package. It is a `data.frame` with a special column that contains a geometry for each row, in this case polygons. In order to plot in tmap, you first need to specify it with `tm_shape`. Layers can be added with the `+` operator, in this case `tm_polygons`. There are many layer functions in tmap, which can easily be found in the documentation by their `tm_` prefix. See also `?tm_shape_element`.


### Interactive maps

Each map can be plotted as a static image or viewed interactively using `"list"` and `"view"` modes, respectively. The mode can be set with the function `tm_map_mode`, and toggling between the modes can be done with the `Switch tm()` (which stands for toggle thematic map).

```
tm_map_mode("view")
tm_shape(world) +
  tm_polygons("HPI")
```



## multiple shapes and layers



## multiple maps via facets




## leaflet base- and tilemaps



interactive bar chart

interactive map

# An interactive map



Source: Statistische Ämter des Bundes und der Länder via [Unfallatlas](#) • Geoportal Berlin via [Technologiestiftung Berlin](#)



cedricscherer.netlify.com



cedricphilipscherer@gmail.com




@CedScherer



@Z3tt

[interactive bar chart](#)[interactive map](#)


# An interactive map



Source: Statistische Ämter des Bundes und der Länder via [Unfallatlas](#) • Geoportal Berlin via [Technologiestiftung Berlin](#)

[interactive bar chart](#)[interactive map](#)

# An interactive map



Source: Statistische Ämter des Bundes und der Länder via [Unfallatlas](#) • Geoportal Berlin via [Technologiestiftung Berlin](#)

[cedricscherer.netlify.com](#)[@cedricphilipscherer@gmail.com](mailto:cedricphilipscherer@gmail.com)

@CedScherer



@Z3tt

## R/MOD\_MAP\_TMAP.R

```
mod_map_tmap_server <- function(input, output, session){  
  ns <- session$ns  
  
  output$map <- renderTmap({  
    tmap::tm_shape(traffic_summary_int, name = "Ratio Map") +  
      tmap::tm_polygons(  
        id = "NAME.x",  
        col = "bike"  
      )  
  })  
}
```



## R/MOD\_MAP\_TMAP.R

```
mod_map_tmap_server <- function(input, output, session){  
  ns <- session$ns  
  
  output$map <- renderTmap({  
    tmap::tm_shape(traffic_summary_int, name = "Ratio Map") +  
    tmap::tm_polygons(  
      id = "NAME.x",  
      col = "bike"  
    )  
  })  
}
```

## RENDER MAP FOR UI



## R/MOD\_MAP\_TMAP.R

```
mod_map_tmap_server <- function(input, output, session){  
  ns <- session$ns  
  
  output$map <- renderTmap({  
    tmap::tm_shape(traffic_summary_int, name = "Ratio Map") +  
      tmap::tm_polygons(  
        id = "NAME.x",  
        col = "bike"  
      )  
  })  
}
```

**CHLOROPLETH MAP**  
POLYGONS NAME.X  
COLORED BY BIKE



## R/MOD\_MAP\_TMAP.R

```
mod_map_tmap_server <- function(input, output, session){  
  ns <- session$ns  
  
  output$map <- renderTmap({  
    tmap::tm_shape(traffic_summary_int, name = "Ratio Map") +  
    tmap::tm_polygons(  
      id = "NAME.x",  
      col = "bike", alpha = .75, border.col = "white",  
      palette = rev(rcartocolor::carto_pal(n = 5, "ag_Sunset")),  
      breaks = c(1, 5, 10, 15, 20, 25, 30, Inf),  
      legend.reverse = TRUE,  
      textNA = "No Accidents in 2019",  
      title = "Number of reported\nbike accidents",  
      popup.vars = c("District:" = "Gemeinde_name",  
                   "Total number of bike accidents:" = "n_total",  
                   "Accidents on bicycle infrastructure:" = "n_bike",  
                   "Proportion:" = "perc_bike")  
    )  
  })  
}
```

**MODIFY COLORS +  
LEGEND**



## R/MOD\_MAP\_TMAP.R

```
mod_map_tmap_server <- function(input, output, session){  
  ns <- session$ns  
  
  output$map <- renderTmap({  
    tmap::tm_shape(traffic_summary_int, name = "Ratio Map") +  
    tmap::tm_polygons(  
      id = "NAME.x",  
      col = "bike", alpha = .75, border.col = "white",  
      palette = rev(rcartocolor::carto_pal(n = 5, "ag_Sunset")),  
      breaks = c(1, 5, 10, 15, 20, 25, 30, Inf),  
      legend.reverse = TRUE,  
      textNA = "No Accidents in 2019",  
      title = "Number of reported\nbike accidents",  
      popup.vars = c("District:" = "Gemeinde_name",  
                   "Total number of bike accidents:" = "n_total",  
                   "Accidents on bicycle infrastructure:" = "n_bike",  
                   "Proportion:" = "perc_bike")  
    )  
  })  
}
```

## MODIFY TOOLTIPS



## R/MOD\_MAP\_TMAP.R

```
mod_map_tmap_ui <- function(id){  
  ns <- NS(id)  
  fullPage::pageContainer(  
    tags$style(  
      type = "text/css",  
      "div.info.legend.leaflet-control {text-align:left; }"  
      "div.leaflet-control-layers-expanded {text-align:left;}")  
  ),  
  h1("An interactive map"), br(),  
  shinycssloaders::withSpinner(  
    tmap::tmapOutput(ns("map"), height = 530)  
  ),  
  br(), br(),  
  p("Source: Statistische Ämter des Bundes und der Länder via",  
    tags$a(href = "https://unfallatlas.statistikportal.de/_opendata2020.html", "Unfallatlas"),  
    " • Geoportal Berlin via",  
    tags$a(href = "https://data.technologiestiftung-berlin.de/", "Technologiestiftung Berlin"))  
)  
}
```

## R/MOD\_MAP\_TMAP.R

```
mod_map_tmap_ui <- function(id){  
  ns <- NS(id)  
  fullPage::pageContainer(  
    tags$style(  
      type = "text/css",  
      "div.info.legend.leaflet-control {text-align:left; }"  
      "div.leaflet-control-layers-expanded {text-align:left;}"  
    ),  
    h1("An interactive map"), br(),  
    shinycssloaders::withSpinner(  
      tmap::tmapOutput(ns("map"), height = 530)  
    ),  
    br(), br(),  
    p("Source: Statistische Ämter des Bundes und der Länder via",  
      tags$a(href = "https://unfallatlas.statistikportal.de/_opendata2020.html", "Unfallatlas"),  
      " • Geoportal Berlin via",  
      tags$a(href = "https://data.technologiestiftung-berlin.de/", "Technologiestiftung Berlin"))  
  )  
}
```

## R/MOD\_MAP\_TMAP.R

```
mod_map_tmap_ui <- function(id){  
  ns <- NS(id)  
  fullPage::pageContainer(  
    tags$style(  
      type = "text/css",  
      "div.info.legend.leaflet-control {text-align:left; }  
      div.leaflet-control-layers-expanded {text-align:left;}"  
    ),  
    h1("An interactive map"), br(),  
    shinycssloaders::withSpinner(  
      tmap::tmapOutput(ns("map"), height = 530)  
    ),  
    br(), br(),  
    p("Source: Statistische Ämter des Bundes und der Länder via",  
      tags$a(href = "https://unfallatlas.statistikportal.de/_opendata2020.html", "Unfallatlas"),  
      " • Geoportal Berlin via",  
      tags$a(href = "https://data.technologiestiftung-berlin.de/", "Technologiestiftung Berlin"))  
  )  
}
```

## R/MOD\_MAP\_TMAP.R

```
mod_map_tmap_ui <- function(id){  
  ns <- NS(id)  
  fullPage::pageContainer(  
    tags$style(  
      type = "text/css",  
      "div.info.legend.leaflet-control {text-align:left; }"  
      "div.leaflet-control-layers-expanded {text-align:left;}")  
  ),  
  h1("An interactive map"), br(),  
  shinycssloaders::withSpinner(  
    tmap::tmapOutput(ns("map"), height = 530)  
  ),  
  br(), br(),  
  p("Source: Statistische Ämter des Bundes und der Länder via",  
    tags$a(href = "https://unfallatlas.statistikportal.de/_opendata2020.html", "Unfallatlas"),  
    " • Geoportal Berlin via",  
    tags$a(href = "https://data.technologiestiftung-berlin.de/", "Technologiestiftung Berlin"))  
)  
}
```

Codes on GitHub:

**Z3TT/CORRELCON2020\_GOLEM\_HTML\_WIDGETS**

Additional Code for adding button in branch “buttons”



[cedricscherer.netlify.com](https://cedricscherer.netlify.com)



[cedricphilipscherer@gmail.com](mailto:cedricphilipscherer@gmail.com)



@CedScherer




@Z3tt



[Interactive bar chart](#)
[interactive map](#)

## An interactive bar chart



Source: Statistische Ämter des Bundes und der Länder via [Unfallatlas](#)




Interactive bar chart

interactive map

# An interactive map

Choose set of bike accidents

 All bike accidents    Accidents on roads    Accidents on bicycle infrastructure

Source: Statistische Ämter des Bundes und der Länder via [Unfallatlas](#) • Geoportal Berlin via [Technologiestiftung Berlin](#)



cedricscherer.netlify.com



cedricphilipscherer@gmail.com



@CedScherer



@Z3tt

# RESOURCES



## Books

- „Mastering Shiny“ by Hadley Wickham ([mastering-shiny.org](http://mastering-shiny.org))
- „Engineering Production-Grade Shiny Apps“ by Colin Fay *et al.* ([engineering-shiny.org](http://engineering-shiny.org))
- „JavaScript for R“ by Joene Coene ([javascript-for-r.com](http://javascript-for-r.com))

## Packages for charts

- `{plotly}` ([plot.ly/r](https://plot.ly/r))
- `{echarts4r}` ([echarts4r.john-coene.com](https://echarts4r.john-coene.com))
- `{ggiraph}` ([davidgohel.github.io/ggiraph](https://davidgohel.github.io/ggiraph))
- `{highcharter}` ([jkunst.com/highcharter](https://jkunst.com/highcharter))
- `{dygraphs}` ([rstudio.github.io/dygraphs](https://rstudio.github.io/dygraphs))
- `{charter}` ([github.com/johncoene/charter](https://github.com/johncoene/charter))
- `{rbokeh}` ([hafen.github.io/rbokeh](https://hafen.github.io/rbokeh))
- `{metricsgraphics}` ([hrbrmstr.github.io/metricsgraphics](https://hrbrmstr.github.io/metricsgraphics))
- `{rthreejs}` ([github.com/bwlewis/rthreejs](https://github.com/bwlewis/rthreejs))
- `{visnetwork}` ([dataknowledge.github.io/visNetwork](https://dataknowledge.github.io/visNetwork))
- `{networkD3}` ([christophergandrud.github.io/networkD3/](https://christophergandrud.github.io/networkD3/))
- `{DiagrammeR}` ([rich-iannone.github.io/DiagrammeR](https://rich-iannone.github.io/DiagrammeR))

## Packages for tables

- `{DT}` ([rstudio.github.io/DT](https://rstudio.github.io/DT))
- `{formattable}` ([renkun-ken.github.io/formattable](https://renkun-ken.github.io/formattable))

## Packages for maps

- `{leaflet}` ([rstudio.github.io/leaflet](https://rstudio.github.io/leaflet))
- `{tmap}` ([github.com/mtennekes/tmap](https://github.com/mtennekes/tmap))
- `{mapdeck}` ([symbolixau.github.io/mapdeck](https://symbolixau.github.io/mapdeck))
- `{echarts4r}` ([echarts4r.john-coene.com](https://echarts4r.john-coene.com))

## Packages for theming

- `{shinydashboard}` ([rstudio.github.io/shinydashboard/](https://rstudio.github.io/shinydashboard/))
- `{shinydashboardPlus}` ([rinterface.github.io/shinydashboardPlus](https://rinterface.github.io/shinydashboardPlus))
- `{fullPage}` ([rinterface.github.io/fullPage](https://rinterface.github.io/fullPage))
- `{bs4Dash}` ([rinterface.github.io-bs4Dash](https://rinterface.github.io-bs4Dash))
- `{shinybulma}` ([rinterface.github.io/shinybulma](https://rinterface.github.io/shinybulma))

# RESOURCES



## Books

- „Mastering Shiny“ by Hadley Wickham ([mastering-shiny.org](http://mastering-shiny.org))
- „Engineering Production-Grade Shiny Apps“ by Colin Fay *et al.* ([engineering-shiny.org](http://engineering-shiny.org))
- „JavaScript for R“ by Joene Coene ([javascript-for-r.com](http://javascript-for-r.com))

## Packages for charts

- `{plotly}` ([plot.ly/r](https://plot.ly/r))
- `{echarts4r}` ([echarts4r.john-coene.com](https://echarts4r.john-coene.com))
- `{ggiraph}` ([davidgohel.github.io/ggiraph](https://davidgohel.github.io/ggiraph))
- `{highcharter}` ([jkunst.com/highcharter](https://jkunst.com/highcharter))
- `{dygraphs}` ([rstudio.github.io/dygraphs](https://rstudio.github.io/dygraphs))
- `{charter}` ([github.com/johncoene/charter](https://github.com/johncoene/charter))
- `{rbokeh}` ([hafen.github.io/rbokeh](https://hafen.github.io/rbokeh))
- `{metricsgraphics}` ([hrbrmstr.github.io/metricsgraphics](https://hrbrmstr.github.io/metricsgraphics))
- `{rthreejs}` ([github.com/bwlewis/rthreejs](https://github.com/bwlewis/rthreejs))
- `{visnetwork}` ([dataknowledge.github.io/visNetwork](https://dataknowledge.github.io/visNetwork))
- `{networkD3}` ([christophergandrud.github.io/networkD3/](https://christophergandrud.github.io/networkD3/))
- `{DiagrammeR}` ([rich-iannone.github.io/DiagrammeR](https://rich-iannone.github.io/DiagrammeR))

[gallery.htmlwidgets.org](http://gallery.htmlwidgets.org)  
[nanxstats/awesome-shiny-extensions](https://nanxstats/awesome-shiny-extensions)

## Packages for tables

- `{DT}` ([rstudio.github.io/DT](https://rstudio.github.io/DT))
- `{formattable}` ([renkun-ken.github.io/formattable](https://renkun-ken.github.io/formattable))

## Packages for maps

- `{leaflet}` ([rstudio.github.io/leaflet](https://rstudio.github.io/leaflet))
- `{tmap}` ([github.com/mtennekes/tmap](https://github.com/mtennekes/tmap))
- `{mapdeck}` ([symbolixau.github.io/mapdeck](https://symbolixau.github.io/mapdeck))
- `{echarts4r}` ([echarts4r.john-coene.com](https://echarts4r.john-coene.com))

## Packages for theming

- `{shinydashboard}` ([rstudio.github.io/shinydashboard/](https://rstudio.github.io/shinydashboard/))
- `{shinydashboardPlus}` ([rinterface.github.io/shinydashboardPlus](https://rinterface.github.io/shinydashboardPlus))
- `{fullPage}` ([rinterface.github.io/fullPage](https://rinterface.github.io/fullPage))
- `{bs4Dash}` ([rinterface.github.io/bs4Dash](https://rinterface.github.io/bs4Dash))
- `{shinybulma}` ([rinterface.github.io/shinybulma](https://rinterface.github.io/shinybulma))

# THANK YOU!

-  [cedricscherer.netlify.com](http://cedricscherer.netlify.com)
-  [cedricphilipscherer@gmail.com](mailto:cedricphilipscherer@gmail.com)
-  [@CedScherer](https://twitter.com/CedScherer)
-  [@Z3tt](https://github.com/Z3tt)

