

Boosting

Gradient Boosting

Boosting

Boosting - Intuition

A boosting classifier is an ensemble classifier built **iteratively**.

Start with an ensemble **H** of a single base classifier **h_1**

Boosting - Intuition

A boosting classifier is an ensemble classifier built **iteratively**.

Start with an ensemble **H** of a single base classifier **h_1**

1. Create a **new dataset** emphasising items **misclassified** by **H**

Boosting - Intuition

A boosting classifier is an ensemble classifier built **iteratively**.

Start with an ensemble **H** of a single base classifier **h_1**

1. Create a **new dataset** emphasising items **misclassified** by **H**
2. Fit a classifier **h_{k+1}** and **integrate** it into **H**

Boosting - Intuition


A boosting classifier is an ensemble classifier built **iteratively**.

Start with an ensemble **H** of a single base classifier **h_1**


1. Create a **new dataset** emphasising items **misclassified** by **H**
2. Fit a classifier **h_{k+1}** and **integrate** it into **H**
3. Repeat

We fit classifiers that increasingly and actively focus on "hard points"



Visually




Visually



Visually



Visually



Comments on boosting

- Sequential algorithm

Comments on boosting

- Sequential algorithm
- Later classifiers have decreasing weight in the aggregation
 - weight of $\mathbf{h}_k > \text{weight of } \mathbf{h}_{k+1}$

Comments on boosting

- Sequential algorithm
- Later classifiers have decreasing weight in the aggregation
 - weight of $\mathbf{h}_k > \text{weight of } \mathbf{h}_{k+1}$
- The same principles work for regression

Boosting methods

- What "weights" to use for misclassified points?

Boosting methods

- What "weights" to use for misclassified points?
- What "weights" to use for the sequence of classifiers?

Boosting methods

- What "weights" to use for misclassified points?
- What "weights" to use for the sequence of classifiers?

Many different approaches based on answers.

AdaBoost ('96), LogitBoost ('98), BrownBoost ('01), ...

Boosting methods

- What "weights" to use for misclassified points?
- What "weights" to use for the sequence of classifiers?

Many different approaches based on answers.

AdaBoost ('96), LogitBoost ('98), BrownBoost ('01), ...

Boosting methods can be interpreted as a **gradient descent** which leads to a more generic framework ("AnyBoost") and to extremely popular libraries:

XGBoost ('14), LightGBM ('16), CatBoost ('17)

Gradient Boosting

Gradient Boosting - Intuition

We want to build weak learners that **actively compensate** each others' errors.

Gradient Boosting - Intuition

We want to build weak learners that **actively compensate** each others' errors.

Let's focus on one sample: (\mathbf{X}, y) with $y = 100$

Gradient Boosting - Intuition

We want to build weak learners that **actively compensate** each others' errors.

Let's focus on one sample: (\mathbf{X}, \mathbf{y}) with $y = 100$

1. Train DT1 on (\mathbf{X}, \mathbf{y})

$$DT1(X) = 95$$

Gradient Boosting - Intuition

We want to build weak learners that **actively compensate** each others' errors.

Let's focus on one sample: (\mathbf{X}, y) with $y = 100$

1. Train DT1 on (\mathbf{X}, y)
2. Compute residuals

$$DT1(X) = 95$$

$$r = 100 - 95 = 5$$

Gradient Boosting - Intuition

We want to build weak learners that **actively compensate** each others' errors.

Let's focus on one sample: (\mathbf{X}, y) with $y = 100$

1. Train DT1 on (\mathbf{X}, y)
2. Compute residuals
3. Train DT2 on $(\mathbf{X}, 5)$

$$DT1(X) = 95$$

$$r = 100 - 95 = 5$$

$$DT2(X) = 4$$

Gradient Boosting - Intuition

We want to build weak learners that **actively compensate** each others' errors.

Let's focus on one sample: (\mathbf{X}, y) with $y = 100$

1. Train DT1 on (\mathbf{X}, y)
2. Compute residuals
3. Train DT2 on $(\mathbf{X}, 5)$
4. Aggregate DT1 and DT2

$$DT1(X) = 95$$

$$r = 100 - 95 = 5$$

$$DT2(X) = 4$$

$$DT1(X) + DT2(X) = 95 + 4 = 99$$

Gradient Boosting - Intuition

We want to build weak learners that **actively compensate** each others' errors.

Let's focus on one sample: (\mathbf{X}, y) with $y = 100$

1. Train DT1 on (\mathbf{X}, y)
2. Compute residuals
3. Train DT2 on $(\mathbf{X}, 5)$
4. Aggregate DT1 and DT2
5. Repeat

$$DT1(X) = 95$$

$$r = 100 - 95 = 5$$

$$DT2(X) = 4$$

$$DT1(X) + DT2(X) = 95 + 4 = 99$$

Boosting - Gradient Boosting

too many stages **OR** too complex trees = overfit to noise

Boosting - Gradient Boosting

too many stages **OR** too complex trees = overfit to noise


- Getting the number of stages right is **extremely** important

Boosting - Gradient Boosting

too many stages **OR** too complex trees = overfit to noise

- Getting the number of stages right is **extremely** important
- We need to build **small, constrained** trees

Boosting - Gradient Boosting



Some pros and cons

- + Great **performance** (usually)

Some pros and cons

- + Great **performance** (usually)
- + Decision Trees = we can get **feature importance**

Some pros and cons

- + Great **performance** (usually)
- + Decision Trees = we can get **feature importance**
- Hard to run in **parallel**

Some pros and cons

- + Great **performance** (usually)
- + Decision Trees = we can get **feature importance**
- Hard to run in **parallel**
- Hard to **interpret**

Some pros and cons

- + Great **performance** (usually)
- + Decision Trees = we can get **feature importance**
- Hard to run in **parallel**
- Hard to **interpret**
- Can easily **overfit**

Gradient Boosting

In Practice

Gradient Boosting in practice

A lot of things depend on the family of base models and can be optimised a lot.

XGBoost and **LightGBM** essentially consider decision trees of fixed depth . Then a lot of tricks are applied:

Gradient Boosting in practice

A lot of things depend on the family of base models and can be optimised a lot.

XGBoost and **LightGBM** essentially consider decision trees of fixed depth . Then a lot of tricks are applied:

- (approximate) computation of residuals (fast)
- Sophisticated computations of γ_k (“step size” or “learning rate”)
- Shrinkage methods to avoid "bad" trees (regularisation)
- Lots of software optimisation. . . (and open source!)

Boosting in Python


With Scikit-Learn:

- *AdaBoostClassifier, AdaBoostRegressor*
- *GradientBoostingClassifier, GradientBoostingRegressor*
 - not as optimised as XGB or LGBM but work with any estimator, not just trees

Other gradient boosting libraries include:


- *XGBoost*
- *LightGBM*
- *CatBoost*

Bias vs Variance



- Gradient Boosting allows to reduce bias of shallow trees
- What happens if we keep adding trees?

Bias vs Variance



- Gradient Boosting allows to reduce bias of shallow trees
- What happens if we keep adding trees?
 - We'll start overfitting



Hands-on session

01-boosting.ipynb