# ← Project review - SQL1 Bootcamp. Day03

| | |
|---|---|
| Type of project | Individual |
| Duration | 15 min |
| Passed Peer Reviews | 2/2 |

## Git project

ssh://git@repos-ssh.21-school.ru:2289/students/SQL_beg... Copy link Open

## Student



**nataliam@student.21-school.ru** level 8

## About

### Introduction

School 21 methodology only makes sense if peer-to-peer reviews are taken seriously. Please read all the guidelines carefully before starting the review.

- Please remain courteous, polite, respectful, and constructive in all communications during this review.

- Point out possible flaws in the person's work and take the time to discuss and debate them.
- Keep in mind that sometimes there may be differences in interpretation of tasks and scope of functionality. Please remain open to each other's vision.

### Guidelines

- Evaluate only the files located in the src folder of the student's or group's GIT repository.
- If you have not finished the project yet, it is compulsory to read the entire instruction before starting the review.
- Ensure to start reviewing a group project only when the team is present in full.
- Use special flags in the checklist to report, for example, "empty work" if the repository does not contain the student's (or group's) work in the src folder of the develop branch, or "cheat" in the case of cheating, or if the student (or group) is unable to explain their work at any time during the review, or if any of the items below are not met. However, except in cases of cheating, you are encouraged to continue reviewing the project to identify the problems that caused the situation so that they can be avoided in the next review.
- Double check that the GIT repository is the one corresponding to the student or group.
- Carefully check that nothing malicious has been used to fool you.
- In controversial cases, remember that the checklist determines only the general order of the check. The final decision on project evaluation remains with the reviewer.

## Main part

### Exercise 00

Checks for the file day03_ex00.sql

- The SQL script looks like below.

```
select pizza_name, price, p.name as pizzeria_name, pv.visit_date
from menu inner join pizzeria p on p.id = menu.pizzeria_id
inner join person_visits pv on p.id = pv.pizzeria_id
inner join person p2 on p2.id = pv.person_id
where price between 800 and 1000 and p2.name = 'Kate'
order by 1,2,3
```

- The result is below (raw ordering should be the same like on a screen below)

```
"cheese pizza"  "950"   "DinoPizza"     "2022-01-04"
"pepperoni pizza"       "800"   "Best Pizza"    "2022-01-03"
"pepperoni pizza"       "800"   "DinoPizza"     "2022-01-04"
"sausage pizza" "1000"  "DinoPizza"     "2022-01-04"
"supreme pizza" "850"   "Best Pizza"    "2022-01-03"
```

✓ Yes  No

### Exercise 01

Checks for the file day03_ex01.sql

- The SQL script looks like below.

```
select id as menu_id
from menu
except
select menu_id
from person_order
order by 1
```

- The result is below (raw ordering should be the same like below)

```
"5"
"10"
"11"
"12"
"15"
```

✓ Yes  No

### Exercise 02

Checks for the file day03_ex02.sql

- The SQL script looks like below.

```
select pizza_name, price, p.name
from (
select id as menu_id
from menu
except
select menu_id
from person_order) as t1 inner join menu on t1.menu_id = menu.id
```

```
inner join pizzeria p on p.id = menu.pizzeria_id
order by 1,2
```

- The result is below (raw ordering should be the same like below)

```
"cheese pizza"  "700"   "Papa Johns"
"cheese pizza"  "780"   "DoDo Pizza"
"cheese pizza"  "950"   "DinoPizza"
"sausage pizza" "950"   "Papa Johns"
"supreme pizza" "850"   "DoDo Pizza"
```

✓ Yes  No

### Exercise 03

Checks for the file day03_ex03.sql

- The SQL script looks like below.

```
(select p2.name as pizzeria_name
from person p inner join person_visits pv on p.id = pv.person_id
    inner join pizzeria p2 on p2.id = pv.pizzeria_id
where p.gender = 'female'
except all
select p2.name
from person p inner join person_visits pv on p.id = pv.person_id
    inner join pizzeria p2 on p2.id = pv.pizzeria_id
where p.gender = 'male')
union all
(select p2.name
from person p inner join person_visits pv on p.id = pv.person_id
    inner join pizzeria p2 on p2.id = pv.pizzeria_id
where p.gender = 'male'
except all
select p2.name
from person p inner join person_visits pv on p.id = pv.person_id
    inner join pizzeria p2 on p2.id = pv.pizzeria_id
where p.gender = 'female')
order by 1
```

- The result is below (raw ordering should be the same like below)

```
"Best Pizza"
"Dominos"
"Papa Johns"
```

✓ Yes  No

### Exercise 04

Checks for the file day03_ex04.sql

- The SQL script looks like below.

```
(select p2.name as pizzeria_name
from person p inner join person_order pv on p.id = pv.person_id
    inner join menu on menu.id = pv.menu_id
    inner join pizzeria p2 on p2.id = menu.pizzeria_id
where p.gender = 'female'
except
select p2.name
from person p inner join person_order pv on p.id = pv.person_id
    inner join menu on menu.id = pv.menu_id
    inner join pizzeria p2 on p2.id = menu.pizzeria_id
where p.gender = 'male')
union
(select p2.name
from person p inner join person_order pv on p.id = pv.person_id
    inner join menu on menu.id = pv.menu_id
    inner join pizzeria p2 on p2.id = menu.pizzeria_id
where p.gender = 'male'
except
select p2.name
from person p inner join person_order pv on p.id = pv.person_id
    inner join menu on menu.id = pv.menu_id
    inner join pizzeria p2 on p2.id = menu.pizzeria_id
where p.gender = 'female')
order by 1
```

- The result is below (raw ordering should be the same like below)

```
  "Papa Johns"
```

✓ Yes  No

### Exercise 05

Checks for the file day03_ex05.sql

- The SQL script looks like below.

```
 select p2.name
from person_visits inner join person p on p.id = person_visits.person_id
    inner join pizzeria p2 on p2.id = person_visits.pizzeria_id
where p.name = 'Andrey'
except
select p2.name
```

```
from person_order inner join person p on p.id = person_order.person_id
    inner join menu m on m.id = person_order.menu_id
    inner join pizzeria p2 on p2.id = m.pizzeria_id
where p.name = 'Andrey'
order by 1
```

- The result is below (raw ordering should be the same like below)

```
 "Pizza Hut"
```

✓ Yes No

### Exercise 06

Checks for the file day03_ex06.sql

- The SQL script looks like below.

```
  select m1.pizza_name, p1.name as pizzeria_name_1, p2.name as pizzeria_
    from menu m1 inner join  menu m2 on m1.id <> m2.id and m1.price = m2
    m1.pizza_name = m2.pizza_name
    inner join  pizzeria p1 on m1.pizzeria_id = p1.id
    inner join  pizzeria p2 on m2.pizzeria_id = p2.id
    order by 1
```

- The result is below (raw ordering should be the same like below)

```
  cheese pizza  Best Pizza      Papa Johns      700
  pepperoni pizza DinoPizza Best Pizza  800
  supreme pizza Best Pizza      DoDo Pizza      850
```

✓ Yes No

### Exercise 07

Checks for the file day03_ex07.sql

- The SQL script looks like below.

```
 insert into  menu(id,pizzeria_id,pizza_name,price) values (19,2, 'greek
```

- The check script is below.

```
 select count(*)=1 as check
 from menu
 where id = 19 and pizzeria_id=2 and pizza_name = 'greek pizza' and pric
```

- The result is below

```
true
```

✓ Yes  No

### Exercise 08

Checks for the file day03_ex08.sql

- The SQL script looks like below.

```
insert into  menu(id,pizzeria_id,pizza_name,price) values
((select max(id)+1 from menu),(select id from pizzeria where name = 'Dom
```

- The check script is below.

```
 select count(*)=1 as check
 from menu
 where id = 20 and pizzeria_id=2 and pizza_name = 'sicilian pizza' and p
```

- The result is below

```
true
```

✓ Yes  No

### Exercise 09

Checks for the file day03_ex09.sql

- The SQL script looks like below.

```
insert into  person_visits(id, person_id, pizzeria_id, visit_date) value
((select max(id)+1 from person_visits), (select id from person where nam
(select id from pizzeria where name = 'Dominos'), '2022-02-24')
insert into  person_visits(id, person_id, pizzeria_id, visit_date) value
```

```
((select max(id)+1 from person_visits), (select id from person where nam
(select id from pizzeria where name = 'Dominos'), '2022-02-24')
```

- The check script is below.

```
select count(*)=2 as check
from person_visits
where visit_date = '2022-02-24' and person_id in (6,4) and pizzeria_id=
```

- The result is below

```
true
```

✓ Yes  No

### Exercise 10

Checks for the file day03_ex10.sql

- The SQL script looks like below.

```
insert into  person_order(id, person_id, menu_id, order_date) values
((select max(id)+1 from person_order), (select id from person where name
(select id from menu where pizza_name = 'sicilian pizza'), '2022-02-24')

insert into  person_order(id, person_id, menu_id, order_date) values
((select max(id)+1 from person_order), (select id from person where name
(select id from menu where pizza_name = 'sicilian pizza'), '2022-02-24')
```

- The check script is below.

```
select count(*)=2 as check
from person_order
where order_date = '2022-02-24' and person_id in (6,4) and menu_id=(sel
```

- The result is below

```
true
```

✓ Yes  No

### Exercise 11

Checks for the file day03_ex11.sql

- The SQL script looks like below.

```
update menu
set price = price-price*0.1
where pizza_name ='greek pizza'
```

- The check script is below.

```
 select (800-800*0.1) = price as check
 from menu
 where pizza_name ='greek pizza'
```

- The result is below (raw ordering should be the same like below)

```
 true
```

✓ Yes  No

## Exercise 12

Checks for the file day03_ex12.sql

- The SQL script looks like below.

```
insert into person_order(id,person_id,menu_id,order_date)
select
    g+(select max(id) from person_order) as id,
    id as person_id,
    (select id from menu where pizza_name = 'greek pizza') as menu_id,
    '2022-02-25' as order_date
from person inner join
generate_series(1,(select count(*) from person)) as g on g= person.id
```

- The check script is below.

```
 select count(*)=9 as check
 from person_order
 where order_date='2022-02-25' and menu_id = (select id from menu where
```

- The result is below

```
 true
```

✓ Yes  No

### Exercise 13

Checks for the file day03_ex13.sql

- The SQL script looks like below.

```
delete from person_order where order_date = '2022-02-25';
delete from menu where pizza_name = 'greek pizza';
```

- The check script is below.

```
select count(*)=0 as check
from person_order
where order_date='2022-02-25' and menu_id = (select id from menu where
```

- The result is below

```
true
```

- The check script is below.

```
select count(*)=0 as check
from menu
where pizza_name = 'greek pizza'
```

- The result is below

```
true
```

✓ Yes  No

## Fails

## Record of the online-review

Student+Peer+Review+2024-09-01_184914.webm

## Comment

Leave a comment...

Review