

-
-
-
-
-
-




Fig. 1. Generative model architecture. Registered LV segmentations at ED and ES phases are mapped to a low-dimensional latent space. Each latent dimension is forced to be normally distributed with mean μ and standard deviation σ . A decoder network is then used to reconstruct the input segmentation from a low-dimensional vector z sampled from the learned latent distribution (training) or the μ vector (testing). The μ latent representation is used as input of a MLP to predict disease status.

•

•

•

○ \hat{X}

○

•

○

•

$$\mathcal{L} = \mathcal{L}_{rec} + \alpha \mathcal{L}_{KL} + \beta \mathcal{L}_{MLP}.$$

○

\hat{X}

○

○

●

○

■

○

●

○

○

○

○

○

$$\mu_{i,t} = \mu_{i,t-1} + \lambda \frac{\partial y_1}{\partial \mu_{i,t-1}}, \quad \forall i = 1, \dots d$$

(1)

○

○

●

○

●




Fig. 2. On the left, Laplacian Eigenmaps (LE) bi-dimensional representation of the latent μ of each subject in the training set (red and green dots) and of the μ_t obtained through latent space navigation (light blue dots) for a random healthy shape. This latter is displayed on the right, together with the decoded segmentations corresponding to the sampled μ_t reported on the left at 4 exemplary iterations. The probabilities of class HVOLs and HCM, and the computed LVM and LVCV are also shown.

●

○

○

- ---
