

# The Go Memory Model

## What is a Memory Model?

A **memory model** defines the conditions under which one goroutine's writes to a variable are guaranteed to be visible to reads from another goroutine.

**In simpler terms:** The memory model tells you: "When does goroutine B see the effects of what goroutine A did?"

**Without this specification, concurrent programs are undefined.**

## Why You Need to Understand This

```
var x, y int

// Goroutine A
x = 1
y = 1

// Goroutine B
if y == 1 {
    fmt.Println(x) // Can this print 0? YES!
}
```

**Shocking truth:** Without synchronization, goroutine B can see `y==1` but `x==0`.

**Why?** Compiler and CPU can reorder operations. Memory model defines when reordering is forbidden.

## The Central Concept: Happens-Before

**Happens-before** is a partial ordering of memory operations. If event A happens-before event B, then:

1. A completes before B starts (temporal ordering)
2. A's effects are visible to B (memory visibility)

**Without happens-before, there's NO GUARANTEE of visibility.**

```
// Notation: A →hb B means "A happens-before B"

write(x) →hb read(x) // Read sees write
```

## The Fundamental Guarantee (Sequential Consistency Within Goroutine)

Within a single goroutine, operations execute in program order:

```
func example() {
    x := 1 // (1)
```

```

    y := 2 // (2)
    z := x + y // (3) Sees x=1, y=2
}

// Guaranteed: (1) →hb (2) →hb (3)

```

But this guarantee does NOT extend across goroutines without synchronization.

## The Problem: No Happens-Before Across Goroutines

```

var a, b int

// Goroutine 1
a = 1 // (1)
b = 2 // (2)

// Goroutine 2
if b == 2 { // (3)
    print(a) // (4)
}

```

**Within G1:** (1) →hb (2)

**Within G2:** (3) →hb (4)

**Across goroutines:** NO RELATIONSHIP

**Possible:** (2) →hb (3) →hb (4) but (1) NOT visible to (4)

**Result:** Print 0, even though G2 sees b==2

**This is not a bug. This is how CPUs and compilers work.**

## Synchronization Operations That Create Happens-Before

Go provides specific operations that establish happens-before relationships across goroutines.

### 1. Goroutine Creation

```

var a string

func f() {
    print(a) // (2)
}

func main() {
    a = "hello" // (1)
    go f()      // Start goroutine
}

// Guarantee: (1) →hb (2)
// "go f()" synchronizes: operations before "go" visible inside f()

```

**Rule:** Everything before `go` happens-before the start of the goroutine.

## 2. Goroutine Exit (No Guarantee!)

```
var a string

func f() {
    a = "hello" // (1)
}

func main() {
    go f()
    print(a) // (2)
}

// NO GUARANTEE: (1) NOT →hb (2)
// "a" might be "", might be "hello"
```

**Rule:** Goroutine exit is NOT synchronized with parent. Use channels or sync primitives.

## 3. Channel Communication

**Unbuffered channel:**

```
var c = make(chan int)
var a string

// Goroutine 1
func sender() {
    a = "hello" // (1)
    c <- 0      // (2) Send
}

// Goroutine 2
func receiver() {
    <-c         // (3) Receive
    print(a)    // (4)
}

// Guarantees:
// (1) →hb (2) (same goroutine)
// (2) →hb (3) (send →hb receive)
// (3) →hb (4) (same goroutine)
// Chain: (1) →hb (4)
// Result: Always prints "hello"
```

**Rule (Unbuffered):** Send on channel happens-before the corresponding receive completes.

**Buffered channel:**

```

var c = make(chan int, 1)
var a string

// Goroutine 1
a = "hello" // (1)
c <- 0      // (2)

// Goroutine 2
<-c         // (3)
print(a)    // (4)

// Guarantees:
// (2) →hb (3) (send →hb receive)
// Does (1) →hb (4)? YES, because:
// (1) →hb (2) →hb (3) →hb (4)

```

**Rule (Buffered):** Send on channel happens-before receive from that channel **begins**.

**Channel close:**

```

var c = make(chan int)
var a string

// Goroutine 1
a = "hello" // (1)
close(c)    // (2)

// Goroutine 2
<-c         // (3) Receive from closed channel
print(a)    // (4)

// Guarantee: (2) →hb (3)
// Chain: (1) →hb (2) →hb (3) →hb (4)

```

**Rule:** Close of channel happens-before receive of zero value from closed channel.

#### 4. Locks (Mutex, RWMutex)

```

var mu sync.Mutex
var a string

// Goroutine 1
func writer() {
    mu.Lock()
    a = "hello" // (1)
    mu.Unlock() // (2)
}

// Goroutine 2
func reader() {

```

```

    mu.Lock()    // (3)
    print(a)     // (4)
    mu.Unlock()
}

// Guarantee: (2) →hb (3)
// Chain: (1) →hb (2) → hb (3) →hb (4)

```

**Rule:** Unlock of mutex M happens-before any subsequent Lock of M.

#### RWMutex:

- RUnlock happens-before Lock (reader → writer)
- Unlock happens-before Lock (writer → writer)
- Unlock happens-before RLock (writer → reader)

## 5. sync.WaitGroup

```

var wg sync.WaitGroup
var a string

func worker() {
    a = "hello" // (1)
    wg.Done()   // (2)
}

func main() {
    wg.Add(1)
    go worker()
    wg.Wait()   // (3)
    print(a)    // (4)
}

// Guarantee: (2) →hb (3)
// Chain: (1) →hb (2) →hb (3) →hb (4)

```

**Rule:** Done() happens-before Wait() returns (if it caused counter → 0).

## 6. sync/atomic Operations

```

var a int
var flag int32 // atomic

// Goroutine 1
a = 42 // (1)
atomic.StoreInt32(&flag, 1) // (2)

// Goroutine 2
for atomic.LoadInt32(&flag) == 0 {} // (3) Spin until flag set
print(a) // (4)

```

```
// Guarantee: (2) →hb (3)
// Chain: (1) →hb (2) →hb (3) →hb (4)
```

**Rule:** Atomic write happens-before atomic read of the same variable that observes the write.

## 7. sync.Once

```
var a string
var once sync.Once

func setup() {
    a = "hello" // (1)
}

// Multiple goroutines
once.Do(setup) // (2)
print(a)       // (3)

// Guarantee: (1) →hb (3)
// setup() completes before once.Do() returns
```

**Rule:** once.Do(f) call that executes f() happens-before any once.Do(g) returns.

# Operations That DO NOT Provide Happens-Before

## 1. Time

```
// WRONG: Assuming time provides ordering
func goroutine1() {
    a = 1
}

func goroutine2() {
    time.Sleep(time.Second) // "Let goroutine1 finish"
    print(a) // Might still see 0!
}
```

**No guarantee.** Time is not synchronization.

## 2. Goroutine Yield/Gosched

```
// WRONG
a = 1
runtime.Gosched() // Yield to scheduler
```

**No guarantee.** Yielding doesn't synchronize.

## 3. Finalizers

```
// WRONG: Using finalizer for synchronization
runtime.SetFinalizer(obj, func(o *Object) {
    // Runs when obj is garbage collected
    // NO synchronization with main program
})
```

#### 4. Defer, Panic, Recover

```
// WRONG: Assuming defer creates happens-before
func main() {
    defer print(a)
    go func() { a = 1 }()
}
// No guarantee defer sees a=1
```

### Example: The Double-Checked Locking Bug

```
type Singleton struct {
    instance *Instance
    mu        sync.Mutex
}

// WRONG: Broken double-checked locking
func (s *Singleton) Instance() *Instance {
    if s.instance != nil { // (1) Read without lock
        return s.instance
    }

    s.mu.Lock()
    defer s.mu.Unlock()

    if s.instance == nil {
        s.instance = &Instance{} // (2) Write
    }

    return s.instance
}

// Problem: (1) and (2) are not synchronized
// Goroutine A: Creates instance, releases lock
// Goroutine B: Sees s.instance != nil (pointer is non-nil)
//              But instance FIELDS might not be visible!
//              Using partially-constructed instance → crash
```

#### Fix: Use sync.Once

```
var (
    instance *Instance
```

```

    once    sync.Once
)

func Instance() *Instance {
    once.Do(func() {
        instance = &Instance{}
    })
    return instance // Guaranteed fully constructed
}

```

## Example: The Init Function Trap

```

var a string

func init() {
    a = "hello"
}

func main() {
    go func() {
        print(a) // Guaranteed "hello"? YES
    }()
}

```

**Guarantee:** Package init functions happen-before main.main starts.

**Chain:** init writes a →hb main starts →hb go f() →hb print(a)

## Common Misconceptions

### Misconception 1: "Volatile" Reads and Writes

Go does not have "volatile" keyword like C/C++/Java.

**Wrong assumption:** "Regular reads/writes are atomic and visible."

**Truth:** Without synchronization, visibility is not guaranteed.

### Misconception 2: "Reads Can't See Partial Writes"

```

type T struct {
    x, y int
}

var t T

// Goroutine 1
t = T{1, 2}

// Goroutine 2
fmt.Println(t) // Can print {1, 0}, {0, 2}, or other partial state

```



Without synchronization, non-atomic writes can be observed partially.

### Misconception 3: "If Tests Pass, It's Correct"

```
var x, y int

go func() {
    x = 1
    y = 1
}()

time.Sleep(time.Millisecond) // "Wait"
if y == 1 && x == 0 {
    panic("impossible!") // This CAN happen
}
```

Tests can pass 1000 times and still have races.

## Detecting Violations: The Race Detector

```
go run -race main.go
go test -race
go build -race
```

#### What it detects:

- Unsynchronized access to shared memory
- At least one access is a write
- No happens-before relationship

#### What it doesn't detect:

- Races that don't execute during the test
- Deadlocks, livelocks, resource leaks

Always run tests with `-race` in CI/CD.

## The Safe Patterns

### Pattern 1: Message Passing (Channel)

```
type Message struct {
    Data []int
}

ch := make(chan Message)

// Sender owns Data before send
msg := Message{Data: []int{1,2,3}}
ch <- msg // Happens-before receive
```

```
// Don't use msg.Data after send (ownership transferred)

// Receiver
received := <-ch
// Can safely use received.Data (ownership gained)
```

## Pattern 2: Mutex Protection

```
var (
    mu    sync.Mutex
    data  map[string]int
)

// All access protected
mu.Lock()
data["key"] = value
mu.Unlock()

mu.Lock()
v := data["key"]
mu.Unlock()
```

## Pattern 3: Atomic Operation

```
var counter int64

// All access atomic
atomic.AddInt64(&counter, 1)
atomic.LoadInt64(&counter)
```

## Pattern 4: Write Once, Read Many

```
var config *Config

func init() {
    config = loadConfig() // Write once in init
}

// Many goroutines can read without synchronization
func handler() {
    use(config) // Safe: init →hb main →hb handler
}
```

## Interview Traps

### Trap 1: "This code is fine—it works in tests"

**Wrong.** Absence of observed race  $\neq$  absence of race.

**Correct answer:**

"Tests can pass even with data races due to timing, compiler optimizations, or CPU reordering. The Go memory model specifies that without synchronization (happens-before relationship), reads can see stale or inconsistent values. I must use proper synchronization primitives."

**Trap 2: "Adding time.Sleep fixes the race"**

**Wrong.** time.Sleep is not synchronization.

**Correct answer:**

"Time-based coordination doesn't provide happens-before guarantees. Even with sleep, compiler/CPU reordering can cause reads to see stale values. Proper synchronization (channels, mutexes, atomics) is required to establish memory visibility."

**Trap 3: "Reading a bool doesn't need synchronization"**

**Wrong.** All unsynchronized access to shared data is a race.

**Correct answer:**

"Even single-byte reads/writes can race. While the value might not be corrupted, without synchronization there's no happens-before guarantee, so reads might see stale values indefinitely due to CPU caching. Use atomic.LoadUint32/StoreUint32 for flags."

**Trap 4: "The race detector proves my code is correct"**

**Wrong.** Race detector finds races in executed code paths only.

**Correct answer:**

"The race detector is a dynamic analysis tool—it only detects races that occur during execution. Code paths not executed, rare interleavings, or races that require high contention might not be caught. I must reason about happens-before relationships to ensure correctness."

## Key Takeaways

1. **Happens-before defines memory visibility** (not just time ordering)
2. **Within goroutine: program order guaranteed**
3. **Across goroutines: no guarantee without synchronization**
4. **Synchronization operations create happens-before:**
  - Channel send/receive
  - Mutex lock/unlock
  - WaitGroup done/wait
  - Atomic operations
  - sync.Once
5. **Time, sleep, gosched do NOT synchronize**
6. **Race detector is necessary but not sufficient**
7. **Always reason about happens-before, not time**

## What You Should Be Thinking Now

- "What exactly is the happens-before relationship?"
- "How do I prove my code has proper synchronization?"
- "What's the difference between visibility and ordering?"
- "Why can compilers and CPUs reorder operations?"

Next: [happens-before.md](#) - Deep dive into the happens-before partial order.

---

## Exercises (Do These Before Moving On)

1. Write a program with a data race on a boolean flag. Run with `-race`. Fix it with `atomic`.
2. Create two goroutines: write `x=1; y=1` in one, read `y; x` in the other. Prove the reader can see `y==1` but `x==0` (run billions of times or use CPU-specific barriers).
3. Explain why `time.Sleep` doesn't synchronize using happens-before.
4. Find 3 synchronization points in your own code that create happens-before relationships.

Don't continue until you can explain: "Why can one goroutine see partial effects of another goroutine's operations without synchronization?"