ATLASCORE — SYNTHETIC VENDOR TECHNICAL BID

SIMULATED TEST DOCUMENT — NOT AN ACTUAL VENDOR SUBMISSION

Responses deliberately contain paraphrases, abbreviations, mixed units and some missing specifications. General boilerplate at the end is not evidence for any specific criterion.

Technical Schedule — Response Block 1

ID	Area	Vendor response	Evidence
R01	System processing capacity	Rated system processing capacity is 200 units/s or above.	Page 2
R02	Display brightness	Rated display brightness is 500 nits or above.	Page 2
R03	Storage capacity	Rated storage capacity is 1 TB or above.	Page 2
R04	Operating temperature	Operating temperature: specified range is -9 to 52 °C.	Page 2
R05	Power consumption	Specified power consumption does not exceed 120 W.	Page 2
R06	Battery capacity	Battery capacity: rated at 30 Ah.	Page 2
R07	Battery backup	Rated battery backup is 6 hours or above.	Page 2
R08	Ingress protection	Ingress protection: IP65	Page 2
R09	Warranty period	Rated warranty period is 3 years or above.	Page 3
R10	Delivery period	Specified delivery period does not exceed 30 days.	Page 3

Technical Schedule — Response Block 2

ID	Area	Vendor response	Evidence
R11	Network interface	Network interface: supplier states a related/equivalent capability, but the requested supporting detail is incomplete.	Page 3
R12	Data encryption	The supplied system provides TLS 1.2 or higher in transit.	Page 3
R13	Processor architecture	Processor architecture: 64-bit accepted/configured.	Page 3
R14	Memory capacity	Rated memory capacity is 16 GB or above.	Page 3
R15	USB interface	USB interface: USB 3.0 or higher accepted/configured.	Page 3
R16	Screen resolution	Rated screen resolution is 1920 x 1080 pixels or above.	Page 3
R17	Camera resolution	Rated camera resolution is 8 MP or above.	Page 4
R18	Audio output	Rated audio output is 20 W or above.	Page 4
R19	Noise level	Specified noise level does not exceed 45 dB.	Page 4
R20	Weight	Specified weight does not exceed 15 kg.	Page 4

Technical Schedule — Response Block 3

ID	Area	Vendor response	Evidence
R21	LED efficacy	Rated led efficacy is 120 lm/W or above.	Page 4
R22	LED color temperature	LED color temperature: operating range 4005 to 5010 K.	Page 4
R23	Luminous output	Rated luminous output is 12000 lm or above.	Page 4
R24	Color rendering index	Rated color rendering index is 80 CRI or above.	Page 4
R25	Solar panel efficiency	Rated solar panel efficiency is 20 % or above.	Page 5
R26	Solar module rating	Rated solar module rating is 450 W or above.	Page 5
R27	Charge controller type	Charge controller type: MPPT accepted/configured.	Page 5
R28	Enclosure material	Enclosure material: supplier states a related/equivalent capability, but the requested supporting detail is incomplete.	Page 5
R29	Connector protection	Connector protection: IP67	Page 5
R30	Power factor	Rated power factor is 0.95 or above.	Page 5

Technical Schedule — Response Block 4

ID	Area	Vendor response	Evidence
R31	Flow rate	Rated flow rate is 50 L/min or above.	Page 5
R32	Pressure range	Pressure range: operating range 2 to 6 bar.	Page 5
R33	Measurement accuracy	Measurement accuracy: measurement error limited to ±2%.	Page 6

ID	Area	Vendor response	Evidence
R34	Operating voltage	Operating voltage: operating range 220 to 240 V.	Page 6
R35	Frequency	Frequency: 50 Hz	Page 6
R36	Response time	Specified response time does not exceed 100 ms.	Page 6
R37	Ingress protection for enclosure	Rated ingress protection for enclosure is IP54 or above.	Page 6
R38	Compliance certification	The supplied system provides BIS compliant.	Page 6
R39	Quality certification	The supplied system provides ISO 9001 certified.	Page 6
R40	OEM authorization	The supplied system provides OEM authorization letter required.	Page 6

Technical Schedule — Response Block 5

ID	Area	Vendor response	Evidence
R41	Installation time	Installation time: measured at 3 days.	Page 7
R42	Service response time	Specified service response time does not exceed 24 hours.	Page 7
R43	Spare parts availability	Rated spare parts availability is 5 years or above.	Page 7
R44	Operating humidity	Operating humidity: operating range 20 to 80 % RH.	Page 7
R45	Mounting height	Mounting height: operating range 1.5 to 2.5 m.	Page 7
R46	Cable length	Rated cable length is 10 m or above.	Page 7
R47	Protection class	Protection class: Class II	Page 7
R48	Material grade	Material grade: SS 304 or better accepted/configured.	Page 7
R49	Remote monitoring	The supplied system provides web-based remote monitoring.	Page 8
R50	Documentation	The supplied system provides user manual and maintenance manual supplied.	Page 8

General Company Statement

The supplier maintains standard quality processes, trained personnel, routine maintenance and conventional documentation practices. These statements are intentionally unrelated to individual technical criteria.